

Assignment Project Exam Help

Geometric Modeling

<https://powcoder.com>

Add WeChat powcoder

Computer Graphics

Instructor: Sungkil Lee

Today

- **Fundamental elements of geometry**
 - Points, scalars, and vectors
 - **Vector, Euclidean, and affine spaces**
 - **Additional elements of geometry**
 - **Geometric modeling**
- <https://powcoder.com>
- Add WeChat powcoder

Assignment Project Exam Help
Prerequisites: Vector Spaces
<https://powcoder.com>

Add WeChat powcoder

Vector Spaces

- **Formal definition of a vector space**

- A vector space over a field F is a set V together with addition and multiplication that satisfy the eight axioms.
- Elements of V and F are called vectors and scalars.

Assignment Project Exam Help

Axiom	Meaning
Associativity of addition	$\mathbf{u} + (\mathbf{v} + \mathbf{w}) = (\mathbf{u} + \mathbf{v}) + \mathbf{w}$
Commutativity of addition	$\mathbf{u} + \mathbf{v} = \mathbf{v} + \mathbf{u}$
Identity element of addition	There exists an element $\mathbf{0} \in V$ such that $\mathbf{v} + \mathbf{0} = \mathbf{v}$ for all $\mathbf{v} \in V$.
Inverse elements of addition	For every $\mathbf{v} \in V$, there exists an element $\mathbf{v} \in V$ such that $\mathbf{v} + (-\mathbf{v}) = \mathbf{0}$.
Distributivity of scalar multiplication with respect to vector addition	$a(\mathbf{u} + \mathbf{v}) = a\mathbf{u} + a\mathbf{v}$
Distributivity of scalar multiplication with respect to field addition	$(a + b)\mathbf{v} = a\mathbf{v} + b\mathbf{v}$
Compatibility of scalar multiplication with field multiplication	$a(b\mathbf{v}) = (ab)\mathbf{v}$
Identity element of scalar multiplication	$1\mathbf{v} = \mathbf{v}$, where 1 denotes the multiplicative identity in F .

<https://powcoder.com>

Add WeChat powcoder

Vector Spaces

- **More simply:**

- Vectors can be added, and such a sum is also a vector.
- There is a zero vector and an inverse on vector addition.
- Vectors can be multiplied by a scalar.
- Identity exists for scalar multiplication (i.e., 1)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

More on Algebra

- **Mathematical structures related to the concept of a field can be tracked as follows:**

Assignment Project Exam Help

- A *field* is a *ring* whose nonzero elements form a *abelian group* under multiplication.
- A *ring* is an *abelian group* under addition and a *semigroup* under multiplication; addition is commutative, addition and multiplication are associative, multiplication distributes over addition, each element in the set has an additive inverse, and there exists an additive identity.
- An *abelian group* (*commutative group*) is a group in which commutativity ($a \cdot b = b \cdot a$) is satisfied.
- A *semigroup* is a set A in which $a \cdot b$ satisfies associativity for any two elements a and b and operator \cdot .
- A *group* is a set A in which $a \cdot b$ satisfies closure, associativity, identity element, and inverse element for any two elements a and b and operator \cdot .

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

Geometric Elements

<https://powcoder.com>

Add WeChat powcoder

Geometry and Fundamental Elements

- **Geometry:**

- The study of the relationships among objects in an n -dimensional space

- **In CG, we work with sets of geometric objects, such as points, lines, triangles, and quads.**

- Such objects exist in a 3D space.
- We can define them and their relationships using a limited set of primitives.

- **Three fundamental types of elements:**

- Points, scalars, and vectors

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Fundamental Elements (1): Points

- **Point: a location in space**
 - a mathematical point has neither a size nor a shape.
- **Points are useful in specifying geometric objects but are insufficient by themselves**
 - We need real numbers to specify quantities such as the distance between two points
 - Such real numbers are examples of *scalars*.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Fundamental Elements (2): Scalars

- **Scalars:**

- Objects that obey a set of rules that are abstractions of the operations of ordinary arithmetic.
- Addition and multiplication are well defined and obey fundamental axioms (associativity, commutativity, inverse, and identity).

Assignment Project Exam Help

- **Examples of scalars:**

- real numbers
- complex numbers

<https://powcoder.com>

Add WeChat powcoder

- **Scalars alone have no geometric properties**

Fundamental Elements (3): Vectors

- **A physical definition of vectors:**

- A quantity with direction and magnitude.
- Vectors do not have a fixed location in space.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- **Examples:**

- Force, velocity, and *directed line segments*
- ***Directed*** line segments, connecting two points, will be often used synonymously to the term **vector**.

Operations on Vectors and Points

- **Vectors are insufficient for geometry**


- We need to represent a location in space.
- Points necessary

Assignment Project Exam Help

- **Operations allowed between points and vectors**

- $v = P - Q$: **point-vector subtraction** yields a vector
- $P = Q + v$: equivalent to **point-vector addition**

Add WeChat powcoder



Computer Science View on Geom. Elements

- **We may need to define abstract data types for points, scalars, and vectors independently.**

- The operations allowed between elements can be exactly implemented with operator overloading (in C++).
- We can overload only allowed operators among them, and do not overload others (e.g., do not define point-point addition).

<https://powcoder.com>

- **Notes on GLSL: confusion with vec2, vec3, vec4.**

- Unfortunately, this choice of names by GLSL can cause some confusion.
- They are actually not geometric types but rather storage types.
- Hence, we can use them to store a point, a vector, or a color.

Assignment Project Exam Help
Extensions of Vector Spaces
<https://powcoder.com>

Add WeChat powcoder

Euclidean Space

- **Euclidean space**

- Vector space + *a measure of distance (i.e., Euclidean distance)*
- Euclidean distance allows us to define size or distance as the length of a line segment.
- When we also have the notion of point (i.e., *affine space*), a Euclidean distance between two points can be defined as (in 3D):

<https://powcoder.com>

$$\sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2}$$

Add WeChat powcoder

Affine Space

- **Affine space**

- Vector space (scalars and vectors only) + points
- Operations
 - Vector-vector addition
 - Scalar-vector multiplication
 - Scalar-scalar operations
 - **Vector-point addition (newly defined in affine space)**
- New points are defined by **vector-point addition**
 - Alternatively, we can say there is point-point subtraction (equivalent to vector-point addition).
- **Note that there are no operations between points or scalars.**

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Representations

- **In these abstract spaces (vector space, Euclidean space, and affine space),**
 - Objects can be defined independently of any particular representations.
 - Representation (the lecture covered later) provides the tie between the abstract objects and their implementation (in real spaces).
 - Conversion between representations leads us to geometric transformations. <https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help
Additional Elements of Geometry
<https://powcoder.com>

Add WeChat powcoder

Lines

- The sum of a point and a vector (or the subtraction of two points) leads to the notion of a line in an **affine space**.
 - Consider all points of the parametric form

Assignment Project Exam Help

<https://powcoder.com>

- Here, a line can be defined as a set of all points that pass through P_0 in the direction of the vector d

Add WeChat powcoder




FIGURE 3.10 Line in an affine space.

Rays and Line Segments

$$P(\alpha) = Q + \alpha \mathbf{d} = Q + \alpha(R - Q)$$

- If we restrict α to semi-positive values ($\alpha \geq 0$), this defines a **ray** emanating from Q .
- If we restrict α to $[0, 1]$, this defines a line segment between Q and R .

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




FIGURE 3.11 Affine addition.

Affine Sum

- **In an affine space, the addition of two arbitrary points and multiplication of a point by a scalar are not defined.**
 - However, we have a limited form of an operation that has certain elements of the two operations, *affine addition*.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Affine Sum

- **Affine addition:**

$$P = Q + \alpha v = Q + \alpha(R - Q) = (1 - \alpha)Q + \alpha R$$

- This operation looks like the addition of two points and leads to the equivalent form

$$P = \alpha_1 Q + \alpha_2 R, \quad \text{where } \alpha_1 + \alpha_2 = 1$$

<https://powcoder.com>

Add WeChat powcoder




FIGURE 3.11 Affine addition.

- Then, this defines the two operations, not allowed in an affine space:
 - (1) addition of two points and (2) multiplication of a point by a scalar
 - yet only with the limited condition (the sum of scalars=0).

Affine Sum

- **Affine sum:**

- By extending such a point-vector addition to include n points, we have the following sum:

$$P = \alpha_1 P_1 + \alpha_2 P_2 + \cdots + \alpha_n P_n, \text{ where } \alpha_1 + \alpha_2 + \cdots + \alpha_n = 1$$


- We call this kind of sum the affine sum.
- By this way, we can define the addition of points as well as the multiplication of points by scalars.

Convex Hull

- Given a set of points, $\{P_i\}$, one more constraint, $\alpha_i \geq 0$, defines its **convex hull**, H , as:

$$H = \left\{ \sum_i \alpha_i P_i \mid \sum_i \alpha_i = 1, \alpha_i \geq 0 \right\}$$

- The convex hull is the smallest convex object containing $\{P_1, P_2, \dots, P_n\}$.
- Convex object:** for any two points in the object, all points on the line segment between these points are also in the object.



Triangles: Barycentric Coordinates

- Also, we are able to write the plane in terms of affine sum as:

$$T(\alpha, \beta, \gamma) = \alpha P + \beta Q + \gamma R, \quad \text{where } \alpha + \beta + \gamma = 1.$$

- When $\alpha, \beta, \gamma > 0$, this represents a triangle and its internal points.
<https://powcoder.com>
Hence, triangles are convex by default.
- This representation of a point is called the **barycentric coordinate** representations.
 - c.f., Barycenter: the center of mass

Assignment Project Exam Help

Geometric Modeling

<https://powcoder.com>

Add WeChat powcoder




Models

- **Models:**

- Mathematical abstraction of the real world or virtual worlds.

- **Geometric Models:**

- In CG, we model our worlds with *geometric objects*.
- Building blocks: a set of simple 3D primitives (Point, lines, triangles, ...)
- **Triangular meshes** are common, which comprises a set of triangles connected by their common edges or corners.



3D Primitives



- **3D objects that fit well with graphics HW and SW:**

- described by their **2D surfaces** and can be thought of as being **hollow**.
 - c.f., objects with 3D surfaces are called the **volumetric** objects (e.g., CT).
- can be specified through **a set of vertices**.
- either are composed of or can be approximated by flat, convex polygons.
 - e.g., a circle/sphere approximated by flat triangles.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



3D Primitives

- **Why we set these conditions?**

- Modern graphics systems are optimized for rendering **triangles** or **meshes of triangles** (e.g., more than 100 M triangles / sec.).
 - Points and lines are also supported well.
- Vertices can be processed with the pipeline architecture, independently.

Assignment Project Exam Help

- **Why are triangles fundamental primitives?**

- *The triangles are always flat.*
- General polygons might not lie in the same plane, and then, there is no simple way to define interior of the object.
- Also, general polygons can be decomposed into a set of triangles:
 - then, we can apply the same pipeline on the triangles.

<https://powcoder.com>

Add WeChat powcoder

Triangular Mesh Representation



- **Consider a mesh as a graph**

- There are 8 vertices and 12 edges
- 5 interior polygons and 6 interior (shared) edges
- Decompose non-triangular polygons to triangles

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Triangular Mesh Representation

- **A simple list-based representation**

- Define each polygon by the geometric locations of its vertices, leading to OpenGL code such as.

```
...  
vertex[i+0].pos = vec3(x1, y1, z1);  
vertex[i+1].pos = vec3(x2, y2, z2);  
vertex[i+2].pos = vec3(x7, y7, z7);  
i+=3;  
vertex[i+0].pos = vec3(x2, y2, z2);  
vertex[i+1].pos = vec3(x3, y3, z3);  
vertex[i+2].pos = vec3(x7, y7, z7);  
i+=3;  
...
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- A simple list-based representation is often inefficient and unstructured.
- When a vertex moves to a new location, we must search and replace it for all the occurrences.

Geometry vs. Topology

- **Generally, it is a good idea to look for data structures that separate the geometry from the topology**
 - *Geometry*: locations of the vertices
 - *Topology*: structural organization of the vertices and edges
 - Connectedness is preserved under continuous deformation
 - Topology holds even if geometry changes

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



The cup and torus share the same topology.

Vertex Lists

- Geometries are put into an array
 - Use *indices* from the vertices into this array.
- Topology maintains a triangle list regardless of geometry.

Assignment Project Exam Help

