

Smalltalk Lecture 1

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Assignment Project Exam Help

Why Smalltalk?

Add WeChat powcoder

- > *Pure* object-oriented language and environment
 - “Everything is an object”

<https://powcoder.com>

- > Origin of *many innovations* in OO development
 - RDD, IDE, MVC, XUnit ...

- > Improves on many of its successors
 - Fully interactive and dynamic



What is Smalltalk?

Add WeChat powcoder

> **Pure OO language**

- Single inheritance
- Dynamically typed

Assignment Project Exam Help

> **Language and environment**

<http://powcoder.com>

- Guiding principle: “*Everything is an Object*”
- Graphical Smalltalk implementations have class browser, debugger, inspector, ...
- Mature class library and tools

Add WeChat powcoder

> **Virtual machine**

- Objects exist in a persistent *image* [+ *changes*]
- Incremental compilation

Assignment Project Exam Help

Smalltalk vs. C++ vs. Java

Add WeChat powcoder

	Smalltalk	C++	Java
<i>Object model</i>	Pure	Hybrid	Hybrid
<i>Garbage collection</i>	Automatic	Manual	Automatic
<i>Inheritance</i>	Single	Multiple	Single
<i>Types</i>	Dynamic	Static	Static
<i>Reflection</i>	Fully reflective	Introspection	Introspection
<i>Concurrency</i>	Semaphores, Monitors	Some libraries	Monitors
<i>Modules</i>	Categories, namespaces	Namespaces	Packages

Assignment Project Exam Help

Smalltalk: a State of Mind

Add WeChat powcoder

- > ***Small and uniform language***
 - Syntax fits on one sheet of paper
- > ***Large library of reusable classes***
 - Basic Data Structures, GUI classes, Database Access, Internet, Graphics

<https://powcoder.com>
- > ***Advanced development tools***
 - Browsers, GUI Builders, Inspectors, Change Management Tools, Crash Recovery Tools, Project Management Tools
- > ***Interactive virtual machine technology***
 - Truly platform-independent
- > ***Team Working Environment***
 - Releasing, versioning, deploying

Assignment Project Exam Help

Origins of Smalltalk

Add WeChat powcoder

> **Project at Xerox PARC in 1970s**

- Language and environment for new generation of graphical workstations (target: “Dynabook”)

<https://powcoder.com>

> **In Smalltalk-72, every object was an independent entity**

Add WeChat powcoder

- Language was designed for children (!)
- Evolved towards a meta-reflective architecture

> **Smalltalk-80 is the standard**

Assignment Project Exam Help

Precursor, Innovator & Visionary

Add WeChat powcoder

- > First to be based on Graphics
 - Multi-Windowing Environment (Overlapping Windows)
 - Integrated Development Environment: Debugger, Compiler, Text Editor, Browser
- > With a pointing device (yes, a Mouse)
- > Ideas were taken over
 - Apple Lisa, Mac
 - Microsoft Windows 1.0
- > Platform-independent Virtual Machine
- > Garbage Collector
- > Just-in-time Compilation
- > Everything was there, the complete Source Code

Assignment Project Exam Help

What are Squeak and Pharo?

Add WeChat powcoder

- > We will use text-based GNU Smalltalk in this course
- > Encourage you to also look at graphical-based Smalltalk implementations
- > Squeak is a modern, open-source, highly portable, fast, full-featured Smalltalk implementation
 - Based on original Smalltalk-80 code
- > Pharo is a lean and clean fork of Squeak
 - www.pharo-project.org

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Assignment Project Exam Help

Squeak desktop

Add WeChat powcoder

System Browser: Morph

KernelTests-Processes
Files-Kernel
Morphic-Kernel
MorphicTests-Kernel
Network-Kernel
NetworkTests-Kernel
Protocols-Kernel
SUnit-Kernel
Compiler-Kernel
ToolBuilder-Kernel
Traits-Kernel
TraitsTests-Kernel

Morph
BorderedMorph
MorphicModel
HandMorph
MorphExtension
TheWorldMainDockin
TheWorldMenu

event handling
events-accessing
events-alarms
events-filtering
events-filtering-bubblin
events-filtering-captur
events-processing
event-repaving
*Etoys-custom-events-s
other events

mouseDown:
mouseEnterDraggi
mouseEnter:
mouseLeaveDraggi
mouseLeave:
mouseMove:
mouseStillDov
mouseStillDo
mouseUp:
mouseWheel:
handlerForMo
handlesMouse

Implementors of mouseDown: [65]
AbstractResizeMorph mouseDown: {as yet unclassified} {Morphic-Widgets}
AlternatePluggableListMorphOfMany mouseDown: {event handling} {Morphic-Plugg
BookPageThumbnailMorph mouseDown: {event handling} {MorphicExtras-Books}
BracketSliderMorph mouseDown: {event handling} {Morphic-Widgets}
ButtonProperties mouseDown: {events} {Etoys-Buttons}
StateButtonMorph mouseDown: {event handling} {Nebraska-Audio Chat}

mouseDown: evt
"Handle a mouse down event. The default response is to let my
eventHandler, if any, handle it."
self eventHandler
ifNotNil: [self eventHandler mouseDown: evt from
"Check for option (menu) click"
evt yellowButtonPressed
ifTrue: [^ self yellowButtonActivity: evt shiftPre

mt 4/19/2015 12:15 · event handling · 65 implemento

Senders of mouseDown: [37]
FatBitsPaint toolsForSelection {initialization} {MorphicExtras-AdditionalWidgets}
InterimSoundMorph mouseDown: {event handling} {MorphicExtras-SoundInterface}
MagnifierMorph mouseDown: {event handling} {MorphicExtras-Demo}
MenuItemMorph mouseDown: {events} {Morphic-Menus}
Morph click {event handling} {Morphic-Kernel}
Morph handleMouseDown: {events-processing} {Morphic-Kernel}
Morph showActions {meta-actions} {Morphic-Kernel}
NumericReadoutTile mouseStillDown: {event handling} {Etoys-Scripting Tiles}
PasteUpMorph mouseDown: {event handling} {Morphic-Worlds}
PluggableListMorph mouseDown: {events} {Morphic-Pluggable Widgets}
PluggableListMorphOfMany mouseDown: {event handling} {Morphic-Pluggable Widgets}
PluggableListMorphOfMany mouseMove: {event handling} {Morphic-Pluggable Widgets}

mouseDown: anEvent
last mouse = anEvent cast: Point

mouseDown: evt
evt yellowButtonPressed
ifTrue: [self chooseMagnification: evt]
ifFalse: [super mouseDown: evt]

bf 9/21/1999 10:45 · event handling · 65 implementors · in no change set ·

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

Smalltalk — Key Concepts

Add WeChat powcoder

- > *Everything is an object*
 - numbers, files, editors, compilers, points, tools, booleans ...
- > Everything happens by *sending messages*
- > Every object is an instance of one class
 - which is also an object
 - A class defines the structure and the behavior of its instances.
- > Objects have private (protected) state
 - Encapsulation boundary is the object
- > Dynamic binding
 - Variables are dynamically typed and bound

Assignment Project Exam Help

Objects and Classes

Add WeChat powcoder

- > *Every object is an instance of a class*
 - A class specifies the structure and the behaviour of all its instances <https://powcoder.com>
 - Instances of a class share the same behavior and have a specific state Add WeChat powcoder
 - *Classes are objects* that create other instances
 - Metaclasses are classes that create classes as instances
 - Metaclasses describe class behaviour and state (subclasses, method dictionary, instance variables...)

Assignment Project Exam Help

Messages and Methods

Add WeChat powcoder

- > Message — which action to perform

```
aWorkstation accept: aPacket  
aMonster eat: aCookie
```

- > Method — how to carry out the action

```
accept: aPacket [  
    (aPacket isAddressedTo: self)  
    ifTrue:[  
        Transcript show:  
            'A packet is accepted by the Workstation ',  
            self name asString ]  
    ifFalse: [super accept: aPacket]  
]
```

Assignment Project Exam Help

Smalltalk Run-Time Architecture

Add WeChat powcoder

- > Byte-code is translated to native code by a just-in-time compiler
 - Some Smalltalks, but not Pharo
- > Source and changes are not needed to interpret the byte-code.
 - Just needed for development
 - Normally removed for deployment
- > An application can be delivered as byte-code files that will be executed with a VM.
 - The development image is stripped to remove the unnecessary development components.

Assignment Project Exam Help

Objects in Smalltalk

Add WeChat powcoder

- > *Everything* is an object
 - Things only happen by message passing
 - Variables are dynamically bound
- > State is private to objects
 - “protected” for subclasses
- > Methods are public
 - “private” methods by convention only
- > (Nearly) every object is a reference
 - Unused objects are garbage-collected
- > Single inheritance

Assignment Project Exam Help

Smalltalk Syntax on a Postcard

Add WeChat powcoder

```
exampleWithNumber: x [
```

"A method that illustrates every part of Smalltalk method syntax except primitives. It has unary, binary, and key word messages, declares arguments and temporaries (but not block temporaries), accesses a global variable (but not an instance variable), uses literals (array, character, symbol, string, integer, float), uses the pseudo variables true, false, nil, self and super, and has sequence, assignment, return and cascade. It has both zero argument and one argument blocks. It doesn't do anything useful, though"

```
|y|
```

```
true & false not & (nil isNil) ifFalse: [self halt].
```

```
y := self size + super size.
```

```
#$a #a 'a' 1 1.0)
```

```
do: [:each | Transcript
```

```
show: (each class name);
```

```
show: (each printString);
```

```
show: ' '].
```

```
^ x < y
```

```
]
```

Assignment Project Exam Help

Language Constructs

Add WeChat powcoder

<code>^</code>	return
<code>" ... "</code>	comment
<code>#</code>	symbol or array
<code>' ... '</code>	string
<code>[]</code>	block or byte array
<code>.</code>	statement separator
<code>;</code>	message cascade
<code> ... </code>	local or block variable
<code>:=</code>	assignment (also <code>_</code> or <code>←</code>)
<code>\$ _</code>	character
<code>:</code>	end of selector name
<code>_e_ _r_</code>	number exponent or radix
<code>!</code>	file element separator (used in change sets)
<code><primitive: ...></code>	for VM primitive calls

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

Examples

Add WeChat powcoder

comment:	"a comment"
character:	\$c \$h \$a \$r \$a \$c \$t \$e \$r \$s \$# \$@
string:	'a nice string'
symbol:	#mac #+
array:	\$(1 2 3 (1 3) \$a 4)
dynamic array:	{ 1 + 2 . 3 / 4 . 5 * 6 }
Integer:	72, 2101
real:	1.5, 6.03e-34, 2.4e7
fraction:	1/33
boolean:	true, false
pseudo variables	self, super
point:	10@120

Note that @ is not an element of the syntax, but just a message sent to a number. This is the same for /, bitShift:, ifTrue:, do: ...

Assignment Project Exam Help

Messages instead of keywords

Add WeChat powcoder

> In most languages, basic operators and control constructs are defined as language constructs and keywords

> In Smalltalk, there are only *messages* sent to objects

— bitShift: (>>) is just a message sent to a number

```
10 bitShift: 2
```

<https://powcoder.com>

— ifTrue: (if-then-else) is just a message sent to a boolean

```
(x>1) ifTrue: [ Transcript show: 'bigger' ]
```

— do:, to:do: (loops) are just *messages to collections or numbers*

```
##a ##b ##c ##d) do: [:each | Transcript show: each ; cr]  
1 to: 10 do: [:i | Transcript show: i printString; cr]
```

> Minimal parsing

> Language is *extensible*

Assignment Project Exam Help

Smalltalk Syntax

Add WeChat powcoder

Every expression is a message send

> *Unary messages*

```
Transcript cr  
5 factorial
```

<https://powcoder.com>

> *Binary messages*

```
3 + 4  
5 * 6
```

> *Keyword messages*

```
Transcript show: 'hello world'  
2 raisedTo: 32  
segment fromX: 1 fromY: 1  
          toX: 50 toY: 100
```

Assignment Project Exam Help

Precedence

Add WeChat powcoder

(...) > Unary > Binary > Keyword

1. Evaluate *left to right*
2. Unary messages have *highest precedence*
3. Next are binary messages
4. Keyword messages have *lowest precedence*

```
2 raisedTo: 1 + 3 factorial
```

128

5. Use *parentheses* to change precedence

```
1 + 2 * 3
```

```
1 + (2 * 3)
```

9 (!)

7

Assignment Project Exam Help

Binary Messages

Add WeChat powcoder

> Syntax:

- `aReceiver aSelector anArgument`
- Where `aSelector` is made up of 1 or 2 characters from:
+ - / \ * ~ < > = @ % | & ! ? ,
- Except: second character may not be \$

> Examples:

```
2 * 3
5 >= 7
6 = 7
'hello', ' ', 'world'
(3@4) + (1@2)
2<<5
64>>5
```

Assignment Project Exam Help

More syntax

Add WeChat powcoder

- > Comments are enclosed in *double quotes*

```
"This is a comment."
```

Assignment Project Exam Help

- > Use *periods* to separate expressions

<https://powcoder.com>

```
Transcript cr.
```

```
Transcript show: 'hello world'.
```

```
Transcript cr "NB: don't need one here"
```

- > Use *semi-colons* to send a cascade of messages to the same object

```
Transcript cr; show: 'hello world'; cr
```

Assignment Project Exam Help

Variables

Add WeChat powcoder

- > Declare local variables with `| ... |`

Assignment Project Exam Help

<https://powcoder.com>

- > Use `:=` to assign a value to a variable

`x := 1`

- > Old fashioned assignment operator: \leftarrow (must type “_”)

Assignment Project Exam Help

Method Return

Add WeChat powcoder

- > Use a *caret* to return a value from a method or a block

Assignment Project Exam Help

```
max: aNumber
```

```
  ^ self < aNumber
```

```
    ifTrue: [aNumber]
```

```
    ifFalse: [self]
```

<https://powcoder.com>

Add WeChat powcoder

```
1 max: 2
```

```
2
```

- > Methods *always* return a value
 - By default, methods return `self`

Assignment Project Exam Help

Block closures

Add WeChat powcoder

Assignment Project Exam Help

- > Use *square brackets* to delay evaluation of expressions
<https://powcoder.com>

```
^ 1 < 2 ifTrue. [smaller] ifFalse. [bigger]
```

```
'smaller'
```

Assignment Project Exam Help

Variables

Add WeChat powcoder

- > *Local variables* within methods (or blocks) are delimited by `| var |`
- > *Block parameters* are delimited by `: var |`

```
OrderedCollection>>collect: aBlock [  
  "Evaluate aBlock with each of my elements as the argument."  
  | newCollection |  
  newCollection := self species new: self size.  
  firstIndex to: lastIndex do:  
    [ :index |  
      newCollection addLast: (aBlock value: (array at: index))].  
  ^ newCollection  
]
```

```
[ :n | |x y| x := n+1. y := n-1. x * y] value: 10
```

99

Assignment Project Exam Help

Control Structures

Add WeChat powcoder

- > *Every control structure is realized by message sends*

```
|n|  
n := 10.  
[n>0] whileTrue:  
    [ Transcript display: n; cr.  
      n := n-1
```

```
1 to: 10 do: [:n| Transcript display: n; cr ]
```

```
(1 to: 10) do: [:n| Transcript display: n; cr ]
```

Assignment Project Exam Help

Creating objects

Add WeChat powcoder

> *Class methods*

```
OrderedCollection new  
Array new: 200  
Array with: 10 with: 20 with: 30
```

Add WeChat powcoder

> *Factory methods*

```
1@2      "a Point"  
1/2      "a Fraction"
```

Assignment Project Exam Help

Creating classes

Add WeChat powcoder

- > Send a message to a class (!)

Assignment Project Exam Help

```
Number subclass: #Complex
```

<https://powcoder.com>

```
Complex instanceVariableNames: 'real imaginary'
```

Add WeChat powcoder

Assignment Project Exam Help

Some Conventions

Add WeChat powcoder

- > Method selector is a *symbol*, e.g., #add:
- > Method scope conventions using >>
(for displaying the methods of a class)

— *Instance Method* defined in the class Node

```
Node>accept: aBlock
```

— *Class Method* defined in the class Node class
(i.e., in the class of the the class Node)

```
Node class>>withName: aSymbol
```

- > aSomething is an instance of the class Something

Assignment Project Exam Help

Example: Money (abstract Smalltalk syntax)

Add WeChat powcoder

- > We define Money as a subclass of Object, with getters and setters

Assignment Project Exam Help

```
Object subclass: #Money.
```

```
Money instanceVariableNames: 'amount currency'.
```

Add WeChat powcoder

```
Money>>amount: aNumber  
amount := aNumber.
```

```
Money>>amount  
^ amount
```

```
Money>>currency: aString  
currency := aString.
```

```
Money>>currency  
^ currency
```

Assignment Project Exam Help

GNU Smalltalk syntax

Add WeChat powcoder

- > We define Money as a subclass of Object, with getters and setters

Assignment Project Exam Help

```
Object subclass: #Money.  
Money instanceVariableNames: 'amount currency'.  
  
Money extend [  
    amount [ ^amount ]  
    amount: aNumber [ amount := aNumber ]  
    currency [ ^currency ]  
    currency: aString [ currency := aString ]  
].
```


Assignment Project Exam Help

Test cases

Add WeChat powcoder

```
x := Money new currency: 'USD'; amount: 100.  
y := Money new currency: 'Euro'; amount: 500.  
  
x amount println. "100"  
x currency println. "'USD'"  
y amount println. "500"  
y currency println. "'Euro'"  
  
x amount: 999.  
y currency: 'Yen'.  
  
x amount println. "999"  
x currency println. "'USD'"  
y amount println. "500"  
y currency println. "'Yen'"
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

Comparisons (binary operators)

Add WeChat powcoder

```
Money>>= aMoney
  ^ self currency = aMoney currency
  and: [ self amount = aMoney amount ]
```

```
Money>>~= aMoney
  ^ (self = aMoney) not
```

```
Money extend [ "GNU Smalltalk syntax"
  = aMoney [
    ^ self currency = aMoney currency
    and: [ self amount = aMoney amount ]
  ]
  ~= aMoney [ ^ (self = aMoney) not ]
].
```

Assignment Project Exam Help

More test cases

Add WeChat powcoder

```
x := Money new currency: 'USD'; amount: 100.  
y := Money new currency: 'Euro'; amount: 500.  
z := Money new currency: 'USD'; amount: 100.
```

```
(x = y) println. "false"
```

```
(x ~= y) println. "true"
```

```
(x = z) println. "true"
```

```
(x ~= z) println. "false"
```

Assignment Project Exam Help

Using GNU Smalltalk

Add WeChat powcoder

```
> gst
    "evaluates Smalltalk code line-by-line"
st> 2 + 3 * 4
20
st> "press control-D to exit interpreter"

> gst Money.st
    "runs all the Smalltalk code in given file"

> gst
st> FileStream fileIn: 'Money.st'
    "loads and runs code in file, stays in gst"
st>
```