

# Parallel Computing with GPUs: Shared Memory

Assignment Project Exam Help

<https://powcoder.com>

Dr Paul Richmond

Add WeChat powcoder

<http://paulrichmond.shef.ac.uk/teaching/COM4521/>




The  
University  
Of  
Sheffield.

 NVIDIA

GPU  
RESEARCH  
CENTER

## Mark Distribution for MOLE Quiz 1




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Average Mark: 71%

# Grids, Blocks, Warps & Threads



# Grids, Blocks, Warps & Threads

- ❑ Blocks map to SMs
  - ❑ SMs may have more than one block
  - ❑ Blocks are split into warps by hardware (always pick block size multiple of 32)
  - ❑ Blocks do not migrate between SMs
  - ❑ No guarantee of order of block execution
  - ❑ No communication or synchronisation between blocks
- ❑ Threads map to CUDA cores
  - ❑ Executed in partitions of 32, called warps
  - ❑ Lots of warps means lots of opportunity to hide memory movement

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



# Review of last week

- ❑ We have seen the importance of different types of memory
  - ❑ And observed the performance improvement from read-only and constant cache usage
- ❑ So far we have seen how CUDA can be used for performing thread local computations; e.g.
  - ❑ Load data from memory to registers
  - ❑ Perform thread-local computations
  - ❑ Store results back to global memory
- ❑ We will now consider another important type of memory
  - ❑ Shared memory

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

☐ Shared Memory

☐ Shared Memory Bank Conflicts

☐ 2D Shared Memory Bank Conflicts

☐ Boundary Conditions for Shared Memory Loading

☐ Host-side Configurations for Shared Memory

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Shared Memory

## Architecture Details

- ❑ In Kepler (64KB) of Shared Memory is split between Shared Memory and L1 cache

- ❑ The ratio to SM and L1 can be configured

- ❑ In Maxwell 64KB of Shared Memory is dedicated

- ❑ Its just another Cache, right?


- ❑ User configurable

- ❑ Requires manually loading and synchronising data

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



# Shared Memory

## ☐ Performance

- ☐ Shared memory is very fast
- ☐ Bandwidth > 1 TB/s

## ☐ Block level computation

- ☐ Challenges the thread level view...
- ☐ Allows data to be shared between threads in the same block
- ☐ User configurable cache at the thread block level
- ☐ Still no broader synchronisation beyond the level of thread blocks

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




# Block Local Computation

- ❑ Partition data into groups that fit into shared memory
- ❑ Load subset of data into shared memory
- ❑ Perform computation on the subset
- ❑ Copy subset back to global memory

Assignment Project Exam Help

<https://powcoder.com>



# Move, execute, move

## ☐ From Host view

- ☐ Move: Data to GPU memory
- ☐ Execute: Kernel
- ☐ Move: Data back to host

## ☐ From Device view

- ☐ Move: Data from device memory to registers
- ☐ Execute: instructions
- ☐ Move: Data back to device memory

## ☐ From Host view

- ☐ Move: Data to GPU memory
- ☐ Execute: Kernel
- ☐ Move: Data back to host

## ☐ From Device view

- ☐ Move: Data from device memory to local cache
- ☐ Execute: subset of kernel (reusing cached values)
- ☐ Move: Data back to device memory

## ☐ From Block View

- ☐ Move: Data from local cache
- ☐ Execute: instructions
- ☐ Move: Data back to local cache (or device memory)

Thread level parallelism

Block level parallelism



# A Case for Shared Memory

```
__global__ void sum3_kernel(int *c, int *a)
{
    int i = blockIdx.x*blockDim.x + threadIdx.x;
    int left, right;

    //load value at i-1
    left = 0;
    if (i > 0)
        left = a[i - 1];

    //load value at i+1
    right = 0;
    if (i < (N - 1))
        right = a[i + 1];

    c[i] = left + a[i] + right; //sum three values
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Do we have a candidate for block level parallelism using shared memory?

# A Case for Shared Memory

```
__global__ void sum3_kernel(int *c, int *a)
{
    int i = blockIdx.x*blockDim.x + threadIdx.x;
    int left, right;

    //load value at i-1
    left = 0;
    if (i > 0)
        left = a[i - 1];

    //load value at i+1
    right = 0;
    if (i < (N - 1))
        right = a[i + 1];

    c[i] = left + a[i] + right; //sum three values
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- ☐ Currently: Thread-local computation
- ☐ Bandwidth limited
  - ☐ Requires three loads per thread (at index  $i-1$ ,  $i$ , and  $i+1$ )
- ☐ Block level solution: load each value only once!



# CUDA Shared memory

- ❑ Shared memory between threads in the same block can be defined using `__shared__`
- ❑ Shared variables are only accessible from within device functions
  - ❑ Not addressable in host code
- ❑ Must be careful to avoid race conditions
  - ❑ Multiple threads writing to the same shared memory variable
    - ❑ Results in undefined behaviour
  - ❑ Typically write to shared memory using `threadIdx`
  - ❑ Thread level synchronisation is available through `__syncthreads()`
    - ❑ Synchronises threads in the block

```
__shared__ int s_data[BLOCK_SIZE];
```



# Example

```
__global__ void sum3_kernel(int *c, int *a)
{
    __shared__ int s_data[BLOCK_SIZE];

    int i = blockIdx.x*blockDim.x + threadIdx.x;
    int left, right;

    s_data[threadIdx.x] = a[i];
    __syncthreads();

    //load value at i-1
    left = 0;
    if (i > 0){
        left = s_data[threadIdx.x - 1];
    }

    //load value at i+1
    right = 0;
    if (i < (N - 1)){
        right = s_data[threadIdx.x + 1];
    }

    c[i] = left + s_data[threadIdx.x] + right; //sum
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- ☐ Allocate a shared array
  - ☐ One integer element per thread
- ☐ Each thread loads a single item to shared memory
- ☐ Call `__syncthreads` to ensure shared memory data is populated by all threads
- ☐ Load all elements through shared memory

What is wrong with this code?

# Example

```
__global__ void sum3_kernel(int *c, int *a)
{
    __shared__ int s_data[BLOCK_SIZE];

    int i = blockIdx.x*blockDim.x + threadIdx.x;
    int left, right;

    s_data[threadIdx.x] = a[i];
    __syncthreads();

    //load value at i-1
    left = 0;
    if (i > 0){
        if (threadIdx.x > 0)
            left = s_data[threadIdx.x - 1];
        else
            left = a[i - 1];
    }

    //load value at i+1
    right = 0;
    if (i < (N - 1)){
        if (threadIdx.x < (BLOCK_SIZE-1))
            right = s_data[threadIdx.x + 1];
        else
            right = a[i + 1];
    }

    c[i] = left + s_data[threadIdx.x] + right; //sum
}
```

❑ Additional step required!

❑ Check boundary conditions for the edge of the block

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Problems with Shared memory

- ❑ In the example we saw the introduction of boundary conditions
  - ❑ Global loads still present at boundaries
  - ❑ We have introduced divergence in the code (remember the SIMD model)
  - ❑ This is even more prevalent in 2D examples where we *tile* data into shared memory

```
//boundary condition
left = 0;
if (i > 0){
    if (threadIdx.x > 0)
        left = s_data[threadIdx.x - 1];
    else
        left = a[i - 1];
}
```



☐ Shared Memory

☐ Shared Memory Bank Conflicts

☐ 2D Shared Memory Bank Conflicts

☐ Boundary Conditions for Shared Memory Loading

☐ Host-side Configurations for Shared Memory

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Shared Memory Bank Conflicts

- ❑ Shared memory is arranged into 4byte (32bit banks)

- ❑ A load or store of  $N$  addresses spanning  $N$  distinct banks can be serviced simultaneously

- ❑ Overall bandwidth of  $\times N$  a single module

- ❑ Kepler+ can also serve broadcast accesses simultaneously

- ❑ A bank conflict occurs when two threads request addresses from the same bank

- ❑ Results in serialisation of the access

- ❑ Bank conflicts only occur between threads in a warp

- ❑ There are 32 banks and 32 threads per warp

- ❑ If two threads in a warp access the same bank this is said to be a 2-way bank conflict

Think about you block sized array of floats

**bank = (index \* stride) % 32**

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Access Strides

❑ Stride refers to the size (in increments of the bank size) between each threads memory access pattern


❑ If threads access consecutive 4 byte values (e.g. `int` or `float`) then the stride is 1.

❑ No conflicts

❑ If a thread accesses consecutive 8 bytes values (e.g. `double`) then the stride is 2.

❑ 2 way conflicts

❑ In general odd strides result in no conflicts



Stride (4 byte)	1		
TPB	128		
<b>threadIdx.x</b>		<b>index</b>	<b>bank</b>
0		0	1
1		1	2
2		2	3
3		3	4
4		4	5
5		5	6
6		6	7
7		7	8
8		8	9
9		9	10
10		10	11
31		31	12
		<b>Banks Used</b>	32
		<b>Max Conflicts</b>	1

$$\text{bank} = (\text{index} * \text{stride}) \% 32$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



## More on SM banks


- ❑ Irregular access is fine as long as no bank conflicts
- ❑ Multiple threads can access the same bank conflict-free if they access addresses in broadcast
- ❑ Broadcast can be to any number of threads in a warp

```
__shared__ float s_data[??];  
//read from shared memory using broadcast  
  
some_thread_value = s_data[0] ;
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder





# Strided access example

```
__shared__ char s_data[BLOCK_SIZE];  
  
//load or calculate some_thread_value  
  
s_data[threadIdx.x] = some_thread_value;  
__syncthreads();
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Thread	Bank
0	0
1	1
2	2
3	3
4	4
5	5
6	6
7	7
...	...
31	31

- ☐ What is the stride?
- ☐ What is the level of conflict?
- ☐ How can this be improved?

# Strided access example


```
__shared__ char s_data[BLOCK_SIZE];  
  
//load or calculate some_thread_value  
  
s_data[threadIdx.x] = some_thread_value;  
__syncthreads();
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- ❑ What is the stride? Less than 1 (0.25)
- ❑ What is the level of conflict? 4 way
- ❑ How can this be improved? Increase the stride



# Increase the stride (OK solution)


```
__shared__ char s_data[BLOCK_SIZE*4];  
  
//load or calculate some_thread_value  
  
s_data[threadIdx.x*4] = some_thread_value;  
__syncthreads();
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- ❑ What is the stride? 1
- ❑ What is the level of conflict? 1 way (no conflict)
- ❑ How can this be improved? Use less memory!



...



# Increase the stride (good solution)

```
__shared__ char s_data[BLOCK_SIZE+1];  
  
//load or calculate some_thread_value  
  
s_data[CONFLICT_FREE(threadIdx.x)] = some_thread_value;  
__syncthreads();
```


where

```
#define CHAR_MULTIPLIER 4  
#define CONFLICT_FREE(x) (x*CHAR_MULTIPLIER % (BLOCK_SIZE+1))
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



❑ What is the stride? 1

❑ What is the level of conflict? 1 way (no conflict)

❑ How much shared memory is required?  $BLOCK\_SIZE+1$

## Increase the stride (good solution)

stride	0.25		
multiplier	4		
block_size	128		
threadIdx.x		adjusted index	bank
0		0	0
1		4	1
2		8	2
3		12	3
4		16	4
5		20	5
6		24	6
7		28	7
8		32	8
9		36	9
10		40	10
...		...	...
127		121	30
		Banks Used	32
		Max Conflicts	1

```
=(tid*multiplier) % (block_size+1)
```

$$= (\text{index} * \text{stride}) \% 32$$

# Assignment Project Exam Help

<https://powcoder.com>

# Add WeChat powcoder

□ BLOCK SIZE+1 unique

❑ Much better than  
BLOCK SIZE\*4 unique indices

- ❑ Shared Memory
- ❑ Shared Memory Bank Conflicts
- ❑ 2D Shared Memory Bank Conflicts
- ❑ Boundary Conditions for Shared Memory Loading
- ❑ Host-side Configurations for Shared Memory

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Bank conflicts with 2D tiles

```
__global__ void image_kernel(float *image)
{
    __shared__ float s_data[BLOCK_DIM][BLOCK_DIM];

    for (int i = 0; i < BLOCK_DIM; i++) {
        some_thread_value += f(s_data[threadIdx.x][i]);
    }
}
```

❑ Example where each thread (of 2D block) operates on a row

❑ Loads values by column

bank = threadIdx.x \* stride % 32

Assignment Project Exam Help

<https://powcoder.com>

Shared Memory Bank

Add WeChat																31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2	3	4	5	6	7									31
0	1	2														

Add WeChat powcoder



# Bank conflicts with 2D tiles

```
__global__ void image_kernel(float *image)
{
    __shared__ float s_data[BLOCK_DIM][BLOCK_DIM];

    for (int i = 0; i < BLOCK_DIM; i++) {
        some_thread_value += f(s_data[threadIdx.x][i]);
    }
}
```

❑ Example where each thread (of 2D block) operates on a row

❑ Loads values by column

bank = threadIdx.x \* stride % 32

BLOCK\_DIM=32

i=0

Shared Memory Bank

0	1	2	3	4	5	6	7		31
0	1	2	3	4	5	6	7		31
0	1	2	3	4	5	6	7		31
0	1	2	3	4	5	6	7		31
0	1	2	3	4	5	6	7		31
0	1	2	3	4	5	6	7		31
0	1	2	3	4	5	6	7		31
0	1	2	3	4	5	6	7		31
0	1	2	3	4	5	6	7		0

<https://powcoder.com>

Add WeChat powcoder

❑ 32 way bank conflicts!

❑ Very bad

❑ Stride = 32

# Bank conflicts with 2D tiles

```
__global__ void image_kernel(float *image)
{
    __shared__ float s_data[BLOCK_DIM][BLOCK_DIM];

    for (int i = 0; i < BLOCK_DIM; i++) {
        some_thread_value += f(s_data[threadIdx.x][i]);
    }
}
```

❑ Example where each thread (of 2D block) operates on a row

❑ Loads values by column

bank = threadIdx.x \* stride % 32

BLOCK\_DIM=32

Shared Memory Bank

0	1	2	3	4	5	6	7		31
0	1	2	3	4	5	6	7		31
0	1	2	3	4	5	6	7		31
0	1	2	3	4	5	6	7		31
0	1	2	3	4	5	6	7		31
0	1	2	3	4	5	6	7		31
0	1	2	3	4	5	6	7		31
0	1	2	3	4	5	6	7		31
0	1	2	3	4	5	6	7		0

<https://powcoder.com>

Add WeChat powcoder

❑ How to fix

❑ Memory padding

❑ Transpose the matrix

❑ Or operate on columns (loading by row) if possible

i=0

# Bank conflicts with 2D tiles

```
__global__ void image_kernel(float *image)
{
    __shared__ float s_data[BLOCK_DIM][BLOCK_DIM+1];

    for (int i = 0; i < BLOCK_DIM; i++){
        some_thread_value += f(d_data[threadIdx.x][i]);
    }
}
```

## ❑ Memory Padding Solution

```
bank = threadIdx.x * stride % 32
```

BLOCK DIM+1=33

## Shared Memory Bank

0	1	2	3	4	5	6	7	8	9	10
1	2	3	4	5	6	7	8			1
2	3	4	5	6	7	8	9			2
3	4	5	6	7	8	9	10			3
4	5	6	7	8	9	10	11			4
5	6	7	8	9	10	11	12			5
6	7	8	9	10	11	12	13			6
7	8	9	10	11	12	13	14			7
31	0	1	2	3	4	5	6			31

# Assignment Project Exam Help

0.52  
<https://powcoder.com>

# Add WeChat powcoder

# Bank conflicts with 2D tiles

```
__global__ void image_kernel(float *image)
{
    __shared__ float s_data[BLOCK_DIM][BLOCK_DIM+1];

    for (int i = 0; i < BLOCK_DIM; i++){
        some_thread_value += f(d_data[threadIdx.x][i]);
    }
}
```

## ❑ Memory Padding Solution

bank = threadIdx.x \* stride % 32

BLOCK\_DIM+1=33

Shared Memory Bank

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32
2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33
3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34
4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35
5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37
7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38
8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39
9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42
12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43
13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44
14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45
15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46
16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47
17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48
18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49
19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50
20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52
22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53
23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54
24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55
25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56
26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57
27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58
28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59
29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60
30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61
31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62

<https://powcoder.com>

Add WeChat powcoder

❑ Every thread in warp reads from different bank

❑ *Alternative: Transpose solution left to you!*

i=0



- ❑ Shared Memory
- ❑ Shared Memory Bank Conflicts
- ❑ 2D Shared Memory Bank Conflicts
- ❑ Boundary Conditions for Shared Memory Loading
- ❑ Host-side Configurations for Shared Memory

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Boundary Conditions & Shared Memory Tiling

- ❑ Consider a 2D problem where data is gathered from neighbouring cells
  - ❑ Each cell reads 8 values (gather pattern)
  - ❑ Sounds like a good candidate for shared memory
    - ❑ We can tile data into memory



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Thread Block size is 8x8

- Data tiled into shared memory
- Data not tiled into shared memory



Gather pattern

# Problem with our tiling approach

1	2	3	3	3	3	3	3	2	1
2	4	6	6	6	6	6	6	4	2
3	6	8	8	8	8	8	8	6	3
3	6	8	8	8	8	8	8	6	3
3	6	8	8	8	8	8	8	6	3
3	6	8	8	8	8	8	8	6	3
3	6	8	8	8	8	8	8	6	3
3	6	8	8	8	8	8	8	6	3
2	4	6	6	6	6	6	6	4	2
1	2	3	3	3	3	3	3	2	1

❑ Memory access pattern is good for values inside the boundary

❑ 448 cached reads

❑ 96 loads

❑ Memory outside of boundary is loaded multiple times

❑ 92 un-cached reads

❑ 92 loads

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Boundary Condition Improvements

## ❑ Launch more threads

- ❑ Launch thread block of  $DIM+2 \times DIM+2$
- ❑ Allocate one element of space per thread in SM
- ❑ Every thread loads one value
- ❑ Only threads in inner  $DIM \times DIM$  compute values
  - ❑ Causes under utilisation

$$Utilisation = \frac{DIM^2}{(DIM + 2)^2}$$

DIM	Utilisation
8	64%
12	73%
16	79%
20	83%
24	85%
28	87%
32	89%
36	90%
40	91%
44	91%
48	92%

## ❑ Use more shared memory per thread

- ❑ Launch same  $DIM \times DIM$  threads
- ❑ Allocate  $DIM+2 \times DIM+2$  elements of space in SM
- ❑ Threads on boundary load multiple elements
  - ❑ Causes unbalanced loads
- ❑ All threads perform compute values

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



- ❑ Shared Memory
- ❑ Shared Memory Bank Conflicts
- ❑ 2D Shared Memory Bank Conflicts
- ❑ Boundary Conditions for Shared Memory Loading
- ❑ Host-side Configurations for Shared Memory

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Dynamically Assigned Shared Memory

- ❑ It is possible to dynamically assign shared memory at runtime.
- ❑ Requires both a host and device modification to code
  - ❑ Device: Must declare shared memory as extern
  - ❑ Host: Must declare shared memory size in kernel launch parameters

```
unsigned int sm_size = sizeof(float)*DIM*DIM;  
image_kernel<<<blocksPerGrid, threadsPerBlock, sm_size >>>(d_image);  
  
__global__ void image_kernel(float *image)  
{  
    extern __shared__ float s_data[];  
}
```

Is equivalent to

```
image_kernel<<<blocksPerGrid, threadsPerBlock>>>(d_image);  
  
__global__ void image_kernel(float *image)  
{  
    __shared__ float *s_data[DIM][DIM];  
}
```

## Summary

- ❑ Shared Memory introduces the idea of block level computation rather than just thread level computation
- ❑ Shared Memory is a limited resource but can be very useful for reducing global memory bandwidth
  - ❑ Where data is reused
- ❑ Shared Memory requires user synchronisation unlike other general purpose caches (i.e. L1, L2, L3, Texture)
- ❑ For optimal performance memory banks must be considered and boundary conditions must be handled
- ❑ There are hardware specific options for configuring how Shared Memory is used

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Acknowledgements and Further Reading

- ❑ <http://cuda-programming.blogspot.co.uk/2013/02/bank-conflicts-in-shared-memory-in-cuda.html>
- ❑ <http://acceleware.com/blog/maximizing-shared-memory-bandwidth-nvidia-tesla-k10>

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



# Shared Memory Preferences

❑ In Compute 2.0+ (Fermi) and Compute 3.0+ devices (Kepler) it is possible to configure the ratio of SM and L1 with host function

❑ `cudaDeviceSetCacheConfig(enum cudaFuncCache)`

❑ does this for all kernels

❑ `cudaFuncSetCacheConfig(enum cudaFuncCache)`

❑ for a single kernel

❑ Possible values are;

❑ `cudaFuncCachePreferNone`: default cache configuration

❑ `cudaFuncCachePreferShared`: 48KB SM and 16 KB L1

❑ `cudaFuncCachePreferL1`: 16KB SM and 64 KB L1

❑ `cudaFuncCachePreferEqual`: 32KB SM and 32KB L1 (only available on Kepler)

❑ Not required in Maxwell

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder