

BINARY

ARITHMETIC

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Bernhard Kainz (with thanks to **A. Gopalan**, **N. Dulay** and **E. Edwards**)

b.kainz@imperial.ac.uk

Binary Arithmetic

- Unsigned

- Addition, Subtraction, Multiplication and Division

Assignment Project Exam Help

<https://powcoder.com>

- Signed

Add WeChat powcoder

- Two's Complement Addition, Subtraction, Multiplication and Division
 - Chosen because of its widespread use

Binary Arithmetic

- Couple of definitions

- Subtrahend: what is being subtracted

- Minuend: what it is being subtracted from

- Example: $612 - 485 = 127$

- 485 is the subtrahend, 612 is the minuend, 127 is the result

Binary Addition – Unsigned

- Reasonably straight forward
- Example: Perform the binary addition $111011 + 101010$

Assignment Project Exam Help

Carry		1	1	1		1		
A			1	1	1	0	1	1
B			1	0	1	0	1	0
Sum		1	1	0	0	1	0	1
Step		7	6	5	4	3	2	1

In Decimal: $59 + 42 = 101$

Binary Subtraction – Unsigned

- Reasonably straight forward as well 😊
- Example: Perform the binary subtraction $1010101 - 11100$

A''		0	1	10			
A'		1	0	0	10		
A		1	0	1	0	1	0
B				1	1	1	0
Diff		0	1	1	0	0	1
Step		7	6	5	4	3	2

Step k	$A_k - B_k = \text{Diff}_k$	
1	$1 - 0 = 1$	
2	$0 - 0 = 0$	
3	$1 - 1 = 0$	
4	$0 - 1$ give	Borrow by subtracting 1 from $A_{7..5}=101$ to give $A'_{7..5}=100$ and $A'_4=10$. Now use A' instead of A , e.g. $A'_4 - B_4$
5	$10 - 1 = 1$ $0 - 1$ $=01, A''_5 = 10$.	Subtract 1 from $A'_{7..6}=10$ to give $A''_{7..6}$. Now use A'' instead of A' , e.g. $A''_5 - B_5$
6	$10 - 1 = 1$ $1 - 0 = 1$ i.e. $A''_6 - B_6$.	
7	$0 - 0 = 0$	

Binary Multiplication – Unsigned

- Example: Perform the binary multiplication 11101 x 111

Assignment Project Exam Help

A				1	1	1	0	1
B						1	1	1
				1	1	1	0	1
				1	1	0	1	
		1	1	1	0	1		
Answer	1	1	0	0	1	0	1	1
Carry	1	10	10	1	1			

Binary Division – Unsigned

- Recall:

- Division is: $\frac{\text{dividend}}{\text{divisor}} = \text{quotient} + \frac{\text{remainder}}{\text{divisor}}$
- Or: $\text{dividend} = \text{quotient} \times \text{divisor} + \text{remainder}$
- Left as an exercise ☺
 - Can use long division

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Binary Arithmetic – Signed

- Two's complement Arithmetic because of its widespread use

- Recall

Assignment Project Exam Help

- Addition and subtraction in two's complement works without having a separate sign bit

<https://powcoder.com>

Add WeChat powcoder

- Overflow

- Result of an arithmetic operation is too large or too small to fit into the resultant bit-group (E.g.: 9 can't fit into 4-bits in Two's complement)
- Normally left to programmer to deal with this situation

Two's Complement – Addition

- Add the values and discard any carry-out bit
- Example: Add +3 and -5 using 8-bit two's complement

<https://powcoder.com>

(+3)	0000 1011		(-2)	1111 1100	
+(-8)	1111 1000		+(-5)	1111 1011	
(-5)	1111 1011		(-7)	1 1111 1001	
				↑ Discard Carry-Out	

Two's Complement – Addition

- Overflow

- Occurs if and only if 2 Two's Complement numbers are added and they both have the same sign (both positive or both negative) and the result has the opposite sign
 - Adding two positive numbers must give a positive result
 - Adding two negative numbers must give a negative result
- Never occurs when adding operands with different signs
- E.g.
 - $(+A) + (+B) = -C$
 - $(-A) + (-B) = +C$


Two's Complement – Addition

- Overflow

- Example: Using 4-bit Two's Complement numbers ($-8 \leq x \leq +7$), calculate $(-7) + (-6)$

<https://powcoder.com>

(-7)	1001	
+(-6)	1010	
(+3)	1 0011	"Overflow"



Add WeChat powcoder

Two's Complement – Subtraction

- Accomplished by negating the subtrahend and adding it to the minuend
 - Any carry-out bit is discarded
- Example: Calculate $8 - 5$ using an 8-bit two's complement representation
 - Recall: $8 - 5 \rightarrow 8 + (-5)$

(+8)	0000 1000		0000 1000
-(+5)	0000 0101	-> Negate ->	+ 1111 1011
(+3)			1 0000 0011
			↑ Discard

Two's Complement – Subtraction

- Overflow

- Occurs if and only if 2 two's complement numbers are subtracted, and their signs are different, and the result has the same sign as the subtrahend

<https://powcoder.com>

- E.g.

Add WeChat powcoder

- $(+A) - (-B) = -C$
- $(-A) - (+B) = +C$

Two's Complement – Subtraction

- Overflow

- Example: Using 4-bit Two's Complement numbers ($-8 \leq x \leq +7$), calculate $7 - (-6)$

<https://powcoder.com>

Add WeChat powcoder

(+7)	0111
(-6)	1010

(+7)	0111
$-(-6)$	0110 (Negated)
(-3)	1101 “Overflow”

Two's Complement – Summary

- Addition

- Add the values, discarding any carry-out bit

Assignment Project Exam Help

- Subtraction

- Negate the subtrahend and add, discarding any carry-out bit

<https://powcoder.com>

- Overflow

Add WeChat powcoder

- Adding two positive numbers produces a negative result
 - Adding two negative numbers produces a positive result
 - Adding operands of unlike signs never produces an overflow
 - **Note** - discarding the carry out of the most significant bit during Two's Complement addition is a normal occurrence, and does not by itself indicate overflow

Two's Complement – Multiplication and Division

- Cannot be accomplished using the standard technique

- Example: consider $X * (-Y)$

- Two's complement of $-Y$ is $2^n - Y \Rightarrow X * (Y) = X * (2^n - Y) = 2^n X - XY$

<https://powcoder.com>
Add WeChat powcoder

- Expected result should be $2^{2n} - XY$

Signed multiplication

- Booth's multiplication algorithm
- Let **m** and **r** be the multiplicand and multiplier, respectively; and let x and y represent the number of bits in **m** and **r**.
- Determine the values of A and S , and the initial value of P . All of these numbers should have a length equal to $(x + y + 1)$.
 - A : Fill the most significant (leftmost) bits with the value of **m**. Fill the remaining $(y + 1)$ bits with zeros.
 - S : Fill the most significant bits with the value of $(-m)$ in two's complement notation. Fill the remaining $(y + 1)$ bits with zeros.
 - P : Fill the most significant x bits with zeros. To the right of this, append the value of **r**. Fill the least significant (rightmost) bit with a zero.
- Determine the two least significant (rightmost) bits of P .
 - If they are 01, find the value of $P + A$. Ignore any overflow.
 - If they are 10, find the value of $P + S$. Ignore any overflow.
 - If they are 00, do nothing. Use P directly in the next step.
 - If they are 11, do nothing. Use P directly in the next step.
- Arithmetically shift the value obtained in the 2nd step by a single place to the right. Let P now equal this new value.
- Repeat steps 2 and 3 until they have been done y times.
- Drop the least significant (rightmost) bit from P . This is the product of **m** and **r**.

Booth's multiplication example

- Find $3 \times (-4)$, with $m = 3$ and $r = -4$, and $x = 4$ and $y = 4$:
- $m = 0011$, $-m = 1101$, $r = 1100$
- $A = 0011\ 0000\ 0$
- $S = 1101\ 0000\ 0$
- $P = 0000\ 1100\ 0$
- Perform the loop four times.
 - $P = 0000\ 1100\ 0$. The last two bits are 00.
 - $P = 0000\ 0110\ 0$. Arithmetic right shift.
 - $P = 0000\ 0110\ 0$. The last two bits are 00.
 - $P = 0000\ 0011\ 0$. Arithmetic right shift.
 - $P = 0000\ 0011\ 0$. The last two bits are 10.
 - $P = 1101\ 0011\ 0$. $P = P + S$.
 - $P = 1110\ 1001\ 1$. Arithmetic right shift.
 - $P = 1110\ 1001\ 1$. The last two bits are 11.
 - $P = 1111\ 0100\ 1$. Arithmetic right shift.
- The product is $1111\ 0100$, which is -12 .

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Two's Complement – Multiplication and Division

- Can perform multiplication and division by converting the two's complement numbers to their absolute values and then negate the result if the signs of the operands are different

Assignment Project Exam Help

<https://powcoder.com>

- Most architectures implement more sophisticated algorithms (Booth's multiplication algorithm, Wallace tree, Dadda multiplier)

Add WeChat powcoder