

Sequences

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Class outline:

- Box+Pointer
- Slicing
- Recursive exercises
- Built-ins for iterables

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Where to ask questions?

- **Zoom chat:** Good if you like getting responses from classmates or the lecture helper.
- **Zoom Q&A:** Good for asking questions that likely interest most students, and that should be answered in lecture.
- **Post-lecture OH:** Good for recapping a topic that went too fast. Or any questions!
- **Piazza thread:** Good for longer questions, tangential questions, or any unanswered questions.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Box + Pointer

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Lists in environment diagrams

Lists are represented as a row of index-labeled adjacent boxes, one per element.

```
pair = [1, 2]
```

Assignment Project Exam Help

<https://powcoder.com>



Try in PythonTutor.

Add WeChat powcoder

Nested lists in environment diagrams


Each box either contains a primitive value or points to a compound value.

```
matrix = [ [1,2,0,4], [0,1,3,-1], [0,0,1,8] ]
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Nested lists in environment diagrams

A very nested list:

```
worst_list = [ [1, 2],  
               [],  
               [3, False, None],  
               [4, lambda: 5]]
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



View in PythonTutor

Slicing

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Slicing syntax

Slicing a list creates a new list with a subsequence of the original list.

```
letters = ["A", "B", "C", "D", "E", "F"]  
#      0 1 2 3 4 5
```

```
sublist1 = letters[1:]  
sublist2 = letters[1:4]
```

Slicing also works for strings.

```
compound_word = "cortauñas"
```

```
word1 = compound_word[:5]  
word2 = compound_word[5:]
```

Negatives indices and steps can also be specified.

Slicing syntax

Slicing a list creates a new list with a subsequence of the original list.

```
letters = ["A", "B", "C", "D", "E", "F"]  
#      0 1 2 3 4 5
```

```
sublist1 = letters[1:]    # ['B', 'C', 'D', 'E', 'F']  
sublist2 = letters[1:4]
```

Slicing also works for strings.

```
compound_word = "cortauñas"
```

```
word1 = compound_word[:5]  
word2 = compound_word[5:]
```

Negatives indices and steps can also be specified.

Slicing syntax

Slicing a list creates a new list with a subsequence of the original list.

```
letters = ["A", "B", "C", "D", "E", "F"]  
# 0 1 2 3 4 5  
sublist1 = letters[1:] # ['B', 'C', 'D', 'E', 'F']  
sublist2 = letters[1:4] # ['B', 'C', 'D']
```

Assignment Project Exam Help
<https://powcoder.com>

Slicing also works for strings.

```
compound_word = "cortauñas"  
  
word1 = compound_word[:5]  
word2 = compound_word[5:]
```

Add WeChat powcoder

Negatives indices and steps can also be specified.

Slicing syntax

Slicing a list creates a new list with a subsequence of the original list.

```
letters = ["A", "B", "C", "D", "E", "F"]  
#      0 1 2 3 4 5  
sublist1 = letters[1:]    # ['B', 'C', 'D', 'E', 'F']  
sublist2 = letters[1:4]   # ['B', 'C', 'D']
```

Assignment Project Exam Help
<https://powcoder.com>

Slicing also works for strings.

```
compound_word = "cortauñas"  
  
word1 = compound_word[:5]    # "corta"  
word2 = compound_word[5:]
```

Add WeChat powcoder

Negatives indices and steps can also be specified.

Slicing syntax

Slicing a list creates a new list with a subsequence of the original list.

```
letters = ["A", "B", "C", "D", "E", "F"]  
# 0 1 2 3 4 5  
sublist1 = letters[1:] # ['B', 'C', 'D', 'E', 'F']  
sublist2 = letters[1:4] # ['B', 'C', 'D']
```

Assignment Project Exam Help
<https://powcoder.com>

Slicing also works for strings.

```
compound_word = "cortauñas"  
  
word1 = compound_word[:5] # "corta"  
word2 = compound_word[5:] # "úñas"
```

Add WeChat powcoder

Negatives indices and steps can also be specified.

Copying whole lists

Slicing a whole list copies a list:

```
listA = [2, 3]
listB = listA
```

```
listC = listA[:]  
listA[0] = 4  
listB[1] = 5
```

Assignment Project Exam Help

<https://powcoder.com>

`list()` creates a new list containing existing elements from any iterable:

Add WeChat powcoder

```
listA = [2, 3]
listB = listA
```

```
listC = list(listA)  
listA[0] = 4  
listB[1] = 5
```



Try both in PythonTutor.

Python3 provides more ways in the `copy` module.

Recursion exercises

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Recursively sum a list

Let's code this up recursively:

```
def sum_nums(nums):
```

```
    """Returns the sum of the numbers in NUMS.
```

```
>>> sum_nums([5, 24, 1984])
```

```
2014
```

```
>>> sum_nums([-32, 0, 32])
```

```
0
```

```
"""
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Docstrings typically would not specify whether an approach was recursive or iterative, since that is an implementation detail.

However, we'll make it clear in assignments and exam questions.

Recursively sum a list (solution)

```
def sum_nums(nums):  
    """Returns the sum of the numbers in NUMS.  
    >>> sum_nums([6, 24, 1984])  
    2014  
    >>> sum_nums([0, 1, 2])  
    0  
    """  
    if (nums == []):  
        return 0  
    else:  
        return nums[0] + sum_nums(nums[1:])
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

When recursively processing lists, the base case is often the empty list and the recursive case is often all-but-the-first items.

Iteratively sum a range

Let's code this up iteratively:

```
def sum_up_to(n):  
    """Returns the sum of positive numbers from 1 up to N (inclusive)  
>>> sum_up_to(5)  
15  
"""
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Iteratively sum a range (solution)

Using the `range` type:

```
def sum_up_to(n):  
    """Returns the sum of positive numbers from 1 up to N (inclusive)  
>>> sum_up_to(5)  
15  
    """  
    sum = 0  
    for n in range(0, n+1):  
        sum += n  
    return sum
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Remember that `range(start, end)` always ends right before `end`.

Recursively sum a range

Now try it recursively:

```
def sum_up_to(n):  
    """Returns the sum of positive numbers from 1 up to N (inclusive)  
>>> sum_up_to(5)  
15  
"""
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Recursively sum a range (solution)

Now try it recursively:

```
def sum_up_to(n):  
    """Returns the sum of positive numbers from 1 up to N (inclusive)  
>>> sum_up_to(5)  
15  
"""  
    if n == 1:  
        return 1  
    else:  
        return n + sum_up_to(n-1)
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Reversing a string

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Recursively reversing a string

```
def reverse(s):  
    """Returns a string with the letters of S  
    in the inverse order.  
>>> reverse('ward')  
'draw'  
"""
```

Assignment Project Exam Help

<https://powcoder.com>

Breaking it down into subproblems:

```
reverse("ward") =  
reverse("ard") =  
reverse("rd") =  
reverse("d") =
```

Add WeChat powcoder

Recursively reversing a string

```
def reverse(s):  
    """Returns a string with the letters of S  
    in the inverse order.  
>>> reverse('ward')  
'draw'  
"""
```

Assignment Project Exam Help

<https://powcoder.com>

Breaking it down into subproblems:

```
reverse("ward") = reverse("ard") + "w"  
reverse("ard") = reverse("rd") + "a"  
reverse("rd") = reverse("d") + "r"  
reverse("d") =
```

Add WeChat powcoder

Recursively reversing a string

```
def reverse(s):  
    """Returns a string with the letters of S  
    in the inverse order.  
    >>> reverse('ward')  
    'draw'  
    """
```

Assignment Project Exam Help

<https://powcoder.com>

Breaking it down into subproblems:

```
reverse("ward") = reverse("ard") + "w"  
reverse("ard") = reverse("rd") + "a"  
reverse("rd") = reverse("d") + "r"  
reverse("d") = "d"
```

Add WeChat powcoder

Recursively reversing a string (solution)

```
def reverse(s):  
    """Returns a string with the letters of S  
    in the inverse order.  
    >>> reverse('ward')  
    'draw'  
    """  
    if len(s) == 1:  
        return s  
    else:  
        return reverse(s[1:]) + s[0]
```


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

When recursively processing strings, the base case is typically an empty string or single-character string, and the recursive case is often all-but-the-first characters.

Recursively reversing a string (visual)



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Exercise: Reversing a number

```
def reverse(n):  
    """Returns N with the digits reversed.  
    >>> reverse_digits(123)  
    321  
    """
```

Assignment Project Exam Help

See walkthrough video here <https://powcoder.com>

Add WeChat powcoder

Helper functions

If a recursive function needs to keep track of more state than the arguments of the original function, you may need a helper function.

```
def fUnKyCaSe(text):  
    """Returns TEXT in fUnKyCaSe  
>>> fUnKyCaSe("wats up")  
'wAtS Up'  
"""
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Helper functions

If a recursive function needs to keep track of more state than the arguments of the original function, you may need a helper function.

```
def fUnKyCaSe(text):  
    """Returns TEXT in fUnKyCaSe  
>>> fUnKyCaSe("wats up")  
'wAtS Up'  
    """  
  
    def toggle_case(letter, should_up_case):  
        return letter.upper() if should_up_case else letter.lower()  
  
    def up_down(text, should_up_case):  
        if len(text) == 1:  
            return toggle_case(text, should_up_case)  
        else:  
            return toggle_case(text[0], should_up_case) + up_down(text[1:], not should_up_case)  
  
    return up_down(text, False)
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Recursion on different data types

Data type	Base case condition	Current item	Recursive case argument
Numbers	<code>== 0</code> <code>== 1</code>	<code>n % 10</code>	<code>n // 10</code>
Lists	<code>== []</code>	<code>L[0]</code>	<code>L[1:]</code> <code>L[-1]</code>
Strings	<code>== ''</code> <code>len(S) == 1</code>	<code>S[0]</code>	<code>S[1:]</code> <code>S[-1]</code>

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Built-in functions for iterables

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Functions that process iterables

The following built-in functions work for sequence types (lists, strings, etc) and any other **iterable** data type.

Function	Description
<code>sum(iterable, start)</code>	Returns the sum of values in <code>iterable</code> , initializing sum to <code>start</code>
<code>all(iterable)</code>	Return <code>True</code> if all elements of <code>iterable</code> are true (or if <code>iterable</code> is empty)
<code>any(iterable)</code>	Return <code>True</code> if any element of <code>iterable</code> is true. Return <code>False</code> if <code>iterable</code> is empty.
<code>max(iterable, key=None)</code>	Return the max value in <code>iterable</code>
<code>min(iterable, key=None)</code>	Return the min value in <code>iterable</code>

Examples with sum/any/all

```
sum([73, 89, 74, 95], 0)  # 331
```

```
all([True, True, True, True])
```

```
any([False, False, False, True])
```

```
all([x < 5 for x in range(5)])
```

```
perfect_square = lambda x: x == round(x ** 0.5) ** 2
```

```
any([perfect_square(x) for x in range(50, 60)])
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Examples with sum/any/all

```
sum([73, 89, 74, 95], 0)  # 331
```

```
all([True, True, True, True])  # True
```

```
any([False, False, False, True])
```

```
all([x < 5 for x in range(5)])
```

```
perfect_square = lambda x: x == round(x ** 0.5) ** 2
```

```
any([perfect_square(x) for x in range(50, 60)])
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Examples with sum/any/all

```
sum([73, 89, 74, 95], 0)  # 331
```

```
all([True, True, True, True])  # True
```

```
any([False, False, False, True])  # True
```

```
all([x < 5 for x in range(5)])
```

```
perfect_square = lambda x: x == round(x ** 0.5) ** 2
```

```
any([perfect_square(x) for x in range(50, 60)])
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Examples with sum/any/all

```
sum([73, 89, 74, 95], 0) # 331
```

```
all([True, True, True, True]) # True
```

```
any([False, False, False, True]) # True
```

```
all([x < 5 for x in range(5)]) # True
```

```
perfect_square = lambda x: x == round(x ** 0.5) ** 2
```

```
any([perfect_square(x) for x in range(50, 60)])
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Examples with sum/any/all

```
sum([73, 89, 74, 95], 0) # 331
```

```
all([True, True, True, True]) # True
```

```
any([False, False, False, True]) # True
```

```
all([x < 5 for x in range(5)]) # True
```

```
perfect_square = lambda x: x == round(x ** 0.5) ** 2
```

```
any([perfect_square(x) for x in range(50, 60)]) # False
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Examples with max/min

```
max([73, 89, 74, 95])      # 95  
max(["C+", "B+", "C", "A"])  
max(range(10))
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Examples with max/min

```
max([73, 89, 74, 95])      # 95  
max(["C+", "B+", "C", "A"]) # C+  
max(range(10))
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Examples with max/min

```
max([73, 89, 74, 95])      # 95  
max(["C+", "B+", "C", "A"]) # C+  
max(range(10))             # 9
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Examples with max/min

```
max([73, 89, 74, 95])      # 95
max(["C+", "B+", "C", "A"]) # C+
max(range(10))             # 9
```

A key function can decide how to compare each value:

```
coords = [ [37, -144], [-22, -115], [56, -163] ]
max(coords, key=lambda coord: coord[0])
min(coords, key=lambda coord: coord[0])
```

```
gymnasts = [ ["Brittany", 9.15, 9.4, 9.3, 9.2],
              ["Lea", 9, 8.8, 9.1, 9.5],
              ["Maya", 9.2, 8.7, 9.2, 8.8] ]
min(gymnasts, key=lambda scores: min(scores[1:]))
max(gymnasts, key=lambda scores: sum(scores[1:], 0))
```

Examples with max/min

```
max([73, 89, 74, 95])      # 95
max(["C+", "B+", "C", "A"]) # C+
max(range(10))             # 9
```

A key function can decide how to compare each value:

```
coords = [ [37, -144], [-22, -115], [56, -163] ]
max(coords, key=lambda coord: coord[0]) # [56, -163]
min(coords, key=lambda coord: coord[0])
```

```
gymnasts = [ ["Brittany", 9.15, 9.4, 9.3, 9.2],
              ["Lea", 9, 8.8, 9.1, 9.5],
              ["Maya", 9.2, 8.7, 9.2, 8.8] ]
min(gymnasts, key=lambda scores: min(scores[1:]))
max(gymnasts, key=lambda scores: sum(scores[1:], 0))
```

Examples with max/min

```
max([73, 89, 74, 95])      # 95
max(["C+", "B+", "C", "A"]) # C+
max(range(10))             # 9
```

A key function can decide how to compare each value:

```
coords = [ [37, -144], [-22, -115], [56, -163] ]
max(coords, key=lambda coord: coord[0]) # [56, -163]
min(coords, key=lambda coord: coord[0]) # [-22, -115]
```

```
gymnasts = [ ["Brittany", 9.15, 9.4, 9.3, 9.2],
              ["Lea", 9, 8.8, 9.1, 9.5],
              ["Maya", 9.2, 8.7, 9.2, 8.8] ]
min(gymnasts, key=lambda scores: min(scores[1:]))
max(gymnasts, key=lambda scores: sum(scores[1:], 0))
```

Examples with max/min

```
max([73, 89, 74, 95])      # 95
max(["C+", "B+", "C", "A"]) # C+
max(range(10))             # 9
```

A key function can decide how to compare each value:

```
coords = [ [37, -144], [-22, -115], [56, -163] ]
max(coords, key=lambda coord: coord[0]) # [56, -163]
min(coords, key=lambda coord: coord[0]) # [-22, -115]
```

```
gymnasts = [ ["Brittany", 9.15, 9.4, 9.3, 9.2],
              ["Lea", 9, 8.8, 9.1, 9.5],
              ["Maya", 9.2, 8.7, 9.2, 8.8] ]
min(gymnasts, key=lambda scores: min(scores[1:])) # ["Maya", ..
max(gymnasts, key=lambda scores: sum(scores[1:], 0))
```

Examples with max/min

```
max([73, 89, 74, 95])      # 95
max(["C+", "B+", "C", "A"]) # C+
max(range(10))             # 9
```

A key function can decide how to compare each value:

```
coords = [ [37, -144], [-22, -115], [56, -163] ]
max(coords, key=lambda coord: coord[0]) # [56, -163]
min(coords, key=lambda coord: coord[0]) # [-22, -115]
```

```
gymnasts = [ ["Brittany", 9.15, 9.4, 9.3, 9.2],
              ["Lea", 9, 8.8, 9.1, 9.5],
              ["Maya", 9.2, 8.7, 9.2, 8.8] ]
min(gymnasts, key=lambda scores: min(scores[1:])) # ["Maya", ..
max(gymnasts, key=lambda scores: sum(scores[1:], 0)) # ["Brittany", ..
```

Python Project of The Day!

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Sea Level Rise

Sea Level Rise, by Douwe Osinga: Visualize sea levels and population density on interactive maps.



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Technologies used: Python (notebook) with PIL/numpy/Rasterio,
HTML/CSS/JS with PanZoom
([Github repository](#))