

Assignment Project Exam Help

Algorithms Week 5

<https://powcoder.com>

Ljubomir Perković, DePaul University

Add WeChat powcoder

One of the most famous sequences of numbers is the Fibonacci sequence:

Assignment Project Exam Help
0, 1, 1, 2, 3, 5, 8, 13, 21, 34, ...

<https://powcoder.com>

Add WeChat powcoder

One of the most famous sequences of numbers is the Fibonacci sequence:

Assignment Project Exam Help
0, 1, 1, 2, 3, 5, 8, 13, 21, 34, ...

The sequence can be defined recursively:

$$F(n) = \begin{cases} 1 & \text{if } n = 0 \text{ or } n = 1 \\ F(n-1) + F(n-2) & \text{if } n \geq 2 \end{cases}$$

Add WeChat powcoder

One of the most famous sequences of numbers is the Fibonacci sequence:

Assignment Project Exam Help
0, 1, 1, 2, 3, 5, 8, 13, 21, 34, ...

The sequence can be defined recursively:

<https://powcoder.com>

$$F(n) = \begin{cases} 1 & \text{if } n = 0 \text{ or } n = 1 \\ F(n-1) + F(n-2) & \text{if } n \geq 2 \end{cases}$$

The Fibonacci numbers have various interesting properties, including being related to the golden ratio and its conjugate.

Add WeChat powcoder

$$\phi = \frac{1 + \sqrt{5}}{2} \approx 1.61803 \qquad \hat{\phi} = \frac{1 - \sqrt{5}}{2} \approx -0.61803$$

You could prove by induction that $F(n) = \frac{\phi^n - \hat{\phi}^n}{\sqrt{5}}$.

Fibonacci number recursive algorithm

The obvious algorithm for computing $F(n)$:

```
Fib(n)
  if n = 0 or n = 1
    return 1
  else
    return Fib(n-1) + Fib(n-2)
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Fibonacci number recursive algorithm

The obvious algorithm for computing $F(n)$:

```
Fib(n)
  if n = 0 or n = 1
    return 1
  else
    return Fib(n-1) + Fib(n-2)
```

What is the running time $T(n)$ of this algorithm on input n ?

Fibonacci number recursive algorithm

The obvious algorithm for computing $F(n)$:

```
Fib(n)
  if n = 0 or n = 1
    return 1
  else
    return Fib(n-1) + Fib(n-2)
```

What is the running time $T(n)$ of this algorithm on input n ?


$$T(n) = T(n-1) + T(n-2) + \Theta(1).$$

Consider the recursion tree for $F(n)$:


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Consider the recursion tree for $F(n)$:




Insights:

Consider the recursion tree for $F(n)$:

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Insights:


- The number of recursive calls at depth i is 2^i

Consider the recursion tree for $F(n)$:

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Insights:

- The number of recursive calls at depth i is 2^i
- The shallowest leaf is the leftmost one, with depth $\frac{n}{2}$.

Assignment Project Exam Help

In fact, the solution to the recursion

$$T(n) = T(n-1) + T(n-2) + \Theta(1)$$

is <https://powcoder.com>

$$T(n) = \Theta(\phi^n).$$

Add WeChat powcoder

Assignment Project Exam Help

In fact, the solution to the recursion

$$T(n) = T(n-1) + T(n-2) + \Theta(1)$$

is

<https://powcoder.com>

$$T(n) = \Theta(\phi^n).$$

Add WeChat powcoder

The reason the recursive algorithm is so slow is because the same recursive calls are recomputed over and over.

How do we avoid making all these duplicate recursive calls?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

How do we avoid making all these duplicate recursive calls?

One approach is to augment the recursive algorithm by storing the values returned by the recursive calls.

<https://powcoder.com>

Add WeChat powcoder

How do we avoid making all these duplicate recursive calls?

One approach is to augment the recursive algorithm by storing the values returned by the recursive calls.

- Then, at the beginning of each recursive call, check to see if the value we want already exists.

<https://powcoder.com>

Add WeChat powcoder

How do we avoid making all these duplicate recursive calls?

One approach is to augment the recursive algorithm by storing the values returned by the recursive calls.

- Then, at the beginning of each recursive call, check to see if the value we want already exists.
- If it does, then we re-use it. Otherwise we compute it.

Add WeChat powcoder

How do we avoid making all these duplicate recursive calls?

One approach is to augment the recursive algorithm by storing the values returned by the recursive calls.

- Then, at the beginning of each recursive call, check to see if the value we want already exists.
- If it does, then we re-use it. Otherwise we compute it.

This technique is called memoization.

Add WeChat powcoder

How do we avoid making all these duplicate recursive calls?

One approach is to augment the recursive algorithm by storing the values returned by the recursive calls.

- Then, at the beginning of each recursive call, check to see if the value we want already exists.
- If it does, then we re-use it. Otherwise we compute it.

This technique is called **memoization**. It:

- maintains the familiar, recursive, top-down structure of the algorithm
- but without the exponential costs of re-computing all the values.

Assignment Project Exam Help

Memoized algorithm for Fibonacci numbers:

```
// F[0..n] is a global array
MemFib(n)
  if n = 0 or n = 1 then
    F[n] ← 1
  else if F[n] undefined
    F[n] ← MemFib(n-1) + MemFib(n-2)
  return F[n]
```

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

Memoized algorithm for Fibonacci numbers:


```
// F[0..n] is a global array
MemFib(n)
  if n = 0 or n = 1 then
    F[n] ← 1
  else if F[n] undefined
    F[n] ← MemFib(n-1) + MemFib(n-2)
  return F[n]
```

Running Time?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Assignment Project Exam Help

Memoized algorithm for Fibonacci numbers:

```
// F[0..n] is a global array
MemFib(n)
  if n = 0 or n = 1 then
    F[n] ← 1
  else if F[n] undefined
    F[n] ← MemFib(n-1) + MemFib(n-2)
  return F[n]
```

Running Time? $O(n)$!

Assignment Project Exam Help

Memoized algorithm for Fibonacci numbers:

```
// F[0..n] is a global array
MemFib(n)
  if n = 0 or n = 1 then
    F[n] ← 1
  else if F[n] undefined
    F[n] ← MemFib(n-1) + MemFib(n-2)
  return F[n]
```

Running Time? $O(n)!$ An exponential speedup!

Rather than using a top-down approach to reach the bottom of the recursion and **then** compute Fibonacci numbers bottom-up, dynamic programming does the bottom-up approach directly and iteratively.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Rather than using a top-down approach to reach the bottom of the recursion and then compute Fibonacci numbers bottom-up, dynamic programming does the bottom-up approach directly and iteratively.

To compute $F(n)$:

<https://powcoder.com>

Add WeChat powcoder

0	1	2	3	4	5	6	7

Rather than using a top-down approach to reach the bottom of the recursion and then compute Fibonacci numbers bottom-up, dynamic programming does the bottom-up approach directly and iteratively.

To compute $F(n)$:

- We start by computing $F(2)$ from $F(0) = 1$ and $F(1) = 1$.

Add WeChat powcoder



Rather than using a top-down approach to reach the bottom of the recursion and **then** compute Fibonacci numbers bottom-up, dynamic programming does the bottom-up approach directly and iteratively.

To compute $F(n)$:

- We start by computing $F(2)$ from $F(0) = 1$ and $F(1) = 1$.
- Then we compute $F(3)$ from $F(2)$ and $F(1)$,


Add WeChat powcoder



Rather than using a top-down approach to reach the bottom of the recursion and then compute Fibonacci numbers bottom-up, dynamic programming does the bottom-up approach directly and iteratively.

To compute $F(n)$:

- We start by computing $F(2)$ from $F(0) = 1$ and $F(1) = 1$.
- Then we compute $F(3)$ from $F(2)$ and $F(1)$,
- and then $F(4)$ from $F(3)$ and $F(2)$, and so on.



Assignment Project Exam Help

```
def fib(n):  
    F[0] ← 1  
    F[1] ← 1  
    for i ← 2 to n do  
        F[i] ← F[i-1] + F[i-2]  
    return F[n]
```

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

```
def fib(n):  
    F[0] ← 1  
    F[1] ← 1  
    for i ← 2 to n do  
        F[i] ← F[i-1] + F[i-2]  
    return F[n]
```

<https://powcoder.com>

Running time? Add WeChat powcoder

Assignment Project Exam Help

```
def fib(n):  
    F[0] ← 1  
    F[1] ← 1  
    for i ← 2 to n do  
        F[i] ← F[i-1] + F[i-2]  
    return F[n]
```

<https://powcoder.com>

Running time? Clearly $\Theta(n)$.

Add WeChat powcoder

Assignment Project Exam Help

```
IterFib(n)  
  F[0] ← 1  
  F[1] ← 1  
  for i ← 2 to n do  
    F[i] ← F[i-1] + F[i-2]  
  return F[n]
```

<https://powcoder.com>

Running time? Clearly $\Theta(n)$.
Add WeChat powcoder

Note that this algorithm uses $\Theta(n)$ space. Can you modify it so it uses $\Theta(1)$ space?

The basic idea behind dynamic programming is recursion without repetition.

Assignment Project Exam Help

To develop a dynamic algorithm:

<https://powcoder.com>

Add WeChat powcoder

The basic idea behind dynamic programming is recursion without repetition.

Assignment Project Exam Help

To develop a dynamic algorithm:

- 1 Formulate the problem recursively

<https://powcoder.com>

Add WeChat powcoder

The basic idea behind dynamic programming is recursion without repetition.

Assignment Project Exam Help

To develop a dynamic algorithm:

- 1 Formulate the problem recursively
- 2 Describe the problem that you want to solve recursively

<https://powcoder.com>

Add WeChat powcoder

The basic idea behind dynamic programming is recursion without repetition.

Assignment Project Exam Help

To develop a dynamic algorithm:

- 1 Formulate the problem recursively
 - a Describe the problem that you want to solve recursively
 - b Give a clear recursive formula or algorithm

<https://powcoder.com>

Add WeChat powcoder

The basic idea behind dynamic programming is recursion without repetition.

Assignment Project Exam Help

To develop a dynamic algorithm:

- 1 Formulate the problem recursively
 - a Describe the problem that you want to solve recursively
 - b Give a clear recursive formula or algorithm
- 2 Build solutions to your recurrence from the bottom up

Add WeChat powcoder

The basic idea behind dynamic programming is recursion without repetition.

Assignment Project Exam Help

To develop a dynamic algorithm:

- 1 Formulate the problem recursively
 - a Describe the problem that you want to solve recursively
 - b Give a clear recursive formula or algorithm
- 2 Build solutions to your recurrence from the bottom up
 - a Identify the subproblems

Add WeChat powcoder

The basic idea behind dynamic programming is **recursion without repetition**.

Assignment Project Exam Help

To develop a dynamic algorithm:

- 1 Formulate the problem recursively
 - a Describe the problem that you want to solve recursively
 - b Give a clear recursive formula or algorithm
- 2 Build solutions to your recurrence from the bottom up
 - a Identify the subproblems
 - b Choose a memoization data structure

<https://powcoder.com>

Add WeChat powcoder

The basic idea behind dynamic programming is **recursion without repetition**.

Assignment Project Exam Help

To develop a dynamic algorithm:

- ① Formulate the problem recursively
 - a Describe the problem that you want to solve recursively
 - b Give a clear recursive formula or algorithm
- ② Build solutions to your recurrence from the bottom up
 - a Identify the subproblems
 - b Choose a memoization data structure
 - c Identify dependencies

<https://powcoder.com>

Add WeChat powcoder

The basic idea behind dynamic programming is **recursion without repetition**.

Assignment Project Exam Help

To develop a dynamic algorithm:

- ① Formulate the problem recursively
 - a Describe the problem that you want to solve recursively
 - b Give a clear recursive formula or algorithm
- ② Build solutions to your recurrence from the bottom up
 - a Identify the subproblems
 - b Choose a memoization data structure
 - c Identify dependencies
 - d Find a good evaluation order

<https://powcoder.com>

Add WeChat powcoder

The basic idea behind dynamic programming is **recursion without repetition**.

Assignment Project Exam Help

To develop a dynamic algorithm:

- ① Formulate the problem recursively
 - a Describe the problem that you want to solve recursively
 - b Give a clear recursive formula or algorithm
- ② Build solutions to your recurrence from the bottom up
 - a Identify the subproblems
 - b Choose a memoization data structure
 - c Identify dependencies
 - d Find a good evaluation order
 - e Write down the algorithm

<https://powcoder.com>

Add WeChat powcoder

The basic idea behind dynamic programming is **recursion without repetition**.

Assignment Project Exam Help

To develop a dynamic algorithm:

- ① Formulate the problem recursively
 - a Describe the problem that you want to solve recursively
 - b Give a clear recursive formula or algorithm
- ② Build solutions to your recurrence from the bottom up
 - a Identify the subproblems
 - b Choose a memoization data structure
 - c Identify dependencies
 - d Find a good evaluation order
 - e Write down the algorithm
 - f Analyze space and running time

<https://powcoder.com>

Add WeChat powcoder

Input: A sequence of characters stored in $A[1..n]$.

Output: True if A can be segmented into a sequence of words,
False otherwise.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Input: A sequence of characters stored in $A[1..n]$.

Output: True if A can be segmented into a sequence of words,
False otherwise.

Given: Function $IsWord(w)$ that returns *True* if sequence of
characters w is a word, *False* otherwise.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Input: A sequence of characters stored in $A[1..n]$.

Output: True if A can be segmented into a sequence of words,
False otherwise.

Given: Function $IsWord(w)$ that returns *True* if sequence of characters w is a word, *False* otherwise.

Example: If sequence A consists of characters

<https://powcoder.com>
BOTH EARTH AND SATURN SPIN

and $IsWord(w)$ is True if w is a word in English, then:

Add WeChat powcoder

Input: A sequence of characters stored in $A[1..n]$.

Output: True if A can be segmented into a sequence of words, False otherwise.

Given: Function $IsWord(w)$ that returns *True* if sequence of characters w is a word, *False* otherwise.

Example: If sequence A consists of characters

<https://powcoder.com>
BOTH·EARTH·HANDS·SATURN·SPIN

and $IsWord(w)$ is True if w is a word in English, then:

Add WeChat powcoder
Output *True* because

BOTH·EARTH·AND·SATURN·SPIN
is a valid segmentation of A

Input: A sequence of characters stored in $A[1..n]$.

Output: True if A can be segmented into a sequence of words, False otherwise.

Given: Function $IsWord(w)$ that returns *True* if sequence of characters w is a word, *False* otherwise.

Example: If sequence A consists of characters

<https://powcoder.com>
BOTHEARTHANDSATURNSPIN

and $IsWord(w)$ is True if w is a word in English, then:

Add WeChat powcoder

- Output *True* because
BOTH·EARTH·AND·SATURN·SPIN
is a valid segmentation of A
- By the way,
BOT·HEART·HANDS·AT·URNS·PIN
is another valid segmentation of A .

Dynamic Programming algorithm development, step 1

Formulate the problem recursively

- a. Describe the problem that you want to solve recursively

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Dynamic Programming algorithm development, step 1

Formulate the problem recursively

a. Describe the problem that you want to solve recursively

b. Give a clear recursive formula or algorithm

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Dynamic Programming algorithm development, step 1

Formulate the problem recursively

1. Describe the problem that you want to solve recursively
2. Give a clear recursive formula or algorithm

```
// Is the suffix A[i..n] Splittable?
```

```
Splittable(i):
```

```
    if i > n
```

```
        return True
```

```
    for j ← i to n
```

```
        if Isword(i, j) and Splittable(j + 1)
```

```
            return True
```

```
    return False
```

Dynamic Programming algorithm development, step 1

Formulate the problem recursively

- a. Describe the problem that you want to solve recursively
- b. Give a clear recursive formula or algorithm

```
// Is the suffix A[i..n] Splittable?
```

```
Splittable(i):
```

```
    if i > n
```

```
        return True
```

```
    for j ← i to n
```

```
        if Isword(i, j) and Splittable(j + 1)
```

```
            return True
```

```
    return False
```

Running time?

Dynamic Programming algorithm development, step 1

Formulate the problem recursively

- a. Describe the problem that you want to solve recursively
- b. Give a clear recursive formula or algorithm

```
// Is the suffix A[i..n] Splittable?
```

```
Splittable(i):
```

```
    if i > n
```

```
        return True
```

```
    for j ← i to n
```

```
        if Isword(i, j) and Splittable(j + 1)
```

```
            return True
```

```
    return False
```

Running time? $O(2^n)$

Note that there are:

Only $n + 1$ different ways to call the recursive function `Splittable(i)`, one for each value of i between 1 and $n + 1$

<https://powcoder.com>

Add WeChat powcoder

Note that there are:

- Only $n + 1$ different ways to call the recursive function `Splittable(i)`, one for each value of i between 1 and $n + 1$
- Only $O(n^2)$ different ways to call `IsWord(i, j)`, one for each pair (i, j) such that $1 \leq i \leq j \leq n$

Assignment Project Exam Help
<https://powcoder.com>

Add WeChat powcoder

Note that there are:

Only $n+1$ different ways to call the recursive function `Splittable(i)`, one for each value of i between 1 and $n+1$

- Only $O(n^2)$ different ways to call `IsWord(i, j)`, one for each pair (i, j) such that $1 \leq i \leq j \leq n$

“Why are we spending exponential time computing only a polynomial amount of stuff???”

Add WeChat powcoder

Note that there are:

Only $n+1$ different ways to call the recursive function `Splittable(i)`, one for each value of i between 1 and $n+1$

- Only $O(n^2)$ different ways to call `IsWord(i, j)`, one for each pair (i, j) such that $1 \leq i \leq j \leq n$

“Why are we spending exponential time computing only a polynomial amount of stuff???”

For example:

BLUE	STEM	UNIT	ROBOT	HEARTHANDSATURNSPIN
------	------	------	-------	---------------------

BLUEST	EMU	NITRO	BOT	HEARTHANDSATURNSPIN
--------	-----	-------	-----	---------------------

Dynamic programming algorithm development step 2

Build solutions to your recurrence from the bottom up

- a Each recursive subproblem is `Splittable(i)` with i between 1 and $n + 1$...

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Dynamic programming algorithm development step 2

Build solutions to your recurrence from the bottom up

- a Each recursive subproblem is `Splittable(i)` with i between 1 and $n + 1$...

- b ... so we can memoize the function `Splittable` into an array `SplitTable[1..n+1]`.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Dynamic programming algorithm development step 2

Build solutions to your recurrence from the bottom up

- a Each recursive subproblem is `Splittable(i)` with i between 1 and $n+1$...
- b ... so we can memoize the function `Splittable` into an array `SplitTable[1..n+1]`.
- c Each subproblem `Splittable(i)` depends only on results of subproblems `Splittable(j)` where $j > i$...



- d ... so we should be filling the array in decreasing index order, starting with `SplitTable[n+1] = True`.

Dynamic programming algorithm development step 2

Build solutions to your recurrence from the bottom up

- a Each recursive subproblem is `Splittable(i)` with i between 1 and $n+1$...
- b ... so we can memoize the function `Splittable` into an array `SplitTable[1..n+1]`.
- c Each subproblem `Splittable(i)` depends only on results of subproblems `Splittable(j)` where $j > i$...



- d ... so we should be filling the array in decreasing index order, starting with `SplitTable[n+1] = True`.
- e The algorithm is on the next slide ...
- f Also on next slide, the running time analysis ...

Text segmentation dynamic programming algorithm

Assignment Project Exam Help

```
/* Is A[1..n] splittable?  
FastSplittable(A[1..n]):  
    SplitTable[n + 1] ← True  
    for i ← n down to 1  
        SplitTable[i] ← false  
        for j ← i to n  
            if IsWord(i, j) and SplitTable[j + 1]  
                SplitTable[i] ← true  
    return SplitTable[1]
```

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

```
/* Is A[1..n] splittable?  
FastSplitTable(A[1..n]):  
    SplitTable[n + 1] ← True  
    for i ← n down to 1  
        SplitTable[i] ← false  
        for j ← i to n  
            if IsWord(i, j) and SplitTable[j + 1]  
                SplitTable[i] ← true  
    return SplitTable[1]
```

<https://powcoder.com>

Add WeChat powcoder

Running time?

Assignment Project Exam Help

```
/* Is A[1..n] splittable?  
FastSplitTable(A[1..n]):  
    SplitTable[n + 1] ← True  
    for i ← n down to 1  
        SplitTable[i] ← false  
        for j ← i to n  
            if IsWord(i, j) and SplitTable[j + 1]  
                SplitTable[i] ← true  
    return SplitTable[1]
```

<https://powcoder.com>

Add WeChat powcoder

Running time? $O(n^2)$

Longest Increasing Subsequence

For any sequence S ,

Assignment Project Exam Help

2	6	1	4	2	4	2	9	5	3	5	7	8	3
---	---	---	---	---	---	---	---	---	---	---	---	---	---

<https://powcoder.com>

Add WeChat powcoder

Longest Increasing Subsequence

For any sequence S , a **subsequence** of S is another sequence obtained from S by deleting zero or more elements, without changing the order of the remaining elements.

Assignment Project Exam Help

2	6	1	4	2	4	2	9	5	3	5	7	8	3
---	---	---	---	---	---	---	---	---	---	---	---	---	---

<https://powcoder.com>

Add WeChat powcoder

Longest Increasing Subsequence

For any sequence S , a **subsequence** of S is another sequence obtained from S by deleting zero or more elements, without changing the order of the remaining elements.

Assignment Project Exam Help

2	6	1	4	2	4	2	9	5	3	5	7	8	3
---	---	---	---	---	---	---	---	---	---	---	---	---	---

Problem: Given a sequence of integers S find the Longest Increasing Subsequence (LIS) of S .

<https://powcoder.com>

Add WeChat powcoder

Longest Increasing Subsequence

For any sequence S , a **subsequence** of S is another sequence obtained from S by deleting zero or more elements, without changing the order of the remaining elements.

Assignment Project Exam Help

2 6 1 4 2 4 2 9 5 3 5 7 8 3

Problem: Given a sequence of integers S find the Longest Increasing Subsequence (LIS) of S .

Input: Integer array $A[1..n]$.

Output: Longest possible sequence of indices

$1 \leq i_1 < i_2 < \dots < i_l \leq n$ such that
 $A[i_1] < A[i_2] < \dots < A[i_l]$.

Example: See above.

Dynamic programming algorithm development step 1

Formulate the problem recursively

- a Describe the problem that you want to solve recursively

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Dynamic programming algorithm development step 1

Formulate the problem recursively

- a Describe the problem that you want to solve recursively
- b Give a clear recursive formula or algorithm

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Dynamic programming algorithm development step 1

Formulate the problem recursively

- a Describe the problem that you want to solve recursively
- b Give a clear recursive formula or algorithm

Assignment Project Exam Help

```
// return length of LIS of A[j..n] s.t.  
// every element is larger than A[i]
```

```
LISbigger(i, j):
```

```
    if j > n
```

```
        return 0
```

```
    else if A[i] > A[j]
```

```
        return LISbigger(i, j + 1)
```

```
    else
```

```
        skip ← LISbigger(i, j + 1)
```

```
        take ← LISbigger(j, j + 1) + 1
```

```
        return max{skip, take}
```

<https://powcoder.com>

Add WeChat powcoder

Dynamic programming algorithm development step 1

Formulate the problem recursively

- a Describe the problem that you want to solve recursively
- b Give a clear recursive formula or algorithm

Assignment Project Exam Help

```
// return length of LIS of A[j..n] s.t.  
// every element is larger than A[i]
```

```
LISbigger(i, j):
```

```
    if j > n
```

```
        return 0
```

```
    else if A[i] > A[j]
```

```
        return LISbigger(i, j + 1)
```

```
    else
```

```
        skip ← LISbigger(i, j + 1)
```

```
        take ← LISbigger(j, j + 1) + 1
```

```
        return max{skip, take}
```

Running time?

Dynamic programming algorithm development step 1

Formulate the problem recursively

- a Describe the problem that you want to solve recursively
- b Give a clear recursive formula or algorithm

Assignment Project Exam Help

```
// return length of LIS of A[j..n] s.t.  
// every element is larger than A[i]
```

```
LISbigger(i, j):
```

```
    if j > n
```

```
        return 0
```

```
    else if A[i] ≥ A[j]
```

```
        return LISbigger(i, j + 1)
```

```
    else
```

```
        skip ← LISbigger(i, j + 1)
```

```
        take ← LISbigger(j, j + 1) + 1
```

```
        return max{skip, take}
```

Running time? $O(2^n)$

Assignment Project Exam Help

To develop a dynamic algorithm:

- ① Formulate the problem recursively
 - a Describe the problem that you want to solve recursively
 - b Give a clear recursive formula or algorithm
- ② Build solutions to your recurrence from the bottom up
 - a Identify the subproblems
 - b Choose a memoization data structure
 - c Identify dependencies
 - d Find a good evaluation order
 - e Write down the algorithm
 - f Analyze space and running time

<https://powcoder.com>

Add WeChat powcoder

Dynamic programming algorithm development step 2

Build solutions to your recurrence from the bottom up

- The subproblems are $\text{LISbigger}(i, j + 1)$ and $\text{LISbigger}(j, j + 1)$ with indices i and j with values between 0 and n

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Dynamic programming algorithm development step 2

Build solutions to your recurrence from the bottom up

- a The subproblems are $\text{LISbigger}(i, j + 1)$ and $\text{LISbigger}(j, j + 1)$ with indices i and j with values between 0 and n


- b We can memoize the results of these subproblems into a two dimensional array $\text{LISbigger}[0..n, 1..n+1]$.

Add WeChat powcoder

Dynamic programming algorithm development step 2

Build solutions to your recurrence from the bottom up

- a The subproblems are $\text{LISbigger}(i, j + 1)$ and $\text{LISbigger}(j, j + 1)$ with indices i and j with values between 0 and n .
- b We can memoize the results of these subproblems into a two-dimensional array $\text{LISbigger}[0..n, 1..n+1]$.
- c Each entry $\text{LISbigger}[i, j]$ is filled in using entries $\text{LISbigger}[i, j-1]$ and $\text{LISbigger}[j, j+1]$.



Add WeChat powcoder

Dynamic programming algorithm development step 2

Build solutions to your recurrence from the bottom up

- a The subproblems are $\text{LISbigger}(i, j+1)$ and $\text{LISbigger}(j, j+1)$ with indices i and j with values between 0 and n
- b We can memoize the results of these subproblems into a two dimensional array $\text{LISbigger}[0..n, 1..n+1]$.
- c Each entry $\text{LISbigger}[i, j]$ is filled in using entries $\text{LISbigger}[i, j+1]$ and $\text{LISbigger}[j, j+1]$.
- d Fill in the entries of the two dimensional table column-by-column, right-to-left.

Dynamic programming algorithm development step 2

Build solutions to your recurrence from the bottom up

- a The subproblems are $\text{LISbigger}(i, j+1)$ and $\text{LISbigger}(j, j+1)$ with indices i and j with values between 0 and n
- b We can memoize the results of these subproblems into a two dimensional array $\text{LISbigger}[0..n, 1..n+1]$.
- c Each entry $\text{LISbigger}[i, j]$ is filled in using entries $\text{LISbigger}[i, j+1]$ and $\text{LISbigger}[j, j+1]$.
- d Fill in the entries of the two dimensional table column-by-column, right-to-left.
- e Iterative algorithm on the slide...
- f Running time analysis on the next slide...

```
// return length of LIS of A[1..n]
```

```
FastLIS(A[1 .. n]):
```

```
  A[0] ← -∞
```

```
  for i ← 0 to n
```

```
    LISbigger[i, n + 1] ← 0
```

```
  for j ← n down to 1
```

```
    for i ← 0 to j - 1
```

```
      keep ← 1 + LISbigger[j, j + 1]
```

```
      skip ← LISbigger[i, j + 1]
```

```
      if A[i] ≥ A[j]
```

```
        LISbigger[i, j] ← skip
```

```
      else
```

```
        LISbigger[i, j] ← max{keep, skip}
```

```
  return LISbigger[0, 1]
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
// return length of LIS of A[1..n]
```

```
FastLIS(A[1 .. n]):
```

```
  A[0] ← -∞
```

```
  for i ← 0 to n
```

```
    LISbigger[i, n + 1] ← 0
```

```
  for j ← n down to 1
```

```
    for i ← 0 to j - 1
```

```
      keep ← 1 + LISbigger[j, j + 1]
```

```
      skip ← LISbigger[i, j + 1]
```

```
      if A[i] ≥ A[j]
```

```
        LISbigger[i, j] ← skip
```

```
      else
```

```
        LISbigger[i, j] ← max{keep, skip}
```

```
  return LISbigger[0, 1]
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Running time?

```
// return length of LIS of A[1..n]
```

```
FastLIS(A[1 .. n]):
```

```
  A[0] ← -∞
```

```
  for i ← 0 to n
```

```
    LISbigger[i, n + 1] ← 0
```

```
  for j ← n down to 1
```

```
    for i ← 0 to j - 1
```

```
      keep ← 1 + LISbigger[j, j + 1]
```

```
      skip ← LISbigger[i, j + 1]
```

```
      if A[i] ≥ A[j]
```

```
        LISbigger[i, j] ← skip
```

```
      else
```

```
        LISbigger[i, j] ← max{keep, skip}
```

```
  return LISbigger[0, 1]
```

Running time? $O(n^2)$