

# Assignment Project Exam Help

SQL offers several constructs beyond relational algebra to allow users to write more powerful queries. In the previous lecture, we have studied a collection of constructs for statistical analysis. This lecture will introduce another collection for enhancing the functionality of WHERE and HAVING.

<https://powcoder.com>

We will first discuss WHERE and then HAVING.

Add WeChat powcoder

## Assignment Project Exam Help

Recall that the where clause contains conditions of the form  $A \text{ op } v$  where  $A$  is an attribute/value,  $op$  is an arithmetic operator (e.g.,  $<$ ), and  $v$  is another attribute/value.

Next, we will learn new conditions where <https://powcoder.com>

- $v$  is an SQL statement
- $op$  is an operator that compares a value to the result of  $v$ .

## Add WeChat powcoder

## In $(A_1, \dots, A_n)$ in ([an SQL statement])

where each  $A_i$  is an attribute/value.  $(A_1, \dots, A_n)$  must obey the schema of the table  $T$  returned by the SQL statement.

The expression returns:

- true, if tuple  $(A_1, \dots, A_n)$  appears in  $T$ .
- false, otherwise.

The bracket of " $(A_1, \dots, A_n)$ " can be omitted if  $n = 1$ .

## PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

Assignment Project Exam Help

<https://powcoder.com>

select pid from PROF  
where dept in (select dept from PROF where sal >= 10000)

Try:

Add WeChat powcoder

## PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

# Assignment Project Exam Help

<https://powcoder.com>

select pid from PROF  
where dept in (select dept from PROF where sal >= 10000)

Try:

Add WeChat powcoder

select pid from PROF  
where dept in (CS)

# PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

Assignment Project Exam Help

<https://powcoder.com>

select pid from PROF  
where dept in (select dept from PROF where sal >= 10000)

Result:

Add WeChat powcoder

pid
p1
p3
p6

# PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

## Assignment Project Exam Help

<https://powcoder.com>

select pid from PROF  
where (dept, rank) in (select dept, rank from PROF where sal >= 10000)

Try:

Add WeChat powcoder

## PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

# Assignment Project Exam Help

<https://powcoder.com>

select pid from PROF  
where (dept, rank) in (select dept, rank from PROF where sal >= 10000)

Try:

# Add WeChat powcoder

select pid from PROF  
where (dept, rank) in (CS, full)



# PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Ebol	EE	asst	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

# Assignment Project Exam Help

<https://powcoder.com>

select pid from PROF

where (dept, rank) in (select dept, rank from PROF where sal >= 10000)

Result: Add WeChat powcoder

pid  
p3  
p6

# Assignment Project Exam Help

PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

<https://powcoder.com>

select pid from PROF

where (dept, sal) in (select dept, rank from PROF where sal >= 10000)

**Add WeChat powcoder**  
**Error!** (dept, sal) does not match the schema of the table returned by the nested SQL statement.

Not in

$(A_1, \dots, A_n)$  not in ([; in SQL statement])

where each  $A_i$  is an attribute/value.  $(A_1, \dots, A_n)$  must obey the schema of the table  $T$  returned by the SQL statement.

The expression returns:

- true, if tuple  $(A_1, \dots, A_n)$  does not appear in  $T$ .
- false, otherwise.

The bracket of " $(A_1, \dots, A_n)$ " can be omitted if  $n = 1$ .

# PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

select pid from PROF  
 where (dept,rank) not in  
 (select dept, rank from PROF where sal >= 10000)

Result: Add WeChat powcoder

## PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

# Assignment Project Exam Help

select pid from PROF  
 where (dept, rank) not in  
 (select dept, rank from PROF where sal >= 10000)

Result: Add WeChat powcoder

select pid from PROF  
 where (dept, rank) not in (CS, full)

# PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothea	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

# Assignment Project Exam Help

select pid from PROF  
 where (dept, rank) not in  
 (select dept, rank from PROF where sal >= 10000)

<https://powcoder.com>

Result: Add WeChat powcoder

pid  
 p1  
 p2  
 p4  
 p5

## Assignment Project Exam Help

Some

$A > \text{some} ([\text{an SQL statement}])$

where  $A$  is an attribute/value, and must obey the schema of the table  $T$  returned by the SQL statement.

The expression returns:

- true, if  $A$  is greater than at least one tuple in  $T$
- false, otherwise.

Add WeChat powcoder

## PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

Assignment Project Exam Help

<https://powcoder.com>

select pid from PROF  
where sal > some (select sal from PROF where dept = 'CS')

Result:

Add WeChat powcoder



## PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

# Assignment Project Exam Help

<https://powcoder.com>

select pid from PROF  
where sal > some (select sal from PROF where dept = 'CS')

Result:

Add WeChat powcoder

select pid from PROF  
where sal > some (6000, 10000, 9000)

# PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

## Assignment Project Exam Help

select pid from PROF  
where sal > some (select sal from PROF where dept = 'CS')

Result:

Add WeChat powcoder

pid  
p2  
p3  
p5  
p6

# Assignment Project Exam Help

$A > \text{all} ([\text{an SQL statement}])$

where  $A$  is an attribute/value, and must obey the schema of the table  $T$  returned by the SQL statement.

The expression returns:

- true, if  $A$  is greater than all tuples in  $T$
- false, otherwise.

## PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

# Assignment Project Exam Help

<https://powcoder.com>

select pid from PROF  
where sal > all (select sal from PROF where dept = 'EE')

Try:

# Add WeChat powcoder

## PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

# Assignment Project Exam Help

<https://powcoder.com>

```
select pid from PROF
where sal > all (select sal from PROF where dept = 'EE')
```

Try:

# Add WeChat powcoder

```
select pid from PROF
where sal > all (8000, 5000, 8500)
```

# PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Ebol	EE	asst	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

Assignment Project Exam Help

<https://powcoder.com>

select pid from PROF

where sal > all (select sal from PROF where dept = 'EE')

Result: Add WeChat powcoder

pid  
p3  
p6

# Assignment Project Exam Help

The operator  $>$  in " $>$  some (all)" can be replaced with  $<$ ,  $<=$ ,  $=$ ,  $<>$  and  $>=$ .

The semantics in each case agree with the literal meaning in English. For example, " $<$  some" means "smaller than some element (in a table)".

## Add WeChat powcoder

# Assignment Project Exam Help

Next, we will learn two more useful conditions of the form:

`op ([an SQL statement])`  
<https://powcoder.com>

Add WeChat powcoder



## Exists

exists ([an SQL statement])

The expression returns:

- true, if the SQL statement returns a table with **at least one** tuple.
- false, otherwise.

not exists ([an SQL statement])

The expression returns:

- true, if the SQL statement returns an **empty** table.
- false, otherwise.

## PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	9000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

Assignment Project Exam Help

select pid from PROF as P  
where not exists  
(select sal from PROF  
where sal > P.sal)

### Note

Observe how  $P$  is used in the nested query.

Add WeChat powcoder

Result:

pid  
p3

## PROF

select pid from PROF as P  
where not exists  
(select sal from PROF  
where sal > P.sal)

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

<https://powcoder.com>

Transient:

select pid from PROF as P  
where not exists  
(select sal from PROF  
where sal > 6000 )

Add WeChat powcoder

## PROF

select pid from PROF as P  
where not exists  
(select sal from PROF  
where sal > P.sal)

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

<https://powcoder.com>

Transient:

select pid from PROF as P  
where not exists  
(select sal from PROF  
where sal > 8000 )

Add WeChat powcoder

## PROF

select pid from PROF as P  
where not exists  
(select sal from PROF  
where sal > P.sal)

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

<https://powcoder.com>

Transient:

select pid from PROF as P  
where not exists  
(select sal from PROF  
where sal > 10000 )

Add WeChat powcoder

## PROF

select pid from PROF as P  
where not exists  
(select sal from PROF  
where sal > P.sal)

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Fran	CS	full	9000

What is this query looking for in  
plain English?

pid  
p3

# Assignment Project Exam Help

Next we extend the above discussion to HAVING.

<https://powcoder.com>

Add WeChat powcoder

# Assignment Project Exam Help

```
select A1, ..., At, agg1(B1), ..., aggm(Bm)
```

```
from T1, ..., Tn
```

```
where P
```

```
group by C1, ..., Cg
```

```
having H
```

<https://powcoder.com>

where

- C<sub>1</sub>, ..., C<sub>g</sub> are called group-by attributes.
- H is a group predicate.

Add WeChat powcoder



The group predicate can contain conditions of the form:

$agg(A) \text{ op (SQL statement)}$

where

- $agg$  is an aggregate function
- $op$  can be
  - in, not in
  - $<$  some/all
  - $\leq$  some/all
  - $=$  some/all
  - $<>$  some/all
  - $>$  some/all
  - $\geq$  some/all
- The nested SQL statement must return a table of a single numeric column.

## PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

Assignment Project Exam Help

select dept from PROF  
group by dept  
having avg(sal) >= some (select avg(sal) from PROF)

Transient: Add WeChat powcoder

## PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

# Assignment Project Exam Help

select dept from PROF  
group by dept  
having avg(sal) >= some (select avg(sal) from PROF)

Transient:  
select dept from PROF  
group by dept  
having avg(sal) >= some (7750)

## PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

# Assignment Project Exam Help

select dept from PROF

group by dept

having avg(sal) >= some (7000)

<https://powcoder.com>

Result:

Add WeChat powcoder

## PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

# Assignment Project Exam Help

select dept from PROF

group by dept

having avg(sal) >= some (7750)

<https://powcoder.com>

Result:

pid	name	dept	rank	sal	avg(sal)
p1	Adam	CS	asst	6000	8133.33
p3	Calvin	CS	full	10000	
p6	Frank	CS	full	9000	
p2	Bob	EE	asso	8000	7166.67
p4	Dorothy	EE	asst	5000	
p5	Emily	EE	asso	8500	

# PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asst	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

select dept from PROF  
group by dept

having avg(sal) >= some (select avg(sal) from PROF)

Result:

dept  
cs

## PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Ebol	EE	asst	8000
p3	Carvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

Assignment Project Exam Help

<https://powcoder.com>

select dept from PROF  
group by dept  
having avg(sal) >= some (select sal from PROF)

Try: Add WeChat powcoder

## PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Ebol	EE	asst	8000
p3	Carvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

Assignment Project Exam Help

<https://powcoder.com>

```
select dept from PROF
group by dept
having avg(sal) >= some (select sal from PROF)
```

Try: Add WeChat powcoder

```
select dept from PROF
group by dept
having avg(sal) >= some (6000, 8000, 10000, 5000, 8500, 9000)
```



## PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

# Assignment Project Exam Help

select dept from PROF  
group by dept  
having avg(sal) >= some (6000, 8000, 10000, 5000, 8500, 9000)

Transient:

# Add WeChat powcoder

## PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

# Assignment Project Exam Help

select dept from PROF

group by dept

having avg(sal) >= some (6000, 8000, 10000, 5000, 8500, 9000)

Transient:

pid	name	dept	rank	sal	avg(sal)	
p1	Adam	CS	asst	6000	8333.33	>= some(6000, 8000 10000, 5000 8500, 9000) ?
p3	Calvin	CS	full	10000		
p6	Frank	CS	full	9000		
p2	Bob	EE	asso	8000	7166.67	>= some(6000, 8000 10000, 5000 8500, 9000) ?
p4	Dorothy	EE	asst	5000		
p5	Emily	EE	asso	8000		

PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	9000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8500
p6	Frank	CS	full	9000

# Assignment Project Exam Help

<https://powcoder.com>

```
select dept from PROF
group by dept
having avg(sal) >= some (select sal from PROF)
```

Result Add WeChat powcoder

dept
cs
ee