

Assignment Project Exam Help

SQL offers several constructs beyond relational algebra to allow users to write more powerful queries. In this lecture, we will study a collection of constructs designed for statistical analysis.

<https://powcoder.com>

Add WeChat powcoder

```
select A1, ..., At, agg1(B1), ..., aggm(Bm)  
from T1, ..., Tn  
where P  
group by C1, ..., Cg  
having H
```

where

- T_1, \dots, T_n are tables.
- $A_1, \dots, A_t, B_1, \dots, B_m, C_1, \dots, C_g$ are attributes.
- B_1, \dots, B_m are called **aggregate attributes**.
- C_1, \dots, C_g are called **group-by attributes**.
- Each of A_1, \dots, A_t must be a group-by attribute (i.e., each A_i is identical to some C_j where $j \in [1, t]$).
- P is a **tuple predicate**, and H is an **group predicate**.
- agg_1, \dots, agg_m are **aggregate functions**.

$agg(A)$

- $agg = count$: return the number of the values in A.
- $agg = sum$: return the sum of the values in A.
- $agg = min$: return the minimum value in A.
- $agg = max$: return the maximum value in A.
- $agg = avg$: return the average of the values in A.

Note

A must be numeric for sum, min, max, and avg.

Assignment Project Exam Help

`agg(distinct A)`

- `agg = count`: return the number of **distinct** values in `A`.
- `agg = sum`: return the sum of the **distinct** values in `A`.
- `agg = avg`: return the average of the **distinct** values in `A`.

<https://powcoder.com>

Note

"Distinct" has no effect with `min` and `max`.

Add WeChat powcoder

PROF

pid	name	dept	rank	sal
p1	Adam	CS	ass	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8000

`select count(dept), count(distinct dept), sum(sal), sum(distinct sal)
from PROF`

Let's try.

Add WeChat powcoder

PROF

pid	name	dept	rank	sal
p1	Adam	CS	ass	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8000

```
select count(dept), count(distinct dept), sum(sal), sum(distinct sal)
from PROF
```

Result:

5	2	37000	29000
---	---	-------	-------

PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	6000

Assignment Project Exam Help

```
select count(*), sum(sal), min(sal), max(sal), avg(sal)
from PROF
```

Result:

5 37000 5000 10000 7400

Add WeChat powcoder

Note

count(A) is equivalent to count(*). This is intuitive: count(A) returns the same result no matter which column is used as A. Hence, A can be as well omitted. Note, however, * **cannot** be used with **distinct**, which must always be accompanied by a concrete attribute.

Assignment Project Exam Help

```
select  $A_1, \dots, A_t, agg_1(B_1), \dots, agg_m(B_m)$   
from  $T$   
group by  $C_1, \dots, C_g$ 
```

<https://powcoder.com>

This statement carries out the following steps:

- 1 Divide T into **groups** where each group consists of the tuples that are identical on **all** C_1, \dots, C_g .
- 2 Execute the select clause on each group.

Add WeChat powcoder

PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asst	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8000

select max(sal) from PROF
group by dept

PROF is divided into two groups. The first one includes the tuples with pid = p1, p3 while the second one includes the rest. The query returns:

10000
8000

PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Ebb	EE	asso	8000
p3	Calvin	CS	ful	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8000

Assignment Project Exam Help

```
select dept, rank, count(*) from PROF
group by dept, rank
```

<https://powcoder.com>

Let's try...

Add WeChat powcoder

PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Ebol	EE	asst	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8000

select dept, rank, count(*) from PROF
group by dept, rank

Result:

dept	rank	count
CS	asst	1
CS	full	1
EE	asso	2
EE	asst	1

Assignment Project Exam Help

PROF				
pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8000

<https://powcoder.com>

```
select pid, count(*) from PROF  
group by dept, rank
```

Syntax error Every attribute in the select clause (if not an aggregate attribute) must be a group-by attribute. See the syntax on Slide 3.

Past Muddiest Points - Let's dig deeper!

PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8000

Assignment Project Exam Help

select dept, count(*) from PROF
group by dept, rank

Sort & Grouping...

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p3	Calvin	CS	full	10000
p2	Bob	EE	asso	8000
p5	Emily	EE	asso	8000
p4	Dorothy	EE	asst	5000

Add WeChat powcoder

Past Muddiest Points - Let's dig deeper!

PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asst	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8000

select pid, count(*) from PROF
group by dept, rank

Sort & Grouping...

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p3	Calvin	CS	full	10000
p2	Bob	EE	asso	8000
p5	Emily	EE	asso	8000
p4	Dorothy	EE	asst	5000

pid	count(*)
p1	1
p3	1
p2, p5	2
p4	1

Past Muddiest Points - Let's dig deeper!

PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asst	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8000

select pid, count(*) from PROF
group by dept, rank

Sort & Grouping...

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p3	Calvin	CS	full	10000
p2	Bob	EE	asso	8000
p5	Emily	EE	asso	8000
p4	Dorothy	EE	asst	5000

pid	count(*)
p1	1
p3	1
p2, p5	2
p4	1

Oracle: Syntax Error! MySQL: return p2 or p5, depends on mood!

Assignment Project Exam Help

```
select A1, ..., Ar, agg1(B1), ..., aggn(Bm)  
from T  
group by C1, ..., Cg  
having H
```

This statement carries out the following steps

- 1 Divide T into groups where each group consists of the tuples that are identical on all C_1, \dots, C_g .
- 2 Eliminate the groups that do not satisfy H (i.e., the group predicate).
- 3 Execute the select clause on each of the **remaining** groups.

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

H is a set of aggregate comparisons connected by logic operators: AND, OR, and NOT, where an aggregate comparison has the form

$$\text{agg}(A) \text{ op } v$$

where

- agg is an aggregate function.
- op can be $=, <, >, \leq, \geq, \neq, >.$
- A is an attribute.

<https://powcoder.com>

Add WeChat powcoder

PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8000

Assignment Project Exam Help

```
select rank, max(sal) from PROF
group by rank
having count(*) >= 2
```

<https://powcoder.com>

Let's try...

Add WeChat powcoder

PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8000

Assignment Project Exam Help

```
select rank, max(sal) from PROF
group by rank
having count(*) >= 2
```

<https://powcoder.com>

Add WeChat powcoder

Grouping...

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p4	Dorothy	EE	asst	5000
p2	Bob	EE	asso	8000
p5	Emily	EE	asso	8000
p3	Calvin	CS	full	10000

PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	6000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8000

Assignment Project Exam Help

```
select rank, max(sal) from PROF
group by rank
having count(*) >= 2
```

<https://powcoder.com>

Result:

Add WeChat powcoder

rank	
asst	6000
asso	8000

Note that the group of rank = full has been eliminated by the having clause.

Assignment Project Exam Help

PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asst	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8000

<https://powcoder.com>
select rank, count(*) from PROF
group by rank
having count(*) >= 2 and max(sal) >= 7000

Result:

Add WeChat powcoder

rank
asso
2

Assignment Project Exam Help

```
select A1, ..., At, agg1(B1), ..., aggm(Bm)  
from T
```

```
where P
```

```
group by C1, ..., Cg
```

```
having H
```

<https://powcoder.com>

This statement carries out the following steps:

- 1 Perform a selection on T using P .
- 2 Execute group-by, having and select on the result of the selection.

Add WeChat powcoder

PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Ebb	EE	asst	8000
p3	Calvin	CS	ful	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8000

```
select dept, min(sal) from PROF
where sal >= 8000
group by dept
having count(*) >= 2
```

Let's try...

PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8000

Assignment Project Exam Help

```
select dept, min(sal) from PROF
where sal >= 8000
group by dept
having count(*) >= 2
```

<https://powcoder.com>

Add WeChat powcoder

Grouping...

pid	name	dept	rank	sal
p3	Calvin	CS	full	10000
p2	Bob	EE	asso	8000
p5	Emily	EE	asso	8000

PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Ebol	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8000

```
select dept, min(sal) from PROF
where sal >= 8000
group by dept
having count(*) >= 2
```

Result

dept	
EE	8000

The group dept = CS is eliminated because it has only 1 tuple.

Assignment Project Exam Help

- A comparison in P has the form $A \text{ op } v$, while a comparison in H has the form $\text{agg}(A) \text{ op } v$
- P filters tuples before group by, while H filters groups after group by.

Add WeChat powcoder

Assignment Project Exam Help

```
select A1, ..., At, agg1(B1), ..., aggm(Bm)
```

```
from T1, ..., Tn
```

```
where P
```

```
group by C1, ..., Cg
```

```
having H
```

<https://powcoder.com>

This statement carries out the following steps:

- 1 Perform the cartesian product $T_1 \times \dots \times T_n$.
- 2 Execute where, group-by, having and select on the cartesian product.

Add WeChat powcoder

PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8000

TEACH

pid	cid	year
p1	c1	2011
p2	c2	2012
p1	c2	2012

```

select PROF.pid, count(*)
from PROF, TEACH
where PROF.pid = TEACH.pid
group by PROF.pid
having count(*) >= 2

```

Add WeChat powcoder

Let's try...

PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	asst	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8000

TEACH

pid	cid	year
p1	c1	2011
p2	c2	2012
p1	c2	2012

```

select PROF.pid, count(*)
from PROF, TEACH
where PROF.pid = TEACH.pid
group by PROF.pid
having count(*) >= 2

```

Add WeChat powcoder

pid	name	dept	rank	sal	pid	cid	year
p1	Adam	CS	asst	6000	p1	c1	2011
p1	Adam	CS	asst	6000	p1	c2	2012
p2	Bob	EE	asso	8000	p2	c2	2012

PROF

pid	name	dept	rank	sal
p1	Adam	CS	asst	6000
p2	Bob	EE	asso	8000
p3	Calvin	CS	full	10000
p4	Dorothy	EE	asst	5000
p5	Emily	EE	asso	8000

TEACH

pid	cid	year
p1	c1	2011
p2	c2	2012
p1	c2	2012

```

select PROF.pid, count(*)
from PROF, TEACH
where PROF.pid = TEACH.pid
group by PROF.pid
having count(*) >= 2

```

<https://powcoder.com>

Add WeChat powcoder

Result:

pid	
p1	2

```
SQL> select count(*) from developer_brain;
```

```
select count(*) from developer_brain.  
*
```

ERROR at line 1:

ORA-00942: table or view does not exist

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

http://www.orafaq.com/wiki/Fun_stuff