The core provisions from **Annex IV (Part-ADR.OPS)** of the **EASA Easy Access Rules for Aerodromes**(*Regulation (EU) No 139/2014*) covering **Obstacle Control/Safeguarding** and **Runway Safety (Aerodrome Works & Surface Operations)** are summarized below.

This synthesis presents the mandatory Implementing Rules (Hard Law) alongside the corresponding Acceptable Means of Compliance (AMC) and Guidance Material (GM) (Soft Law).

SECTION 1: OBSTACLE CONTROL & SAFEGUARDING

Point ADR.OPS.B.075 — Safeguarding of aerodromes

(Commission Regulation (EU) No 139/2014)

- **Implementing Rule (Hard Law):**

  1. The aerodrome operator is required to monitor on the aerodrome and its surroundings:

     - Obstacle limitation and protection surfaces (OLS / OPS) established in accordance with the certification basis.
     - The marking and lighting of obstacles to initiate appropriate corrective action within its remit.
     - Hazards arising from human activities and land use (e.g., developments, glare, sources of turbulence, smoke, or wildlife attractants).

  2. The operator must establish and maintain procedures to mitigate operational risks stemming from obstacles, construction, or land use changes within the monitored areas that could compromise the safety of aircraft operations.

- **AMC1 ADR.OPS.B.075 — Monitoring & Coordination:**

  3. **Scope Definition:** The operator, in coordination with the National Competent Authority (such as the DSAC) and the Air Traffic Services (ATS) provider, must define the geographic limits, monitoring frequencies, and specific tasks of the safeguarding process.

  4. **Visual & Instrumental Surveillance:** Daily surveillance procedures must ensure that areas visible during routine movement area inspections are checked for unauthorized structures or mobile equipment penetrating OLS.

  5. **Visual Line-of-Sight Protection:** Safeguarding arrangements must explicitly protect the visual lines of sight required from the control tower visual room (VCR), apron management posts, and the rescue and firefighting (RFFS) watch room.

- **GM1 ADR.OPS.B.075 — Risk Assessment & Local Authority Interface:**

1. Where obstacles or activities fall outside the aerodrome boundary (beyond the direct legal authority of the operator), the operator establishes formal liaison with municipal planning bodies, regional authorities, and the civil aviation directorate to review building permits, crane operations, and zoning plans before development commences.

Point ADR.OPS.B.080 — Marking and lighting of vehicles and other mobile objects

(Commission Regulation (EU) No 139/2014)

- **Implementing Rule:**
  - All vehicles and mobile objects—excluding operating aircraft—deployed on the movement area must be conspicuously marked.
  - When operated at night or in low visibility conditions, vehicles must display service lights (e.g.,flashing obstacle beacons).
  - Dedicated apron-only servicing equipment may be exempted under conditions defined in the aerodrome manual.

SECTION 2: RUNWAY SAFETY & AERODROME WORKS

Point ADR.OPS.B.070 — Aerodrome works safety

(Amended by Regulation (EU) 2020/2148 and ED Decision 2024/004/R)

- **Implementing Rule (Hard Law):**
  - The aerodrome operator must establish and apply procedures ensuring that:
    1. Aircraft safety is not compromised by aerodrome works.
    2. Construction and maintenance activities are protected from hazards caused by operational aircraft (e.g., jet blast, prop wash, engine ingestion).
  - Unannounced or unplanned works on or near active runways and taxiways are prohibited; all activities must follow prior coordination, safety impact assessment, and formal hand-back criteria.
- **AMC1 ADR.OPS.B.070 — Worksite Management & Runway Safety Zones:**
  - **Safety Assessment:** Any work taking place on the manoeuvring area requires a risk assessment evaluating runway incursion potential, surface contamination from debris/FOD, and temporary closures.
  - **Temporary Obstacles:** Equipment, excavated soil, and temporary scaffolding must remain strictly outside the cleared runway strip and approach/take-off climb surfaces while the runway is active.
  - **Reduced Runway Length Operations:** When works necessitate displaced thresholds or shortened declared distances (TORA, TODA, ASDA, LDA), safety buffer zones must be physically demarcated,visual aids/markings adapted, and aeronautical data published via NOTAM without delay.
- **GM1 ADR.OPS.B.070(d) — Worksite Demarcation & Return to Service:**
  - Worksites on or near active paved surfaces must be marked with illuminated frangible barriers,hazard cones, or unserviceability lights.
  - **Return to Service:** Before an affected runway or taxiway segment is reopened to traffic, a joint physical inspection must be conducted to certify that the pavement is broom-clean (free of foreign object debris/FOD), all temporary lighting/signage alterations are restored, and visual aids match published operational conditions.

Key Cross-References for Surveillance & Inspections

Topic	Implementing Rule	Key Soft Law Reference	Focus Area
Runway Strips & Clearances	Part-ADR.OPS.B.015 / B.070	AMC1 ADR.OPS.B.015	Surface conditions, clearance of temporary obstructions on strip margins.
FOD Control Programme	Part-ADR.OPS.B.0	AMC1 ADR.OPS.B.01	Regular runway sweeping, FOD detection mechanisms post-
Surface Guidance / Incursions	Part-ADR.OPS.B.025 / B.030	AMC1 ADR.OPS.B.030	Vehicle driver permits, runway-holding position stopbars, ATS read-backs.
Obstacle Surface	Part-ADR.OPS.B.0	AMC1 / GM1 ADR.OPS.B.07	OLS monitoring protocol, notification of crane permits, local urban planning.