

[OVERVIEW](#) [PACKAGE](#) [CLASS](#) [USE](#) [TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)[PREV CLASS](#) [NEXT CLASS](#) [FRAMES](#) [NO FRAMES](#) [ALL CLASSES](#)[SUMMARY: NESTED](#) | [FIELD](#) | [CONSTR](#) | [METHOD](#) [DETAIL: FIELD](#) | [CONSTR](#) | [METHOD](#)`messageController`

Class MessageControllerSender

```
java.lang.Object
  java.lang.Thread
    messageController.MessageControllerSender
```

All Implemented Interfaces:

```
java.lang.Runnable
```

```
public class MessageControllerSender
  extends java.lang.Thread
```

Sends messages to all tablets connected to the message controller.

Author:

cms549

Nested Class Summary

Nested classes/interfaces inherited from class java.lang.Thread

```
java.lang.Thread.State, java.lang.Thread.UncaughtExceptionHandler
```

Field Summary

Fields inherited from class java.lang.Thread

```
MAX_PRIORITY, MIN_PRIORITY, NORM_PRIORITY
```

Constructor Summary

Constructors

Constructor and Description

```
MessageControllerSender()
```

Constructor

Method Summary

All Methods **Instance Methods** **Concrete Methods**

Modifier and Type	Method and Description
void	run() Starts sending messages in pendingMessage.

Methods inherited from class java.lang.Thread

activeCount, checkAccess, countStackFrames, currentThread, destroy, dumpStack, enumerate, getAllStackTraces, getContextClassLoader, getDefaultUncaughtExceptionHandler, getId, getName, getPriority, getStackTrace, getState, getThreadGroup, getUncaughtExceptionHandler, holdsLock, interrupt, interrupted, isAlive, isDaemon, isInterrupted, join, join, join, resume, setContextClassLoader, setDaemon, setDefaultUncaughtExceptionHandler, setName, setPriority, setUncaughtExceptionHandler, sleep, sleep, start, stop, stop, suspend, toString, yield

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Detail

MessageControllerSender

```
public MessageControllerSender()
```

Constructor

Method Detail

run

```
public void run()
```

Starts sending messages in pendingMessage.

Specified by:

run in interface java.lang.Runnable

Overrides:

```
run in class java.lang.Thread
```

[OVERVIEW](#) [PACKAGE](#) [CLASS](#) [USE](#) [TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)

[PREV CLASS](#) [NEXT CLASS](#) [FRAMES](#) [NO FRAMES](#) [ALL CLASSES](#)

SUMMARY: [NESTED](#) | [FIELD](#) | [CONSTR](#) | [METHOD](#) [DETAIL: FIELD](#) | [CONSTR](#) | [METHOD](#)