

[OVERVIEW](#) [PACKAGE](#) [CLASS](#) [USE](#) [TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)[PREV CLASS](#) [NEXT CLASS](#) [FRAMES](#) [NO FRAMES](#) [ALL CLASSES](#)[SUMMARY: NESTED](#) | [FIELD](#) | [CONSTR](#) | [METHOD](#) [DETAIL: FIELD](#) | [CONSTR](#) | [METHOD](#)

manager

Class ManagerScreen

```
java.lang.Object
  java.awt.Component
    java.awt.Container
      javax.swing.JComponent
        javax.swing.JPanel
          manager.ManagerScreen
```

All Implemented Interfaces:

```
java.awt.image.ImageObserver, java.awt.MenuContainer, java.io.Serializable,
javax.accessibility.Accessible
```

```
public class ManagerScreen
  extends javax.swing.JPanel
```

Panel that is displayed when manager logs on. Shows all of the messages sent by any employees to the manger. Also allows for manager to broadcast a message to all employees.

Author:

cms549

See Also:

[Serialized Form](#)

Nested Class Summary

Nested classes/interfaces inherited from class javax.swing.JComponent

```
javax.swing.JComponent.AccessibleJComponent
```

Nested classes/interfaces inherited from class java.awt.Component

```
java.awt.Component.BaselineResizeBehavior
```

Field Summary

Fields

Modifier and Type	Field and Description
<code>ManagerInterface</code>	<code>mi</code>

Fields inherited from class `javax.swing.JComponent`

`TOOL_TIP_TEXT_KEY`, `UNDEFINED_CONDITION`, `WHEN_ANCESTOR_OF_FOCUSED_COMPONENT`, `WHEN_FOCUSED`, `WHEN_IN_FOCUSED_WINDOW`

Fields inherited from class `java.awt.Component`

`BOTTOM_ALIGNMENT`, `CENTER_ALIGNMENT`, `LEFT_ALIGNMENT`, `RIGHT_ALIGNMENT`, `TOP_ALIGNMENT`

Fields inherited from interface `java.awt.image.ImageObserver`

`ABORT`, `ALLBITS`, `ERROR`, `FRAMEBITS`, `HEIGHT`, `PROPERTIES`, `SOMEBITS`, `WIDTH`

Constructor Summary

Constructors

Constructor and Description

`ManagerScreen`(`ManagerInterface` MI)

Create the panel.

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
<code>void</code>	<code>updateScreen</code> ()

Methods inherited from class `javax.swing.JPanel`

`getAccessibleContext`, `getUI`, `getUIClassID`, `setUI`, `updateUI`

Methods inherited from class `javax.swing.JComponent`

`addAncestorListener`, `addNotify`, `addVetoableChangeListener`, `computeVisibleRect`, `contains`, `createToolTip`, `disable`, `enable`,

firePropertyChange, firePropertyChange, firePropertyChange,
getActionForKeyStroke, getActionMap, getAlignmentX, getAlignmentY,
getAncestorListeners, getAutoscrolls, getBaseline,
getBaselineResizeBehavior, getBorder, getBounds, getClientProperty,
getComponentPopupMenu, getConditionForKeyStroke, getDebugGraphicsOptions,
getDefaultLocale, getFontMetrics, getGraphics, getHeight,
getInheritsPopupMenu, getInputMap, getInputMap, getInputVerifier, getInsets,
getInsets, getListeners, getLocation, getMaximumSize, getMinimumSize,
getNextFocusableComponent, getPopupLocation, getPreferredSize,
getRegisteredKeyStrokes, getRootPane, getSize, getToolTipLocation,
getToolTipText, getToolTipText, getTopLevelAncestor, getTransferHandler,
getVerifyInputWhenFocusTarget, getVetoableChangeListeners, getVisibleRect,
getWidth, getX, getY, grabFocus, hide, isDoubleBuffered,
isLightweightComponent, isManagingFocus, isOpaque,
isOptimizedDrawingEnabled, isPaintingForPrint, isPaintingTile,
isRequestFocusEnabled, isValidRoot, paint, paintImmediately,
paintImmediately, print, printAll, putClientProperty,
registerKeyboardAction, registerKeyboardAction, removeAncestorListener,
removeNotify, removeVetoableChangeListener, repaint, repaint,
requestDefaultFocus, requestFocus, requestFocus, requestFocusInWindow,
resetKeyboardActions, reshape, revalidate, scrollRectToVisible,
setActionMap, setAlignmentX, setAlignmentY, setAutoscrolls, setBackground,
setBorder, setComponentPopupMenu, setDebugGraphicsOptions, setDefaultLocale,
setDoubleBuffered, setEnabled, setFocusTraversalKeys, setFont,
setForeground, setInheritsPopupMenu, setInputMap, setInputVerifier,
setMaximumSize, setMinimumSize, setNextFocusableComponent, setOpaque,
setPreferredSize, setRequestFocusEnabled, setToolTipText,
setTransferHandler, setVerifyInputWhenFocusTarget, setVisible,
unregisterKeyboardAction, update

Methods inherited from class java.awt.Container

add, add, add, add, add, add, addContainerListener, addPropertyChangeListener,
addPropertyChangeListener, applyComponentOrientation,
areFocusTraversalKeysSet, countComponents, deliverEvent, doLayout,
findComponentAt, findComponentAt, getComponent, getComponentAt,
getComponentAt, getComponentCount, getComponents, getComponentZOrder,
getContainerListeners, getFocusTraversalKeys, getFocusTraversalPolicy,
getLayout, getMousePosition, insets, invalidate, isAncestorOf,
isFocusCycleRoot, isFocusCycleRoot, isFocusTraversalPolicyProvider,
isFocusTraversalPolicySet, layout, list, list, locate, minimumSize,
paintComponents, preferredSize, printComponents, remove, remove, removeAll,
removeContainerListener, setComponentZOrder, setFocusCycleRoot,
setFocusTraversalPolicy, setFocusTraversalPolicyProvider, setLayout,
transferFocusDownCycle, validate

Methods inherited from class java.awt.Component

```
action, add, addComponentListener, addFocusListener,
addHierarchyBoundsListener, addHierarchyListener, addInputMethodListener,
addKeyListener, addMouseListener, addMouseMotionListener,
addMouseWheelListener, bounds, checkImage, checkImage, contains,
createImage, createImage, createVolatileImage, createVolatileImage,
dispatchEvent, enable, enableInputMethods, firePropertyChange,
firePropertyChange, firePropertyChange, firePropertyChange,
firePropertyChange, getBackground, getBounds, getColorModel,
getComponentListeners, getComponentOrientation, getCursor, getDropTarget,
getFocusCycleRootAncestor, getFocusListeners, getFocusTraversalKeysEnabled,
getFont, getForeground, getGraphicsConfiguration,
getHierarchyBoundsListeners, getHierarchyListeners, getIgnoreRepaint,
getInputContext, getInputMethodListeners, getInputMethodRequests,
getKeyListeners, getLocale, getLocation, getLocationOnScreen,
getMouseListeners, getMouseMotionListeners, getMousePosition,
getMouseWheelListeners, getName, getParent, getPeer,
getPropertyChangeListeners, getPropertyChangeListeners, getSize, getToolkit,
getTreeLock, gotFocus, handleEvent, hasFocus, imageUpdate, inside,
isBackgroundSet, isCursorSet, isDisplayable, isEnabled, isFocusable,
isFocusOwner, isFocusTraversable, isFontSet, isForegroundSet, isLightweight,
isMaximumSizeSet, isMinimumSizeSet, isPreferredSizeSet, isShowing, isValid,
isVisible, keyDown, keyUp, list, list, list, location, lostFocus, mouseDown,
mouseDrag, mouseEnter, mouseExit, mouseMove, mouseUp, move, nextFocus,
paintAll, postEvent, prepareImage, prepareImage, remove,
removeComponentListener, removeFocusListener, removeHierarchyBoundsListener,
removeHierarchyListener, removeInputMethodListener, removeKeyListener,
removeMouseListener, removeMouseMotionListener, removeMouseWheelListener,
removePropertyChangeListener, removePropertyChangeListener, repaint,
repaint, repaint, resize, resize, setBounds, setBounds,
setComponentOrientation, setCursor, setDropTarget, setFocusable,
setFocusTraversalKeysEnabled, setIgnoreRepaint, setLocale, setLocation,
setLocation, setName, setSize, setSize, show, show, size, toString,
transferFocus, transferFocusBackward, transferFocusUpCycle
```

Methods inherited from class java.lang.Object

```
equals, getClass, hashCode, notify, notifyAll, wait, wait, wait
```

Field Detail

mi

```
public ManagerInterface mi
```

Constructor Detail

ManagerScreen

```
public ManagerScreen(ManagerInterface MI)
```

Create the panel.

Parameters:

waiterInterface -

Method Detail

updateScreen

```
public void updateScreen()
```

[OVERVIEW](#) [PACKAGE](#) [CLASS](#) [USE](#) [TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)

[PREV CLASS](#) [NEXT CLASS](#) [FRAMES](#) [NO FRAMES](#) [ALL CLASSES](#)

[SUMMARY: NESTED](#) | [FIELD](#) | [CONSTR](#) | [METHOD](#) [DETAIL: FIELD](#) | [CONSTR](#) | [METHOD](#)