

Anomaly Detection Overview

Identify rare items/events that differ from normal patterns



Popular Anomaly Detection Algorithms

Key methods for identifying outliers and anomalies



Statistical Methods

- **Z-Score**

Measures standard deviations from mean. Points beyond 3σ are anomalies.

- **IQR (Interquartile Range)**

Uses quartiles Q1 and Q3. Outliers beyond $Q1 - 1.5 \times IQR$ or $Q3 + 1.5 \times IQR$.



Imbalanced data distribution



Defining Normal behavior



Lack of labeled anomalies

Models normal data, identifies points in low-probability regions.



Evolving patterns over time



Distance-based Methods

- **K-Nearest Neighbors (KNN)**

Detects anomalies based on distance to k-nearest neighbors.

- **Mahalanobis Distance**

Accounts for correlation between features in multivariate data.



Density-based Methods

- **LOF (Local Outlier Factor)**

Measures local density deviation. Fast training, effective for local anomalies.

- **DBSCAN**

Clustering algorithm that identifies points not belonging to any cluster.

- **K-Means Clustering**

Points far from cluster centers are considered anomalies.



Ensemble Methods

- **Isolation Forest**

Isolates anomalies using decision trees. Works well on most datasets.

- **Random Forest**

Can be adapted for anomaly detection in classification tasks.



Advanced Methods & Learning Approaches

Modern techniques and learning paradigms for anomaly detection



Machine Learning Methods

- **One-Class SVM**

Creates hypersphere around normal data, separating anomalies.

- **Autoencoders**

Neural networks that reconstruct data. High reconstruction error indicates anomalies.

- **LSTM Networks**

Captures temporal patterns in time-series data for sequence anomaly detection.



Dimensionality Reduction

- **PCA (Principal Component Analysis)**

Reduces dimensions, highlights influential features and outliers.

- **t-SNE**

Non-linear technique for visualizing high-dimensional data and clusters.

- **UMAP**

Fast dimensionality reduction preserving global structure.



Learning Paradigms

Supervised

Requires labeled data with normal and anomalous examples

SVM, Neural Networks, Random Forest

Unsupervised

No labels needed. Most common approach in practice

Isolation Forest, LOF, K-Means, Autoencoders

Semi-supervised

Trained on normal data only, detects deviations

One-Class SVM, Novelty Detection



Key Insight

Algorithm choice depends on data characteristics, computational resources, and whether labels are available. Isolation Forest and LOF are popular starting points due to their effectiveness and ease of use.

Implementation & Popular Tools

Python libraries and practical considerations

Python Libraries

Scikit-learn

Isolation Forest, One-Class SVM, LOF, DBSCAN

PyOD

Python Outlier Detection - 40+ algorithms specialized for anomaly detection

TensorFlow/PyTorch

Deep learning models: Autoencoders, LSTM, Variational Autoencoders

PyCaret

Low-code ML library with built-in anomaly detection module

Implementation Tips

Data Preprocessing

Normalize/standardize features for distance-based methods

Feature Engineering

Create relevant features that capture domain knowledge

Threshold Tuning

Adjust contamination rate based on expected anomaly percentage

Model Comparison

Test multiple algorithms to find best fit for your data

Interpretability

Use explainable methods when stakeholder understanding is critical

Performance Considerations



Speed

LOF: Fast training
Isolation Forest: Moderate



Accuracy

Depends on data characteristics & tuning



Scalability

Consider distributed algorithms for big data



Adaptability

Retrain models for evolving patterns

Best Practice

Start with simple statistical methods (Z-score, IQR) for baseline performance, then progress to more sophisticated algorithms (Isolation Forest, One-Class SVM) if needed. Always validate results with domain experts.