# Electronic Supplement to System One Decision Models: A Survey of the Typed Decision Contract, Its Ecosystem and Its Evidence

AMIR RAFE, PH.D., Texas State University, USA
SUBASISH DAS, PH.D., Texas State University, USA

This electronic supplement accompanies the survey of typed probabilistic decision models. It gives the proofs of the propositions, the search record, the risk-of-bias grade of every study, the card checklist, the census detail, the pattern catalogue and the evidence ledger.

Additional Key Words and Phrases: System One models, decision models, evidence ledger, risk of bias, census

## S1 Proofs of the propositions

This part of the electronic supplement gives the proofs of the three propositions of Section 5 whose arguments take more than a few lines. The proofs of Propositions 5.1, 5.2 and 5.3 are short and appear in the main text. All probabilities below are taken over the population on which the contract is evaluated, and the same arguments hold in a finite sample when every probability is replaced by the corresponding empirical share.

### S1.1 Proof of Proposition 5.4

Proof. The recall identity is the multiplication rule of conditional probability applied to the events $G$ and $H$ given $Y = 1$, and it needs no assumption about how the two stages depend on each other. The cost of one item is the random quantity $C = c_1 + \mathbf{1}_{\text{esc}}\, c_2 + \mathbf{1}_{\text{rev}}\, c_{\text{R}} + L_{\text{res}}$, since the screening stage always runs, and linearity of expectation gives the stated expected cost without any independence among its terms.

Let $p$ be a calibrated probability, so that $\Pr(Y = 1 \mid p) = p$. Flagging an item then has expected cost $(1 - p)\, c_{\text{FP}}$ and passing it has expected cost $p\, c_{\text{FN}}$, so flagging is optimal exactly when $(1 - p)\, c_{\text{FP}} \le p\, c_{\text{FN}}$, which rearranges to $p \ge t^*$ [54].

A review that returns the correct label at cost $c_{\text{R}}$ adds a third action whose expected cost is $c_{\text{R}}$ for every $p$. The optimal action minimizes the three expected costs, as in the reject option of Chow [34], so review is optimal exactly when $c_{\text{R}} \le p\, c_{\text{FN}}$ and $c_{\text{R}} \le (1 - p)\, c_{\text{FP}}$. The inequalities are equivalent to $p \ge c_{\text{R}}/c_{\text{FN}}$ and $p \le 1 - c_{\text{R}}/c_{\text{FP}}$, which is the band (7). The band is non-empty exactly when $c_{\text{R}}/c_{\text{FN}} \le 1 - c_{\text{R}}/c_{\text{FP}}$, and multiplying by $c_{\text{FP}}c_{\text{FN}}$ gives $c_{\text{R}}(c_{\text{FP}} + c_{\text{FN}}) \le c_{\text{FP}}c_{\text{FN}}$, with positive width exactly when the inequality is strict.

The lower edge satisfies $c_{\text{R}}/c_{\text{FN}} \le t^*$ exactly when $c_{\text{R}} \le c_{\text{FP}}c_{\text{FN}}/(c_{\text{FP}} + c_{\text{FN}})$, and the upper edge satisfies $1 - c_{\text{R}}/c_{\text{FP}} \ge t^*$ under the same condition, so a non-empty band always contains $t^*$. Outside the band the rule reduces to the two-action rule, passing items below $c_{\text{R}}/c_{\text{FN}}$ and flagging items above $1 - c_{\text{R}}/c_{\text{FP}}$. Under calibration the expected cost of the rule is $\mathbb{E}[\min(p\, c_{\text{FN}}, (1 - p)\, c_{\text{FP}}, c_{\text{R}})]$ and the expected share of items sent to review is $\Pr(c_{\text{R}}/c_{\text{FN}} \le p \le 1 - c_{\text{R}}/c_{\text{FP}})$, and both depend on the distribution of $p$ alone.

The union bound is Boole's inequality, which holds for events with any dependence. When the failure events are independent with probabilities $e_j$, the probability of at least one failure equals $1 - \prod_j (1 - e_j)$, which never exceeds $\sum_j e_j$. Either expression is an identity or a bound in terms of the rates $\Pr(D_j)$ under the deployed workflow, so it becomes an estimate only when those rates are measured on the inputs that each component receives inside that workflow. □

Authors' Contact Information: Amir Rafe, Ph.D., Texas State University, San Marcos, USA, amir.rafe@txstate.edu; Subasish Das, Ph.D., Texas State University, San Marcos, USA, subasish@txstate.edu.

### S1.2 Proof of Proposition 5.5

Proof. Locality means that the logit of an option is a function $\ell(n, r)$ of its own name and rubric once the state and the question are fixed, and every pair in $\mathcal{N} \times \mathcal{R}$ is realized by some assignment of names to rubrics. The decomposition (8) is the two-way decomposition of the array $\ell$, with $\mu$ its grand mean, $\alpha(r)$ the mean over names minus $\mu$, $\beta(n)$ the mean over rubrics minus $\mu$, and $\gamma$ the remainder. If two such decompositions existed, their difference would be a centered decomposition of the zero array, and averaging it over all cells, over names and over rubrics shows in turn that every term of the difference is zero.

An assignment is a bijection $\sigma$ from rubrics to names, and the returned distribution identifies only log-odds, which remove $\mu$ and any constant shared by the options of one query. The log-odds of rubric $r$ against rubric $r'$ equal $\ell(\sigma(r), r) - \ell(\sigma(r'), r')$. If $\sigma$ gives name $n$ to $r$ and $n'$ to $r'$ and the swap exchanges them, the change in these log-odds equals $2[\beta(n) - \beta(n')] + \gamma(n, r) + \gamma(n, r') - \gamma(n', r) - \gamma(n', r')$. For a binary question $\gamma(n, r) + \gamma(n, r')$ is the sum of $\gamma$ over all rubrics for the name $n$, which is zero, and the same holds for $n'$. For general $K$, averaging the interaction contrast over all ordered pairs of distinct rubrics gives a multiple of $\sum_r \gamma(n, r) - \sum_r \gamma(n', r)$, which is zero, so the average change identifies $\beta(n) - \beta(n')$.

Let the names be random, exchangeable and independent of the rubrics. The log-odds of $r$ against $r'$ are $\ell(N_r, r) - \ell(N_{r'}, r')$, and because $N_r$ and $N_{r'}$ share one marginal distribution, their expectation is $\mathbb{E}_N[\ell(N, r)] - \mathbb{E}_N[\ell(N, r')]$, a function of the rubrics alone. Exchangeability also gives the swapped pair $(N_{r'}, N_r)$ the same joint distribution as $(N_r, N_{r'})$, so a swap has no effect on the distribution of the output.

For name invariance, write $f(n, r) = \beta(n) + \gamma(n, r)$, so that under $\sigma$ the logit of rubric $r$ is $\mu + \alpha(r) + f(\sigma(r), r)$. Two logit vectors give the same softmax distribution exactly when they differ by a constant, so invariance holds exactly when, for a fixed reference $\sigma_0$ and every $\sigma$, the difference $f(\sigma(r), r) - f(\sigma_0(r), r)$ is the same for every rubric $r$. If $\beta \equiv 0$ and $\gamma \equiv 0$ then $f \equiv 0$ and invariance holds. For the converse with $K > 2$, set $G(n, r) = f(n, r) - f(\sigma_0(r), r)$, which invariance makes constant along every bijection. Any two cells $(n, r)$ and $(n', r')$ with $n \neq n'$ and $r \neq r'$ lie on a common bijection, so $G$ takes one value on them. Two cells in one row or one column share a value with a third cell outside both their rows and both their columns, which exists because $K > 2$, so $G$ is a constant $b$.

It follows that $f(n, r) = f(\sigma_0(r), r) + b$ depends on $r$ alone. Averaging $f$ over rubrics gives $\beta(n)$, because $\gamma$ is centered over rubrics, so $\beta$ is constant and, being centered, equal to zero. Then $\gamma(n, r)$ depends on $r$ alone, and centering over names makes it zero. For a binary question the centering leaves one free interaction value $g$, with $\gamma = g$ on the two cells of one assignment and $\gamma = -g$ on the two cells of the other. The log-odds under the two assignments are then $\Delta\alpha + \Delta\beta$ and $\Delta\alpha - \Delta\beta$, in which $g$ cancels, so the outputs coincide exactly when $\Delta\beta = 0$, and $g$ is unidentified and changes no output. □

### S1.3 Proof of Proposition 5.6

Proof. The expected level is a linear map from the probability simplex on the levels, whose dimension is $L - 1$, to the interval $[1, L]$. For $L > 2$ this map is many-to-one, so there are distinct distributions $A$ and $B$ with $m(A) = m(B)$, and the mean does not determine the cumulative probabilities. Let a model issue $A$ for every item while the outcomes follow $B$. Then $\mathbb{E}[Y \mid m(\hat{p})] = m(B) = m(A)$, so the expected level is calibrated, while $A \neq B$ implies that the cumulative probabilities of $A$ and $B$ differ at some $k < L$, where ordinal calibration fails. When $L = 2$ the mean determines the distribution and the two notions coincide.

The worked example of Section 5 is the extreme case in which every cumulative probability fails. Forecast $A$ places 0.8 on the middle level and 0.1 on each neighbor, forecast $B$ places 0.5 on each extreme level, and both have expected level 3.0. The cumulative probability of $B$ equals 0.5 at every $k < L$, while the cumulative probabilities of $A$ are 0, 0.1, 0.1 + 0.8 and 1, none of which equals 0.5.

For strict propriety, let the outcome follow a distribution $q$ with cumulative probabilities $Q_k$. For every threshold $k$ the expected squared difference satisfies $\mathbb{E}[(\hat{F}_k - \mathbf{1}\{Y \le k\})^2] = (\hat{F}_k - Q_k)^2 + Q_k(1 - Q_k)$, which is the Brier score of the threshold event $\{Y \le k\}$ [15]. The expected RPS is the average of these terms over $k < L$, so it is minimized exactly when $\hat{F}_k = Q_k$ for every $k$, and because the cumulative probabilities determine the distribution, the unique minimizer is $\hat{p} = q$ [55, 64].

A program that acts when the level exceeds $k$ consumes the probability $1 - \hat{F}_k$ of that event, and by Proposition 5.4 its Bayes threshold is guaranteed optimal when $\Pr(Y > k \mid \hat{F}_k) = 1 - \hat{F}_k$, which is ordinal calibration at $k$. Neither calibration of the expected level, shown above to be insufficient, nor top-label calibration, which concerns the modal level alone, implies this property. The vendor numbers levels from zero, which shifts every expected level by one and leaves every statement above unchanged. □

## S2 Search strings, sweep log and screening counts

The literature sweep of Section 2 ran through the protocol in the companion repository. Table S1 lists every arXiv application programming interface query the sweep issued, in the order it was run, together with its hit count and any retries the client attempted before a query returned a result or gave up. A query whose client received no feed after its retries is marked as failed rather than as a query with zero hits, and each failed query appears again as a rerun. Sixteen additional identifiers already known from the seed list and from early screening were force included rather than found by a query, and the candidate file of the companion repository lists them. Citation chasing from the launch post and from two early Jev evaluations returned no citing works on OpenAlex or on Semantic Scholar, since both papers were too recent to have accrued citations by the cutoff.

Screening against the definition of Section 2 judged 243 of the 271 candidate arXiv records eligible for the evidence ledger and excluded 28 as unrelated to a typed decision model despite matching a query term. Grey literature outside arXiv contributed 8 further evaluations, for 248 studies in total across the ledger of Section 7.

The second sweep of version v1.2 reran every query of the first over the window from 14 September 2026 to 28 October 2026 and added queries for the models released after the first cutoff, paging through every result. It returned 249 records not screened before. We screened them on title and abstract, extracted the included papers in batches of about ten under the extraction brief of the companion repository, and graded each study against its full text under the written anchors of Section S3. A script then checked that every excerpt of the second sweep appears verbatim in the saved full text and contains the extracted value, or for a table that its caption does and its value appears in the paper. A value computed from printed numbers quotes each of them. Each number that enters the synthesis does so through a selection line that names the ledger row, the column it is read from and the reason, and each accuracy contrast carries a coded comparator class.

The ecosystem census ran a parallel sweep of Hugging Face model and dataset search and of GitHub search, using terms such as system-one, decision model, typed decision, jev, laya, kev, nimble and decider, with every query and its hit count recorded in the companion repository. The Hugging Face sweep returned 513 unique entries created on or after 15 September 2026, and direct lookups of named models brought the screened set to 522 entries. Screening placed 101 of these entries in the tier of original implementations, which define or train their own decision head, and 259 in the tier of derivatives, such as format conversions, quantizations and fine-tunes of an original

**Table S1.** Every arXiv API query of the two literature sweeps, with its hit count and any retries. Queries marked [v1.2] belong to the second sweep, over submissions from 14 September to 28 October 2026.

| Query | Hits | Retries | Outcome |
|---|---|---|---|
| `all:Jev` | 16 | 0 | OK |
| `all:"System One model"` | 3 | 0 | OK |
| `all:"System One models"` | 3 | 0 | OK |
| `all:"decision model" AND all:typed` | 3 | 0 | OK |
| `all:"typed decision"` | 5 | 0 | OK |
| `all:Laya AND all:calibrat*` | – | 4 | No feed after retries, rerun below |
| `all:Kev AND all:decision` | 1 | 0 | OK |
| `all:Nimble AND all:decision` | – | 4 | No feed after retries, rerun below |
| `all:TypeSafe` | – | 4 | No feed after retries, rerun below |
| `all:"decision models" AND all:calibration` | 2 | 0 | OK |
| `abs:"typed probabilistic"` | – | 4 | No feed after retries, rerun below |
| `all:"decision model" AND all:Jev` | 6 | 0 | OK |
| `all:jev-1.13` | – | 4 | No feed after retries, rerun below |
| `all:RLCD` | – | 4 | No feed after retries, rerun below |
| `all:"calibrated decisions"` | 1 | 0 | OK |
| `all:Laya AND all:calibrat* [curl rerun]` | 0 | 3 | OK; 0 not previously screened |
| `all:Nimble AND all:decision [curl rerun]` | 0 | 0 | OK; 0 not previously screened |
| `all:TypeSafe [curl rerun]` | 2 | 0 | OK; 2 not previously screened |
| `abs:"typed probabilistic" [curl rerun]` | 0 | 0 | OK; 0 not previously screened |
| `all:"jev-1.13" [curl rerun]` | 0 | 0 | OK; 0 not previously screened |
| `all:RLCD [curl rerun]` | 2 | 0 | OK; 2 not previously screened |
| `all:"System One" AND all:decision [curl rerun]` | 6 | 0 | OK; 2 not previously screened |
| `all:"decision models" AND all:LLM [curl rerun]` | 2 | 0 | OK; 1 not previously screened |
| `all:Jev [v1.2]` | 182 | 0 | OK; 164 not previously screened [v1.2] |
| `all:"System One model" [v1.2]` | 51 | 0 | OK; 47 not previously screened [v1.2] |
| `all:"System One models" [v1.2]` | 51 | 0 | OK; 47 not previously screened [v1.2] |
| `all:"decision model" AND all:typed [v1.2]` | 66 | 0 | OK; 61 not previously screened [v1.2] |
| `all:"typed decision" [v1.2]` | 58 | 0 | OK; 53 not previously screened [v1.2] |
| `all:Laya AND all:calibrat* [v1.2]` | 0 | 0 | OK; 0 not previously screened [v1.2] |
| `all:Kev AND all:decision [v1.2]` | 10 | 0 | OK; 9 not previously screened [v1.2] |
| `all:Nimble AND all:decision [v1.2]` | 4 | 0 | OK; 4 not previously screened [v1.2] |
| `all:TypeSafe [v1.2]` | 23 | 0 | OK; 21 not previously screened [v1.2] |
| `all:"decision models" AND all:calibration [v1.2]` | 61 | 0 | OK; 58 not previously screened [v1.2] |
| `abs:"typed probabilistic" [v1.2]` | 1 | 0 | OK; 1 not previously screened [v1.2] |
| `all:"decision model" AND all:Jev [v1.2]` | 89 | 0 | OK; 82 not previously screened [v1.2] |
| `all:"jev-1.13" [v1.2]` | 6 | 0 | OK; 6 not previously screened [v1.2] |
| `all:RLCD [v1.2]` | 9 | 0 | OK; 7 not previously screened [v1.2] |
| `all:"calibrated decisions" [v1.2]` | 18 | 0 | OK; 15 not previously screened [v1.2] |
| `all:"System One" AND all:decision [v1.2]` | 58 | 0 | OK; 52 not previously screened [v1.2] |
| `all:"decision models" AND all:LLM [v1.2]` | 58 | 0 | OK; 54 not previously screened [v1.2] |
| `all:"jev-1.14" [v1.2]` | 0 | 0 | OK; 0 not previously screened [v1.2] |
| `all:"Decision-1" AND all:Microsoft [v1.2]` | 0 | 0 | OK; 0 not previously screened [v1.2] |
| `all:Clef AND all:decision [v1.2]` | 5 | 0 | OK; 5 not previously screened [v1.2] |
| `all:"pplx-decider" [v1.2]` | 1 | 0 | OK; 1 not previously screened [v1.2] |
| `all:"Trio-Spark" [v1.2]` | 0 | 0 | OK; 0 not previously screened [v1.2] |
| `all:"System-1" AND all:"decision model" [v1.2]` | 12 | 0 | OK; 12 not previously screened [v1.2] |
| `all:"decision models" AND all:typed [v1.2]` | 66 | 0 | OK; 61 not previously screened [v1.2] |

implementation. The remaining entries split between 54 datasets and 108 exclusions, most of them name collisions or repositories with an empty card. The GitHub sweep screened 226 repositories, and all 226 were created on or after the release date of the hosted model. By category, the screen found 54 integrations, 48 local servers, 47 applications, 36 repositories with training code for an open decision model, 25 evaluation packages, 15 directories and 1 mirror. A concurrent analysis reports many more GitHub projects [121], because it collects every repository that calls the hosted model, while this screen kept the repositories that its search terms returned.

The census sweep of version v1.2 added 2,645 Hugging Face entries and 15,788 GitHub repositories created by 28 October 2026. The GitHub total includes repositories created before the first cutoff that the first sweep, which kept a limited number of results per query, had missed.

A first attempt to rerun eight of the arXiv queries on the cutoff date met a machine-wide rate limit during full-text downloads and received no feed, and the sweep log records that attempt as unresolved rather than as a count of zero. A second rerun through a different HTTP client on the next day was answered for all eight queries, and it is listed in Table S1 with the label curl rerun. It returned three records not screened before, all dated on or before the cutoff, of which two entered the ledger and one was excluded against the definition. Its hit counts are included in the totals above, and the ledger describes the sweep after that rerun.

## S3 Risk-of-bias ratings by study

This part of the electronic supplement reports the risk-of-bias rating that each study in the evidence ledger of Section 7 received. The instrument adapts the domain logic of PROBAST [252] and QUADAS-2 [251] to studies that measure a typed probabilistic decision model. It also follows the concerns that the artificial-intelligence extensions of these tools raise, as set out in the QUADAS-AI tool [208] and in the STARD-AI protocol [207]. Five domains are each rated low, unclear or high. They cover the independence of the reference labels, the sampling design and its reporting, and the pinning of model versions and run dates. They also cover the parity of the tuning budget between the decision model and its comparators, and the exposure of the test items to training data. Each rating carries a one-line justification that cites the full text of the study or its extraction note.

Both sweeps were rated a second time, independently of the first rating. For the first sweep, a computer scientist outside the author team screened all 22 arXiv candidates and agreed on 21, with a kappa of 0.78. The same rater read 40 randomly sampled ledger values from their sources, of which 38 matched, and rated the five domains for a random sample of studies, agreeing on 30 of 40 ratings with a weighted kappa of 0.57. A first round without written anchors had reached a weighted kappa of 0.46, after which the anchors for each domain in the protocol of the companion repository were written from the reasons recorded with the first ratings. The other 19 studies of the first sweep were later rated by 5 further raters who never saw the first rating, each also reading one extracted value per study from its source. They agreed on 60 of 95 domain ratings, with a weighted kappa of 0.44, and on 18 of 19 values. For the second sweep, 10 second raters who never saw the first rating shared the whole of the work. Together they screened all 249 candidates, rated the five domains for all 215 graded studies, read 294 extracted values from their sources, at least one per study, and coded the decision head of 36 census originals. They agreed with the first rating on 235 screening decisions, with a kappa of 0.70, on 793 of 1066 domain ratings, with a weighted kappa of 0.63, on 293 values and on 33 head codes, with a kappa of 0.87. Among the domains, the weighted kappa was highest for sampling and reporting, at 0.74, and for test-set exposure, at 0.71. It was lowest for reference-label independence, at 0.46, and for tuning-budget parity, at 0.51, the two domains that ask how a study built its labels and chose its settings. We adjudicated every disagreement of both rounds against the full text. In the first round this changed six ratings and one extracted value. In the second round we first wrote rules for the cases that the anchors left open,

which the protocol now states, and then decided the 273 disputed domain ratings under them. Of these, 149 kept the first rating and 124 changed, which moved the overall grade of 30 studies. The adjudication also added 6 studies that the first screening had excluded, which we then extracted and graded like every other study. It changed 2 head codes, and the same rule applied to every census original changed 1 more. The later first-sweep round was decided under the same rules and one further rule for model names without a dated snapshot, and 22 of its 35 disputed ratings changed. Every study graded before the adjudication, 242 in all, therefore has an independent second rating. The counts in this section describe the adjudicated ratings. The overall grade follows a fixed rule that is applied mechanically. A study is graded low when all five domains are low, or when exactly one domain is unclear and none is high. It is graded high when reference-label independence or test-set exposure is high, or when any two domains are high, and it is graded some concerns otherwise. Under this rule, 3 of the 248 studies are graded low, 103 are graded some concerns and 142 are graded high. The paper written by the authors of this survey [180] is graded by the same rules as every other study.

The grade distribution is most sensitive to the way public benchmarks are rated on test-set exposure. A rating of high on that domain is reserved for verbatim items with answer keys from openly distributed benchmarks released before 2026, because the training data of the hosted model are undisclosed and the study ran no contamination check. If every such rating is read as unclear instead, 3 studies are graded low, 184 are graded some concerns and 61 are graded high. Among the studies that move from high to some concerns are Li [105] and Yu and Yao [274], whose only high rating is on test-set exposure, and Zhang et al. [278], whose other high rating is on tuning-budget parity. The choice therefore changes the grades of several of the most carefully designed measurement studies in the ledger, while it leaves the grade of every vendor and practitioner source unchanged.

Table S2 gives the five domain ratings and the overall grade for every graded study, with each grey-literature source cited under the key its numbers carry in the main text. Table S3 then gives the recorded justification for each domain rated high, so that a reader can see which feature of a study produced each high rating before reusing one of its numbers.

**Table S2.** Risk-of-bias ratings for every ledger study on D1 reference labels, D2 sampling and reporting, D3 version pinning, D4 tuning parity and D5 test-set exposure, each ● high, ◑ unclear or ○ low.

| Study | D1 | D2 | D3 | D4 | D5 | Overall |
|---|---|---|---|---|---|---|
| Ahmed [1] | ◑ | ○ | ● | ● | ● | high |
| Amit [2] | ◑ | ◑ | ◑ | ◑ | ● | high |
| Antunes et al. [4] | ◑ | ○ | ● | ○ | ◑ | some concerns |
| Asseri and Asseri [5] | ◑ | ○ | ○ | ○ | ● | high |
| Azizi et al. [6] | ◑ | ◑ | ◑ | ○ | ◑ | some concerns |
| Azizi et al. [7] | ● | ◑ | ● | ● | ◑ | high |
| Bailo [8] | ● | ○ | ● | ◑ | ○ | high |
| Bellver-Soler et al. [11] | ◑ | ○ | ● | ● | ● | high |
| Besanson [12] | ● | ○ | ◑ | ○ | ○ | high |
| Brom [16] | ◑ | ○ | ◑ | ◑ | ● | high |
| Bru et al. [17] | ◑ | ○ | ◑ | ◑ | ◑ | some concerns |
| Buecheler et al. [18] | ○ | ○ | ● | ○ | ○ | some concerns |
| Bukhari et al. [19] | ◑ | ◑ | ◑ | ● | ◑ | some concerns |
| Cao et al. [21] | ◑ | ◑ | ◑ | ◑ | ● | high |
| Chen [22] | ○ | ○ | ◑ | ◑ | ◑ | some concerns |
| Chen [24] | ○ | ○ | ◑ | ◑ | ◑ | some concerns |

| Study | D1 | D2 | D3 | D4 | D5 | Overall |
|---|---|---|---|---|---|---|
| Chen and Li [23] | ● | ○ | ◑ | ○ | ○ | high |
| Chen et al. [27] | ◑ | ● | ● | ○ | ● | high |
| Chen [25] | ◑ | ○ | ● | ◑ | ◑ | some concerns |
| Chen et al. [26] | ◑ | ◑ | ● | ◑ | ● | high |
| Chen et al. [30] | ◑ | ○ | ◑ | ◑ | ◑ | some concerns |
| Chen and Le [29] | ◑ | ○ | ○ | ◑ | ◑ | some concerns |
| Chen et al. [28] | ◑ | ◑ | ◑ | ◑ | ◑ | some concerns |
| Cheng et al. [31] | ◑ | ◑ | ● | ◑ | ● | high |
| Cheng et al. [32] | ● | ◑ | ● | ● | ○ | high |
| Chouhan and Perry [33] | ◑ | ○ | ● | ● | ◑ | high |
| Chung et al. [35] | ◑ | ◑ | ◑ | ◑ | ● | high |
| Cinà [36] | ○ | ○ | ● | ● | ◑ | high |
| Dai et al. [40] | ◑ | ◑ | ● | ◑ | ◑ | some concerns |
| Dai et al. [41] | ● | ◑ | ● | ◑ | ○ | high |
| Deka [42] | ◑ | ○ | ◑ | ◑ | ◑ | some concerns |
| Demir [43] | ◑ | ○ | ◑ | ○ | ◑ | some concerns |
| Deng et al. [44] | ◑ | ◑ | ◑ | ○ | ○ | some concerns |
| Denney and DiGiuseppe [45] | ◑ | ○ | ○ | ◑ | ● | high |
| Deußer et al. [46] | ◑ | ○ | ◑ | ◑ | ◑ | some concerns |
| Ding et al. [47] | ◑ | ◑ | ◑ | ● | ◑ | some concerns |
| Ding [48] | ○ | ◑ | ◑ | ◑ | ● | high |
| Dinzinger et al. [49] | ◑ | ◑ | ◑ | ◑ | ● | high |
| Dong et al. [50] | ● | ◑ | ◑ | ● | ○ | high |
| Rosario and Atef [191] | ○ | ○ | ◑ | ● | ● | high |
| dos Santos Barbosa [51] | ○ | ● | ● | ● | ◑ | high |
| Du et al. [52] | ◑ | ◑ | ◑ | ○ | ● | high |
| Duan et al. [53] | ◑ | ◑ | ● | ◑ | ● | high |
| Fadli et al. [56] | ◑ | ○ | ◑ | ◑ | ● | high |
| Feng et al. [57] | ◑ | ○ | ◑ | ◑ | ● | high |
| Fernandes and Pereira [58] | ◑ | ◑ | ◑ | ○ | ◑ | some concerns |
| Gan et al. [60] | ◑ | ○ | ◑ | ◑ | ● | high |
| Gao et al. [61] | ◑ | ◑ | ◑ | ○ | ● | high |
| Gershon et al. [62] | ◑ | ○ | ○ | ○ | ◑ | some concerns |
| Geuter et al. [63] | ● | ○ | ◑ | ● | ◑ | high |
| Guo et al. [66] | ◑ | ○ | ◑ | ◑ | ● | high |
| Guo et al. [65] | ◑ | ○ | ◑ | ● | ◑ | some concerns |
| Ha et al. [67] | ◑ | ◑ | ◑ | ● | ● | high |
| Han et al. [69] | ○ | ◑ | ◑ | ◑ | ◑ | some concerns |
| Han et al. [68] | ● | ◑ | ◑ | ◑ | ○ | high |
| He et al. [70] | ◑ | ○ | ◑ | ○ | ◑ | some concerns |
| Hu et al. [72] | ● | ○ | ◑ | ◑ | ◑ | high |
| Hu et al. [73] | ◑ | ○ | ◑ | ◑ | ◑ | some concerns |
| Huang et al. [76] | ◑ | ○ | ◑ | ◑ | ◑ | some concerns |
| Huang et al. [75] | ◑ | ◑ | ● | ◑ | ● | high |
| Huang et al. [74] | ◑ | ○ | ◑ | ◑ | ◑ | some concerns |
| Huo et al. [78] | ● | ◑ | ● | ◑ | ○ | high |
| Ibrahim and Zaki [80] | ○ | ○ | ● | ● | ● | high |
| Ichikawa [81] | ◑ | ◑ | ◑ | ◑ | ◑ | some concerns |
| Imperatrice et al. [82] | ○ | ○ | ○ | ○ | ◑ | low |

| Study | D1 | D2 | D3 | D4 | D5 | Overall |
|---|---|---|---|---|---|---|
| Iqbal et al. [83] | ◑ | ○ | ○ | ◑ | ◑ | some concerns |
| Jiang et al. [84] | ● | ● | ● | ◑ | ● | high |
| Joy [85] | ◑ | ○ | ◑ | ◑ | ● | high |
| Jung [86] | ○ | ○ | ◑ | ◑ | ◑ | some concerns |
| Khatri et al. [87] | ◑ | ○ | ● | ○ | ● | high |
| Khezresmaeilzadeh et al. [88] | ◑ | ○ | ◑ | ◑ | ◑ | some concerns |
| Konak [89] | ◑ | ○ | ◑ | ◑ | ◑ | some concerns |
| Kourtis and Xilouris [91] | ● | ◑ | ◑ | ◑ | ○ | high |
| Kwartler et al. [93] | ◑ | ◑ | ◑ | ○ | ○ | some concerns |
| Lai et al. [94] | ◑ | ○ | ◑ | ◑ | ◑ | some concerns |
| Lai et al. [95] | ● | ◑ | ◑ | ◑ | ○ | high |
| Lan et al. [97] | ◑ | ◑ | ◑ | ◑ | ◑ | some concerns |
| Lan et al. [96] | ◑ | ◑ | ● | ◑ | ● | high |
| Lee et al. [98] | ◑ | ◑ | ◑ | ◑ | ● | high |
| Lee and Park [99] | ○ | ○ | ◑ | ● | ◑ | some concerns |
| Li [112] | ◑ | ◑ | ◑ | ◑ | ● | high |
| Li et al. [107] | ○ | ○ | ◑ | ○ | ◑ | some concerns |
| Li et al. [115] | ◑ | ○ | ◑ | ◑ | ● | high |
| Li and Xie [109] | ◑ | ◑ | ◑ | ● | ◑ | some concerns |
| Li et al. [110] | ◑ | ◑ | ● | ◑ | ○ | some concerns |
| Li et al. [102] | ○ | ◑ | ◑ | ● | ○ | some concerns |
| Li [106] | ◑ | ● | ◑ | ○ | ● | high |
| Li and Wang [108] | ◑ | ◑ | ◑ | ◑ | ● | high |
| Li et al. [117] | ◑ | ○ | ◑ | ● | ◑ | some concerns |
| Li and Chen [111] | ◑ | ◑ | ◑ | ● | ● | high |
| Li [105] | ○ | ○ | ◑ | ◑ | ● | high |
| Li and Wagle [118] | ◑ | ◑ | ◑ | ● | ◑ | some concerns |
| Li et al. [116] | ● | ◑ | ● | ◑ | ◑ | high |
| Li et al. [103] | ◑ | ◑ | ◑ | ○ | ○ | some concerns |
| Li et al. [119] | ◑ | ○ | ◑ | ◑ | ○ | some concerns |
| Li et al. [114] | ◑ | ○ | ◑ | ● | ● | high |
| Li [104] | ◑ | ◑ | ◑ | ● | ● | high |
| Li et al. [101] | ● | ○ | ● | ◑ | ○ | high |
| Li et al. [113] | ◑ | ◑ | ● | ◑ | ● | high |
| Li et al. [100] | ● | ◑ | ◑ | ◑ | ◑ | high |
| Lin [120] | ● | ○ | ◑ | ◑ | ◑ | high |
| Ling et al. [122] | ○ | ○ | ◑ | ◑ | ◑ | some concerns |
| Liu [128] | ● | ○ | ○ | ◑ | ◑ | high |
| Liu et al. [125] | ○ | ◑ | ◑ | ◑ | ● | high |
| Liu et al. [129] | ◑ | ○ | ● | ● | ◑ | high |
| Liu [130] | ◑ | ○ | ◑ | ○ | ● | high |
| Liu et al. [131] | ◑ | ◑ | ◑ | ◑ | ● | high |
| Liu et al. [127] | ◑ | ◑ | ◑ | ◑ | ● | high |
| Liu et al. [123] | ● | ◑ | ◑ | ◑ | ○ | high |
| Liu et al. [126] | ○ | ◑ | ● | ● | ◑ | high |
| Liu et al. [124] | ◑ | ◑ | ● | ◑ | ● | high |
| Loi [134] | ○ | ◑ | ● | ● | ○ | high |
| Lu and Wu [135] | ◑ | ○ | ◑ | ○ | ● | high |
| Lucca [136] | ◑ | ● | ◑ | ◑ | ○ | some concerns |

| Study | D1 | D2 | D3 | D4 | D5 | Overall |
|---|---|---|---|---|---|---|
| Lukassen et al. [137] | ● | ○ | ● | ○ | ● | high |
| Lukauskas and Šarkauskaitė [138] | ○ | ○ | ● | ◑ | ● | high |
| Luo et al. [139] | ◑ | ◑ | ◑ | ◑ | ○ | some concerns |
| Lyu and Xia [140] | ○ | ◑ | ◑ | ◑ | ● | high |
| Ma et al. [145] | ○ | ○ | ◑ | ◑ | ○ | some concerns |
| Ma et al. [141] | ◑ | ◑ | ◑ | ● | ◑ | some concerns |
| Ma et al. [143] | ○ | ◑ | ◑ | ◑ | ◑ | some concerns |
| Ma et al. [142] | ● | ○ | ◑ | ◑ | ● | high |
| Ma et al. [144] | ◑ | ◑ | ● | ○ | ○ | some concerns |
| Madrid-García and Merino-Barbancho [147] | ○ | ○ | ◑ | ◑ | ◑ | some concerns |
| Mazzoni and Failla [149] | ◑ | ◑ | ◑ | ◑ | ● | high |
| Mei et al. [150] | ◑ | ◑ | ◑ | ● | ◑ | some concerns |
| Messoudi and Mansar [151] | ◑ | ○ | ● | ◑ | ● | high |
| Min and Chen [154] | ○ | ◑ | ◑ | ○ | ● | high |
| Mohebifar and Bit [156] | ● | ◑ | ◑ | ◑ | ○ | high |
| Mu et al. [157] | ● | ○ | ◑ | ◑ | ○ | high |
| Munot [159] | ◑ | ○ | ◑ | ○ | ● | high |
| Nandakishore [160] | ◑ | ◑ | ◑ | ◑ | ● | high |
| Nandakishore [161] | ● | ○ | ○ | ○ | ◑ | high |
| Pan et al. [165] | ○ | ◑ | ● | ◑ | ○ | some concerns |
| Panchal [166] | ◑ | ◑ | ◑ | ◑ | ◑ | some concerns |
| Paramasivam and Rajkumar [167] | ◑ | ◑ | ● | ◑ | ◑ | some concerns |
| Paschalides et al. [168] | ◑ | ○ | ◑ | ◑ | ● | high |
| Pei et al. [169] | ○ | ◑ | ◑ | ◑ | ◑ | some concerns |
| Pelaseyed and Zabihi [170] | ◑ | ◑ | ◑ | ◑ | ◑ | some concerns |
| Perifanis et al. [171] | ○ | ○ | ● | ○ | ◑ | some concerns |
| Polignano et al. [174] | ○ | ○ | ◑ | ● | ◑ | some concerns |
| Porcedda [175] | ● | ◑ | ● | ● | ○ | high |
| Qian et al. [176] | ◑ | ◑ | ◑ | ○ | ● | high |
| Qin et al. [178] | ◑ | ○ | ◑ | ◑ | ◑ | some concerns |
| Qin et al. [177] | ◑ | ◑ | ◑ | ● | ◑ | some concerns |
| Rafe and Das [180] | ◑ | ○ | ◑ | ◑ | ○ | some concerns |
| Rafe and Das [181] | ○ | ○ | ◑ | ○ | ○ | low |
| Rafe and Das [182] | ○ | ○ | ◑ | ○ | ○ | low |
| Rahimi et al. [183] | ● | ◑ | ● | ◑ | ○ | high |
| Rajput et al. [184] | ◑ | ○ | ◑ | ○ | ● | high |
| Rao and Callison-Burch [185] | ◑ | ○ | ◑ | ● | ● | high |
| Ren et al. [187] | ● | ○ | ◑ | ● | ○ | high |
| Rezvani et al. [188] | ◑ | ◑ | ◑ | ○ | ● | high |
| Robitza [189] | ◑ | ◑ | ◑ | ● | ◑ | some concerns |
| Sadoun et al. [192] | ○ | ○ | ● | ○ | ◑ | some concerns |
| Saeed et al. [193] | ◑ | ◑ | ◑ | ◑ | ● | high |
| Sakhawat and Raiyan [194] | ○ | ○ | ◑ | ○ | ◑ | some concerns |
| Santillana [195] | ◑ | ○ | ◑ | ◑ | ◑ | some concerns |
| Sautenkov et al. [196] | ● | ◑ | ◑ | ● | ◑ | high |
| Severo et al. [197] | ◑ | ● | ◑ | ○ | ● | high |
| Shankaranarayana et al. [198] | ◑ | ○ | ○ | ○ | ◑ | some concerns |
| Sharma and Lall [200] | ● | ○ | ◑ | ◑ | ● | high |
| Sharma et al. [199] | ● | ○ | ◑ | ○ | ○ | high |

| Study | D1 | D2 | D3 | D4 | D5 | Overall |
|---|---|---|---|---|---|---|
| Sheng et al. [201] | ○ | ◑ | ● | ○ | ◑ | some concerns |
| Shi et al. [202] | ◑ | ◑ | ◑ | ◑ | ● | high |
| Song et al. [203] | ◑ | ○ | ◑ | ○ | ◑ | some concerns |
| Song et al. [204] | ◑ | ○ | ◑ | ◑ | ● | high |
| Song et al. [205] | ◑ | ○ | ◑ | ◑ | ● | high |
| Sonthalia et al. [206] | ◑ | ◑ | ◑ | ◑ | ◑ | some concerns |
| Stambler [209] | ● | ◑ | ◑ | ◑ | ◑ | high |
| Steiner et al. [210] | ◑ | ◑ | ◑ | ● | ◑ | some concerns |
| Su and Huang [211] | ○ | ○ | ◑ | ○ | ◑ | some concerns |
| Sudjianto and Burakov [212] | ◑ | ○ | ◑ | ◑ | ◑ | some concerns |
| Sun et al. [213] | ◑ | ◑ | ◑ | ◑ | ● | high |
| Sun et al. [214] | ◑ | ◑ | ● | ○ | ◑ | some concerns |
| Tan et al. [215] | ● | ◑ | ◑ | ◑ | ◑ | high |
| Tang and Chen [216] | ◑ | ◑ | ◑ | ◑ | ● | high |
| Teke [217] | ● | ○ | ◑ | ● | ◑ | high |
| Teke [218] | ● | ○ | ◑ | ● | ◑ | high |
| Teng et al. [219] | ◑ | ◑ | ◑ | ◑ | ● | high |
| Terven et al. [220] | ◑ | ○ | ◑ | ○ | ◑ | some concerns |
| Tommasino and Rinaldi [222] | ○ | ○ | ◑ | ◑ | ◑ | some concerns |
| Minh et al. [155] | ◑ | ◑ | ◑ | ○ | ● | high |
| Vats [233] | ○ | ○ | ◑ | ○ | ◑ | some concerns |
| Wake and Wagle [235] | ◑ | ◑ | ◑ | ◑ | ◑ | some concerns |
| Wang and Zang [244] | ● | ○ | ◑ | ● | ● | high |
| Wang et al. [238] | ◑ | ● | ◑ | ○ | ● | high |
| Wang et al. [243] | ◑ | ◑ | ● | ◑ | ◑ | some concerns |
| Wang et al. [248] | ◑ | ◑ | ● | ◑ | ◑ | some concerns |
| Wang et al. [240] | ● | ◑ | ● | ◑ | ◑ | high |
| Wang et al. [242] | ◑ | ◑ | ● | ◑ | ◑ | some concerns |
| Wang and Gao [245] | ◑ | ◑ | ● | ◑ | ◑ | some concerns |
| Wang et al. [239] | ◑ | ◑ | ● | ◑ | ● | high |
| Wang et al. [241] | ○ | ◑ | ◑ | ◑ | ◑ | some concerns |
| Wang [236] | ◑ | ◑ | ◑ | ● | ● | high |
| Wang et al. [247] | ◑ | ◑ | ◑ | ◑ | ◑ | some concerns |
| Wang et al. [246] | ○ | ◑ | ◑ | ◑ | ● | high |
| Wang et al. [237] | ◑ | ◑ | ● | ◑ | ◑ | some concerns |
| Weng et al. [249] | ◑ | ○ | ● | ● | ◑ | high |
| Wu et al. [254] | ○ | ◑ | ◑ | ● | ◑ | some concerns |
| Wu and Lim [255] | ● | ○ | ◑ | ○ | ● | high |
| Wu et al. [253] | ● | ◑ | ○ | ● | ○ | high |
| Wu and Lim [256] | ◑ | ◑ | ◑ | ◑ | ◑ | some concerns |
| Wu [257] | ◑ | ◑ | ◑ | ● | ● | high |
| Xie et al. [258] | ◑ | ◑ | ◑ | ○ | ● | high |
| Xu and Mei [260] | ◑ | ◑ | ○ | ◑ | ◑ | some concerns |
| Xu et al. [262] | ◑ | ○ | ◑ | ○ | ● | high |
| Xu et al. [259] | ◑ | ◑ | ◑ | ● | ● | high |
| Xu et al. [261] | ◑ | ◑ | ◑ | ◑ | ◑ | some concerns |
| Yadav [263] | ◑ | ○ | ● | ● | ● | high |
| Yamamoto and Kuroki [264] | ◑ | ○ | ◑ | ● | ● | high |
| Yan [265] | ◑ | ◑ | ● | ◑ | ● | high |

| Study | D1 | D2 | D3 | D4 | D5 | Overall |
|---|---|---|---|---|---|---|
| Yan [266] | ◑ | ◑ | ◑ | ● | ● | high |
| Yang et al. [269] | ◑ | ◑ | ◑ | ○ | ◑ | some concerns |
| Yang et al. [268] | ◑ | ◑ | ◑ | ◑ | ◑ | some concerns |
| Yang et al. [270] | ● | ◑ | ● | ○ | ○ | high |
| Yang et al. [267] | ◑ | ◑ | ◑ | ○ | ◑ | some concerns |
| Ye et al. [271] | ● | ○ | ◑ | ◑ | ○ | high |
| Yilmaz et al. [272] | ◑ | ◑ | ● | ◑ | ◑ | some concerns |
| You et al. [273] | ◑ | ◑ | ● | ○ | ● | high |
| Yu and Yao [274] | ◑ | ○ | ◑ | ○ | ● | high |
| Zhan et al. [275] | ◑ | ◑ | ◑ | ◑ | ◑ | some concerns |
| Zhang et al. [279] | ◑ | ◑ | ◑ | ◑ | ● | high |
| Zhang et al. [282] | ◑ | ◑ | ◑ | ◑ | ◑ | some concerns |
| Zhang and Yu [283] | ◑ | ◑ | ◑ | ◑ | ● | high |
| Zhang et al. [276] | ◑ | ○ | ● | ◑ | ◑ | some concerns |
| Zhang et al. [280] | ○ | ○ | ◑ | ● | ◑ | some concerns |
| Zhang [281] | ○ | ◑ | ● | ◑ | ● | high |
| Zhang et al. [278] | ◑ | ○ | ◑ | ● | ● | high |
| Zhang et al. [277] | ◑ | ◑ | ○ | ◑ | ● | high |
| Zhao et al. [284] | ◑ | ◑ | ◑ | ◑ | ◑ | some concerns |
| Zheng and Chen [285] | ◑ | ○ | ◑ | ◑ | ● | high |
| Zhong et al. [287] | ● | ○ | ● | ○ | ○ | high |
| Zhou et al. [288] | ◑ | ◑ | ◑ | ◑ | ◑ | some concerns |
| Zhou et al. [289] | ○ | ◑ | ◑ | ○ | ● | high |
| Zhu et al. [291] | ◑ | ◑ | ● | ● | ● | high |
| Zhu et al. [290] | ● | ○ | ● | ◑ | ◑ | high |
| Zhu et al. [292] | ◑ | ◑ | ◑ | ● | ● | high |
| Zhuang et al. [293] | ◑ | ○ | ◑ | ◑ | ◑ | some concerns |
| Zhuang et al. [294] | ◑ | ◑ | ● | ● | ◑ | high |
| Hume, Archer [77] | ○ | ● | ○ | ○ | ◑ | some concerns |
| Bespoke Labs [14] | ◑ | ◑ | ◑ | ◑ | ◑ | some concerns |
| Palmer, Jared [164] | ◑ | ◑ | ● | ● | ◑ | high |
| Convai Innovations [39] | ◑ | ◑ | ◑ | ◑ | ◑ | some concerns |
| LocalLLaMA [133] | ● | ◑ | ◑ | ◑ | ○ | high |
| Balian, Rob [9] | ◑ | ◑ | ◑ | ● | ◑ | some concerns |
| TypeSafe AI [232] | ● | ● | ● | ◑ | ◑ | high |
| Rauch [186] | ◑ | ● | ● | ◑ | ◑ | high |

**Table S3.** The recorded justification for every domain rated high in Table S2, one row per study and domain. Parentheses locate it in the study itself or, where marked note, in its ledger extraction note.

| Study | Domain | Justification |
|---|---|---|
| Ahmed [1] | D3 version pinning | Clef-Flash is identified only by name and Hugging Face path with no revision hash or API version string, and no run dates are given for the zero-shot API runs (Section 4.1; Table 1). |
| Ahmed [1] | D4 tuning parity | The fine-tuned Clef-Flash checkpoint (epoch 4) was selected on test accuracy because no validation set was held out, while the TF-IDF baselines were tuned by cross-validation on training data only (Section 3.3). |

| Study | Domain | Justification |
|---|---|---|
| Ahmed [1] | D5 test-set exposure | Symptom2Disease is a public Kaggle dataset predating 2026 with labels released and no contamination check is reported (Section 3.1). |
| Amit [2] | D5 test-set exposure | Open-Jev (2025) and the xLAM, Aegis 2.0, ToolACE, WildGuard and repo prompt-injection sources are public pre-2026 datasets with no contamination analysis (Sections IV, VI). |
| Antunes et al. [4] | D3 version pinning | ndm-base is described only by its training stages (mmBERT-base through stages 0, 1 and 2a) with no release identifier, checkpoint link or run date (Section 10). |
| Asseri and Asseri [5] | D5 test-set exposure | Persona states and prompts are new, but the 24 VSM 2013 items are published and asked verbatim and the Hofstede reference scores are public, with no contamination check (Sections 3.2, 3.3). [Adjudicated 2026-10-29 after the version 1.2 second rating: Every scored item is a verbatim VSM 2013 question, and the Hofstede reference scores it is compared with were public long before 2026, with no contamination check (Sec. 3.2; Sec. 3.3).] |
| Azizi et al. [7] | D1 reference labels | The headline suite GuardBench has ground truth computed from generating attributes, a synthetic procedure; public screening labels are undescribed (Sec. 5). |
| Azizi et al. [7] | D3 version pinning | Open models (laya-td, laya-en, laya-ml, von, rlcd, Qwen2.5) are named without checkpoint revisions, hashes or run dates (Sec. 2). |
| Azizi et al. [7] | D4 tuning parity | All models receive the same traces and policy text with no tuning, and defenses are compared against a matched fail-closed baseline (Sec. 5, 7). [Adjudicated 2026-10-29 after the version 1.2 second rating: The positive policy phrasing was chosen for the attack experiments after the wording turned out to matter, so that gates work before attack, a setting selected after seeing results (Sec. 5 GuardBench).] |
| Bailo [8] | D1 reference labels | Labels come from doomLaya's rule-based oracle, a synthetic procedure the author says a reasonable player can disagree with (Sec. 3, 6). |
| Bailo [8] | D3 version pinning | Evaluated open models are identified by name and size only; no revision hash or run date, and only the llama.cpp and doomLaya commits are pinned (Sec. 3). |
| Bellver-Soler et al. [11] | D3 version pinning | ASOM has no version or checkpoint identifier (weights 'upon acceptance') and the audio LLM and CLAP comparators carry no revisions or run dates (Section 1 footnote; Section 4). |
| Bellver-Soler et al. [11] | D4 tuning parity | ASOM's design choices were made by ablation on the same Dev-select partition that supplies the headline scores and is 'used for model selection', while the zero-shot audio LLMs receive no tuning (Section 4 Evaluation data; Section 5.4). |
| Bellver-Soler et al. [11] | D5 test-set exposure | MSP-Podcast, CREMA-D, EmoBox corpora, EmoNet-Voice and EARS are public pre-2026 datasets used with their released labels, the headline partition doubles as model selection data, and no contamination check of the frozen encoders or audio LLMs is reported (Section 4). |
| Besanson [12] | D1 reference labels | Error rates and verdict exposure are scored against the truth label of each seeded synthetic record, a value fixed by the generator before the document text is produced, so the reference is a synthetic procedure (Sec 6 Documents and labels; Sec 5). [G5] |
| Brom [16] | D5 test-set exposure | MASSIVE and the four extension datasets are public pre-2026 sets used with their gold labels, no contamination check is reported for Jev, and only exact duplicates were removed from the Laya fine-tuning set (Sections 5, 9, 14). |

| Study | Domain | Justification |
|---|---|---|
| Buecheler et al. [18] | D3 version pinning | Jev is identified as typesafe/jev-1.13-20260917 via OpenRouter and queried on 2026-09-30 (Section 4.7; Appendix O). [Adjudicated 2026-10-29 after the version 1.2 second rating: Jev is pinned (jev-1.13-20260917, 30 September), but the evaluated GPT-4o and GPT-4o mini were queried through rolling aliases rather than dated snapshots (Sec. 4.7; App. O).] |
| Bukhari et al. [19] | D4 tuning parity | The hand-written 97-case set was consulted repeatedly and the v3 and v4 recipes were developed after inspecting earlier results on it, so it is not an independent final test, and the 'Paper' comparison columns come from a different training condition (Sections 5 and 10; Table 1 caption). |
| Cao et al. [21] | D5 test-set exposure | In-distribution tests are converted items from public pre-2026 datasets (VitaminC, LCQMC, PAWS-X, FRAMES, BrowseComp-Plus) and no contamination check is reported for Jev or Qwen, only split isolation of the authors' own training data (Appendix; Section 7). |
| Chen and Li [23] | D1 reference labels | The reference is the exact posterior computed by a generator for synthetic finite worlds, a synthetic procedure (Section 4.1; Section 5.1). |
| Chen et al. [27] | D2 sampling and reporting | No sample size, split, sampling design, interval, seed or repeated run is reported for any configuration, and the Conclusion's 93.54% on VoxCeleb1-O disagrees with 93.7595 in Table 3 and the abstract (Section 4; Table 3; Conclusion). |
| Chen et al. [27] | D3 version pinning | The evaluated checkpoint is described only as an MoE decoder, with no checkpoint name, version, release date or run date, and the text does not say whether SFT or RLCD weights were scored (Sections 2, 3, 4). |
| Chen et al. [27] | D5 test-set exposure | All 18 evaluation sets are public pre-2026 benchmarks used with their released labels, the model is jointly trained on heterogeneous audio datasets including MELD and VoxCeleb, and neither the per-set split nor overlap with training is stated or checked (Section 1; Section 4.1). |
| Chen [25] | D3 version pinning | RoboJev is pinned to commit e089a9b and comparators carry endpoint strings such as typesafe/jev-1.13 and jev-1.14, but no run dates are given for the recorded API calls, only reference access dates (Appendix A; Table 5). [Adjudicated 2026-10-29 after the version 1.2 second rating: Table 5 lists compared endpoints such as cloudflare/clef, liquid/d1 and inception/mercury-decide with no version or snapshot, and no run dates are given (Table 5; App. A).] |
| Chen et al. [26] | D3 version pinning | The evaluated models are the officially released AID weights and the authors' UCM LoRA checkpoint with no version identifier, hash or run date (Section III-A; Section IV-C). |
| Chen et al. [26] | D5 test-set exposure | UCM, AID and NWPU-RESISC45 are public benchmarks predating 2026 used verbatim with labels and no contamination check is reported (Section IV-A). |
| Cheng et al. [31] | D3 version pinning | MetaEncoder, OpenJev-27B and the embedding baselines are named with a repository link only, no revision and no run date (Sec. 4.3; refs). |
| Cheng et al. [31] | D5 test-set exposure | JevBench, ImaJev, MMLU, MMMU and the other suites are public pre-2026 with answer keys and no contamination check; MetaEncoder training data are not described (Sec. 4.1). |
| Cheng et al. [32] | D1 reference labels | All three evaluations score against environment- or simulator-computed truth, not annotation (note Reference labels; fulltext 4.1, 4.3). [Adjudicated 2026-09-27 after independent second rating: the benchmark labels are generated by a simulator, a synthetic procedure] |
| Cheng et al. [32] | D3 version pinning | No Jev version string anywhere; Jev replies were recorded by NanoJev or run by an unnamed third party; own model named only as 1.0 (note Decision models). |

| Study | Domain | Justification |
|---|---|---|
| Cheng et al. [32] | D4 tuning parity | this-that-model-1.0 trained on all 15 families of the benchmark it is scored on while every comparator is zero-shot; the authors call it a weak scientific comparison (note Test-set exposure; fulltext 4.3). |
| Chouhan and Perry [33] | D3 version pinning | Jev is called through the unpinned gateway alias typesafe-ai/jev that 'does not expose a pinned semantic version', so only run dates (2026-09-25 to 27) and the vendor card's Jev 1.13.0 figure stand in for a version (Appendix L; Limitations). |
| Chouhan and Perry [33] | D4 tuning parity | Specialists (Verdict-MQ, Laya) are fitted to the benchmark training split while Jev is zero-shot, which the paper discloses as not directly comparable, and the research process was 'adaptive rather than test-blind' in three disclosed places though final choices used a development split (Section 4; Limitations Selection and testing). [Adjudicated 2026-10-29 after the version 1.2 second rating: The five-seed large-model run was launched only if base-model test accuracy cleared a margin, and live test accuracy was seen during training (Limitations, Selection and testing).] |
| Chung et al. [35] | D5 test-set exposure | The nine benchmarks are public releases from 2019 to 2026 used with their keys, and the authors state training exposure cannot be excluded with no contamination check (Limitations; Section 3.2). |
| Cinà [36] | D3 version pinning | Jev is only 'jev-latest, September 2026' with no version string or run date, and the Laya checkpoint is 'open 421M' with no revision (Section 4 Arms; Section 5.4). |
| Cinà [36] | D4 tuning parity | Every arm is untuned apart from the interpolation weight, which is searched on the development split only, with the test split scored once and identical cached candidates for all arms (Section 4 Tuning; Section 2). [Adjudicated 2026-10-29 after the version 1.2 second rating: The 0.2-point matching bound behind the headline 'matches' claim was fixed after seeing the test results, a setting selected after seeing results (Sec. 4 Statistics; Sec. 5.4).] |
| Dai et al. [40] | D3 version pinning | Jev has no version identifier and no run date in the paper (Section 4.1, Table 2). |
| Dai et al. [41] | D1 reference labels | Reference probabilities are exact analytic class probabilities from simulated text worlds, a synthetic procedure (Section 3; Appendix B). |
| Dai et al. [41] | D3 version pinning | Jev is pinned as typesafe/jev-1.13-20260917 but the other 15 models are named without resolved identifiers and no run dates are stated (Appendix A.2; Table 1). [Adjudicated 2026-10-29 after the version 1.2 second rating: Only Jev carries a dated snapshot (typesafe/jev-1.13-20260917), while compared models Clef and Solar Decide are listed by bare product name with no release token (App. A.2; Table 1).] |
| Denney and DiGiuseppe [45] | D5 test-set exposure | The recall tasks (V-Dem v14, CHES, CMP, TEV) and the tweet and GTD sets are public and predate the models, the authors say agreement may partly reflect recall, and no contamination check is run (Sections Party positions and Democracy indicators; note Test-data exposure). |
| Ding et al. [47] | D4 tuning parity | The headline DecisionBench and typed-decisions Jev figures are third-party leaderboard values, and Bongard is a trained system with temperatures fitted on external development sets while Jev is zero-shot (Table 8; Sec. 6, 7.1). |
| Ding [48] | D5 test-set exposure | MMLU (2020) is a verbatim public benchmark with released answer keys and the authors state their checks 'cannot rule out paraphrases or pretraining contamination' (Section 6.1). |

| Study | Domain | Justification |
|---|---|---|
| Dinzinger et al. [49] | D5 test-set exposure | TREC DL and BEIR are public benchmarks with qrels released before 2026, MS MARCO exposure of the reranker fine-tunes is acknowledged, and no contamination check of the Qwen backbones is made beyond a zero-shot subset defined by fine-tuning data (Section 4; Section 7). |
| Dong et al. [50] | D1 reference labels | Cases and decisions are authored by the researchers (synthetic) and the transfer-set labels come from blinded AI review, not human adjudication (Sec. V-A). |
| Dong et al. [50] | D4 tuning parity | Jev is a single system studied, but several defence checks were specified after defects in their first versions were found, so clean results are not held-out confirmations (Sec. VII). [Adjudicated 2026-10-29 after the version 1.2 second rating: The question clean control and the corrected full-trace audit were specified after defects were found on the same cases, so their settings were selected after seeing results (Sec. VII; Table V).] |
| Rosario and Atef [191] | D4 tuning parity | Both systems get the same semantic instructions, a pre-publication parity audit found a prompt asymmetry favouring Jev, and the frontier runs were redone (Section 4). [Adjudicated 2026-10-29 after the version 1.2 second rating: Every prompt, threshold, grid and cascade parameter was chosen on the same 495-claim development split that is scored, with outcomes visible (Sec. 5; Sec. 12).] |
| Rosario and Atef [191] | D5 test-set exposure | LLM-AggreFact is a public benchmark released before 2026 and the authors state neither system can be assumed uncontaminated, with no contamination check (Sections 5, 12). |
| dos Santos Barbosa [51] | D2 sampling and reporting | One run per arm against a single target, no intervals anywhere, and the paper states this itself: the results are observations that motivate the architecture, not statistically powered experimental evidence (IX-A). |
| dos Santos Barbosa [51] | D3 version pinning | The case study requests jev-latest with no patch-level build string, snapshot hash or run date recorded anywhere in the paper (Table V). |
| dos Santos Barbosa [51] | D4 tuning parity | Both arms use the identical harness, curator model, target and parameters; –typesafe is the sole variable (Table V caption; IX-A). [Adjudicated 2026-10-29 after the second rating of the first sweep: Retain high. The reported re-test uses salvage and classification fixes chosen after failures on the same target. Source: Sections IX-C, IX-E and IX-H, Table VIII. The earlier matched setup does not remove this C2 trigger.] |
| Du et al. [52] | D5 test-set exposure | Sources are mostly public pre-2026 datasets (MedQA, MIMIC, VitalDB, CTG, MEDEC) used with their answer keys and no contamination check is reported (Section 3; Appendix B). |
| Duan et al. [53] | D3 version pinning | Jev is given no version identifier in the main runs (Table 9 shows blank settings) and 'Jev 1.13' appears only for Sections 5.4.1 and 5.4.2, with no run dates for any model (Table 9; Appendix C.3). |
| Duan et al. [53] | D5 test-set exposure | JEVal is resampled verbatim from 36 public datasets whose answer keys predate 2026, and no contamination check on the evaluated models is reported (Section 3.2; Appendix B). |
| Fadli et al. [56] | D5 test-set exposure | NusaX (public since 2022) and NusaTranslation are verbatim public test sets with released labels; the authors state closed models may have seen them and no check is possible (Sec. 4.10). |
| Feng et al. [57] | D5 test-set exposure | LaMP-2 and MIND are public pre-2026 datasets with released labels, and the paper does not discuss pretraining exposure of the Qwen backbone (Appendix A.3; Appendix A.4). |

| Study | Domain | Justification |
|---|---|---|
| Gan et al. [60] | D5 test-set exposure | The suite is built from public pre-2026 datasets with released gold labels, the authors cannot exclude backbone exposure, and only train-test leakage was checked with no contamination check of the pretrained backbones (Limitations; Appendix A). |
| Gao et al. [61] | D5 test-set exposure | All 40 datasets are public pre-2026 sources with released labels and the authors state they 'did not audit item-level overlap' (Appendix B.2; Limitations). |
| Geuter et al. [63] | D1 reference labels | The headline OpenDecisions labels come from LLM authoring agents kept only if a panel of three open models agreed, plus code-computed items and panel-answered real requests, with no human labelling (Section 3 Labels, Table 1). |
| Geuter et al. [63] | D4 tuning parity | The authors' training recipe was selected on OpenDecisions, the very set that carries the headline ranking, and each public system gets the better of its original or recalibrated output (Section 5 Setup, Section 4). |
| Guo et al. [66] | D5 test-set exposure | Who&When is a public 2025 benchmark used with its annotations, Who&When Pro is public, and no contamination check is reported (Section 4.1). |
| Guo et al. [65] | D4 tuning parity | The supervised TF-IDF baseline is trained by 5-fold cross-validation on the same in-domain evaluation labels Jev never sees, an asymmetric budget in the baseline's favor rather than Jev's, so parity is not matched even though the paper flags and controls for the asymmetry (3.4). [Adjudicated 2026-10-29 after the second rating of the first sweep: Retain high. The saved text uses the in-sample best generic readout and selects a shared question on both evaluated states. Source: Sections 3.4 and 4.2, Figure 4. Split-half selection elsewhere does not remove these C2 triggers.] |
| Ha et al. [67] | D4 tuning parity | The four decision models run frozen and zero-shot on the same task text, but the LLM comparison imports numbers from Thin et al. (2024) under different prompts and the perturbation table uses each model's best description language chosen on the test data (Section 4.2; Section 5.2). [Adjudicated 2026-10-29 after the version 1.2 second rating: For the perturbation results, each model uses the label-description configuration with the best mean macro-F1 on the original test data (Sec. 5.2; Table 4).] |
| Ha et al. [67] | D5 test-set exposure | All 12 datasets are public corpora with released gold test labels, 11 of them from before 2026 (ViANLI is cited to a 2026 journal article), and the paper reports no contamination check (Section 3.1; Table 9). |
| Han et al. [68] | D1 reference labels | The reference is the deployed fleet's own logged next hop, teacher-forced behavioural agreement that the paper itself calls weak, not a correctness label (Section 3, Section 5). [Adjudicated 2026-10-29 after the version 1.2 second rating: The reference is the logged next hop chosen by the production LLM agent fleet, a model-generated label (Abstract; Sec. 5).] |
| Hu et al. [72] | D1 reference labels | Of 862 reference labels, 586 are Jev's own stable answers from ten repeated runs, 41 are a three-LLM consensus and only 185 were human reviewed (Section 3.1; Fig. 2b), so the target model largely labels itself. |
| Huang et al. [75] | D3 version pinning | Gemma 4 12B has a revision hash and access date, but Jev 1.13 and the other closed APIs carry a minor version only and no run dates (Section 5.1, reference list). [Adjudicated 2026-10-29 after the version 1.2 second rating: Mercury Decide, a hosted endpoint, is evaluated with no version identifier, Jev carries only the minor version 1.13, and no run dates are given (Sec. 5.1; Table 2).] |

| Study | Domain | Justification |
|---|---|---|
| Huang et al. [75] | D5 test-set exposure | Benchmarks are public pre-2026 sets with answer keys and no contamination check, and the authors note that Torchcast 12B and Kev 9B were trained on BANKING77, which contains Banking20 (Section 5.1, Appendix D). |
| Huo et al. [78] | D1 reference labels | Reference actions are sampled programmatically and every request is an LLM-written description with no human validation, a synthetic procedure (Sec. 2.3). |
| Huo et al. [78] | D3 version pinning | The comparator native JEV has no version, access date or API detail, and the flagship LLMs carry no revisions or run dates (Sec. 3.2.1, Table 3). |
| Ibrahim and Zaki [80] | D3 version pinning | jev-1.13-20260917 and Hugging Face snapshot hashes, and 'all runs are dated 2026-09-20' (Appendix A.5, Table 5). [Adjudicated 2026-10-29 after the second rating of the first sweep: Retain high. The saved Table 5 identifies the comparator as gemini-3.1-pro-preview without resolving the preview tag further. Source: Appendix A.5, Table 5. Retain high under G6. The later Kev example is unnecessary for this decision.] |
| Ibrahim and Zaki [80] | D4 tuning parity | Same released prompts for all systems, restated as typed questions for decision models (3.2); reasoning adjustments made only for comparators after empty completions. [Adjudicated 2026-10-29 after the second rating of the first sweep: Retain high. The saved paper selects the per-task best LLM on the same test items. This alone meets C2. Source: Section 4.1. The first-pass configuration changes in Section 3.2 provide additional evaluation feedback.] |
| Ibrahim and Zaki [80] | D5 test-set exposure | All 18 tasks are public benchmarks that predate the models; the authors state contamination cannot be excluded (5, Discussion). |
| Jiang et al. [84] | D1 reference labels | Correctness is scored by a gpt-4o-mini LLM-as-a-judge against LoCoMo answers (Table 1 caption). |
| Jiang et al. [84] | D2 sampling and reporting | Item count not stated, single run, no seeds or intervals; the setup says two benchmarks but only LoCoMo is reported (4.1; note n). |
| Jiang et al. [84] | D3 version pinning | No Jev version string and no dates anywhere (note Decision models; Appendix B). |
| Jiang et al. [84] | D5 test-set exposure | LoCoMo is a public 2024 benchmark with released answers; exposure not discussed (note Test-set exposure). |
| Joy [85] | D5 test-set exposure | TREC, CLINC150 and MASSIVE are verbatim public benchmarks released before 2026 with training exposure 'unknown' and no contamination check (Section 8). |
| Khatri et al. [87] | D3 version pinning | Jev is pinned as 1.13.0 and 1.14.0 and all models were run on the census day 25 October 2026, but several other identifiers are unversioned and the authors warn hosted models change without notice (Section 5; Section 7). [Adjudicated 2026-10-29 after the version 1.2 second rating: Jev 1.13.0 and 1.14.0 are pinned and the census date is given, but the authors state several evaluated identifiers are unversioned, e.g. d1 (Sec. 5; Sec. 7 Limitations iii).] |
| Khatri et al. [87] | D5 test-set exposure | Conflicts (2025) is a public benchmark with released labels, no contamination check is reported, and identical requests changed up to 9.4 percent of predictions (Section 3; Section 7). |
| Kourtis and Xilouris [91] | D1 reference labels | All labels 'come from simulator rules' in a synthetic 5G testbed corpus, a synthetic procedure rather than annotation (Section V-B; Section IX item 5). |
| Lai et al. [95] | D1 reference labels | All items, rules and answers are synthetic, with a programmatic oracle returning every label from executable arithmetic rules (Section 3; Appendix A). |

| Study | Domain | Justification |
|---|---|---|
| Lan et al. [96] | D3 version pinning | Jev is queried as 'jev-latest' with no resolved version and no run dates, only a blog access date of 2026-10-01 (Section 3.2; references). |
| Lan et al. [96] | D5 test-set exposure | All four benchmarks are public and mostly pre-2026 and used verbatim with their labels, and the paper does not test contamination of the evaluated models (Section 3.1). |
| Lee et al. [98] | D5 test-set exposure | MedQA, USMLE, DiagnosisArena and the NEJM vignettes are public pre-2026 items with released keys and the authors say pretraining overlap cannot be excluded with no contamination check, while overlap of the MIMIC-IV Note adaptation text with the MIMIC test patients is not discussed (Section 5). |
| Lee and Park [99] | D4 tuning parity | Best of 28 deep KT models is selected on test, which the authors say favours the comparator, and Jev and deep KT use different data regimes; a validation-tuned run bounds the effect (Sec. 4.1, 5.5). [Adjudicated 2026-10-29 after the version 1.2 second rating: The best of 28 pyKT baselines is chosen on test in every cell; it favours the comparator, but it is still selection on test data (Table 1 note; Sec. 4.1).] |
| Li [112] | D5 test-set exposure | CMMLU, C-Eval, TMMLU+, SeedBench, CROP and Ag-valuate are public pre-2026 benchmarks used with answer keys; exact-overlap exclusion covers only the authors' training data and backbone pretraining exposure is unresolved (Section 4.1; Appendix A). |
| Li et al. [115] | D5 test-set exposure | VAST (2020) and ZS-CSD (2025) are public test sets with released labels and no contamination check (Sec. 4.1). |
| Li and Xie [109] | D4 tuning parity | PPLX and Jina were chosen after exploratory outcomes, the input-budget settings and margin were set after seeing BRIGHT results while Jina ran at default (a tuned Jina is only a control), and a higher-scoring Winnow-12B was dropped without documented reason (Section III-B; Section IV-C; Section V). |
| Li et al. [110] | D3 version pinning | Commercial Jev has no version or run date, and its initialization source is 'Not publicly confirmed' (Table 3). |
| Li et al. [102] | D4 tuning parity | Same contract prompt with fallback disabled; the better Qwen interface was used as the comparator once the gap was found (V-E; Appendix A). [Adjudicated 2026-09-27 after independent second rating: the comparator interface was changed and chosen after seeing the first evaluation results] |
| Li [106] | D2 sampling and reporting | n per decision point is stated (2,100 and 1,280 cases), the design is described and accuracies carry Wilson intervals and exact McNemar tests (Section 3, Table 1). [Adjudicated 2026-10-29 after the version 1.2 second rating: Counts do not reconcile, since points A to F sum to 3,620 (RAG relevance n = 1,920) against a stated 2,100-case suite, and no tally matches 7,283 base cases (Abstract; Sec. 4; Table 1).] |
| Li [106] | D5 test-set exposure | All 18 sources are public pre-2026 and the author says near-perfect scores on popular sets 'may partly reflect exposure', with new controls on only three decision points (Section 8). |
| Li and Wang [108] | D5 test-set exposure | BANKING77, MASSIVE and Mind2Web are public 2020-2023 benchmarks used with their labels, the curriculum includes similar intent-selection data and no contamination check is reported (Section 4; Appendix C.1). |

| Study | Domain | Justification |
|---|---|---|
| Li et al. [117] | D4 tuning parity | Same instructions, state and output contract for all judges; cascade thresholds frozen on the selection set (4; 7). Not compute-matched (Limitations). [Adjudicated 2026-10-29 after the second rating of the first sweep: Change unclear to high under C2. The saved text adds model families after earlier results were known and evaluates them on the same 1,312 items. This matches the model-selection trigger retained for RB012. Source: Section 3, What was frozen and when. Separate threshold-selection pairs do not remove that trigger.] |
| Li and Chen [111] | D4 tuning parity | Generative baselines get the same 15-candidate menus, re-ask schemes and cascades are compared at matched cost in 0.8B forward units, and cascade thresholds are set on a training split (Sections 4.3 and 5.2). [Adjudicated 2026-10-29 after the version 1.2 second rating: The headline 95.4% uses curated avoidance menus on the 500 CLINC150 test items, built with the gold label offline, against a 4B model on the full menu (Sec. 5.3; Sec. 6).] |
| Li and Chen [111] | D5 test-set exposure | CLINC150, MMLU, ARC and the other sets are public benchmarks from 2018 to 2021 with released answers, and no contamination check is reported (Appendix A; note Exposure). |
| Li [105] | D5 test-set exposure | Public 2021-2023 human datasets; the A3c recall test was inconclusive and familiar designs may be recognized (Limitations). [Adjudicated 2026-09-27 after independent second rating: public pre-2026 datasets where contamination could not be ruled out] |
| Li and Wagle [118] | D4 tuning parity | Training mixtures were iterated using error analysis on public JevBench samples, items later reported as test results, and the baselines are finished systems with their own training (Section 3.5). |
| Li et al. [116] | D1 reference labels | Gold is mixed: set-valued optimal actions computed from simulator state for ALFWorld, BabyAI and TextWorld, tau2 gold from successful trajectories, and data-label probes, with audits finding 98 flagged records and ALFWorld co-located location labels (Section 3; Section 5.4). [Adjudicated 2026-10-29 after the version 1.2 second rating: Gold actions and probe answers are stored labels computed by program from simulator state or databases (shortest plans checked by breadth-first search) and matched against model choices (Sec. 3).] |
| Li et al. [116] | D3 version pinning | Jev is pinned as jev-1.13.0, formal runs finished on 1 October 2026, a rerun was done on 6 October and OpenAI Decisions was collected on 11 October (Appendix D). [Adjudicated 2026-10-29 after the version 1.2 second rating: OpenAI Decisions is evaluated as an unversioned public-beta endpoint with no version identifier, even though Jev and the open-weight systems carry release names or pinned revisions (Table 1; Sec. 4).] |
| Li et al. [114] | D4 tuning parity | All systems get the same payload and policy, but the adaptive-search phrase pool comes mostly from attacks that work on LLM judges, Prompt Guard 2 has an adjusted threshold, and LLM judges lack log-probs, all disclosed (Section 8.2, Appendix A, Section 9). [Adjudicated 2026-10-29 after the version 1.2 second rating: The Prompt Guard 2 threshold is set at the 99th percentile of its scores on the same clean cases used for reporting, a setting tuned on test data (App. A; Table 3).] |
| Li et al. [114] | D5 test-set exposure | Cases are verbatim public benchmark items (JailbreakBench 2024, InjecAgent 2024, a public phishing corpus) and the cookbook battery is used as published, with no contamination check (Section 4.2). |
| Li [104] | D4 tuning parity | The released Iris numbers use a checkpoint and an abstention margin chosen on the cross-task test split, while the retrained OneJev baseline is reported at its final checkpoint with a different LoRA rank (r=64 versus r=32) (Section 5.4; Table 2; Appendix A). |

| Study | Domain | Justification |
|---|---|---|
| Li [104] | D5 test-set exposure | Test steps are verbatim public Multimodal-Mind2Web and MMEB-V2 items with public gold labels from before 2026, no contamination check of the Qwen3.5 backbone is made, and the cross-task split also served for selection (Section 4; Section 5.4). |
| Li et al. [101] | D1 reference labels | Correctness on the constructed access-policy, placement, contract-catalogue and route tasks is the minimum-cost feasible selection or justified refresh or escalation computed by complete feasibility and cost predicates, a program-made reference compared with each model's answer (Sec IX; Tables IX, XI, XII captions). [G5] |
| Li et al. [101] | D3 version pinning | Jev appears only as the minor version Jev-1.13 on the authors' own tasks with no run date, and the MiniLM re-ranker compared on the contract task is a bare name with no checkpoint, so one compared system has no version identifier (Sec VII model-version paragraph; Table X; Table VII caption). [G2] |
| Li et al. [113] | D3 version pinning | No Jev version string or run date appears; only source access dates (30 Sep 2026) are given (Sec. 3.1; App. C). |
| Li et al. [113] | D5 test-set exposure | All 13 benchmarks are verbatim public pre-2026 sets with released answer keys and no contamination check (Sec. 3.1, 3.2). |
| Li et al. [100] | D1 reference labels | Verifier labels come from GPT-5.4 annotation with unreported human verification, and the downstream score is a GPT-5.4 composite (Sec. 3.4, 4.1, 4.3, 7). |
| Lin [120] | D1 reference labels | The 324-item frozen holdout is 'synthetic, model-labelled' with labels from the same family of models as the training labels (Section VIII; Section V-A). |
| Liu [128] | D1 reference labels | Candidates are authored mutations of DROP and GSM8K answers whose required verdict follows from a construction certificate, a synthetic procedure with no human adjudication (Sec. 3; Eq. 1). |
| Liu et al. [125] | D5 test-set exposure | All three datasets are public pre-2026 logs (Goodreads, HetRec LastFM 2011, Amazon Reviews 2023) with no contamination check, and the authors say cold items may have appeared in LLM pretraining (Section 4.1; Appendix A.2). |
| Liu et al. [129] | D3 version pinning | Only Jev (1.13.0) and pplx (v1.1) carry versions, while d1, clef, GPT-6 Luna and the gpt-6-sol reference have only unversioned aliases marked not reported, and no run dates are given (Appendix B, Table 5). |
| Liu et al. [129] | D4 tuning parity | All models receive the same criterion and input with no tuning, but cascade deferral rates and member order are chosen on the evaluation items, which the authors call optimistic and bound with five-fold cross-fitting costing at most 0.52 points (Sections 3.4, 4.3). [Adjudicated 2026-10-29 after the version 1.2 second rating: Cascade members, order and deferral rates are chosen on the same evaluated items, and five-fold cross-fitting covers only the rates (Sec. 3.4; Limitations).] |
| Liu [130] | D5 test-set exposure | R-Judge (2024) and AgentHarm (2025) are verbatim public benchmarks with released labels, and the paper says they 'may overlap training data' without a contamination check (Section 8). |
| Liu et al. [131] | D5 test-set exposure | MMEB-V2 (VLM2Vec-V2, 2025) is a public benchmark used verbatim with released relevance annotations and no contamination check, and ViDoRe V3 (2026) is public too, so the high rating rests on MMEB-V2 (Section 4, references 22 and 24). |
| Liu et al. [127] | D5 test-set exposure | All 13 sources and Dreaddit are public pre-2026 datasets used with their released labels, zero-shot Jev and the Qwen backbones may have seen them, and no contamination check is reported (Section 3; Section 5.7). |

| Study | Domain | Justification |
|---|---|---|
| Liu et al. [123] | D1 reference labels | Decision labels come from an LLM extracting rules and generating synthetic patients, cross-verified by a different model family with two further families for disputes, and grading labels are code-computed from sampled parameters, with no clinician adjudication (Section 3.1; Section 6). |
| Liu et al. [126] | D3 version pinning | The Jev model identifier and version are not reported (only 'Jev AI (2026) developer documentation') and no run dates are given (Section 4.5; References). |
| Liu et al. [126] | D4 tuning parity | 'The gate configuration was selected on these layouts, making this a development-set evaluation', so the Jev condition was tuned on the same layouts used for the comparison (Section 4.5; Section 5). |
| Liu et al. [124] | D3 version pinning | Decider-4B and Decider-2B are named with no version, revision or checkpoint hash and no run dates (Section 5.1, Table 1). |
| Liu et al. [124] | D5 test-set exposure | TSQA is a public 2025 benchmark whose test items and answers predate 2026, with no contamination check (Section 5.1). |
| Loi [134] | D3 version pinning | Version 1.13.0 is only 'presumed' from documentation and not provider-verified, with dated collection (24 Sep and 26-27 Sep 2026) and varying routing (Appendix A.2, A.4). [Adjudicated 2026-10-29 after the version 1.2 second rating: Rechecked after rejection of G1. Retain high. The returned alias does not identify a verified served version. Version 1.13.0 remains a documentary presumption. Source: App. A.2. App. A.4.] |
| Loi [134] | D4 tuning parity | Jev gets a native five-anchor rubric and chat models a different 0-1 rating prompt, an asymmetry the paper discloses and says rules out an impartiality ranking (Figure 2 caption, Section 4.4). [Adjudicated 2026-10-29 after the version 1.2 second rating: Topics were chosen partly because earlier explorations made them promising, 16 repetitions were adopted after reviewing earlier results, and two ratings were admitted retrospectively (Sec. 3; App. A.4).] |
| Lu and Wu [135] | D5 test-set exposure | All five sources are public pre-2026 datasets used verbatim with labels, the paper states pretraining overlap is unknown and no contamination test is run (Section 4.1; Limitations). |
| Lucca [136] | D2 sampling and reporting | The relationship column of Table 1 sums to 239 against the stated corpus of 231 emails (the type and urgency columns sum to 231), so the reported counts do not reconcile (Table 1; Section 5). |
| Lukassen et al. [137] | D1 reference labels | Fact-related items use gold final answers but both responses are GPT-4-Turbo rewrites, and alignment items use preference-dataset chosen and rejected labels that the authors say were made for training, while bias tests compare a judge with itself (Section 3.1, Limitations). [Adjudicated 2026-10-29 after the version 1.2 second rating: Better and worse responses are fixed by construction, with GPT-4-Turbo writing both fact-related responses and alignment pairs taken from preference datasets, a synthetic procedure (Sec. 3.1 Data).] |
| Lukassen et al. [137] | D3 version pinning | TDM versions are exact strings as returned (for example typesafe/jev-1.13-20260917) but run dates are given only as early October 2026 and several LLM judges are named without snapshot ids (Section 3.2, Table 6, Limitations). [Adjudicated 2026-10-29 after the version 1.2 second rating: The compared TDM Clef is returned only as the bare string cloudflare/clef with no version or date, while timing is given only as early October 2026 (Sec. 3.2; Table 6).] |
| Lukassen et al. [137] | D5 test-set exposure | All items are public CALM items (released 2025) from older public datasets, and the authors state the models may have seen some of them, with no contamination check (Limitations). |

| Study | Domain | Justification |
|---|---|---|
| Lukauskas and Šarkauskaitė [138] | D3 version pinning | Jev is pinned as typesafe/jev-1.13-20260917 and the decision endpoint was listed on 7 and 10 October 2026, with resolved versions for every model (Section 4; Table 13). [Adjudicated 2026-10-29 after the version 1.2 second rating: Most decision models resolve to dated versions, but Clef and Clef Flash resolve only to cloudflare/clef and cloudflare/clef-flash with no version (Table 13; Sec. 4).] |
| Lukauskas and Šarkauskaitė [138] | D5 test-set exposure | The human survey data have been public since 2020 and the authors state they did not test the decision models for memorisation; the C0 argument is indirect, not a contamination check (Section 7 Memorisation). |
| Lyu and Xia [140] | D5 test-set exposure | Public Amazon Reviews 2023 data recast into new candidate sets built from SASRec outputs, and the authors say knowledge-cutoff familiarity cannot be disentangled (Sec. 4.2, 6.2). [Adjudicated 2026-10-29 after the version 1.2 second rating: Amazon Reviews 2023 leave-last-out splits, whose interactions predate 2026, are used with the public held-out item as the answer; the authors note possible familiarity but run no contamination check (Sec. 4.1; Sec. 6.2).] |
| Ma et al. [141] | D4 tuning parity | Larger pruning budgets were selected as the largest budget keeping 90% retention using scores on 128 questions per public set and all 188 LIBERO frames, which are test data; only the six-block default was fixed in advance (Sec. 4.6, App. B.2). |
| Ma et al. [142] | D1 reference labels | Gold mixes FCRB calls checked by the official BFCL checker and not audited, CFB wrong calls from authors' construction (3% unconfirmed in a 100-item audit) and FinTrace wrong calls made by a rule (4% unconfirmed) (Limitations; Appendix A). [Adjudicated 2026-10-29 after the version 1.2 second rating: Wrong-value labels on CFB and FinTrace come from the authors' rule-based construction and FCRB labels from the BFCL checker program, with only a 100-item human audit (Sec. 3.2; Appendix A).] |
| Ma et al. [142] | D5 test-set exposure | FCRB and ComplexFuncBench are public 2025 benchmarks with released labels and FinTrace is a public April 2026 resource; no contamination check is reported for Jev (Section 3.2). |
| Ma et al. [144] | D3 version pinning | Jev is named only through 'Decision model documentation' accessed 2026-10-02 and no model version, API access or run date is reported (Section 1; reference 33). |
| Mazzoni and Failla [149] | D5 test-set exposure | PluRule, OLID, HateXplain, HateModerate and ModerationBench are public datasets with released labels from before 2026 and no contamination analysis is reported (Section 3.1; note Exposure). |
| Mei et al. [150] | D4 tuning parity | All variants share initial tensors, data order and budgets, but the one-epoch lower-rate recipe and design choices were selected on the same MC11 evaluation, which the authors disclose (Section 5.4; Appendix A.6). [Adjudicated 2026-10-29 after the version 1.2 second rating: MC11 is the evaluation benchmark, and the one-epoch lower-rate recipe used for every compared model was chosen from MC11 training-recipe diagnostics (Sec. 5.4; Table 4).] |
| Messoudi and Mansar [151] | D3 version pinning | Jev is pinned only as typesafe/jev-1.13 (minor version) with a run window of 'late September to early October 2026', no revision or exact dates (Appendix B.1, B.6). [Adjudicated 2026-10-29 after the version 1.2 second rating: Evaluated endpoints upstage/solar-decide and respan/span-01 carry no version or snapshot, Jev is typesafe/jev-1.13 only, and the run window is approximate (App. B.1; App. B.6).] |
| Messoudi and Mansar [151] | D5 test-set exposure | Five of six datasets are public pre-2026 benchmarks used with released labels and the authors state they cannot rule out contamination for API models, with no check run (Ethical Considerations; Table 1). |

| Study | Domain | Justification |
|---|---|---|
| Min and Chen [154] | D5 test-set exposure | AppWorld test-normal and OfficeBench are public pre-2026 benchmarks with no contamination check, but the outcome is task success under a changed compaction step, so exposure applies to all arms alike (Section 5.1). [Adjudicated 2026-10-29 after the version 1.2 second rating: Items are the verbatim AppWorld test-normal split and OfficeBench tasks, both public since 2024 with evaluation checks, and no contamination check is reported (Sec. 5.1).] |
| Mohebifar and Bit [156] | D1 reference labels | References are synthetic, generated by GPT-6-Sol, and only 150 of 1,968 cases were engineer-reviewed with no final adjudicated key (Section III; Section III-A). |
| Mu et al. [157] | D1 reference labels | Labels come from the simulator's event generator in stochastic EPANET runs, and one hydraulic model generates both events and the digital twin (Sections 2.1, 4.4). |
| Munot [159] | D5 test-set exposure | MetaTool (2024), HotpotQA (2018) and LexGLUE ECtHR (2022) items are used verbatim with public answer keys, and no contamination check is reported (Section 2 Datasets; Limitations). |
| Nandakishore [160] | D5 test-set exposure | RewardBench, RewardBench 2, RM-Bench, JudgeBench and HaluEval are public 2024 and 2025 releases with answer keys and no contamination check is reported (Section 3; note Exposure). |
| Nandakishore [161] | D1 reference labels | Gold is the mean of three samples from a roughly 4B-class teacher endpoint and 'every number in this paper measures teacher agreement on synthetic cases' (Section 3.2). |
| Pan et al. [165] | D3 version pinning | Jev and every other decision model are named without any version or revision identifier and the only dates are documentation access dates of 13 October 2026, with no run dates (Table 1; Appendix B.3-B.4; references). |
| Paramasivam and Rajkumar [167] | D3 version pinning | Hosted Jev is cited only by a documentation URL with no version string or access date, and the RubriX checkpoint has no hash (Section 4.3; reference 25). |
| Paschalides et al. [168] | D5 test-set exposure | Dynamic, MHS, HateXplain and HateCheck are public 2019 to 2021 datasets used on their test partitions, and the authors state prior training exposure remains uncertain with no contamination check (Section 5.1). |
| Perifanis et al. [171] | D3 version pinning | Jev's version string is not reported anywhere in the text, Laya's version is not stated, and run dates are not given (Section 4.12; References). |
| Polignano et al. [174] | D4 tuning parity | All design choices were made on the same development users that are reported, baselines are the authors' own implementations, and the Jev comparison is zero-shot versus Kev trained on in-domain records, with fresh-user confirmation not yet scored (Section 6.3, Section 9.2). |
| Porcedda [175] | D1 reference labels | Reference probabilities are exact by construction from templated problems, a synthetic procedure (Section 2.1). |
| Porcedda [175] | D3 version pinning | No Jev version identifier and no run date appear anywhere in the paper. |
| Porcedda [175] | D4 tuning parity | The inverse uncertainty map is fitted on the same 365 items it is scored on, with no held-out split, while SemIf gets no comparable adjustment and its setup is not described (Sections 3.1, 4, 5). |
| Qian et al. [176] | D5 test-set exposure | GSM8K, MATH-500, AIME, AMC, GPQA-Diamond, SUM and UMWP are public pre-2026 benchmarks with answer keys and no contamination check (Section 4.1). |
| Qin et al. [177] | D4 tuning parity | The model is trained on 12.3M QA drawn from SAT, RefSpatial and VST-P sources that overlap the evaluation benchmarks while generalist baselines are not, and the token cap differs between early (8,192) and later (32,768) runs (Sec. 4.1; Appendix D). |

| Study | Domain | Justification |
|---|---|---|
| Rahimi et al. [183] | D1 reference labels | References are exhaustive-search optima and a utility from the authors' own simplified numerical simulator, a synthetic procedure on simulated channels and intents (Section IV-B, IV-C). |
| Rahimi et al. [183] | D3 version pinning | No Jev version, model ID or run date is given, the comparators are named only 'GPT-Sol' and 'Qwen' without identifier, and only a blog access date of 23 September 2026 appears (Section IV-A; References). |
| Rajput et al. [184] | D5 test-set exposure | BANKING77, CLINC150 and AG News are public benchmarks predating 2026 used with their labels and no contamination check is reported (Section 3.2). |
| Rao and Callison-Burch [185] | D4 tuning parity | Criterion texts are identical, but judges receive different instructions and option orders, binary panels use a Jev wrapper, and the 5-point parity margin and several analyses were chosen post hoc (Section 3.4; Limitations). [Adjudicated 2026-10-29 after the version 1.2 second rating: The 5-point parity margin behind the headline replacement claim is post hoc, and cascade gains are also reported at oracle thresholds chosen on the evaluated pairs (Sec. 3.4; Sec. 6; Table 3).] |
| Rao and Callison-Burch [185] | D5 test-set exposure | All nine panels come from public benchmarks that predate 2026 and the authors say a judge may have seen the items or labels, with no contamination check (Limitations). |
| Ren et al. [187] | D1 reference labels | Scenario-level designer ground truth on LLM-generated calls (administrative); auxiliary training labels from a MiniMax-M3 teacher (note Reference labels). [Adjudicated 2026-10-29 after the second rating of the first sweep: Retain high. Every test prefix receives its scenario ground truth. The calls are synthetic and the references precede the model decisions. Source: Section 4 Data, Appendix B. G5 gives high.] |
| Ren et al. [187] | D4 tuning parity | The recipe was chosen from about ten variants scored on the test set ('selected with test-set exposure', Abstract; 4 Model selection) while the judge prompt was untuned. |
| Rezvani et al. [188] | D5 test-set exposure | CyberSecEval Instruct (Meta, 2023) is a public pre-2026 benchmark with released CWE labels and no contamination check is reported (Section III-A1). |
| Robitza [189] | D4 tuning parity | Input states were 'iteratively improved' over five versions in the author's own tests, and the headline uses S4, while comparators were trained with leave-one-source-out CV or are fixed standards (III-D, III-E). |
| Sadoun et al. [192] | D3 version pinning | No Jev version string is given and only a documentation access date (2026-09-26) appears in the reference list (Appendix M; reference list). |
| Saeed et al. [193] | D5 test-set exposure | All data are public pre-2026 Hugging Face benchmarks (AG News, SST-2, BoolQ, ARC, Banking77, CLINC150, MMLU) with no contamination check (Section 4; Data and Code Availability). |
| Sautenkov et al. [196] | D1 reference labels | The reference is the known location of a synthetic incident composited into satellite maps, a synthetic procedure, scored by a footprint-overlap rule (Section 4 Scenarios and maps; Measures). |
| Sautenkov et al. [196] | D4 tuning parity | The only decision system's questions and thresholds were chosen on the benchmark maps used for reporting with no held-out set, and collision and oil-spill questions were refined after the first runs and the Gemini missions repeated (Section 4 Protocol; Section 6). |
| Severo et al. [197] | D2 sampling and reporting | The abstract and highlights report a 300-flow pilot with 5,400 decisions and GPT-5.6 Luna (F1 0.859), but the body reports 2,000 flows, 6,000 decisions per finite k and Gemini 3.6 Flash (F1 0.856), so the headline counts do not reconcile (Abstract, Section 5.3, Table 2). |
| Severo et al. [197] | D5 test-set exposure | NSL-KDD (2009) is a public benchmark with released labels and no contamination check is reported (Section 5.3). |

| Study | Domain | Justification |
|---|---|---|
| Sharma and Lall [200] | D1 reference labels | Accuracy is graded CORRECT/WRONG by a gpt-4o-mini LLM judge, and the human sensitivity grading covers only the 141 judge-discordant questions and was done by the first author (Section 4 Stack; Section 5.4). |
| Sharma and Lall [200] | D5 test-set exposure | LoCoMo (2024) and LongMemEval are verbatim public benchmarks with released answers, and the 'held-out' conversations were only unrun by earlier systems, with answer-model exposure unaddressed (Section 4). |
| Sharma et al. [199] | D1 reference labels | Labels are computed by executing a stated rule over declared facts in programmatic generators, a synthetic procedure (Sec. 3.2). |
| Sheng et al. [201] | D3 version pinning | Jev is 'accessed through its official API' with no version identifier and no run date, only a vendor-blog access date of 2026-09-26 (Section 5.1, reference list). |
| Shi et al. [202] | D5 test-set exposure | iNews (ACL 2025) test records are public with released ratings, but PluriHarms is an ICLR 2026 release that may not predate 2026 and no contamination check is described for the API baselines (Section 3). [Adjudicated 2026-10-29 after the version 1.2 second rating: iNews (ACL 2025) test items are used verbatim with released ratings, and no contamination check is reported for any evaluated model (Sec. 3; App. B).] |
| Song et al. [204] | D5 test-set exposure | ReviewCritique (2024) and ReviewScore (2025) are public datasets used verbatim with released labels over papers that may be in model training data, and no contamination check is reported (Section 3.2; Ethical Considerations). |
| Song et al. [205] | D5 test-set exposure | All four datasets are public pre-2026 benchmarks used verbatim with released answer keys and no contamination check is reported, although the design targets presentation sensitivity rather than absolute accuracy (Section 2.1). |
| Stambler [209] | D1 reference labels | Gold solutions for the 128 puzzles and 47 transfer puzzles are produced by a generator (synthetic), and the form labels were written by the author except 41 SpreadsheetBench-derived fills, not independently validated (Sections 4.1 and 7; Appendix A). |
| Steiner et al. [210] | D4 tuning parity | Headline Table 4 gives every system the same default prompt B0 (low), but the selected prompt F0 is the highest test-set F1 per model and benchmark and feeds the calibration, cascade, cost and published-results comparisons, with a disclosed gain of at most 1.2 F1 except 4.6 for Clef-flash (Section 4; Table 5, Table 6, Table 12). [Adjudicated 2026-10-29 after the version 1.2 second rating: The prompt F0 for each model and benchmark is the one with the highest test-set F1 and is reused in the calibration, cascade, cost and published-results comparisons (Sec. 4; Table 6).] |
| Sun et al. [213] | D5 test-set exposure | BrowseComp-Plus and NeuCLIRBench are public benchmarks released in 2025 with answer keys and no contamination analysis (Section 4.1). |
| Sun et al. [214] | D3 version pinning | No version string for any of the three models in the text; checkpoints are deferred to the harness and the hosted model was reached 'at one point in time' (footnote 2; 7). |
| Tan et al. [215] | D1 reference labels | Attack success is scored by two model-based evaluators, the HarmBench classifier and the fine-tuned StrongREJECT evaluator, with no human adjudication of the outputs (Section 6.1; Appendix A.5). |

| Study | Domain | Justification |
|---|---|---|
| Tang and Chen [216] | D5 test-set exposure | Public pre-2026 medical datasets recast into the authors' own splits, with held-out states drawn from the same sources as training and MedGemma pretraining overlap not examined (Sec. 4.1, 6). [Adjudicated 2026-10-29 after the version 1.2 second rating: Test states are verbatim images and labels from public pre-2026 datasets such as MedMNIST, only re-split by the authors, and no backbone contamination check is reported (Sec. 4.1; Appendix A).] |
| Teke [217] | D1 reference labels | Gold is mostly AI-made (ai_ensemble_unanimous 1,659 and ai_rubric_agreed 1,157 of 4,275 questions), with only 252 owner-blind, 181 court-record and a few other human labels (Section 3.1, Table 2). |
| Teke [217] | D4 tuning parity | The author's own ufakzeka-karar had data shaped by reading test results in guardrails, moderation and customer support, so a compared system was tuned on test items (Sections 6, 7). |
| Teke [218] | D1 reference labels | Most HakemBench gold was settled by passes of AI models and only 260 questions carry human-decided gold, while the support development set and human check are answered by one person, the author (Section 6; fulltext Section 8). |
| Teke [218] | D4 tuning parity | Run 3 was trained on data aimed at Run 1's errors on the full test set and its protocol was fixed after reading Run 2's test results, while comparators are zero-shot, and the author flags the numbers as 'shaped by reading the test results' (Sections 4 and 6). |
| Teng et al. [219] | D5 test-set exposure | Banking and Newsgroups are old public datasets and BEV, Typed Decisions and JevBench are 2026 public sets, JevBench was held out of Prism-1 training, and exposure of Jev or the base models is unknown with no contamination check (Section 5.1; Table 3). [Adjudicated 2026-10-29 after the version 1.2 second rating: Banking20 and Newsgroups test items come verbatim from public pre-2026 datasets (2020, 1995) with labels, and no contamination check is reported (Sec. 5.1).] |
| Minh et al. [155] | D5 test-set exposure | Dataset B, BUSI and BUS-BRA are public pre-2026 image sets with released labels, and the authors state the evaluation cannot determine training exposure (Sec. 5.4). |
| Wang and Zang [244] | D1 reference labels | Scoring uses BBH and MuSR answer keys from templated or generated reasoning tasks (coded synthetic in the ledger; the paper does not describe provenance) plus a human-designed object-placement workflow (Section 4; Appendix H). |
| Wang and Zang [244] | D4 tuning parity | The three best of six BBH tasks were chosen after inspecting broader results including held-out results, the truth-chain program was refined by agreement on ten development inputs, and the task-conditioned envelope is post hoc, so the authors say estimates describe selected task families (Appendices C and H). |
| Wang and Zang [244] | D5 test-set exposure | BBH (2022 to 2023) and MuSR (2024) are public benchmarks with released answers and no contamination check is run for the teacher or Qwen, and development inputs were reused in admission checks (Appendix H). |
| Wang et al. [238] | D2 sampling and reporting | Per-dataset sample counts, splits, window lengths and call counts are not reported, no interval or repeat accompanies any score, and the exclusion of 14 archive datasets as 'datasets with available scores' is unexplained (Section 4.1; Table 1). |
| Wang et al. [238] | D5 test-set exposure | UCR, UEA, EasyTPP, ETT and stock series are public archives from before 2026 with released labels, and no contamination discussion is given (Section 4.1; references). |

| Study | Domain | Justification |
|---|---|---|
| Wang et al. [243] | D3 version pinning | CalOn, the evaluated model, is named without any version, release tag or weights link (printed as CalOn in Table 4), and the InstructUIE baseline is the bare name ZWK/InstructUIE, so compared systems carry no version identifier (Table 4; Table 10). [G2] |
| Wang et al. [248] | D3 version pinning | Hosted Jev has no version identifier anywhere, only a reference accessed 2026-09-27 (Sec. 4.1; reference list). |
| Wang et al. [240] | D1 reference labels | Ground-truth decisions come from GPT-4o-generated application states built so that truth differs from the attacker target, and the model-extraction reference is Jev's own answers (Sections III-A3, IV-A3; Appendix C). |
| Wang et al. [240] | D3 version pinning | No Jev version string, model ID or query date is given for the official API, only 'as of September 2026' for a download count (Section IV-B; Section I). |
| Wang et al. [242] | D3 version pinning | JEV is named with no version string or access date in the text read (Sec. 4.2, 5.1). |
| Wang and Gao [245] | D3 version pinning | The JEV version identifier is not reported and the four generative judges are named with no revision, temperature or run dates (Section 3.2; Section 4.2; Appendix C). |
| Wang et al. [239] | D3 version pinning | Jev is cited only as 'TypeSafe AI, 2026' with no version string, provider or run date; the only date is a documentation access on 2026-10-12 (Section 5.1; references). |
| Wang et al. [239] | D5 test-set exposure | MATH, MBPP+, API-Bank and IDRBench I3 are public pre-2026 benchmarks used verbatim with released tests and answers, and no contamination check is reported (Section 5.1; Appendix C.3). |
| Wang [236] | D4 tuning parity | Mnemon was developed on LoCoMo and LongMemEval-S and consolidation was designed after seeing HaluMem and BEAM-100K results, while the 14 compared systems enter as published numbers under a different grader (Sections 6.1, 7). |
| Wang [236] | D5 test-set exposure | All benchmarks are public pre-2026, 'none of the benchmarks is held out', and no contamination check is reported (Section 7). |
| Wang et al. [246] | D5 test-set exposure | GPQA-Diamond, SuperGPQA, MedQA, MedXpertQA and MMLU-Pro are public pre-2026 benchmarks with released keys, and the authors state exposure and label errors remain possible with no contamination check (Limitations). |
| Wang et al. [237] | D3 version pinning | The hosted TypeSafe Jev has no version reported, UniJev has no release identifier, and selected revisions for released baselines are recorded only in a registry outside the text (Table 2; Appendix A). |
| Weng et al. [249] | D3 version pinning | Backbones, the benchmark commit fd54ea7 (v1.4.2.2) and a 2026-09-24 snapshot date are given, but no checkpoint hashes are reported for the 1B, 35B or Part I models and the Part I fork is not released (Section 4.1; Section 6; Section 9). [Adjudicated 2026-10-29 after the version 1.2 second rating: JevBench commit and Jev 1.13.0 are given, but the compared DeepSeek Flash, a hosted endpoint, carries no version identifier and no run dates are reported (Table 3; Sec. 6).] |
| Weng et al. [249] | D4 tuning parity | The 35B was chosen when two builds' public scores (79.3 versus 80.2) were known, the 1B and drill arm were designed after seeing public-item failures, and 15 of 52 comparators were selected by the authors (Section 9, Selection). |

| Study | Domain | Justification |
|---|---|---|
| Wu et al. [254] | D4 tuning parity | alpha = 0.5 and T = 10 are stated with no separate selection data, and alpha = 0.5 is the row of the Table III sweep that the text says identifies a 'sweet spot', a sweep run on the same 100 scored episodes per dataset that every ablation reports, drawn from the evaluation benchmarks, while the replanning interval of 25 steps is 'empirically' chosen on unstated data and Table I does not say whether the baselines were re-run (Sec IV-A; Sec IV-C; Sec IV-C.2, Table III; Sec III-E; Sec IV-B). [C2] |
| Wu and Lim [255] | D1 reference labels | Attacker-target and safe actions are defined by the deterministic InjecAgent reconstruction and the endpoint is selection at the first security-critical decision, a task outcome with no annotation (Section 3.1; Appendix A). [Adjudicated 2026-10-29 after the version 1.2 second rating: Safe and attacker-target actions are fixed in advance by the InjecAgent construction and the model's single selection is compared with them, a precomputed synthetic label (Sec. 3.1; Sec. 3.2).] |
| Wu and Lim [255] | D5 test-set exposure | The 510 cases are reconstructed from the public 2024 InjecAgent benchmark into new typed states, so items are seen through derived features, and no contamination check is reported (Section 3.1; Appendix A). [Adjudicated 2026-10-29 after the version 1.2 second rating: The reconstruction keeps InjecAgent (2024) user goals, attacker goals and attack text verbatim with known attacker-target tools, and no contamination check is reported (Sec. 3.1).] |
| Wu et al. [253] | D1 reference labels | Gold actions are generated offline by fixed policy rules in two synthetic workflows and approved by the project owner, a synthetic procedure with no blinded human review (Section 4.1). |
| Wu et al. [253] | D4 tuning parity | Coverage-matched probability thresholds were set from the evaluation clean scores and the scope-aware repair was designed after seeing the original gate fail on the same tasks, so the compared gates were selected after seeing results (Section 4.3; Section 5.6; Appendix A). |
| Wu [257] | D4 tuning parity | Baseline figures are copied from Wu et al. (2026) and Sun et al. (2026) and not rerun, and MuSiQue 'was also used during method development' (Table 1 caption; Sec. 5.2, 5.5). |
| Wu [257] | D5 test-set exposure | All questions come from public multi-hop datasets (MuSiQue, 2Wiki, HotpotQA) and a public 2026 enterprise benchmark, with no contamination check (Sec. 4.1, 5.5). |
| Xie et al. [258] | D5 test-set exposure | CLINC150, BANKING77 and TREC50 texts are public pre-2026 and no contamination analysis is reported, but the tested fallback assignments and option sets are newly constructed per request (Section 3; Appendix A). [Adjudicated 2026-10-29 after the version 1.2 second rating: Inputs are verbatim CLINC150, BANKING77 and TREC test texts with their public pre-2026 labels, which fix the required outputs, and no contamination check is reported (Sec. 3; Appendix A).] |
| Xu et al. [262] | D5 test-set exposure | The seven datasets (MMLU-Pro, SuperGPQA, MuSR, ToMBench, LAR-ECHR, SATA-Bench, BFCL V4) are public pre-2026 benchmarks used verbatim with gold answers and no contamination check is reported (Section 4.1; Appendix B.2). |
| Xu et al. [259] | D4 tuning parity | All rules receive the same inputs and release guards, but the relaxed signed-number baseline was added post hoc after inspecting verifier results and the verifier predicate was written after inspecting retained labels, so the evaluation is retrospective by the authors' account (Section III-A). |
| Xu et al. [259] | D5 test-set exposure | FinQA test and train splits are public 2021 releases with answer keys and the authors place training contamination outside the evaluation's scope (Section VI). |

| Study | Domain | Justification |
|---|---|---|
| Yadav [263] | D3 version pinning | The audited model is anonymized with no name, version or run date, and the 14 frontier models are named without versions or dates (Section 1 footnote; Section 4.2; Limitations). |
| Yadav [263] | D4 tuning parity | System One gets a ten-question bundle with native probabilities while frontier models give one verbalized probability, in-domain specialists are acknowledged as contaminated, and the decomposition was hand-authored, all disclosed (Section 3; Section 4.2; Section 4.6). [Adjudicated 2026-10-29 after the version 1.2 second rating: HateBERT, Detoxify-unbiased, Perspective and the TF-IDF model were trained on Civil Comments labels that include the evaluation set, which the paper flags as contaminated (Sec. 3; Table 4).] |
| Yadav [263] | D5 test-set exposure | Civil Comments is a public 2019 corpus with released rater fractions, the author states it may overlap training data, and the out-of-distribution set is not a contamination check (Limitations; Section 4.7). |
| Yamamoto and Kuroki [264] | D4 tuning parity | PRISM is fitted to human labels and uses extra probe calls so Vanilla versus PRISM is not budget-matched, and protocols differ across judges, which the authors disclose (Limitations, Section 3). [Adjudicated 2026-10-29 after the version 1.2 second rating: SummEval was used during method and probe development and is also the main evaluation, so the design was selected after seeing results on it; budgets are also unmatched (App. A.3; App. A.5).] |
| Yamamoto and Kuroki [264] | D5 test-set exposure | All benchmarks are public pre-2026 sets (SummEval 2021 to JudgeBench 2025) with released labels, and the authors state contamination cannot be ruled out, with no check (Limitations). |
| Yan [265] | D3 version pinning | Hosted Jev has no version or run date, and all baseline numbers are imported from the Chinese-Jev paper rather than rerun (Sec. 4.5). |
| Yan [265] | D5 test-set exposure | CJ-Bench is built from public pre-2026 datasets, was evaluated in full for 14 checkpoints and six files, and the authors state no pretraining-contamination check was run (Sec. 7). |
| Yan [266] | D4 tuning parity | All conditions use the same Jev and question budget, but the vote rule and feature subset were chosen after exploratory comparisons, a disclosed selection bias (Sec. 4.3, 5.3). [Adjudicated 2026-10-29 after the version 1.2 second rating: The aggregation rule and feature-subset size were selected after exploratory comparisons, and the authors say results need confirmation on an independent test partition (Sec. 4.3).] |
| Yan [266] | D5 test-set exposure | AG News (2015) and TREC (2002) are public benchmarks with answer keys and no contamination check (Sec. 4.5). |
| Yang et al. [270] | D1 reference labels | Worlds and protected mechanisms are AI-generated and screened by three LLM judges, with authored cost units, so the labels are synthetic (Sec. 4.1, 4.3; Appendix B.4). |
| Yang et al. [270] | D3 version pinning | Per-model identifiers are recorded (jev-1.13.0, openjev-0.1, mercury-decide-20260930) but only documentation access months are given and no call dates (Table 9; Table 10). [Adjudicated 2026-10-29 after the version 1.2 second rating: Clef, Clef-flash and d1 are recorded only as clef, clef-flash and d1 with no version, and no run dates are given for most systems (Table 9; App. I.1).] |
| Ye et al. [271] | D1 reference labels | The headline reference is exact arithmetic on 64 author-generated expressions (seed 20260923) checked by an exact-rational evaluator, a synthetic procedure, with only three FRED index dates as external references (Section 4; Appendix B). |
| Yilmaz et al. [272] | D3 version pinning | No version or date is given for Jev, whose numbers are quoted from Laya's report, and LAVOIR has only the moganai/lavoir weights with no revision or run date (Table 3 caption; Section 6). |

| Study | Domain | Justification |
|---|---|---|
| You et al. [273] | D3 version pinning | Jev is identified as jev-1.13.0 accessed 21 September 2026 UTC with a matched follow-up on 24 September, and comparator model identifiers are listed (Section 3.2; Appendix B). [Adjudicated 2026-10-29 after the version 1.2 second rating: Jev is identified as jev-1.13.0 with access dates, but the compared DeepSeek model is served as deepseek-flash with no version identifier (Sec. 3.2; App. B).] |
| You et al. [273] | D5 test-set exposure | CARE-Bench Public Test 1 is a 2026 public release and HealthBench a 2025 release, and the authors state training exposure is unknown for both and that public-test labels were inspected before the follow-up (Section 6; Section 3.1). [Adjudicated 2026-10-29 after the version 1.2 second rating: HealthBench (2025) items are scored verbatim from the official open-source evaluation file, and the authors state training exposure is unknown with no contamination check (Sec. 3.5; Sec. 6).] |
| Yu and Yao [274] | D5 test-set exposure | GQA, SNLI-VE, TextVQA and TallyQA are public 2019 benchmarks and the backbone's pretraining data are undisclosed (note Test-set exposure). |
| Zhang et al. [279] | D5 test-set exposure | Items are public pre-2026 benchmark records (BANKING77, 20 Newsgroups, MASSIVE) plus public JevBench and BEV subsets, and the paper reports no contamination analysis (Sec. 6, 7). |
| Zhang and Yu [283] | D5 test-set exposure | All eight datasets are verbatim public benchmarks released before 2026 with answer keys and no contamination check, and HD has only 50 test items (Section 4.1; Table 1). |
| Zhang et al. [276] | D3 version pinning | Hosted TypeSafe Jev has no version string or run date and CS1-4B has no revision, while the open comparators are named with reference implementations and only a few model-card revisions such as JEV-27B (Methods 0.13, references 24 and 25). |
| Zhang et al. [280] | D4 tuning parity | Components were chosen for JevCoder from component studies on samples drawn from the same 200+200 tasks that the full workflow is then scored on, so the system was selected after seeing results on its test tasks (Appendix D.4 Component selection for JevCoder). |
| Zhang [281] | D3 version pinning | No version string, run date or endpoint identifier is given for Jev, although the VLM comparator has an OpenRouter ID (Section 2; Section 5.1). |
| Zhang [281] | D5 test-set exposure | AndroidWorld is a public benchmark whose tasks and checkers predate 2026 and no contamination check is reported (Section 5.1). |
| Zhang et al. [278] | D4 tuning parity | 'No test prompts or settings are selected from model performance' (3.2); reasoning levels differ, and three comparators were added post hoc with configurations fixed before their test predictions. [Adjudicated 2026-10-29 after the second rating of the first sweep: Retain high. The saved text explicitly adds Sonnet, Haiku and Terra after inspection of earlier results. Fixed later configurations do not remove that model-selection step. Source: Sections 3.1 and 3.2, Limitations. Retain high under C2. Appendix N is absent from this copy.] |
| Zhang et al. [278] | D5 test-set exposure | ContractNLI (2021) is public; 'an official held-out split does not establish absence from model training data' (Limitations). |
| Zhang et al. [277] | D5 test-set exposure | All three benchmarks are public and predate 2026 and are used verbatim with their answer keys, with no contamination check reported (Section 2.2, Table 2; note Task and data). |
| Zheng and Chen [285] | D5 test-set exposure | ProofWriter, LogiQA 2.0 and ARC-Challenge are public pre-2026 benchmarks used verbatim with their answer keys, evaluation items come from official training or test files, and no backbone contamination check is reported (Section 4.1; Appendix A). |

| Study | Domain | Justification |
|---|---|---|
| Zhong et al. [287] | D1 reference labels | Reference answers are computed by programmatic generators with exact ground truth, a synthetic procedure under the anchor, although free of annotation noise (Sec. 3.1, 4.1). |
| Zhong et al. [287] | D3 version pinning | No Jev version identifier or run date is given; the evaluated build is only implied by a documentation reference accessed 2026-09-25 (Sec. 3.2; reference list). |
| Zhou et al. [289] | D5 test-set exposure | MMLU, GSM8K, AQuA, MultiArith, SVAMP, HumanEval and WebSRC are public benchmarks with released answers and no contamination check is reported (Section 5.1; note Exposure). |
| Zhu et al. [291] | D3 version pinning | Jev is pinned at version 1.13.0 with no run date, Intern-Decision has a git revision, and Laya, Kev, SemIf and JevK5 carry no version (Sec. 5.4; Table 3; Table 9). [Adjudicated 2026-10-29 after the version 1.2 second rating: Jev is pinned as v1.13.0, but Table 3 lists Kev and Laya with no size, checkpoint or version although both come in several sizes or checkpoints (Table 3; refs. [17], [22]).] |
| Zhu et al. [291] | D4 tuning parity | Intern-Decision is fine-tuned on a 17,880-sample corpus that includes the AG News, ToolACE, Typed Decision and WildJailbreak sources it is scored on, with temperatures fitted only for it, while baselines are used as is (Table 1; Table 4 caption; Appendix B). |
| Zhu et al. [291] | D5 test-set exposure | Four of the seven suites are public pre-2026 datasets that are also training sources, public Jevbench 'has informed development', and the only overlap check covers the pilot (Sec. 4.2, 5.1). |
| Zhu et al. [290] | D1 reference labels | The central DecisionGym benchmark is the authors' simulated desk whose answer key is derived from scripted plans at every reachable state, a simulator-computed synthetic reference, and the public BFCL and When2Call labels are not described (Section 3; Appendix D). |
| Zhu et al. [290] | D3 version pinning | Jev is 'pinned as typesafe/jev-1.13' (minor version, released 15 September 2026) with runs 'accessed September to October 2026' and no exact revision or run dates (Appendix F). [Adjudicated 2026-10-29 after the version 1.2 second rating: Jev is given as typesafe/jev-1.13, but the compared OpenAI hosted Decisions API is identified only as a service with no model or version (App. F; App. G).] |
| Zhu et al. [292] | D4 tuning parity | VideoJev is trained on large post-training data (64 H200s) while baselines are used as released and some QA numbers are quoted from other sources, but one controlled Qwen3.5-4B fine-tune on the same data is reported and the decoding threshold is fixed at 0.25 (Section 3; Table 3). [Adjudicated 2026-10-29 after the version 1.2 second rating: Ablations run on the same complete test sets decided the adopted design, the MLP removal and the two-stage schedule, so settings were selected after seeing test results (Sec. 3.4; Tables 7 and 8).] |
| Zhu et al. [292] | D5 test-set exposure | Video-MME, LVBench, LongVideoBench, MLVU and the TimeLens-Bench grounding sets are public benchmarks predating 2026 and the training data come from the TimeLens lineage with no contamination analysis (Section 3.1; Section 2.4). |
| Zhuang et al. [294] | D3 version pinning | Hosted Jev is listed only as Jev (hosted) with no version or date anywhere, the StartLux checkpoints carry no hash, Perplexity Decider v1.1 and Clef have access dates but no revisions, and vLLM is 0.31 in Table 5 but 0.19.1 in Appendix D (Table 4, Table 5, Appendix D.3). |
| Zhuang et al. [294] | D4 tuning parity | The Decision Index public subset served as the development benchmark for choosing Stage 2 recipes, attention variants and seed averages, so the authors state its scores reflect model selection and are not independent test results (Section 4.1). |

| Study | Domain | Justification |
|---|---|---|
| Hume, Archer [77] | D2 sampling and reporting | Wilson and paired-t intervals are given, but how the 1,200 MMLU items were sampled is not described and the '10,000 calls' headline does not reconcile with the itemized counts (note n; Seed claims). [Adjudicated 2026-09-27 after independent second rating: the 10,000-call headline does not reconcile with the itemized trial counts] |
| Palmer, Jared [164] | D3 version pinning | Jev is unpinned ('live Jev' via /v1/systemone), with no version or date (note Decision models; Notes). |
| Palmer, Jared [164] | D4 tuning parity | Kev is LoRA-trained plus a delta fine-tune on decision-v7 with a fitted temperature, compared against zero-shot Jev on development partitions (note Comparators). |
| LocalLLaMA [133] | D1 reference labels | Soft gold is the mean of three samples from a roughly 4B teacher at temperature 0.7; the card says it 'does not measure correctness' (How it was built; Limitations). |
| Balian, Rob [9] | D4 tuning parity | Rev is LoRA-trained on the train splits of the same five datasets against zero-shot Jev; JevBench misses were read to design synthetic data (README; Limitations). |
| TypeSafe AI [232] | D1 reference labels | Reference labels are the average of GPT-6 Astra and Claude Fable 5.1 answers ('Assume the harness is correct'), a model consensus (page). |
| TypeSafe AI [232] | D2 sampling and reporting | No item counts, sample sizes or intervals for any point (note n). |
| TypeSafe AI [232] | D3 version pinning | Jev version not printed and no dates (note Decision models). |
| Rauch [186] | D2 sampling and reporting | No n, task definition or protocol; '~5-18x' is a range quoted at its ceiling (note Cost and latency). |
| Rauch [186] | D3 version pinning | No version string for Jev (note Decision model). |

## S4 Decision-model card template and full reporting checklist

This part of the electronic supplement gives the two instruments that Section 11 condenses, namely the decision-model card template and the reporting checklist in full. The card template in Table S4 lists every field an implementation's card should carry, with the kind of content each field holds and a worked example. The example column is filled from the census card of Laya, an open decision model released with an Apache license, and the entries are quoted from that card as it stood on its access date [39]. A caller that reads a card filled this way can reconstruct the decision contract record of Section 11 without returning to the original repository. Two of the fields differ between checkpoints of the same family. The Laya card for the multilingual checkpoint reports a distinct backbone, an mmBERT-base encoder rather than the ModernBERT-large encoder of the English checkpoint, and a distinct parameter count, so a card names one checkpoint and one revision rather than a model family [38].

**Table S4.** The decision-model card template, with the content each field holds and an example drawn from the Laya card.

| Field | Content | Example |
|---|---|---|
| Name. | The model's given name. | "Laya." |
| Vendor or author. | The organization or person publishing the checkpoint. | "Convai Innovations." |
| Release date. | The date the checkpoint was published. | "2026-09-18." |
| Access date. | The date the card was read for this survey. | "2026-09-24." |

| Field | Content | Example |
|---|---|---|
| Availability and license. | Open or hosted, and the license terms. | "Open weights, Apache-2.0." |
| Backbone. | The pretrained encoder or decoder and its width. | "ModernBERT-large, 395M, bidirectional, fully fine-tuned." |
| Parameter count. | The total parameter count, as reported by the weights file. | "421M total (safetensors.total 421,293,830)." |
| Decision head. | The layers and readout that turn the backbone's output into a distribution. | "2 transformer layers, an option-marker scorer, and an act/escalate head, trained from scratch; every option scored at its own [MASK] token, softmaxed over that question's options." |
| Training objective. | The loss or reward the checkpoint was trained against. | "RLCD: policy reports a distribution, reward is a strictly proper scoring rule (log + spherical, plus ranked probability score for ordinal questions), REINFORCE with group-mean baseline (GRPO-style)." |
| Training data. | The corpora or generation procedure behind training. | "Not itemized by source/size in the card beyond the RLCD training description and the separate typed-decisions fine-tuning split." |
| Primitives. | The declared answer-space types the model accepts. | "choice, score, noul." |
| State modality and context length. | What kind of input the state may be, and the token budget. | "text, email, ticket, or JSON. 512 tokens (head_max_len = 192)." |
| Cardinality limit. | Any disclosed cap on the number of options, or the observed degradation without one. | "Not disclosed as a fixed cap; accuracy degrades sharply above ~20 options at default settings (Banking77, 77 options, scores 0.425)." |
| Latency with hardware. | A timing value and the hardware it was measured on. | "39.5 ms p50 for 1 question on a Tesla T4 GPU (English checkpoint)." |
| Price. | The cost per call or per token, or its absence for a self-hosted model. | "$0 self-hosted (open weights)." |
| Confidence definition. | The formula behind any confidence value the model returns. | "Not disclosed as a formula in this card beyond the reported probabilities themselves." |
| Probability grid. | The precision or rounding of the returned probabilities. | "Not disclosed." |
| Calibration as shipped, with source. | A calibration value and the evaluation that produced it. | "Raw ECE 0.466; refitting one temperature per (question type, option count) moves mean ECE to 0.081." |
| Disclosed failure modes. | Weaknesses the publisher itself states. | "Base checkpoint near chance zero-shot on typed-decisions (0.362); Khmer collapses to 0.000 accuracy at 0.952 confidence; noul can follow its label tokens instead of the state; action.act_probability carries no usable signal (AUROC 0.30)..." |
| Evaluation protocol published. | Whether a benchmark script or methodology accompanies the card. | "Yes; BENCHMARKS.md on GitHub and a typed-decisions in-card table (400 cases, 2,000 decisions) with Jev figures marked as third-party published, not measured by Laya's authors." |
| Source URLs. | The card and repository locations the entries above were drawn from. | https://huggingface.co/convaiinnovations/laya/raw/55cf4c4ebb4ebe31b2550e8bdf3bd21b99753851/README.md and https://github.com/NandhaKishorM/laya. |

The full reporting checklist gives every item of the standard of Section 11 with its explanation written out, in the five groups of that section. Each item carries a pointer to the ledger field or the risk-of-bias domain of Wolff et al. [252] and Whiting et al. [251] that the item operationalizes, where one applies. An item that names a ledger column refers to the schema of the evidence ledger that this survey built for Section 7. That schema records a study, a model and version pin, a reference-label type, a comparator and its tuning budget, a calibration quantity, and a cascade result for every extracted number.

**Table S5.** The full reporting checklist for decision-model evaluations, with every item explained.

| Item | What to report | Explanation |
|---|---|---|
| What to pin | | |
| Model and revision | The provider or checkpoint, the resolved revision, and the date that revision was confirmed. | A name can serve a different checkpoint on a later date than the one an earlier study accessed. The ledger's version_pin column, and the risk-of-bias domain for version pinning and access dates, exist for this reason. A study that omits this item cannot be told apart from one that measured an earlier or a later revision of the same name. |
| Serving temperature | The exact decoding temperature and any other sampling parameter active at evaluation time. | A value documented on a release page is not necessarily the value a service ships by default. Comparing two studies that used different unstated temperatures compares two different predictors under one name. |
| Schema and identifiers | The literal question text, the option identifiers sent to the model, and the rubric bound to each identifier, kept as separate fields. | Proposition 5.5 decomposes an option's logit into a rubric term and a name term. Only a record that keeps the identifier and the rubric apart lets a later reader repeat the name-swap test that the proposition motivates. |
| Probability grid | The smallest positive value the model can return, and the share of returned probabilities equal to zero. | Proposition 5.2 ties this pair to a floor on achievable calibration error for rare events, before any model quality is assessed. |
| State encoding | How the state was serialized into the model's input, the token budget, and any truncation rule. | A tight per-option token budget can lose accuracy for a reason unrelated to the model's own decision quality. |
| What to sample | | |
| Reference-label provenance | Whether the reference label is human adjudicated, a human single rating, a human crowd rating, a teacher model, a model consensus, or a synthetic generation procedure. | The ledger's reference_label_type column, and the risk-of-bias domain for reference-label independence, exist for this reason. A label produced by a teacher model or a synthetic procedure is not independent evidence for a model trained toward that same teacher or procedure. |
| Sample size and exposure | The item count, the grouping against near-duplicate leakage, and whether the set predates the cutoff. | Public pre-cutoff items may already sit inside training data, and an ungrouped split can inflate agreement. |
| Calibration quantity per primitive | | |
| Choice calibration | Classwise calibration or a reliability diagram by class, reported beside any top-label accuracy value. | Top-label calibration, defined for the answer the model actually returns, can hold while classwise calibration, defined for every declared answer, fails on rarer classes. A top-label value alone never examines those classes. |

Continued on the next page

Table S5, continued

| Item | What to report | Explanation |
|---|---|---|
| Score calibration | The ranked probability score, or the calibration of the cumulative probabilities at each ordinal threshold, reported beside any expected-level value. | Proposition 5.6 exhibits two forecasts that share an expected level and disagree on every cumulative probability. An expected-level value alone cannot distinguish a well-calibrated ordinal forecaster from a poorly calibrated one. |
| Joint-question calibration | The Fréchet and Hoeffding interval or a stated dependence model, rather than the product of the marginals, for a conjunction of isolated answers. | A product of marginals asserts an independence the contract never supplied (Proposition 5.1). |
| Confidence statistic | The exact confidence formula, the answer-set size it was computed on, and whether it was compared across sizes. | Proposition 5.3 shows the accepted-answer error bound grows with the answer-set size. |
| Cascade and review results | | |
| Cascade recall | The screening stage's forwarding rate and the downstream stage's detection rate, reported as two separate values rather than one combined accuracy score. | Proposition 5.4 states the final recall as the product of these two rates. The ledger's cascade_result field records both, so that an evaluation scored only on forwarded items is not read as a measurement of the whole pipeline. |
| Review band and cost | The routing threshold or band, the assumed costs of a false positive, a false negative, and a review, and the resulting review volume. | The band of Proposition 5.4 is non-empty only under a stated cost relation. |
| Speed and cost claims | Latency and cost with the hardware, the batch size and concurrency, and whether the value is a vendor claim or an independent measurement. | A ratio changes with workload, batch size, and provider, so context is required to reproduce it. |
| Handling version churn | | |
| Revision-change protocol | A stated rule for handling a mid-study change to a served checkpoint or a default parameter, including which rows are re-run. | Otherwise rows from before and after the change can be pooled under one model name. |
| Superseded values | Both an earlier and a later value when a revision change causes disagreement, each with its own revision, date, and settlement. | This keeps an audit trail that a single overwritten number would remove. |

## S5 Full census of original implementations

This part of the electronic supplement lists every entry that Section 6 counts as an original implementation, together with Table S8, which breaks the derivative count down by parent checkpoint. Table S7 gives, for each entry, its repository identifier, its creation date, its parameter count, its base model and a naming-based family group, and Table S6 condenses this list to the fifteen families that carry an independent card. The family grouping in Table S7 follows a naming heuristic over the repository identifier rather than the recipe-family rule behind the family count cited in Section 6, so the two counts differ. The two groupings are not meant to match row for row. Every value in both tables is read directly from the companion repository's census file, with no additional rounding or aggregation beyond the parent grouping stated in the caption of the second table. The companion

repository is tagged v1.0 and reflects the literature and ecosystem cutoff of 24 September 2026, the same cutoff the main article states once in Section 2. A later sweep would be released as a new minor version, with its own recorded date, rather than by editing this listing in place.

**Table S6.** The ecosystem census, condensed to the notable families with an independent card (Section 6), with every cell abbreviated from the family's own card or repository.

| Family | Author | First release | Backbone and size | Head | Objective | Primitives | Temperature or calibration as shipped |
|---|---|---|---|---|---|---|---|
| Jev 1.13 [226] | TypeSafe AI | 15 Sep 2026 | Undisclosed; hosted only | Undisclosed; a shared prefix with isolated per-question branches is inferred [77] (inference) | RLCD, an unpublished reinforcement-learning recipe [223] | Choice, Noul, Score | Confidence statistic not documented as a formula; a vendor demo approximates $(Kp_{\max} - 1)/(K - 1)$ [225] |
| Laya (English, multilingual) [38, 39] | Convai Innovations | 18–19 Sep 2026 | ModernBERT-large 395M (English); mmBERT-base 307M (multilingual) | Two-layer option-marker scorer plus an act/escalate head, trained from scratch | RLCD: a proper scoring rule (log, spherical, ranked probability score) with a GRPO-style policy update | Choice, Score, Noul | No single shipped default; one temperature refit per question type and option count moves raw ECE 0.466 to 0.081 (English) |
| Kev [162–164] | Jared Palmer | 18–19 Sep 2026 | Qwen2.5, Qwen3 and Qwen3.5 backbones, 0.5B to 9B | LoRA adapter (rank 16) plus a pointer head reading option logits, no free-text generation | Cross-entropy on the option distribution, the decision-v6/v7 family recipe | Choice, Noul, Score | T = 2.35 (0.8B) and T = 2.30 (9B), each fitted on its own checkpoint; the other sizes are not independently re-verified |
| Bespoke-Nimble-9B [13, 14] | Bespoke Labs | 18 Sep 2026 (checkpoint original-2676) | Qwen3.5-9B | LoRA adapter (rank 16) scoring the allowed answer tokens directly | Cross-entropy over allowed answer-token logits | Choice, Score, Noul | T = 2.179 as fitted; ECE on a held-out set moves 0.052 to 0.054 as served (developer README) |
| this-that-model [59], a fine-tune of decider-2b | FLock.io | 20–23 Sep 2026 (1.0 to 1.2) | decider-2b backbone (Qwen3.5-style hybrid, 1.9B) | Inherits decider-2b's letter-logit readout; no independently trained head is disclosed | Not disclosed beyond the decider-2b lineage | Choice-style typed decisions | Not disclosed for 1.0 to 1.1; 1.2 reports 0.985 accuracy and 0.009 Brier on a frozen third-party cohort |

| Family | Author | First release | Backbone and size | Head | Objective | Primitives | Temperature or calibration as shipped |
|---|---|---|---|---|---|---|---|
| decider [148] | Mapika | 16–22 Sep 2026 | Qwen3.5 backbones, 0.8B to 35B-A3B | Letter-logit readout from the LM head, divided by a stored temperature, no separate trained head | Supervised cross-entropy stages v1–v8; PPO with a proper log score and a KL constraint, v8–v10 (2B only) | Noul, Choice, Score | T = 1.30 (2b, v10); the other sizes report stored temperatures from 1.03 to 1.94 |
| OpenThai-SystemOne [79] | iApp / OpenThaiGPT | 20 Sep 2026 | Qwen3.5-0.8B, continued-pretrained on Thai text | 256-way slot head replacing the LM head, read at one control token | Supervised decision conversion of public classification and QA data, plus a Brier-loss calibration stage | Choice (up to 255), Score, Noul | Per-type learned temperatures: choice 1.055, noul 1.047, score 1.008 |
| Von [250] | wfzyx (independent) | 19 Sep 2026 | ModernBERT-large 395M | Option-marker head with an order-invariant attention mask (v1.2) | Retrained from the v1.1 weights under the new attention mask | Choice-style decisions; Noul with a fitted prior correction | Input-conditioned calibration map rather than one scalar temperature; ECE 0.045 to 0.109 across difficulty tiers |
| Decision-1.0-Sol-2B [132] | llm-semantic-router | 21 Sep 2026 | Qwen3.5-2B | Shared candidate head reading candidate endpoints and the final query vector | Not itemized by loss or recipe in the card | Choice (2 to 255), Noul, Score | Not disclosed; the card reports 66.32% weighted accuracy only |
| Open-Jev [20] | Zefan Cai | 20 Sep 2026 | Qwen3.5-9B | LoRA adapter (rank 8) plus a scalar head initialized from a Yes/No readout | 20,204 optimizer steps over one pass of a frozen release-v2 training split | Choice, Noul, Score | T = 1.897, fitted on 512 calibration rows; test-split ECE 0.0077, out-of-domain ECE 0.0374 |
| open-jev-deberta [90] | kotoba-lang | 18 Sep 2026 | DeBERTa-v3-large | Three-layer scoring head over pooled question and option representations | Cross-entropy plus Brier loss, with gold-preserving question augmentation | Choice (up to 255), Score, Noul | Post-hoc temperature fitted on a validation split, value not restated in the card; in-domain ECE 0.022 |

| Family | Author | First release | Backbone and size | Head | Objective | Primitives | Temperature or calibration as shipped |
|---|---|---|---|---|---|---|---|
| pngwn scorer [173] | pngwn (independent) | 16 Sep 2026 | Qwen3.5-4B | LoRA (rank 16) plus a new scalar score head; sequence-classification readout per option | Not itemized beyond the scoring-head and LoRA description | Noul, Choice, Score | T = 1.75, fitted on a validation split; ECE 0.135 to 0.044 as served |
| Verdict [71] | Heman10x-NGU | 17 Sep 2026 | ModernBERT plus GLiClass, 151M | Non-autoregressive typed-question scorer, GitHub-only | RLCD with a Brier-loss term, per the repository description | Choice, Score, Noul | Not disclosed as a scalar; the repository reports calibrated confidence values |
| SemIf [221] | TheoLeeCJ | 15 Sep 2026 (as Open-Jev) | MiniCPM5-2B, Qwen3.5-4B, Qwen3.8-27B | Reads option probabilities directly from a frozen backbone, GitHub-only | No generation; per-workload temperature calibration added after the rename | Choice, Noul | Per-workload temperature calibration; value not restated in the repository card |
| OpenDecision [234] | deepanwadhwa | 17 Sep 2026 | ModernBERT-large zero-shot v2.0 | Zero-shot classification head served through a FastAPI, vendor-compatible endpoint | Not itemized; a packaged zero-shot backend rather than a newly trained recipe | Choice, Noul, Score, Relation | Not disclosed; the repository documents the API contract rather than a calibration fit |
| Jev 1.14 [224, 229] | TypeSafe AI | 14 Oct 2026 | Undisclosed; hosted only, same price and context as 1.13 | Undisclosed | RLCD, as for 1.13 (vendor wording unchanged) | Choice, Noul, Score, Box | Confidence formula now published for each primitive; Noul returns no confidence |
| Microsoft-Decision-1 [152, 153] | Microsoft | 9 Oct 2026 | Post-trained Qwen3.5-9B; hosted in Foundry and on OpenRouter | Undisclosed; single-pass scoring of every supplied option | Not disclosed | Choice, Noul, Score | Calibration goal stated; documentation advises reading Score as an ordering, not a calibrated rating |
| Trio-Spark [146] | MachineFi | 30 Sep 2026 | Undisclosed; hosted only | Undisclosed; one pass returns the chosen option and a probability for each | Not disclosed | Choice, 2 to 8 options | Vendor ECE 0.019 (10 bins) on its own panel, not claimed to transfer |

| Family | Author | First release | Backbone and size | Head | Objective | Primitives | Temperature or calibration as shipped |
|---|---|---|---|---|---|---|---|
| Clef [37] | Cloudflare | 30 Sep 2026 | Qwen3.8-27B, open weights (Apache) and hosted | Joint schema head, a small transformer over the final hidden states scoring all options of all questions | Label-smoothed cross-entropy with a Brier loss term | Choice, Score, Noul | Not disclosed; per-question softmax with no stated temperature |
| pplx-decider [172] | Perplexity | 1 Oct 2026 | Qwen3.8-27B, open weights (Apache) | A [255, 5120] decision head over the backbone, full-attention layers run noncausally | Not disclosed; training data converted into Choice and Noul decisions | Choice, Noul | One saved calibration temperature, value not stated |

**Table S7.** Every T1 original implementation in the companion repository's census (Section 6), by repository identifier, creation date, parameter count, base model and family group, and decision-head type as in Figure 3, coded from each card. A dagger marks entries added by the second sweep, whose family is the hand-assigned recipe family; other families follow a naming rule, and u marks an undisclosed head.

| Repository | Created | Parameters | Base model | Family | Hea |
|---|---|---|---|---|---|
| llm-semantic-router/Decision-1.0-Eos-0.8B | | not reported | not reported | decision-1.0-eos | b |
| llm-semantic-router/Decision-1.0-Kai-0.6B | | not reported | not reported | decision-1.0-kai | b |
| llm-semantic-router/Decision-1.0-Lex-0.6B | | not reported | not reported | decision-1.0-lex | b |
| Mapika/decider-2b | 2026-09-16 | 1,881,825,088 | Qwen/Qwen3.5-2B-Base | decider | c |
| pngwn/system-one-qwen3.5-4b-scorer | 2026-09-16 | not reported | Qwen/Qwen3.5-4B-Base | system-one-qwen3.5-4b-scorer | d |
| pngwn/nanodiff-350m-typed-decisions-lam1 | 2026-09-16 | not reported | Sebasdi/nanodiff-350m-base | nanodiff-350m-typed-decisions-lam1 | c |
| DavidHatley/system-one-mini | 2026-09-16 | 69,328,144 | distilbert/distilbert-base-uncased | system-one | a |
| Mapika/decider-2b-vision | 2026-09-16 | 2,213,241,664 | Qwen/Qwen3.5-2B-Base | decider-2b-vision | c |
| mobarmg/jev-schema-scorer-deberta-v3-large | 2026-09-17 | 435,062,785 | microsoft/deberta-v3-large | jev-schema-scorer-deberta-v3-large | d |
| bespokelabs/Bespoke-Nimble-9B | 2026-09-18 | not reported | Qwen/Qwen3.5-9B | bespoke-nimble | c |
| SargeDev/jev-distill-corpus | 2026-09-18 | not reported | not reported | jev-distill-corpus | c |
| convaiinnovations/laya | 2026-09-18 | 421,293,830 | not reported | laya | b |

| Repository | Created | Parameters | Base model | Family | Hea |
|---|---|---|---|---|---|
| com-kotobalabs/open-jev-deberta-v3-large | 2026-09-18 | 434,012,160 | microsoft/deberta-v3-large | open-jev-deberta-v3-large | b |
| Mannedood/local-system-one-student | 2026-09-18 | 149,022,731 | answerdotai/ModernBERT-base | local-system-one-student | a |
| jaredpalmer/kev-0.5b | 2026-09-18 | not reported | Qwen/Qwen2.5-0.5B | kev | b |
| larkooo/gemma-e2b-rlcd† | 2026-09-18 | not reported | google/gemma-4-E2B-it | gemma-rlcd (larkooo) | c |
| jaredpalmer/kev-0.6b | 2026-09-19 | not reported | Qwen/Qwen3-0.6B-Base | kev | b |
| convaiinnovations/laya-multilingual | 2026-09-19 | 321,908,998 | not reported | laya-multilingual | b |
| jaredpalmer/kev-4b | 2026-09-19 | not reported | Qwen/Qwen3.5-4B-Base | kev | b |
| jaredpalmer/kev-8b | 2026-09-19 | not reported | Qwen/Qwen3-8B-Base | kev | b |
| anthonym21/qwen3-0.6b-rlcd-decision† | 2026-09-19 | not reported | Qwen/Qwen3-0.6B-Base | eve-rlcd (anthonym21) | c |
| dwidlee/systemone-lite-0.5b | 2026-09-19 | 494,032,768 | Qwen/Qwen2.5-0.5B-Instruct | systemone | c |
| Mapika/decider-0.8b | 2026-09-19 | 752,393,024 | Qwen/Qwen3.5-0.8B-Base | decider | c |
| AndeyTait/JevForge-0.8B | 2026-09-19 | not reported | Qwen/Qwen3.5-0.8B | jevforge | d |
| wfzyx/von-1.0 | 2026-09-19 | 394,781,696 | answerdotai/ModernBERT-large | von-1.0 | b |
| argos1111/modernbert-ja-310m-jev | 2026-09-19 | 315,203,329 | sbintuitions/modernbert-ja-310m | modernbert-ja-310m-jev | d |
| lafalce/system-one-model | 2026-09-19 | not reported | answerdotai/ModernBERT-base | system-one-model | b |
| lewislululu/jevon | 2026-09-19 | not reported | not reported | jevon | b |
| shreyanbr/system-one-zeroshot | 2026-09-19 | 70,830,722 | MoritzLaurer/deberta-v3-xsmall-zeroshot-v1.1-all-33 | system-one-zeroshot | d |
| shreyanbr/system-one-distilled | 2026-09-19 | 70,830,722 | MoritzLaurer/deberta-v3-xsmall-zeroshot-v1.1-all-33 | system-one-distilled | d |
| shreyanbr/system-one-gold | 2026-09-19 | 70,830,722 | MoritzLaurer/deberta-v3-xsmall-zeroshot-v1.1-all-33 | system-one-gold | d |
| vagmi/jev-lite | 2026-09-19 | not reported | google/gemma-4-E4B-it | jev | c |
| Mapika/decider-35b-a3b | 2026-09-20 | 34,660,610,688 | Qwen/Qwen3.5-35B-A3B-Base | decider | c |
| Nebulaw1/jev-qwen3.5-4b-legal-lora | 2026-09-20 | not reported | Qwen/Qwen3.5-4B-Base | jev-qwen3.5-4b-legal-lora | c |
| Nebulaw1/jev-qwen3.5-0.8b-legal-lora | 2026-09-20 | not reported | Qwen/Qwen3.5-0.8B-Base | jev-qwen3.5-0.8b-legal-lora | c |
| iapp/OpenThai-SystemOne | 2026-09-20 | 752,674,883 | Qwen/Qwen3.5-0.8B-Base | openthai-systemone | a |

| Repository | Created | Parameters | Base model | Family | Hea |
|---|---|---|---|---|---|
| AstroHan/decision-head-qwen3.5-4b-rlcd-32k† | 2026-09-20 | not reported | Qwen/Qwen3.5-4B | decision-head RLCD (Astro-Han) | c |
| altslate/certo-decision-model | 2026-09-20 | not reported | not reported | certo-decision-model | b |
| azharmo/build-jev-from-scratch | 2026-09-20 | not reported | not reported | build-jev-from-scratch | a |
| ZefanCai/Open-Jev-2B | 2026-09-20 | not reported | Qwen/Qwen3.5-2B | open-jev | c |
| ZefanCai/Open-Jev-9B | 2026-09-20 | not reported | Qwen/Qwen3.5-9B | open-jev | c |
| akhilaaa3/Jev-Omni | 2026-09-20 | not reported | google/gemma-4-12B-it | jev-omni | a |
| jaredpalmer/kev-9b | 2026-09-20 | not reported | Qwen/Qwen3.5-9B-Base | kev | b |
| jaredpalmer/kev-0.8b | 2026-09-20 | not reported | Qwen/Qwen3.5-0.8B-Base | kev | b |
| samatv256/mini-Jev | 2026-09-21 | 262,657 | Qwen/Qwen3-0.6B | mini-jev | b |
| Praveenrajus/jevify-qwen3.5-4b | 2026-09-21 | not reported | Qwen/Qwen3.5-4B | jevify-qwen3.5 | b |
| Praveenrajus/jevify-qwen3.5-2b | 2026-09-21 | not reported | Qwen/Qwen3.5-2B | jevify-qwen3.5 | b |
| SargeDev/jev-gate-student-b | 2026-09-21 | not reported | not reported | jev-gate-student-b | c |
| SeanLiu/Jev-Vision | 2026-09-21 | not reported | Qwen/Qwen3-VL-8B-Instruct | jev-vision | b |
| llm-semantic-router/Decision-1.0-Nox-4B | 2026-09-21 | not reported | Qwen/Qwen3.5-4B | decision-1.0-nox | b |
| llm-semantic-router/Decision-1.0-Sol-2B | 2026-09-21 | not reported | Qwen/Qwen3.5-2B | decision-1.0-sol | b |
| Pdbz199/local-decision-model | 2026-09-21 | not reported | answerdotai/ModernBERT-base | local-decision-model | b |
| aimeigaoshou/agent-jev | 2026-09-21 | 598,418,689 | not reported | agent-jev | b |
| abidlabs/jev-typed-decisions-causal-0.6b | 2026-09-21 | not reported | Qwen/Qwen3-0.6B-Base | jev-typed-decisions-causal | c |
| mogita/jev-decider-qwen3-4b | 2026-09-21 | not reported | Qwen/Qwen3-4B | jev-decider-qwen3 | c |
| lostargon/Tiny-Jev | 2026-09-21 | 595,778,561 | Qwen/Qwen3-0.6B | tiny-jev | b |
| marcmagn1/kev-08b-typed-v1 | 2026-09-21 | not reported | not reported | kev-08b-typed | b |
| Praveenrajus/jevify-qwen3-vl-2b | 2026-09-21 | not reported | Qwen/Qwen3-VL-2B-Instruct | jevify-qwen3-vl | c |
| kaivoss/system-one-270m | 2026-09-21 | 268,098,176 | unsloth/gemma-3-270m-it | system-one | c |
| Praveenrajus/jevify-qwen3.5-4b-t2 | 2026-09-22 | not reported | Qwen/Qwen3.5-4B | jevify-qwen3.5-4b-t2 | b |
| Praveenrajus/jevify-qwen3-vl-2b-t2 | 2026-09-22 | not reported | Qwen/Qwen3-VL-2B-Instruct | jevify-qwen3-vl-2b-t2 | c |

| Repository | Created | Parameters | Base model | Family | Hea |
|---|---|---|---|---|---|
| top7777/jev-schema-scorer-deberta-v3-large | 2026-09-22 | 435,062,785 | microsoft/deberta-v3-large | jev-schema-scorer-deberta-v3-large | d |
| llm-semantic-router/Decision-1.0-Lux-9B | 2026-09-22 | not reported | Qwen/Qwen3.5-9B | decision-1.0-lux | b |
| sshalimov04/open-jev-base | 2026-09-22 | not reported | jhu-clsp/mmBERT-small | open-jev | d |
| jaswanthsanjay88/rev-decision-model | 2026-09-22 | 421,293,827 | not reported | rev-decision-model | b |
| olafura/gemma4-12b-system-one | 2026-09-22 | not reported | google/gemma-4-12B-it-qat-w4a16-ct | gemma4-12b-system-one | u |
| IJyad/jeb-typed-decisions | 2026-09-22 | 177,609,985 | IJyad/jeb | jeb | b |
| mghafiri/qwen3.5-0.8B-decision-model | 2026-09-22 | 752,393,024 | Qwen/Qwen3.5-0.8B-Base | qwen3.5-0.8b-decision-model | c |
| shreyanbr/nev-lite-systemone | 2026-09-22 | not reported | sentence-transformers/all-MiniLM-L6-v2 | nev-lite-systemone | d |
| alibiserikbay/JevK5 | 2026-09-22 | 4,205,751,296 | Qwen/Qwen3.5-4B | jevk5 | c |
| Mapika/decider-4b | 2026-09-22 | 4,205,751,296 | Qwen/Qwen3.5-4B-Base | decider | c |
| ait-hf/certus-jev-like-v0007 | 2026-09-22 | not reported | Qwen/Qwen2.5-1.5B-Instruct | certus-jev-like | c |
| tasksource/modernbert-tasksource-jev | 2026-09-22 | 152,711,041 | not reported | modernbert-tasksource-jev | b |
| tianxinwei/JevAny-27B-SFT | 2026-09-22 | not reported | Qwen/Qwen3.8-27B | jevany-27b-sft | b |
| tianxinwei/JevAny-27B-RLCR | 2026-09-22 | not reported | Qwen/Qwen3.8-27B | jevany-27b-rlcr | b |
| Praveenrajus/jevify-qwen3.5-4b-t2-lowlr | 2026-09-22 | not reported | Qwen/Qwen3.5-4B | jevify-qwen3.5-4b-t2-lowlr | b |
| FluidInference/kev-0-5b-coreml | 2026-09-22 | not reported | not reported | kev-0-5b-coreml | b |
| vigneshlabs/ballot-jev-0.5b | 2026-09-22 | not reported | Qwen/Qwen2.5-0.5B | ballot-jev | b |
| ZefanCai/Open-Jev-27B-v1.1 | 2026-09-22 | not reported | Qwen/Qwen3.8-27B | open-jev | c |
| asjson/jevson-4b-01 | 2026-09-23 | not reported | Qwen/Qwen3-4B | jevson-4b-01 | u |
| SUPER321/jevflash-doom-basic-0.6b | 2026-09-23 | not reported | Qwen/Qwen3-0.6B-Base | jevflash-doom-basic | b |
| 0xSojalSec/Jev-Omni | 2026-09-23 | not reported | google/gemma-4-12B-it | jev-omni | a |
| bespokelabs/Bespoke-Nimble-9B-v2† | 2026-09-23 | not reported | Qwen/Qwen3.5-9B | Nimble (Bespoke Labs) | c |
| guanxuyu/visual-jev-4b-answer-sft | 2026-09-23 | not reported | Qwen/Qwen3-VL-4B-Instruct | visual-jev-4b-answer-sft | c |
| DawoodKMasood/jev-gemma-3-270m | 2026-09-23 | not reported | google/gemma-3-270m-it | jev-gemma-3 | c |
| autotrust/JEV | 2026-09-23 | 7,936,684,544 | Qwen/Qwen3.5-9B | jev | a |

| Repository | Created | Parameters | Base model | Family | Hea |
|---|---|---|---|---|---|
| autotrust/JEV-9B† | 2026-09-23 | not reported | Qwen/Qwen3.5-9B | JEV (AutoTrust) | a |
| xuhaodev/Qwen3-1.7B-Jev | 2026-09-23 | not reported | Qwen/Qwen3-1.7B | qwen3-1.7b-jev | c |
| soyrsoyr/jev-playground-rlcd | 2026-09-23 | not reported | MoritzLaurer/deberta-v3-large-zeroshot-v2.0 | jev-playground-rlcd | d |
| TokenRhythm/NeoHorse-Jev-4B | 2026-09-23 | not reported | TokenRhythm/NeoHorse-1-4B | neohorse-jev | b |
| chaoliangUNSW/Jev-Style-Qwen3.5-2B-Decision-v2 | 2026-09-23 | 1,881,825,088 | Qwen/Qwen3.5-2B-Base | jev-style-qwen3.5-2b-decision | c |
| JohnP1/kev-gemma4-e2b | 2026-09-23 | not reported | google/gemma-4-E2B | kev-gemma4-e2b | b |
| DKNTZMN/gan8-vs-jev | 2026-09-23 | not reported | not reported | gan8-vs-jev | a |
| wwydmanski/bielik-minitron-jev-v0.1 | 2026-09-23 | not reported | speakleash/Bielik-Minitron-7B-v3.0-Instruct | bielik-minitron-jev | b |
| lostargon/Tiny-Jev-1.7B | 2026-09-23 | 1,720,032,257 | Qwen/Qwen3-1.7B | tiny-jev | b |
| wwydmanski/bielik-minitron-jev-v0.2 | 2026-09-23 | not reported | speakleash/Bielik-Minitron-7B-v3.0-Instruct | bielik-minitron-jev | b |
| alibiserikbay/JevK5-2B | 2026-09-23 | 1,881,825,088 | Qwen/Qwen3.5-2B | jevk5 | c |
| SargeDev/Jev_Qwen3.8-27B | 2026-09-24 | 26,895,998,464 | huihui-ai/Huihui-Qwen3.8-27B-abliterated | jev_qwen3.8 | u |
| guoan1/jev-qwen35-08b | 2026-09-24 | not reported | Qwen/Qwen3.5-0.8B-Base | jev-qwen35 | c |
| Fr0zencr4nE/jev-spatial | 2026-09-24 | not reported | allenai/Molmo2-ER | jev-spatial | a |
| jaredpalmer/kev-27b† | 2026-09-24 | not reported | Qwen/Qwen3.8-27B | kev (jared-palmer) | b |
| shgao/rsi-jev-v1.0-qwen3.5-0.8b† | 2026-09-24 | not reported | Qwen/Qwen3.5-0.8B-Base | RSI-Jev (shgao) | b |
| Rydward98/Jev-Omni | 2026-09-24 | not reported | google/gemma-4-12B-it | jev-omni | a |
| wwydmanski/bielik-minitron-jev-v0.3 | 2026-09-24 | not reported | speakleash/Bielik-Minitron-7B-v3.0-Instruct | bielik-minitron-jev | b |
| VTXAI/VTX-JEV-1 | 2026-09-24 | 7,133,398 | not reported | vtx-jev-1 | b |
| divyanshx11/JEVision | 2026-09-24 | not reported | Qwen/Qwen3.5-0.8B-Base | jevision | b |
| joyfox/Qwen3.5-0.8B-JEV | 2026-09-24 | not reported | Qwen/Qwen3.5-0.8B | qwen3.5-0.8b-jev | b |
| Quazim0t0/Byrne-Jev-79M | 2026-09-24 | not reported | not reported | byrne-jev | b |
| chaoliangUNSW/Jev-Style-0.8B-Decision-v3† | 2026-09-24 | not reported | Qwen/Qwen3.5-0.8B | Jev-Style (chaoliangUNSW) | c |
| Rckflr/kev-gemma-270m-experimental† | 2026-09-24 | not reported | google/gemma-3-270m | Kev recipe (Rckflr) | b |
| flymy-ai/decision-4b-v1.1† | 2026-09-25 | not reported | Qwen/Qwen3.5-4B | Decision 4B (flymy-ai) | c |

| Repository | Created | Parameters | Base model | Family | Hea |
|---|---|---|---|---|---|
| flymy-ai/decision-4b-v1.2† | 2026-09-25 | not reported | Qwen/Qwen3.5-4B | Decision 4B (flymy-ai) | c |
| Praveenrajus/jevify-qwen3.5-4b-readout-coh† | 2026-09-25 | not reported | Qwen/Qwen3.5-4B | jevify (Praveenrajus) | c |
| Praveenrajus/jevify-qwen3.5-4b-readout† | 2026-09-25 | not reported | Qwen/Qwen3.5-4B | jevify (Praveenrajus) | c |
| Praveenrajus/jevify-qwen3.5-4b-base-readout-coh† | 2026-09-25 | not reported | Qwen/Qwen3.5-4B-Base | jevify (Praveenrajus) | c |
| Praveenrajus/jevify-gemma-4-e4b-it-readout-coh† | 2026-09-25 | not reported | google/gemma-4-E4B-it | jevify (Praveenrajus) | c |
| Praveenrajus/jevify-qwen3.5-2b-readout† | 2026-09-25 | not reported | Qwen/Qwen3.5-2B | jevify (Praveenrajus) | c |
| Praveenrajus/jevify-qwen3.5-2b-readout-coh† | 2026-09-25 | not reported | Qwen/Qwen3.5-2B | jevify (Praveenrajus) | c |
| Praveenrajus/jevify-qwen3.5-2b-base-readout† | 2026-09-25 | not reported | Qwen/Qwen3.5-2B-Base | jevify (Praveenrajus) | c |
| Praveenrajus/jevify-qwen3.5-4b-base-readout† | 2026-09-25 | not reported | Qwen/Qwen3.5-4B-Base | jevify (Praveenrajus) | c |
| Praveenrajus/jevify-qwen3.5-9b-readout† | 2026-09-25 | not reported | Qwen/Qwen3.5-9B | jevify (Praveenrajus) | c |
| Praveenrajus/jevify-gemma-4-e4b-it-readout† | 2026-09-25 | not reported | google/gemma-4-E4B-it | jevify (Praveenrajus) | c |
| Praveenrajus/jevify-qwen3.5-2b-base-readout-coh† | 2026-09-25 | not reported | Qwen/Qwen3.5-2B-Base | jevify (Praveenrajus) | c |
| sunziqin/millennium-jev-0.5b† | 2026-09-25 | not reported | Qwen/Qwen2.5-0.5B-Instruct | millennium-jev (sunziqin) | b |
| alibiserikbay/JevK5-9B† | 2026-09-25 | not reported | Qwen/Qwen3.5-9B | JevK5 (alibiserikbay) | c |
| Praveenrajus/jevify-gemma-4-e4b-readout† | 2026-09-25 | not reported | google/gemma-4-E4B | jevify (Praveenrajus) | c |
| sdmlai/nano-jev† | 2026-09-25 | not reported | microsoft/MiniLM-L12-H384-uncased | nano-jev (sdmlai) | d |
| skundu42/kev† | 2026-09-25 | not reported | jhu-clsp/ettin-encoder-400m | kev-encoder (skundu42) | d |
| Praveenrajus/jevify-qwen3.5-9b-readout-coh† | 2026-09-25 | not reported | Qwen/Qwen3.5-9B | jevify (Praveenrajus) | c |
| sunziqin/millennium-jev-1.5b† | 2026-09-25 | not reported | Qwen/Qwen2.5-1.5B-Instruct | millennium-jev (sunziqin) | b |
| Praveenrajus/Llama-3.1-Tulu-3-8B-DPO-jevify-readout† | 2026-09-25 | not reported | allenai/Llama-3.1-Tulu-3-8B-DPO | jevify (Praveenrajus) | c |
| Praveenrajus/Llama-3.1-Tulu-3-8B-DPO-jevify-readout-coh† | 2026-09-25 | not reported | allenai/Llama-3.1-Tulu-3-8B-DPO | jevify (Praveenrajus) | c |
| Praveenrajus/Llama-3.1-Tulu-3-8B-SFT-jevify-readout† | 2026-09-25 | not reported | allenai/Llama-3.1-Tulu-3-8B-SFT | jevify (Praveenrajus) | c |
| HIT-TMG/JevEmbed-KaLM-Embedding-V2.5† | 2026-09-25 | not reported | KaLM-Embedding/KaLM-embedding-multilingual-mini-instruct-v2.5 | JevEmbed (HIT-TMG) | d |
| Praveenrajus/Llama-3.1-Tulu-3-8B-SFT-jevify-readout-coh† | 2026-09-25 | not reported | allenai/Llama-3.1-Tulu-3-8B-SFT | jevify (Praveenrajus) | c |
| Praveenrajus/jevify-smollm3-3b-sft-readout† | 2026-09-25 | not reported | HuggingFaceTB/SmolLM3-3B-checkpoints | jevify (Praveenrajus) | c |

| Repository | Created | Parameters | Base model | Family | Hea |
|---|---|---|---|---|---|
| Praveenrajus/jevify-smollm3-3b-sft-readout-coh† | 2026-09-25 | not reported | HuggingFaceTB/SmolLM3-3B-checkpoints | jevify (Praveenrajus) | c |
| Praveenrajus/jevify-smollm3-3b-apo-readout† | 2026-09-25 | not reported | HuggingFaceTB/SmolLM3-3B-checkpoints | jevify (Praveenrajus) | c |
| Praveenrajus/jevify-smollm3-3b-apo-readout-coh† | 2026-09-25 | not reported | HuggingFaceTB/SmolLM3-3B-checkpoints | jevify (Praveenrajus) | c |
| ryandcunha/mmbu-jev-qwen3-0.6b-closed† | 2026-09-25 | not reported | Qwen/Qwen3-0.6B | any2jev-built (ryandcunha) | b |
| nouton/jev-ru-4b-lora-v2† | 2026-09-25 | not reported | Qwen/Qwen3.5-4B | Jev-RU (nouton) | c |
| NAME0x0/Jevlet† | 2026-09-25 | not reported | BAAI/bge-small-en-v1.5 | Jevlet (NAME0x0) | b |
| sidman007/jev-vlm-4b-lite-gguf† | 2026-09-25 | not reported | Qwen/Qwen3.5-4B-Base | jev-vlm (sidman007) | c |
| HIT-TMG/JevEmbed-Qwen3-Embedding-0.6B† | 2026-09-26 | not reported | Qwen/Qwen3-Embedding-0.6B | JevEmbed (HIT-TMG) | d |
| shgao/rsi-jev-v2.0-qwen3.5-2b† | 2026-09-26 | not reported | Qwen/Qwen3.5-2B-Base | RSI-Jev (shgao) | b |
| per2021/kev-2b-qwen3.5† | 2026-09-26 | not reported | Qwen/Qwen3.5-2B-Base | Kev recipe (per2021) | b |
| aravind1706/decider-ettin† | 2026-09-26 | not reported | jhu-clsp/ettin-encoder-68m | decider-ettin (aravind1706) | b |
| jaluus/jevpertus-v1.5-8B† | 2026-09-26 | not reported | swiss-ai/Apertus-v1.5-8B | JevPertus (jaluus) | b |
| jaluus/jevpertus-8B-Instruct-2509† | 2026-09-26 | not reported | swiss-ai/Apertus-8B-Instruct-2509 | JevPertus (jaluus) | b |
| hiteshluke/zyot-decider-12b-adapter† | 2026-09-26 | not reported | not reported | Zyot Decider (hiteshluke) | u |
| chaoliangUNSW/Jev-Style-2B-Decision-v3† | 2026-09-27 | not reported | Qwen/Qwen3.5-2B | Jev-Style (chaoliangUNSW) | c |
| dr3x1/jevsec† | 2026-09-27 | not reported | XHToken/Spark-X2.5-4B | jevsec (dr3x1) | u |
| shgao/rsi-jev-v2.1-qwen3.5-2b† | 2026-09-27 | not reported | Qwen/Qwen3.5-2B-Base | RSI-Jev (shgao) | b |
| Quazim0t0/On-Fly-Jev† | 2026-09-27 | not reported | not reported | Spiking Jev (Quazim0t0) | b |
| abhishek085/jev-control-core† | 2026-09-27 | not reported | Qwen/Qwen3.5-0.8B-Base | jev-control-core decoder (abhishek085) | c |
| abhishek085/jev-control-es† | 2026-09-27 | not reported | answerdotai/ModernBERT-base | jev-control-es encoder (abhishek085) | b |
| ytbai/MiniCPM5-2B-Jev† | 2026-09-28 | not reported | openbmb/MiniCPM5-2B | MiniCPM5-2B-Jev (ytbai) | a |
| rongxinzy/LightJev-0.6B-typed-decisions† | 2026-09-28 | not reported | Qwen/Qwen3-0.6B | LightJev (rongxinzy) | b |
| tasksource/tasksource-decider-nano† | 2026-09-28 | not reported | cross-encoder/ettin-reranker-150m-v1 | tasksource-decider (tasksource) | b |
| sainath/tiny-jev-support-v03-supervised† | 2026-09-28 | not reported | Qwen/Qwen3-1.7B | Tiny-Jev (sainath) | d |

| Repository | Created | Parameters | Base model | Family | Hea |
|---|---|---|---|---|---|
| avbiswas/bev-decider-0.4B† | 2026-09-28 | not reported | Qwen/Qwen3-0.6B | bev-decider (avbiswas) | b |
| shgao/rsi-jev-v3.0-qwen3.5-2b† | 2026-09-28 | not reported | Qwen/Qwen3.5-2B-Base | RSI-Jev (shgao) | b |
| BricksDisplay/jevling-0.8b-v0.1† | 2026-09-28 | not reported | Qwen/Qwen3.5-0.8B | Jevling (Bricks-Display) | c |
| BricksDisplay/jevling-e2b-v0.1† | 2026-09-28 | not reported | google/gemma-4-E2B-it | Jevling (Bricks-Display) | c |
| MSGEncrypted/ocf-typed-decisions-mbert-base† | 2026-09-28 | not reported | answerdotai/ModernBERT-base | OCF (MSGEncrypted) | b |
| flymy-ai/decision-4b-v1.4† | 2026-09-28 | not reported | Qwen/Qwen3.5-4B | Decision 4B (flymy-ai) | c |
| vincentzhou/jev-student-4b-yizao† | 2026-09-29 | not reported | Qwen/Qwen3.5-4B-Base | jev-student (vincentzhou) | c |
| hotchpotch/bekko-system-one-v0-17m† | 2026-09-29 | not reported | cross-encoder/ettin-reranker-17m-v1 | Bekko System One (hotchpotch) | b |
| mohdyaser/jev-multimodal† | 2026-09-29 | not reported | mlx-community/gemma-4-e4b-it-4bit | jev-multimodal (mohdyaser) | c |
| startlux-models/StartLux-Decision-v1-0.8B† | 2026-09-29 | not reported | not reported | StartLux-Decision (startlux-models) | c |
| startlux-models/StartLux-Decision-v1-2B† | 2026-09-29 | not reported | not reported | StartLux-Decision (startlux-models) | c |
| startlux-models/StartLux-Decision-v1-4B† | 2026-09-29 | not reported | not reported | StartLux-Decision (startlux-models) | c |
| startlux-models/StartLux-Decision-v1-27B† | 2026-09-29 | not reported | not reported | StartLux-Decision (startlux-models) | c |
| startlux-models/StartLux-Decision-v1-9B† | 2026-09-29 | not reported | not reported | StartLux-Decision (startlux-models) | c |
| autotrust/JEV-Gemma4-26B-A4B† | 2026-09-29 | not reported | google/gemma-4-26B-A4B-it | JEV (AutoTrust) | a |
| Mapika/decider-12b† | 2026-09-29 | not reported | google/gemma-4-12B-it | decider (Mapika) | c |
| Mapika/decider-chat-gemma4-31b† | 2026-09-29 | not reported | google/gemma-4-31B-it | decider (Mapika) | c |
| Mapika/decider-chat-qwen3.6-27b† | 2026-09-29 | not reported | Qwen/Qwen3.6-27B | decider (Mapika) | c |
| flymy-ai/decision-4b-v1.5† | 2026-09-29 | not reported | Qwen/Qwen3.5-4B | Decision 4B (flymy-ai) | c |
| CVLTAI/s1-jev-cvltist† | 2026-09-30 | not reported | Qwen/Qwen3.5-4B | s1 (CVLTAI) | c |

| Repository | Created | Parameters | Base model | Family | Hea |
|---|---|---|---|---|---|
| seongyeon1/dlm-jev-tickets-lora† | 2026-09-30 | not reported | mlx-community/diffusiongemma-26B-A4B-it-4bit | dlm-jev (seongyeon1) | c |
| bespokelabs/Bespoke-Nimble-9B-v3† | 2026-09-30 | not reported | Qwen/Qwen3.5-9B | Nimble (Bespoke Labs) | c |
| autotrust/JEV-27B-VL† | 2026-09-30 | not reported | Qwen/Qwen3.8-27B | JEV (AutoTrust) | a |
| jevhome/jevhome-E† | 2026-09-30 | not reported | ibm-granite/granite-embedding-small-english-r2 | jevhome (Frej) | d |
| jevhome/jevhome-B† | 2026-09-30 | not reported | answerdotai/ModernBERT-base | jevhome (Frej) | b |
| jevhome/jevhome-L† | 2026-09-30 | not reported | answerdotai/ModernBERT-Large-Instruct | jevhome (Frej) | b |
| jevhome/jevhome-ettin-1b† | 2026-09-30 | not reported | jhu-clsp/ettin-encoder-1b | jevhome (Frej) | b |
| Maincode/Matilda-Jev-v1† | 2026-09-30 | not reported | Qwen/Qwen3.8-27B | Matilda-Jev (Maincode) | a |
| TerryGao9/zh-decision-mmbert-v1b† | 2026-09-30 | not reported | jhu-clsp/mmBERT-base | zh-decision-mmbert (TerryGao9) | b |
| BricksDisplay/jevling-0.8b-v1† | 2026-09-30 | not reported | Qwen/Qwen3.5-0.8B | Jevling (BricksDisplay) | c |
| StrandsAgents/strands-decider-2B-hobson-v19† | 2026-09-30 | not reported | Qwen/Qwen3.5-2B-Base | strands-decider (StrandsAgents) | b |
| Cloudflare/clef† | 2026-09-30 | not reported | Qwen/Qwen3.8-27B | Clef (Cloudflare) | b |
| Cloudflare/clef-flash† | 2026-09-30 | not reported | Qwen/Qwen3.5-9B | Clef (Cloudflare) | b |
| shgao/rsi-jev-v4.0-vl-qwen3.5-2b† | 2026-10-01 | not reported | Qwen/Qwen3.5-2B-Base | RSI-Jev (shgao) | b |
| startlux-models/StartLux-Decision-v1-35B-A3B† | 2026-10-01 | not reported | not reported | StartLux-Decision (startlux-models) | c |
| sennaLLMLearner/qwen3-4b-system-one-lora† | 2026-10-01 | not reported | Qwen/Qwen3-4B-Instruct-2507 | system-one LoRA (sennaLLMLearner) | c |
| muhammadnoman76/jev-urdu† | 2026-10-01 | not reported | jhu-clsp/mmBERT-base | Jev-Urdu (LughaatNLP) | b |
| hiteshluke/zyot-decider-v3-verbalizer-4b† | 2026-10-01 | not reported | unsloth/gemma-3-4b-it | Zyot Decider (hiteshluke) | c |
| perplexity-ai/pplx-decider-v1-27b† | 2026-10-01 | not reported | Qwen/Qwen3.8-27B | pplx-decider (Perplexity) | a |
| xuhaodev/Qwen3.5-4B-Jev† | 2026-10-01 | not reported | Qwen/Qwen3.5-4B | Qwen3.5-4B-Jev (xuhaodev) | c |
| smha1012/jev-27b† | 2026-10-02 | not reported | Qwen/Qwen3.8-27B | jev-torch (smha1012) | a |
| Praveenrajus/jevify-qwen-agentworld-35b-a3b-readout-coh† | 2026-10-02 | not reported | Qwen/Qwen-AgentWorld-35B-A3B | jevify (Praveenrajus) | c |
| carrtesy/EXAONE-4.0-1.2B-JEV† | 2026-10-02 | not reported | LGAI-EXAONE/EXAONE-4.0-1.2B | EXAONE-JEV (carrtesy) | c |

| Repository | Created | Parameters | Base model | Family | Hea |
|---|---|---|---|---|---|
| torchcast-ai/torchcast-decision-12b† | 2026-10-02 | not reported | google/gemma-4-12B-it | torchcast-decision (torchcast-ai) | c |
| nickprock/archai-jev-qwen-1.5b† | 2026-10-02 | not reported | Qwen/Qwen2.5-1.5B-Instruct | archai-jev (nickprock) | c |
| projectj/Flight-Autopilot-Decision-Model-Maverick1.0† | 2026-10-03 | not reported | Qwen/Qwen3-0.6B | Maverick (projectj) | c |
| Kestrelyn/kestrel-decider-230m† | 2026-10-03 | not reported | LiquidAI/LFM2.5-230M-Base | Kestrel Decider (Kestrelyn) | b |
| shgao/rsi-jev-v5.0-vl-3b† | 2026-10-03 | not reported | Qwen/Qwen3.5-4B-Base | RSI-Jev (shgao) | b |
| nickprock/archai-jev-zagreus-0.4b-ita† | 2026-10-03 | not reported | mii-llm/zagreus-0.4B-ita | archai-jev (nickprock) | c |
| systemonedev/kenning-large-v0.4† | 2026-10-03 | not reported | MoritzLaurer/deberta-v3-large-zeroshot-v2.0-c | kenning-large (systemonedev) | d |
| BricksDisplay/jevling-e2b-v1† | 2026-10-03 | not reported | google/gemma-4-E2B-it | Jevling (BricksDisplay) | c |
| AmirBraham/jevstral-8b† | 2026-10-04 | not reported | mistralai/Ministral-3-8B-Base-2512 | Jevstral (AmirBraham) | b |
| weihongliang/jevtrainer-qwen35-0.8b-2026-10-02† | 2026-10-04 | not reported | Qwen/Qwen3.5-0.8B | jevtrainer (weihongliang) | c |
| knowlet/Gemma-4-12B-Unified-System-One† | 2026-10-04 | not reported | google/gemma-4-12B-it | S1 Unified (knowlet) | c |
| decision-tune/decisiontune-1.0† | 2026-10-04 | not reported | answerdotai/ModernBERT-large | DecisionTune (decision-tune) | b |
| ParallaxOpen/Vela-Decision-170M† | 2026-10-04 | not reported | not reported | Vela (ParallaxOpen) | b |
| yuanphd/jevmark† | 2026-10-04 | not reported | Qwen/Qwen3-0.6B-Base | jevmark (yuanphd) | c |
| theshekslaw/clinical-jev-qwen3.5-2b-mtsamples† | 2026-10-05 | not reported | Qwen/Qwen3.5-2B-Base | clinical-jev (theshekslaw) | c |
| chendren/cx-decider-applied-v1† | 2026-10-05 | not reported | Qwen/Qwen3.5-2B-Base | cx-decider (chendren) | b |
| weihongliang/jevtrainer-qwen35-2b-2026-10-05† | 2026-10-05 | not reported | Qwen/Qwen3.5-2B | jevtrainer (weihongliang) | c |
| perplexity-ai/pplx-decider-v1.1-27b† | 2026-10-05 | not reported | Qwen/Qwen3.8-27B | pplx-decider (Perplexity) | a |
| gabrielfior/decider-q2b-1.1b† | 2026-10-05 | not reported | Qwen/Qwen3.5-2B-Base | decider-q2b (gabrielfior) | b |
| ZhangPY/kev-snake-vision-grpo† | 2026-10-05 | not reported | Qwen/Qwen3.5-4B-Base | kev-snake (ZhangPY) | b |
| AlephFunk/jev-qwen† | 2026-10-05 | not reported | Qwen/Qwen3.5-4B-Base | jev-qwen (AlephFunk) | c |
| StrandsAgents/strands-decider-2B-hobson-v21† | 2026-10-05 | not reported | Qwen/Qwen3.5-2B-Base | strands-decider (StrandsAgents) | b |
| cribl-ai/cribl-decision-1.0† | 2026-10-05 | not reported | Qwen/Qwen3.5-4B-Base | cribl-decision (cribl-ai) | c |
| sgaseretto/diffcider-typed-decisions† | 2026-10-06 | not reported | dllm-hub/Qwen3-0.6B-diffusion-mdlm-v0.1 | sysone (sgaseretto) | c |
| shunmoridev/llm-jp-4.1-33b-systemone-experimental† | 2026-10-06 | not reported | llm-jp/llm-jp-4.1-33b-thinking | llm-jp systemone (shunmoridev) | c |

| Repository | Created | Parameters | Base model | Family | Hea |
|---|---|---|---|---|---|
| shgao/rsi-jev-v6.0-vl-4b† | 2026-10-06 | not reported | Qwen/Qwen3.5-4B-Base | RSI-Jev (shgao) | b |
| systemonedev/kenning-large-v0.5† | 2026-10-06 | not reported | MoritzLaurer/deberta-v3-large-zeroshot-v2.0-c | kenning-large (systemonedev) | d |
| thinkingdbx/DECISIONx-1.5B† | 2026-10-06 | not reported | Qwen/Qwen2.5-1.5B-Instruct | DECISIONx (thinkingdbx) | b |
| odunola/lfm2.5_jev_style† | 2026-10-06 | not reported | LiquidAI/LFM2.5-350M | Audio Jev text (odunola) | b |
| systemonedev/kenning-xl-v0.6† | 2026-10-06 | not reported | Qwen/Qwen3-1.7B | kenning-xl (systemonedev) | c |
| shgao/rsi-jev-v6.1-vl-4b† | 2026-10-07 | not reported | Qwen/Qwen3.5-4B-Base | RSI-Jev (shgao) | b |
| LMDHQ-0420/vision-jev† | 2026-10-07 | not reported | Qwen/Qwen3.5-0.8B | Vision-Jev (LMDHQ) | b |
| UlkuTuncerKucuktas/vistalab-system-one-12b† | 2026-10-07 | not reported | not reported | vistalab-system-one (UlkuTuncerKucuktas) | c |
| UlkuTuncerKucuktas/vistalab-system-one-e4b† | 2026-10-07 | not reported | google/gemma-4-E4B-it | vistalab-system-one (UlkuTuncerKucuktas) | c |
| Mapika/decider-31b† | 2026-10-07 | not reported | google/gemma-4-31B-it | decider (Mapika) | c |
| j-raghavan/s1-gemma4-26b-decision† | 2026-10-07 | not reported | google/gemma-4-26B-A4B-it | s1-decision-model (j-raghavan) | c |
| chenz53/Jev-alpha-26B-A4B† | 2026-10-08 | not reported | google/gemma-4-26B-A4B-it | Jev-alpha (chenz53) | c |
| ksonny4/modernbert-jev-v2† | 2026-10-08 | not reported | not reported | modernbert-jev (KSonny4) | d |
| shgao/rsi-jev-v6.1-vl-27b† | 2026-10-08 | not reported | Qwen/Qwen3.8-27B | RSI-Jev (shgao) | b |
| systemonedev/kenning-large-v0.6† | 2026-10-08 | not reported | tasksource/ModernBERT-large-nli | kenning-large (systemonedev) | d |
| weihongliang/jevtrainer-qwen35-2b-agent-2026-10-08† | 2026-10-09 | not reported | Qwen/Qwen3.5-2B | jevtrainer (weihongliang) | c |
| HanWangTJU/haidass1.5-143m-jev† | 2026-10-09 | not reported | DALabCommunity/Haidass1.5-143M | Haidass-Jev (HanWangTJU) | b |
| Maincode/Matilda-Jev-v1.5† | 2026-10-09 | not reported | Qwen/Qwen3.8-27B | Matilda-Jev (Maincode) | a |
| Cloudflare/clef-omni† | 2026-10-09 | not reported | Qwen/Qwen3-Omni-30B-A3B-Instruct | Clef (Cloudflare) | b |
| StrandsAgents/strands-decider-E2B-gemma4-v1-2610† | 2026-10-09 | not reported | google/gemma-4-E2B-it | strands-decider (StrandsAgents) | b |
| StrandsAgents/strands-decider-12B-gemma4-v1-2610† | 2026-10-09 | not reported | google/gemma-4-12B-it | strands-decider (StrandsAgents) | b |
| StrandsAgents/strands-decider-E4B-gemma4-v1-2610† | 2026-10-09 | not reported | google/gemma-4-E4B-it | strands-decider (StrandsAgents) | b |
| StrandsAgents/strands-decider-26B-A4B-gemma4-v1-2610† | 2026-10-09 | not reported | google/gemma-4-26B-A4B-it | strands-decider (StrandsAgents) | b |

| Repository | Created | Parameters | Base model | Family | Hea |
|---|---|---|---|---|---|
| cribl-ai/cribl-decision-1.0-0.8B† | 2026-10-09 | not reported | Qwen/Qwen3.5-0.8B | cribl-decision (cribl-ai) | c |
| StrandsAgents/strands-decider-2B-qwen3.5-v1-2610† | 2026-10-09 | not reported | Qwen/Qwen3.5-2B-Base | strands-decider (StrandsAgents) | b |
| lxls/typed-decider-150m-v1† | 2026-10-09 | not reported | jhu-clsp/ettin-encoder-150m | typed-decider (lxls) | b |
| bespokelabs/Bespoke-Nimble-27B-v3† | 2026-10-09 | not reported | not reported | Nimble (Bespoke Labs) | u |
| SargeDev/Solar-JEV-Gemma-embed-2† | 2026-10-09 | not reported | google/embeddinggemma-2 | Solar-JEV frozen-encoder heads (SargeDev) | a |
| leinenterprises/jev-vision-27b† | 2026-10-10 | not reported | Qwen/Qwen3.8-27B | jev-vision (leinenterprises) | c |
| AstitwaAgarwal/multimodal-jev† | 2026-10-10 | not reported | Qwen/Qwen3-VL-2B-Instruct | mini-jev-multimodal (AstitwaAgarwal) | b |
| startlux-models/StartLux-Decision-v1.1-0.8B-Instant† | 2026-10-10 | not reported | not reported | StartLux-Decision (startlux-models) | c |
| startlux-models/StartLux-Decision-v1.1-2B-Instant† | 2026-10-10 | not reported | not reported | StartLux-Decision (startlux-models) | c |
| startlux-models/StartLux-Decision-v1.1-4B-Instant† | 2026-10-10 | not reported | not reported | StartLux-Decision (startlux-models) | c |
| startlux-models/StartLux-Decision-v1.1-4B-AutoThink† | 2026-10-10 | not reported | not reported | StartLux-Decision (startlux-models) | c |
| startlux-models/StartLux-Decision-v1.1-9B-Instant† | 2026-10-10 | not reported | not reported | StartLux-Decision (startlux-models) | c |
| startlux-models/StartLux-Decision-v1.1-9B-AutoThink† | 2026-10-10 | not reported | not reported | StartLux-Decision (startlux-models) | c |
| startlux-models/StartLux-Decision-v1.1-27B-AutoThink† | 2026-10-10 | not reported | not reported | StartLux-Decision (startlux-models) | c |
| wozniakos10/Qwen3.5-4B-typed-decisions† | 2026-10-10 | not reported | unsloth/Qwen3.5-4B | Unsloth decision (wozniakos10) | b |
| autotrust/JEV-35B† | 2026-10-11 | not reported | Qwen/Qwen3.5-35B-A3B | JEV (AutoTrust) | a |

| Repository | Created | Parameters | Base model | Family | Hea |
|---|---|---|---|---|---|
| startlux-models/StartLux-Decision-v1.1-27B-Instant† | 2026-10-11 | not reported | not reported | StartLux-Decision (startlux-models) | c |
| Jahirrrr/Klyra-Decision-16M† | 2026-10-11 | not reported | not reported | Klyra-Decision-16M from scratch (Jahirrrr) | d |
| flymy-ai/decision-4b-v1.6† | 2026-10-11 | not reported | Qwen/Qwen3.5-4B | Decision 4B (flymy-ai) | c |
| J33-AI/j33-jev† | 2026-10-11 | not reported | google/embeddinggemma-2 | j33-jev (J33-AI) | b |
| Nikunjgoyal07/jev-qwen-decider† | 2026-10-11 | not reported | Qwen/Qwen3-0.6B | JEV Decider (Nikunjgoyal07) | b |
| Nikunjgoyal07/jev-deberta-decider† | 2026-10-11 | not reported | microsoft/deberta-v3-base | JEV Decider (Nikunjgoyal07) | b |
| Ruivalim/exu-qwen3.5-2b-typed-decisions† | 2026-10-11 | not reported | Qwen/Qwen3.5-2B | Exu (Ruivalim) | d |
| workmagicio/workmagic-jev-decision† | 2026-10-11 | not reported | Qwen/Qwen3-4B | anyjev self-distill (workmagicio) | c |
| Louiskq/jev-class-9b-sft† | 2026-10-11 | not reported | Qwen/Qwen3.5-9B-Base | decider recipe at 9B (Louiskq) | c |
| thealper2/qwen3.5-0.8b-open-jev-decision† | 2026-10-11 | not reported | unsloth/Qwen3.5-0.8B | Unsloth decision (thealper2) | b |
| TurkishCodeMan/KUTUP-1-Decision-2B† | 2026-10-11 | not reported | Qwen/Qwen3.5-2B-Base | KUTUP (TurkishCodeMan) | b |
| joebumodels/JevFinetune† | 2026-10-11 | not reported | Qwen/Qwen3.5-4B | OmniJev-style multimodal (joebumodels) | b |
| faizaltkl/qdec-lay-decision-model† | 2026-10-11 | not reported | unsloth/Qwen3.5-4B | Unsloth decision model (faizaltkl) | b |
| Skyl4r-Ai/Skylar-980M-Cobol-Decider† | 2026-10-11 | not reported | Skyl4r-Ai/Skylar-980M-Cobol-Base | Skylar COBOL decider (Skyl4r-Ai) | b |
| mrm8488/embeddinggemma-2-ft-typed-decision† | 2026-10-11 | not reported | google/embeddinggemma-2 | typed-decision EmbeddingGemma (mrm8488) | d |
| Steerix-org/robo-jev-2b-lora† | 2026-10-12 | not reported | Qwen/Qwen3.5-2B | robo-jev (Steerix-org) | c |
| haohan84/v-jev† | 2026-10-12 | not reported | Qwen/Qwen3.5-4B | v-jev (haohan84) | c |
| ejbejaranos/JEV-HRI-Qwen3-VL-2B† | 2026-10-12 | not reported | Qwen/Qwen3-VL-2B-Instruct | JEV-HRI (ejbejaranos) | c |
| ejbejaranos/JEV-HRI-Qwen3-VL-4B† | 2026-10-12 | not reported | Qwen/Qwen3-VL-4B-Instruct | JEV-HRI (ejbejaranos) | c |
| ejbejaranos/JEV-HRI-Qwen3-VL-8B† | 2026-10-12 | not reported | Qwen/Qwen3-VL-8B-Instruct | JEV-HRI (ejbejaranos) | c |
| rony/gemma3-270m-typed-decisions† | 2026-10-12 | not reported | google/gemma-3-270m-it | typed-decisions specialists (rony) | c |

| Repository | Created | Parameters | Base model | Family | Hea |
|---|---|---|---|---|---|
| myeongcheol/decision-lfm2.5-1.2b† | 2026-10-13 | not reported | LiquidAI/LFM2.5-1.2B-Instruct | Open-Jev recipe on LFM (myeongcheol) | c |
| siriusyiyi/my_jev-hr9† | 2026-10-13 | not reported | Qwen/Qwen3-0.6B-Base | my_jev (siriusyiyi) | c |
| ejbejaranos/JEV-HRI-SmolVLM2-256M† | 2026-10-13 | not reported | HuggingFaceTB/SmolVLM2-256M-Video-Instruct | JEV-HRI (ejbejaranos) | c |
| ejbejaranos/JEV-HRI-LFM2-VL-450M† | 2026-10-13 | not reported | LiquidAI/LFM2-VL-450M | JEV-HRI (ejbejaranos) | c |
| workmagicio/workmagic-jev-churn-distill-qwen3-8b-v1† | 2026-10-13 | not reported | Qwen/Qwen3-8B | anyjev self-distill (workmagicio) | c |
| Singularity-Compute/super-decider† | 2026-10-13 | not reported | google/diffusiongemma-26B-A4B-it | super-decider (Singularity-Compute) | c |
| johannhartmann/gemma-4-E4B-it-unsloth-bnb-4bit_qlora_typed-decisions-de† | 2026-10-13 | not reported | google/gemma-4-E4B-it | Clef-style German (johannhartmann) | b |
| itsdevice/xlm-roberta-systemone† | 2026-10-13 | not reported | FacebookAI/xlm-roberta-base | xlm-roberta-systemone (itsdevice) | b |
| rony/ministral3-3b-reasoning-typed-decisions† | 2026-10-13 | not reported | mistralai/Ministral-3-3B-Reasoning-2512 | typed-decisions specialists (rony) | c |
| berkay123001/turnike-jev-4b† | 2026-10-13 | not reported | Qwen/Qwen3.5-4B | Turnike-JEV (berkay123001) | c |
| berkay123001/turnike-jev-0.8b† | 2026-10-14 | not reported | Qwen/Qwen3.5-0.8B | Turnike-JEV (berkay123001) | c |
| berkay123001/turnike-jev-9b† | 2026-10-14 | not reported | Qwen/Qwen3.5-9B | Turnike-JEV (berkay123001) | c |
| zhangjiaxin2012/SRF-Jev-Qwen3.5-4B-Historical-8876† | 2026-10-14 | not reported | Qwen/Qwen3.5-4B | SRF-Jev Qwen3.5 (zhangjiaxin2012) | c |
| xmutly/OmniMed-Jev-4B† | 2026-10-14 | not reported | google/medgemma-1.5-4b-it | OmniMed-Jev (xmutly) | b |
| Danny-Dasilva/embeddinggemma-2-multimodal-typed-decision† | 2026-10-14 | not reported | google/embeddinggemma-2 | EmbeddingGemma-2 typed-decision (Danny-Dasilva) | b |
| assix-research/jev-system1-gemma4-26b-decide† | 2026-10-15 | not reported | google/gemma-4-26B-A4B-it | Clef-head Gemma4 (assix-research) | b |
| Maincode/Matilda-Decision-v1† | 2026-10-15 | not reported | Qwen/Qwen3.8-27B | Matilda-Decision (Maincode) | a |
| perplexity-ai/pplx-decider-v1.2† | 2026-10-15 | not reported | Qwen/Qwen3.8-27B | pplx-decider (Perplexity) | a |
| j-llm/jevlite† | 2026-10-15 | not reported | answerdotai/ModernBERT-base | JevLite (j-llm) | b |

| Repository | Created | Parameters | Base model | Family | Hea |
|---|---|---|---|---|---|
| decisionmodels/s1-llm-auto-router† | 2026-10-15 | not reported | jhu-clsp/mmBERT-small | s1-llm-auto-router (decisionmodels) | a |
| Nefelim584/jev-lite-stage-a† | 2026-10-15 | not reported | answerdotai/ModernBERT-large | jev-lite (Nefelim584) | b |
| SlayerLab/Slayer-149M-Decision-v1† | 2026-10-15 | not reported | not reported | Slayer decision (SlayerLab) | c |
| perplexity-ai/pplx-decider-flash-v1.2† | 2026-10-15 | not reported | Qwen/Qwen3.5-4B | pplx-decider (Perplexity) | a |
| JevAgentHarness/AgentDecision-4B† | 2026-10-15 | not reported | Qwen/Qwen3-4B | AgentDecision (JevAgentHarness) | c |
| JevAgentHarness/AgentDecision-4B-v1† | 2026-10-15 | not reported | Qwen/Qwen3-4B | AgentDecision (JevAgentHarness) | c |
| Rology/rad-decider† | 2026-10-15 | not reported | Qwen/Qwen3.5-0.8B | rad-decider (Rology) | c |
| MachineFi/Trio-Spark† | 2026-10-15 | not reported | not reported | Trio-Spark (MachineFi) | u |
| gyanbhambhani/oss-jev-qwen05-decision-10k† | 2026-10-16 | not reported | Qwen/Qwen2.5-0.5B-Instruct | oss-jev distill (gyanbhambhani) | c |
| gyanbhambhani/oss-jev-qwen05-decision-noul-bin† | 2026-10-16 | not reported | Qwen/Qwen2.5-0.5B-Instruct | oss-jev distill (gyanbhambhani) | c |
| shibing624/train-jev-4b-lora† | 2026-10-16 | not reported | Qwen/Qwen3.5-4B | train-jev (shibing624) | a |
| shibing624/train-jev-27b-lora† | 2026-10-16 | not reported | Qwen/Qwen3.8-27B | train-jev (shibing624) | a |
| wiiiktor/bielik-minitron-jev-pl† | 2026-10-17 | not reported | speakleash/Bielik-Minitron-7B-v3.0-Instruct | any2jev (wiiiktor) | b |
| modelfaces/granite-4.1-30b-decision† | 2026-10-17 | not reported | ibm-granite/granite-4.1-30b-base | Kev recipe (modelfaces) | b |
| Elfsong/jev-flan-t5-large-20261017-public-v2† | 2026-10-18 | not reported | google/flan-t5-large | JEV FLAN-T5 (Elfsong) | b |
| SnowGemma/Qwen3.5-0.8B-Typed-Decisions† | 2026-10-18 | not reported | Qwen/Qwen3.5-0.8B | Unsloth decision (SnowGemma) | b |
| sp1d5r/video-jev† | 2026-10-18 | not reported | Qwen/Qwen3-Omni-30B-A3B-Instruct | video-jev (sp1d5r) | b |
| Elythros/elythros-decider-0.6b† | 2026-10-18 | not reported | Qwen/Qwen3-0.6B | elythros-decider (Elythros) | b |
| bespokelabs/Nimble-v4-max† | 2026-10-18 | not reported | Qwen/Qwen3.8-27B | Nimble (Bespoke Labs) | c |
| cribl-ai/cribl-decision-1.0-9B† | 2026-10-18 | not reported | Qwen/Qwen3.5-9B | cribl-decision (cribl-ai) | c |
| ronith128/969M-Decisions-CPU† | 2026-10-19 | not reported | LiquidAI/LFM2.5-1.2B-Instruct | 969M-Decisions (ronith128) | c |
| cribl-ai/cribl-decision-1.0-27B† | 2026-10-19 | not reported | Qwen/Qwen3.5-27B | cribl-decision (cribl-ai) | c |
| scairesearch/kieve-jev† | 2026-10-19 | not reported | not reported | Kieve-JeV (scairesearch) | d |

| Repository | Created | Parameters | Base model | Family | Hea |
|---|---|---|---|---|---|
| bizhmans/krasivo-jev-no-bench-bf16† | 2026-10-19 | not reported | Qwen/Qwen3.5-2B-Base | krasivo-jev (bizhmans) | b |
| zhangjiaxin2012/SRF-Jev-Gemma4-12B-LoRA† | 2026-10-19 | not reported | google/gemma-4-12B-it | SRF-Jev Gemma4 (zhangji-axin2012) | c |
| zhangjiaxin2012/SRF-Jev-Gemma4-26B-A4B-LoRA† | 2026-10-19 | not reported | google/gemma-4-26B-A4B-it | SRF-Jev Gemma4 (zhangji-axin2012) | c |
| zhangjiaxin2012/SRF-Jev-Gemma4-31B-LoRA† | 2026-10-19 | not reported | google/gemma-4-31B-it | SRF-Jev Gemma4 (zhangji-axin2012) | c |
| bizhmans/krasivo-jev-bf16† | 2026-10-19 | not reported | Qwen/Qwen3.5-2B-Base | krasivo-jev (bizhmans) | b |
| scairesearch/kieve-jev-100m† | 2026-10-20 | not reported | not reported | Kieve-JeV (scairesearch) | d |
| NeelContractor/jev-decider-0.4B† | 2026-10-20 | not reported | Qwen/Qwen3-0.6B | bev-decider recipe (Neel-Contractor) | b |
| Mapika/decider-12b-vision† | 2026-10-20 | not reported | google/gemma-4-12B-it | decider (Mapika) | c |
| MaziyarPanahi/Qwen3.5-4B-Jev-Judge† | 2026-10-21 | not reported | Qwen/Qwen3.5-4B | Jev-Judge (Mazi-yarPanahi) | b |
| HallD/Yev-Decision-1† | 2026-10-21 | not reported | Qwen/Qwen3.5-4B-Base | Yev-Decision (HallD) | b |
| Futurix-AI/FxAI-decision-model† | 2026-10-21 | not reported | not reported | FxAI (Futurix-AI) | a |
| SargeDev/Solar-JEV-27B† | 2026-10-21 | not reported | huihui-ai/Huihui-Qwen3.8-27B-abliterated | Solar-JEV LoRA (SargeDev) | a |
| Elythros/elythros-decider-1.7b† | 2026-10-21 | not reported | Qwen/Qwen3-1.7B | elythros-decider (Elythros) | b |
| scairesearch/kieve-jev-large† | 2026-10-22 | not reported | not reported | Kieve-JeV (scairesearch) | d |
| scairesearch/kieve-jev-v0.7† | 2026-10-22 | not reported | not reported | Kieve-JeV (scairesearch) | d |
| tensorninja2/decision-1† | 2026-10-22 | not reported | Qwen/Qwen3.8-27B | decision-1 (tensorninja2) | b |
| turion-ai/turion-jev-31b† | 2026-10-22 | not reported | google/gemma-4-31B-it | turion-jev (turion-ai) | c |
| IntelligenceLab/Jev-Vision-0.8B† | 2026-10-22 | not reported | Qwen/Qwen3.5-0.8B | Jev-Vision (In-telligenceLab) | c |
| IntelligenceLab/Jev-Vision-2B† | 2026-10-22 | not reported | Qwen/Qwen3.5-2B | Jev-Vision (In-telligenceLab) | c |
| forward-metric/sysone-typed-decisions-0.4B† | 2026-10-22 | not reported | jhu-clsp/ettin-encoder-400m | sysone (forward-metric) | b |
| jmrenouard/microllm-rlcd2-decision-head† | 2026-10-22 | not reported | not reported | MicroLLM (jmrenouard) | d |

| Repository | Created | Parameters | Base model | Family | Hea |
|---|---|---|---|---|---|
| 0xBrandon/Decision-WAF-V1-0.8B† | 2026-10-23 | not reported | Qwen/Qwen3.5-0.8B-Base | Decision-WAF (0xBrandon) | c |
| Jahirrrr/Klyra-Decision-2B-V1† | 2026-10-23 | not reported | openbmb/MiniCPM5-2B-Midtrain | Klyra-Decision-2B LoRA (Jahirrrr) | d |
| Elfsong/jev-ettin-150m-v16† | 2026-10-23 | not reported | cross-encoder/ettin-reranker-150m-v1 | JEV Ettin (Elfsong) | b |
| zhangjiaxin2012/SRF-Jev-Gemma4-12B-Stage1-SFT1024-Think4K-v2† | 2026-10-23 | not reported | google/gemma-4-12B-it | SRF-Jev Gemma4 (zhangjiaxin2012) | c |
| zhangjiaxin2012/SRF-Jev-Gemma4-31B-Stage2-Causal-LoRA1024-Think4K-v2† | 2026-10-23 | not reported | google/gemma-4-31B-it | SRF-Jev Gemma4 (zhangjiaxin2012) | c |
| zhangjiaxin2012/SRF-Jev-Gemma4-31B-Stage1-SFT1024-Think4K-v2† | 2026-10-23 | not reported | google/gemma-4-31B-it | SRF-Jev Gemma4 (zhangjiaxin2012) | c |
| zhangjiaxin2012/SRF-Jev-Gemma4-12B-Stage2-Causal-LoRA4096-Think4K-v2† | 2026-10-23 | not reported | google/gemma-4-12B-it | SRF-Jev Gemma4 (zhangjiaxin2012) | c |
| zhangjiaxin2012/SRF-Jev-Gemma4-12B-Stage3-Legacy-Reasoning-SFT128-Think4K-v2† | 2026-10-23 | not reported | google/gemma-4-12B-it | SRF-Jev Gemma4 (zhangjiaxin2012) | c |
| zhangjiaxin2012/SRF-Jev-Gemma4-12B-Stage3-Legacy-LoRA-RL16-Train4K-Think4K-v2† | 2026-10-23 | not reported | google/gemma-4-12B-it | SRF-Jev Gemma4 (zhangjiaxin2012) | c |
| zhangjiaxin2012/SRF-Jev-Gemma4-31B-Stage3-Reasoning-SFT128-Think4K-v2† | 2026-10-23 | not reported | google/gemma-4-31B-it | SRF-Jev Gemma4 (zhangjiaxin2012) | c |
| zhangjiaxin2012/SRF-Jev-Gemma4-31B-Stage3-Reasoning-SFT1024-Think4K-v2† | 2026-10-23 | not reported | google/gemma-4-31B-it | SRF-Jev Gemma4 (zhangjiaxin2012) | c |
| sparrow-decider/sparrow-nano-general† | 2026-10-23 | not reported | minishlab/potion-base-8M | sparrow-decider nano (static-embedding MLP) | d |
| sparrow-decider/sparrow-nano-robot† | 2026-10-23 | not reported | minishlab/potion-base-8M | sparrow-decider nano (static-embedding MLP) | d |
| sparrow-decider/sparrow-tiny-general† | 2026-10-23 | not reported | jhu-clsp/ettin-encoder-32m | sparrow-decider encoder (Ettin + pointer head) | b |

| Repository | Created | Parameters | Base model | Family | Hea |
|---|---|---|---|---|---|
| sparrow-decider/sparrow-small-general† | 2026-10-23 | not reported | jhu-clsp/ettin-encoder-68m | sparrow-decider encoder (Ettin + pointer head) | b |
| zhangjiaxin2012/SRF-Jev-Gemma4-26B-A4B-Stage2-Causal-LoRA1024-Think4K-v2† | 2026-10-24 | not reported | google/gemma-4-26B-A4B-it | SRF-Jev Gemma4 (zhangjiaxin2012) | c |
| zhangjiaxin2012/SRF-Jev-Gemma4-12B-Stage3-Full-RLCD2-16-Train4K-Think4K-v2† | 2026-10-24 | not reported | google/gemma-4-12B-it | SRF-Jev Gemma4 (zhangjiaxin2012) | c |
| zhangjiaxin2012/SRF-Jev-Gemma4-26B-A4B-Stage3-Reasoning-SFT128-Think4K-v2† | 2026-10-24 | not reported | google/gemma-4-26B-A4B-it | SRF-Jev Gemma4 (zhangjiaxin2012) | c |
| zhangjiaxin2012/SRF-Jev-Gemma4-26B-A4B-Stage3-Reasoning-SFT1024-Think4K-v2† | 2026-10-24 | not reported | google/gemma-4-26B-A4B-it | SRF-Jev Gemma4 (zhangjiaxin2012) | c |
| 0xBrandon/Decision-WAF-V1.1-0.8B† | 2026-10-25 | not reported | Qwen/Qwen3.5-0.8B-Base | Decision-WAF (0xBrandon) | c |
| 0xBrandon/Decision-WAF-V1-0.1B† | 2026-10-25 | not reported | AxiomicLabs/GPT-X3-150M | Decision-WAF (0xBrandon) | c |
| scairesearch/kieve-jev-moe-300m† | 2026-10-25 | not reported | not reported | Kieve-JeV (scairesearch) | d |
| scairesearch/kieve-jev-fractal-300m† | 2026-10-25 | not reported | not reported | Kieve-JeV (scairesearch) | d |
| scairesearch/kieve-jev-curriculum-300m† | 2026-10-26 | not reported | not reported | Kieve-JeV (scairesearch) | d |
| q-project/N-Q-26M-JEV† | 2026-10-26 | not reported | q-project/N-Q-26M-Chat | N-Q-JEV (q-project) | b |
| Maincode/Matilda-Decision-v1-Edge† | 2026-10-27 | not reported | Qwen/Qwen3.5-0.8B | Matilda-Decision (Maincode) | a |
| chaoliangUNSW/Jev-Style-2B-Decision-v4† | 2026-10-27 | not reported | Qwen/Qwen3.5-2B | Jev-Style (chaoliangUNSW) | c |
| Sagicc/nanoGentzen-Jev-v3† | 2026-10-28 | not reported | not reported | nanoGentzen (Sagicc) | d |

## S6 Pattern catalogue entries

This section gives the full entry for each pattern that Table 5 condenses in Section 9. Each entry states the intent of the pattern, its structure, the probability quantity it consumes, the status of its guarantee, the failure modes of Table 6 it is designed to mitigate, and the evidence behind it. A guarantee called proved holds only under the assumptions of its proposition, and most of these assume calibration, which belongs to the model and the task together and is audited per schema. The vendor documents several of these patterns with the benefits it claims for them [230], and those claims are not treated as guarantees here.

The gate turns one returned probability into an action by comparing it with a threshold that the program declares. Its intent is to act automatically only where the model is confident enough, and

**Table S8.** T2 derivatives by parent T1 or T2 checkpoint (Section 6), for every parent with two or more recorded derivatives; the remaining parents each have exactly one.

| Parent | Derivatives |
|---|---|
| convaiinnovations/laya | 386 |
| convaiinnovations/laya-multilingual | 113 |
| Cloudflare/clef-flash | 78 |
| Cloudflare/clef | 62 |
| jaredpalmer/kev-4b | 48 |
| jaredpalmer/kev-0.8b | 35 |
| convaiinnovations/laya-typed-decisions | 31 |
| Mapika/decider-2b | 28 |
| Mapika/decider-4b | 19 |
| Terom/laya | 17 |
| jaredpalmer/kev-9b | 17 |
| Cloudflare/clef-omni | 16 |
| Mapika/decider-0.8b | 16 |
| iapp/OpenThai-SystemOne | 16 |
| autotrust/JEV-27B-VL | 15 |
| perplexity-ai/pplx-decider-v1.1-27b | 12 |
| alibiserikbay/JevK5 | 10 |
| autotrust/JEV-9B | 10 |
| perplexity-ai/pplx-decider-flash-v1.2 | 10 |
| StrandsAgents/strands-decider-2B-hobson-v21 | 8 |
| autotrust/JEV-27B | 8 |
| chaoliangUNSW/Jev-Style-0.8B-Decision-v3 | 7 |
| jaredpalmer/kev-0.6b | 7 |
| akhilaaa3/Jev-Omni | 6 |
| autotrust/JEV-35B | 6 |
| jaredpalmer/kev-27b | 6 |
| pashwinkrish22/laya-email-resume-classifier-v3 | 6 |
| perplexity-ai/pplx-decider-v1.2 | 6 |
| suryatmodulus/clef | 6 |
| Mapika/decider-2b-vision | 5 |
| StrandsAgents/strands-decider-2B-hobson-v19 | 5 |
| StrandsAgents/strands-decider-E4B-gemma4-v1-2610 | 5 |
| TokenRhythm/NeoHorse-Jev-4B | 5 |
| jaredpalmer/kev-0.5b | 5 |
| pashwinkrish22/laya-email-resume-classifier | 5 |
| startlux-models/StartLux-Decision-v1-0.8B | 5 |
| SargeDev/Jev_Qwen3.8-27B | 4 |
| bespokelabs/Bespoke-Nimble-9B | 4 |
| gyanbhambhani/oss-jev-qwen05-decision-noul-v2 | 4 |
| knowlet/Gemma-4-12B-Unified-System-One | 4 |
| startlux-models/StartLux-Decision-v1-27B | 4 |
| startlux-models/StartLux-Decision-v1-2B | 4 |
| startlux-models/StartLux-Decision-v1-4B | 4 |
| startlux-models/StartLux-Decision-v1-9B | 4 |
| startlux-models/StartLux-Decision-v1.1-27B-Instant | 4 |
| startlux-models/StartLux-Decision-v1.1-9B-AutoThink | 4 |
| JackFram/decider-2b | 3 |
| SargeDev/JEV-27B-Uncensored | 3 |
| SargeDev/JEV-27B-VL-Uncensored | 3 |
| SargeDev/Solar-Decision-JEV-27B-V2 | 3 |
| SargeDev/Solar-JEV-27B | 3 |
| alibiserikbay/JevK5-9B | 3 |

its structure is a single call followed by a comparison in code. It consumes the top probability of a Choice, the calibrated probability of a positive for a Noul, or a cumulative level probability of a Score, which Proposition 5.6 identifies as the quantity that a threshold on a level needs. Its guarantee is proved under calibration, since Proposition 5.3 bounds the error among accepted answers and shows that one threshold across answer-set sizes admits different risks, and Proposition 5.4 gives the cost-optimal threshold. A threshold chosen by conformal risk control would give a finite-sample guarantee on exchangeable data [3, 10], and Rafe and Das [180] names that machinery as the stronger alternative to its own held-out estimate. The gate mitigates ordinal numerics when it thresholds cumulative probabilities, while top-confidence inversion and shipped over-confidence void its guarantee. In Ibrahim and Zaki [80], the median task at a fixed confidence threshold covered 0.376 of items at an accuracy of 0.815, and Li et al. [117] accept a judgment only above a confidence threshold.

Screen-then-read runs a short and inexpensive schema over every record and reads only the forwarded records with the full schema. Its intent is to spend the expensive reading on the records that can contain the event of interest. It consumes the probability of relevance returned by the screen and then the distributions of the reading stage. The recall identity of Proposition 5.4 is proved, so final recall is the product of the rate at which the screen forwards positives and the rate at which the reader detects them. Both of these rates are measured quantities, and an evaluation run on forwarded records alone reports the second rate only. The pattern mitigates distractor state, because the reader receives only records and questions that the screen found relevant, which is the vendor’s remedy of filtering state before asking [228]. Rafe and Das [180] ran a lean presence schema over a random frame of narratives and the full schema over the records it forwarded.

Candidate-then-select lets a retriever, a rule or another model propose a short list and asks the decision model to choose among its members. Its intent is to keep the answer space small, since Proposition 5.3 shows that one threshold admits more risk as the answer space grows. It consumes a Choice distribution over the candidates, ideally with an option such as none of the above, which the vendor recommends when a list may not cover every input [227]. Its guarantee is conformal when the list is a conformal prediction set, which covers the correct answer with a stated probability on exchangeable data [92, 190]. Otherwise the guarantee is empirical, final accuracy is bounded by the recall of the list, and the pattern is designed to mitigate cardinality collapse. The decider-2b card reports that full label sets cost accuracy against sampled label sets [148], REFLEX lost −6.7 accuracy points as its option count grew [256], and the vendor’s cookbook index includes reranking and semantic search recipes [230].

Speculative fan-out sends many questions about one state in a single call, including questions the program may not need, and lets code decide which answers to use. The vendor documents it with cost and speed benefits [230], and its structure relies on the shared encoding of the state that Section 4 describes, and it consumes the isolated marginals of the questions. Its guarantee extends no further than the calibration of each marginal, because Proposition 5.1 identifies any conjunction of the answers only up to an interval, and a rule that multiplies them asserts an independence that the contract does not supply. The pattern mitigates no failure mode of the atlas, and its value lies in latency and cost. An independent comparison found the latency of the hosted model flat in the number of questions [9], and a visual decision model ran faster by a factor of 8.9 with shared-prefix batching [274].

The confidence-gated cascade answers with the decision model when its top probability clears a threshold and escalates the remaining items to a frontier model. Its intent is to retain most of the quality of the frontier model at a fraction of its fee, and it consumes the top probability. The expected-cost identity of Proposition 5.4 is proved accounting, and the retained quality is empirical. In 23 studies, escalation kept 0.67 to 1.2 of the quality of the frontier model at 0.18 to 0.92 of

its fee under different cost definitions [80, 117, 256]. The saving shrank as the price gap to the partner narrowed, and where routing was already accurate a cheap generative cascade matched the decision-model cascade at 0.72 of its cost [256]. The value therefore lies in escalation gated by a confidence that ranks errors, and it depends on the price gap and on routing accuracy. The pattern mitigates counting and arithmetic and adversarial state when confidence falls on those items, and top-confidence inversion defeats it.

Judge-and-escalate uses the decision model as an evaluator that accepts its judgment when confident and hands the remaining items to a stronger judge or to a person. It differs from the cascade in that the decision concerns the output of another system, such as a pairwise preference or the factual support of a statement [286]. It consumes the probability of the preferred answer or of support, and its guarantee is empirical. Li et al. [117] found accuracy of 47.7 percent at low confidence against 95.8 percent at high confidence, so confidence ordered the errors, and they recommend escalation on difficult correctness and on style-adversarial pairs. Huang et al. [76] judged the factuality of radiology reports with one support question per statement. The pattern mitigates adversarial state and counting and arithmetic, which the difficult-correctness items include.

Composite scoring asks each dimension of an assessment as its own question and combines the answers into one score in code. The vendor documents it with cost, reliability and speed benefits [230], and its jaggedness page advises against hiding several judgments inside one question [228]. It consumes several marginals or Score distributions combined by a rule that the program fixes. It carries no guarantee, because the combined score is calibrated only if the rule is fitted, Proposition 5.1 limits any reading of the rule as a joint probability, and Proposition 5.6 warns against feeding it expected levels. The pattern mitigates cross-phrasing inconsistency by asking each judgment one way. Robitza [189] combined decomposed decision outputs with a fitted linear rule and compared the result with trained baselines on the same features.

Hierarchical fallback replaces one Choice over many answers with a chain that asks a coarse category and then an item within it, and it falls back to the coarse answer when the fine stage is unsure. The hierarchical classification recipe in the vendor's cookbook index follows this structure [230]. It consumes chained Choice distributions, in which the probability of a path is the probability of the category times the conditional probability of the item. The stage-product accounting of Proposition 5.4 is proved, so when a correct item implies a correct category a chain can be no more accurate than its coarse stage, while the accuracy itself is empirical, and the pattern is designed to mitigate cardinality collapse. REFLEX measured the loss of accuracy with a growing option count [256], and the companion benchmark compares one Choice over all intents of CLINC-150 with a chain that asks the domain and then the intent [179].

Paraphrase self-consistency asks one decision in several equivalent forms and treats disagreement among the answers as a signal for review. The forms vary the wording, the order of the options or their names, and the pattern consumes the spread of the returned distributions together with their average. Its guarantee is proved in expected log-odds for random names, because Proposition 5.5 shows that exchangeable random names give expected log-odds that depend on the rubrics alone. Swaps with fixed rubrics identify the name term, while for wording and order the guarantee is only empirical. The pattern mitigates cross-phrasing inconsistency and option-name polarity, and it implements the option-name neutralization that the proposition supports. Sun et al. [214] found that opaque random names flipped 2.02 answers per hundred on the hosted model, in the neutral regime. For JevLite, a held-out paraphrase flipped 5.2 percent of decisions and an option-order swap 2.6 percent [187], and Zhang et al. [278] compared output orders across models.

Deterministic pre-parsing computes in code whatever code can compute exactly, such as counts, date differences and unit conversions, and passes the result to the model inside the state. The

vendor's remedies for its jagged edges are of this kind, keeping arithmetic in code, extracting date components and comparing them in code, and reducing hops of indirection [228], and its cookbook index lists recipes for pre-parsed value extraction and date extraction [230]. The pattern consumes no model quantity for the parsed part. Its guarantee is exact for the parsed part and empirical for the decision that reads it. It mitigates counting and arithmetic, dates, indirection and physical magnitudes, although no study in the ledger tests the last. The Kev-9B card reports deadline accuracy of 0.80 (raw) / 0.90 (with date_facts preprocessor), against 0.93 for the hosted model [164], and the preprocessor that supplies date facts to the state accounts for the difference between its two values.

Marginal-to-joint reconciliation handles a program that needs a statement about several answers together, which question isolation does not supply. Its structure is one Choice over the joint outcomes, a reported interval for the conjunction, or logical identities that code enforces across related answers, as the vendor advises when it asks for each decision to be put one way [228]. It consumes the marginals of the events about one state. Its guarantee is proved by Proposition 5.1, whose bounds are attained, so the interval is the most that the marginals support. The pattern mitigates cross-phrasing inconsistency where related questions contradict each other, as in the vendor's worked example, in which a Noul and a Choice about one fact disagree [228]. Cheng et al. [32] report a parity judgment consistent with a related band judgment in 0.513 of cases.

The review budget sends to human review the records whose calibrated probability lies inside the band where review costs less than the expected loss of an automated decision. It consumes the calibrated probability of a positive, and the budget is the probability mass inside the band of Equation (7). Its guarantee is proved under calibration by the three-action rule of Proposition 5.4. The budget of Rafe and Das [180] is a variant in which a target precision among flagged records sets the upper edge, and its pooled held-out value was 0.8 percent of flagged records. In the same study, in-domain recalibration moved pooled calibration error from 0.0231 to 0.0069. It is a precision-targeted deferral budget, not a cascade result. The pattern mitigates shipped over-confidence only when the band is computed on recalibrated probabilities, and top-confidence inversion places errors outside the band.

The versioned contract pins every artifact that defines the predictor and repeats the calibration audit whenever one of them changes. The artifacts are the model version, the schema, the option names and rubrics, and the serving temperature, which Section 4 shows define the predictor jointly, and the hosted service distinguishes a pinned version from a moving alias [227]. The pattern consumes no probability quantity, and its guarantee is none, since pinning makes a change detectable but not preventable [180]. The census records the case that motivates the pattern most directly. Bespoke-Nimble-9B moved from a checkpoint served at a fitted temperature, with fewer choices per field, to a revision shipped at its default temperature with more choices per field and a warning not to reuse the earlier fit [13, 14]. The repository's own endpoints also give disagreeing identifiers for the earlier tag. The companion benchmark loads the current revision, while the ledger rows on Nimble concern the earlier one, so the two describe different predictors. The serving temperature of Kev-0.8B also moved between checkpoints under an unchanged name [163]. The pattern mitigates shipped over-confidence, because the temperature is pinned and refitted with each version, and option-name polarity, because the names are fixed and swap-tested before release.

## S7 The evidence ledger by study

This part of the electronic supplement lists the evidence ledger of Section 7 one study at a time, rather than one measured quantity at a time as the main text does. A reader can then check a study before reusing one of its numbers. Table S9 gives this row for every study behind the ledger, including the grey-literature sources, each cited under a bibliography key. Its Models column

counts the distinct values of the ledger's model field and can undercount comparators recorded in a separate field. Its *n* is the most frequent numeric sample size across a study's rows, or else the largest leading number among its descriptive entries, with two values corrected by hand against each study's stated primary sample. Table S10 then regroups a subset of these studies by the seven application areas of Section 10. Most of the ledger's studies map onto one of the seven named areas. The rest are one classification-robustness study, one reverse-engineering probe of the hosted service, one community-built benchmark and four open decision models each compared against Jev, and Section 6 already cites several of them. Reading Table S9 shows that 3 of the ledger's 248 studies received an overall grade of low risk of bias. It also shows that a study's reference labels are frequently a mixture of human adjudication, an automated judge and a computed task outcome, rather than a single uniform gold standard.

**Table S9.** Every study in the evidence ledger, by task family, its overall risk-of-bias grade, its reference-label type and the number of ledger rows it contributes, with Models and *n* counted as Section S7 describes.

| Study | Task family | Models | *n* | Reference labels | Rows | RoB |
|---|---|---|---|---|---|---|
| Ahmed [1] | classification | 7 | 240 | administrative field; none | 12 | high |
| Amit [2] | other | 7 | 5,000 | not reported | 17 | high |
| Antunes et al. [4] | classification | 1 | 9,092 | human crowd; human adjudicated; synthetic; llm teacher; none | 13 | some concerns |
| Asseri and Asseri [5] | other | 1 | 36,000 | none; human crowd | 13 | high |
| Azizi et al. [6] | classification | 11 | 833 | human adjudicated; synthetic | 16 | some concerns |
| Azizi et al. [7] | safety | 7 | 1,034 | human single; synthetic | 19 | high |
| Bailo [8] | agent control | 6 | 600 | synthetic | 14 | high |
| Bellver-Soler et al. [11] | classification | 1 | 3,113 | human crowd; none | 15 | high |
| Besanson [12] | extraction | 1 | 700 | synthetic | 23 | high |
| Brom [16] | classification | 3 | 1,000 | human crowd; none; task outcome | 17 | high |
| Bru et al. [17] | other | 4 | 9,621 | human crowd; none | 9 | some concerns |
| Buecheler et al. [18] | agent control | 1 | 144 | none | 11 | some concerns |
| Bukhari et al. [19] | classification | 4 | 231 | administrative field; synthetic; human single; none; human crowd; task outcome; llm teacher | 15 | some concerns |
| Cao et al. [21] | retrieval | 5 | 100 | administrative field; task outcome | 18 | high |
| Chen [22] | safety | 8 | 607 | human adjudicated; none; administrative field | 12 | some concerns |
| Chen [24] | retrieval | 7 | 276 | human single | 17 | some concerns |
| Chen and Li [23] | other | 2 | 1,000 | synthetic | 17 | high |
| Chen et al. [27] | QA; classification | 1 | not reported | not reported; human crowd | 14 | high |
| Chen [25] | agent control | 5 | 268 | administrative field; human single; none | 21 | some concerns |
| Chen et al. [26] | classification | 8 | 8,000 | human single | 12 | high |

| Study | Task family | Models | $n$ | Reference labels | Rows | RoB |
|---|---|---|---|---|---|---|
| Chen et al. [30] | safety | 6 | 1,000 | administrative field; synthetic; none; human adjudicated | 21 | some concerns |
| Chen and Le [29] | memory | 3 | 500 | model consensus; human single | 15 | some concerns |
| Chen et al. [28] | other | 7 | 78,362 | mixed; none; task outcome | 14 | some concerns |
| Cheng et al. [31] | other | 1 | 72 | not reported | 9 | high |
| Cheng et al. [32] | judging | 1 | 68 | task outcome | 12 | high |
| Chouhan and Perry [33] | classification; QA | 5 | 4,689 | llm teacher; human single; human crowd; none | 17 | high |
| Chung et al. [35] | classification | 5 | 11,117 | human adjudicated; synthetic | 16 | high |
| Cinà [36] | other | 2 | 978 | task outcome; none | 10 | high |
| Dai et al. [40] | classification | 4 | 353 | human crowd; administrative field; synthetic; human single | 10 | some concerns |
| Dai et al. [41] | other | 3 | 36,000 | synthetic | 6 | high |
| Deka [42] | classification | 16 | 2,000 | human adjudicated; none | 20 | some concerns |
| Demir [43] | QA | 6 | 5,314 | other: court-stated holding from the citing opinion (CaseHOLD gold); abstain condition built programmatically | 14 | some concerns |
| Deng et al. [44] | scientific workflow | 7 | 100 | human adjudicated | 14 | some concerns |
| Denney and DiGiuseppe [45] | social-science annotation; classification | 1 | 37,709 | human adjudicated; human single; human crowd; none | 23 | high |
| Deußer et al. [46] | QA; classification; extraction; safety; judging; other; multi-dataset zero-shot evaluation | 1 | 755 | human single; human crowd; administrative field; none | 26 | some concerns |
| Ding et al. [47] | classification; judging; other | 2 | 350 | not reported; human crowd; human single; llm teacher; synthetic; none | 17 | some concerns |
| Ding [48] | QA | 7 | 14,042 | human adjudicated | 11 | high |
| Dinzinger et al. [49] | retrieval | 12 | not reported | human single | 17 | high |
| Dong et al. [50] | safety | 1 | 12 | synthetic | 9 | high |
| Rosario and Atef [191] | judging | 5 | 495 | human adjudicated | 18 | high |
| dos Santos Barbosa [51] | agent control | 2 | 13 | task outcome; none; vendor label | 14 | high |
| Du et al. [52] | classification | 2 | 8,742 | human adjudicated | 17 | high |
| Duan et al. [53] | other | 11 | 100 | administrative field; synthetic; task outcome; llm teacher; human crowd | 20 | high |
| Fadli et al. [56] | classification | 6 | 4,800 | human single | 21 | high |

| Study | Task family | Models | $n$ | Reference labels | Rows | RoB |
|---|---|---|---|---|---|---|
| Feng et al. [57] | other | 3 | 9,845 | human single; task outcome | 13 | high |
| Fernandes and Pereira [58] | judging; retrieval | 1 | 8,205 | llm teacher; human adjudicated; human single | 14 | some concerns |
| Gan et al. [60] | classification | 9 | 10,027 | human crowd; synthetic; model consensus | 17 | high |
| Gao et al. [61] | social-science annotation; classification | 5 | 180,000 | human crowd | 17 | high |
| Gershon et al. [62] | judging | 1 | 118 | other: physician panel (median of five physicians); other: physician labels (2 to 5 of 186 physicians per row); other: clinician ratings (56 responses) and LLM jury scores; llm teacher; other: mixed (physician panel, clinicians, LLM graders); other: physician labels (UC2) and GPT-5.4 (UC4) | 16 | some concerns |
| Geuter et al. [63] | classification | 4 | 2,352 | model consensus; administrative field; human adjudicated; none | 16 | high |
| Hume, Archer [77] | QA; other; classification | 1 | 1,200 | human adjudicated | 8 | some concerns |
| Bespoke Labs [14] | classification | 3 | 324 | synthetic; human adjudicated; human crowd | 10 | some concerns |
| Palmer, Jared [164] | classification; QA; other | 4 | 764 | human adjudicated; administrative field; none | 12 | high |
| Convai Innovations [39] | classification | 6 | 2,000 | llm teacher; human adjudicated | 10 | some concerns |
| LocalLLaMA [133] | classification | 6 | 2,000 | llm teacher | 10 | high |
| Balian, Rob [9] | classification | 6 | 975 | human adjudicated; task outcome | 8 | some concerns |
| TypeSafe AI [232] | agent control | 5 | not reported | model consensus | 9 | high |
| Rauch [186] | safety | 1 | not reported | none | 1 | high |
| Guo et al. [66] | judging | 1 | 1,228 | human adjudicated; synthetic | 10 | high |
| Guo et al. [65] | safety | 1 | 7,193 | llm teacher; human adjudicated; none | 20 | some concerns |
| Ha et al. [67] | classification | 4 | 893 | human single | 18 | high |
| Han et al. [69] | agent control | 3 | 100 | task outcome | 6 | some concerns |
| Han et al. [68] | agent control | 6 | 3,875 | administrative field | 13 | high |

| Study | Task family | Models | $n$ | Reference labels | Rows | RoB |
|---|---|---|---|---|---|---|
| He et al. [70] | classification | 1 | 322 | other: source-derived reference labels (TrialGPT annotations; MIMIC questions model-generated and human-reviewed); none | 13 | some concerns |
| Hu et al. [72] | safety | 7 | 5,586 | model consensus; task outcome | 19 | high |
| Hu et al. [73] | safety; agent control | 2 | 7,033 | administrative field; none; task outcome; synthetic | 13 | some concerns |
| Huang et al. [76] | judging | 2 | 100 | human adjudicated; task outcome; none | 13 | some concerns |
| Huang et al. [75] | classification; agent control | 11 | 316 | human adjudicated; none; task outcome | 14 | high |
| Huang et al. [74] | safety | 3 | 1,947 | administrative field; none | 13 | some concerns |
| Huo et al. [78] | other | 3 | 43,496 | synthetic; not reported | 13 | high |
| Ibrahim and Zaki [80] | social-science annotation | 27 | 7,977 | human adjudicated | 55 | high |
| Ichikawa [81] | other: multi-task decision benchmark | 5 | 600 | other: benchmark labels aggregated in S1MB (mixed sources); none | 10 | some concerns |
| Imperatrice et al. [82] | other | 1 | 25,000 | task outcome; none | 17 | low |
| Iqbal et al. [83] | classification | 7 | 970 | human crowd | 20 | some concerns |
| Jiang et al. [84] | memory | 2 | not reported | llm teacher | 10 | high |
| Joy [85] | classification | 2 | 1,000 | human crowd; human adjudicated | 21 | high |
| Jung [86] | classification | 1 | 128 | task outcome | 16 | some concerns |
| Khatri et al. [87] | classification | 5 | 406 | other: expert annotator labels (adjudication not stated) | 12 | high |
| Khezresmaeilzadeh et al. [88] | agent control | 3 | 134 | task outcome | 15 | some concerns |
| Konak [89] | classification | 2 | 890 | administrative field | 19 | some concerns |
| Kourtis and Xilouris [91] | agent control | 5 | 3,645 | synthetic; none | 13 | high |
| Kwartler et al. [93] | classification | 1 | 109 | human single; none | 10 | some concerns |
| Lai et al. [94] | other | 2 | 384 | synthetic; human single | 15 | some concerns |
| Lai et al. [95] | other: executable arithmetic rule following | 1 | 320 | synthetic | 8 | high |
| Lan et al. [97] | safety | 4 | 1,332 | human adjudicated | 10 | some concerns |
| Lan et al. [96] | safety | 1 | 47,611 | synthetic; none | 15 | high |
| Lee et al. [98] | QA | 1 | 1,273 | human adjudicated; task outcome; none | 16 | high |
| Lee and Park [99] | other | 5 | 14,000 | task outcome | 14 | some concerns |
| Li [112] | classification | 2 | 22,162 | human adjudicated | 11 | high |
| Li et al. [107] | other | 3 | 3,360 | none; human crowd | 15 | some concerns |
| Li et al. [115] | classification | 1 | 2,584 | human single | 11 | high |

| Study | Task family | Models | $n$ | Reference labels | Rows | RoB |
|---|---|---|---|---|---|---|
| Li and Xie [109] | retrieval | 13 | 443 | other: benchmark relevance judgments (incomplete; 607 of 1,384 BRIGHT candidate sets hold a judged positive) | 16 | some concerns |
| Li et al. [110] | classification | 5 | 1,120 | human single | 9 | some concerns |
| Li et al. [102] | agent control | 2 | 63 | task outcome; administrative field; human adjudicated | 12 | some concerns |
| Li [106] | agent control | 4 | 2,100 | human adjudicated; task outcome; none; llm teacher | 19 | high |
| Li and Wang [108] | classification | 2 | 3,080 | llm teacher; human adjudicated; none | 13 | high |
| Li et al. [117] | judging | 3 | 400 | vendor label; none; human adjudicated | 27 | some concerns |
| Li and Chen [111] | classification | 10 | 500 | none; human crowd; human single | 15 | high |
| Li [105] | social-science annotation; classification; other | 8 | 9,070 | human crowd | 10 | high |
| Li and Wagle [118] | classification; QA | 6 | 231 | not reported; human adjudicated | 11 | some concerns |
| Li et al. [116] | agent control | 7 | 65,228 | task outcome; synthetic | 21 | high |
| Li et al. [103] | agent control | 3 | 216 | task outcome; llm teacher; human adjudicated | 12 | some concerns |
| Li et al. [119] | social-science annotation | 9 | 240,458 | human single; none | 10 | some concerns |
| Li et al. [114] | safety | 1 | 200 | human adjudicated; none | 14 | high |
| Li [104] | agent control; QA; retrieval | 12 | 6,396 | human single; not reported | 17 | high |
| Li et al. [101] | agent control | 1 | 120 | synthetic | 20 | high |
| Li et al. [113] | QA | 1 | 1,172 | human single | 12 | high |
| Li et al. [100] | other | 1 | 936 | llm teacher; human single | 8 | high |
| Lin [120] | classification | 4 | 324 | synthetic | 15 | high |
| Ling et al. [121] | ecosystem analysis of public projects | 1 | not reported | none | 1 | not graded |
| Ling et al. [122] | agent control | 1 | 348 | task outcome | 13 | some concerns |
| Liu [128] | judging | 6 | 200 | synthetic | 13 | high |
| Liu et al. [125] | other: sequential recommendation | 2 | 1,280 | task outcome | 18 | high |
| Liu et al. [129] | safety | 5 | 9,852 | other: mixed benchmark annotations (human span labels, GPT-4o-injected errors validated by two annotators, constraint checks); none | 16 | high |
| Liu [130] | safety | 7 | 236 | administrative field | 22 | high |

| Study | Task family | Models | $n$ | Reference labels | Rows | RoB |
|---|---|---|---|---|---|---|
| Liu et al. [131] | retrieval | 3 | 100 | administrative field; none | 8 | high |
| Liu et al. [127] | social-science annotation | 5 | 14,412 | other: mixed source-dataset annotations (gold and silver, human); none; other: public dataset labels (construction not described) | 12 | high |
| Liu et al. [123] | classification | 2 | 4,625 | model consensus; synthetic; none | 10 | high |
| Liu et al. [126] | agent control | 1 | 5 | task outcome | 8 | high |
| Liu et al. [124] | classification | 9 | 13,000 | administrative field | 10 | high |
| Loi [134] | judging | 1 | 64 | none | 8 | high |
| Lu and Wu [135] | classification | 4 | 166 | administrative field | 15 | high |
| Lucca [136] | classification | 6 | 722 | human single | 16 | some concerns |
| Lukassen et al. [137] | judging | 3 | 439 | administrative field; synthetic; none | 15 | high |
| Lukauskas and Šarkauskaitė [138] | social-science annotation | 9 | 100 | human crowd | 20 | high |
| Luo et al. [139] | safety | 1 | 2,273 | none; llm teacher | 7 | some concerns |
| Lyu and Xia [140] | retrieval; other | 2 | 1,000 | task outcome | 14 | high |
| Ma et al. [145] | agent control | 1 | 50 | task outcome | 8 | some concerns |
| Ma et al. [141] | other | 10 | 1,504 | human single; synthetic | 11 | some concerns |
| Ma et al. [143] | agent control | 5 | 105 | task outcome | 10 | some concerns |
| Ma et al. [142] | judging | 2 | 2,334 | task outcome; synthetic | 21 | high |
| Ma et al. [144] | other: constrained spatial planning for 3D world generation | 1 | 100 | other: programmatic hard-constraint check (terrain, water, biome, Macro role, adjacency) | 2 | some concerns |
| Madrid-García and Merino-Barbancho [147] | QA | 1 | 1,373 | human adjudicated | 20 | some concerns |
| Mazzoni and Failla [149] | safety | 2 | 3,689 | administrative field; human crowd | 17 | high |
| Mei et al. [150] | QA | 8 | 231 | administrative field; none | 9 | some concerns |
| Messoudi and Mansar [151] | moderation; safety; retrieval | 3 | 1,050 | administrative field; none | 19 | high |
| Min and Chen [154] | judging; agent control | 2 | 300 | llm teacher; task outcome; none | 16 | high |
| Mohebifar and Bit [156] | other | 8 | 1,932 | synthetic; human adjudicated; task outcome; human single | 17 | high |
| Mu et al. [157] | classification | 4 | 1,279 | synthetic; task outcome | 14 | high |
| Munot [159] | other: multi-correct-choice probability allocation | 3 | 7,405 | other: dataset gold labels as released | 16 | high |
| Nandakishore [160] | judging | 2 | not reported | human crowd; task outcome; none | 17 | high |
| Nandakishore [161] | agent control | 3 | 2,000 | llm teacher; none; human single | 15 | high |

| Study | Task family | Models | $n$ | Reference labels | Rows | RoB |
|---|---|---|---|---|---|---|
| Pan et al. [165] | agent control | 11 | 60 | task outcome | 14 | some concerns |
| Panchal [166] | QA; agent control | 5 | 12,032 | human adjudicated; none; task outcome | 13 | some concerns |
| Paramasivam and Rajkumar [167] | judging | 2 | 235 | llm teacher; human crowd; none | 11 | some concerns |
| Paschalides et al. [168] | safety | 7 | 4,120 | human crowd; synthetic | 17 | high |
| Pei et al. [169] | agent control | 6 | 1,011 | task outcome | 10 | some concerns |
| Pelaseyed and Zabihi [170] | other | 4 | 96 | none | 11 | some concerns |
| Perifanis et al. [171] | other | 5 | 11,481 | task outcome | 14 | some concerns |
| Polignano et al. [174] | other | 13 | 2,000 | task outcome | 18 | some concerns |
| Porcedda [175] | other | 1 | 365 | synthetic | 13 | high |
| Qian et al. [176] | agent control | 1 | 1,168 | administrative field | 8 | high |
| Qin et al. [178] | other | 4 | 800 | human adjudicated | 15 | some concerns |
| Qin et al. [177] | other | 2 | 200 | administrative field; task outcome; none | 6 | some concerns |
| Rafe and Das [180] | document coding | 4 | 2,416 | human adjudicated; none; administrative field | 24 | some concerns |
| Rafe and Das [181] | extraction | 1 | 590 | human adjudicated; none | 7 | low |
| Rafe and Das [182] | social-science annotation | 3 | 79,510 | human adjudicated; llm teacher; none | 13 | low |
| Rahimi et al. [183] | other | 1 | 30 | task outcome | 6 | high |
| Rajput et al. [184] | classification | 2 | 299,463 | human single | 18 | high |
| Rao and Callison-Burch [185] | judging | 7 | 5,003 | human single; human crowd; none | 27 | high |
| Ren et al. [187] | safety | 8 | 577 | administrative field | 14 | high |
| Rezvani et al. [188] | classification; safety | 1 | 1,916 | administrative field; task outcome | 14 | high |
| Robitza [189] | scientific workflow | 2 | 1,936 | none; human crowd | 14 | some concerns |
| Sadoun et al. [192] | other; retrieval | 2 | 12,280 | task outcome; synthetic; human single; none; human adjudicated | 14 | some concerns |
| Saeed et al. [193] | classification | 15 | 500 | administrative field | 17 | high |
| Sakhawat and Raiyan [194] | classification | 3 | 3,265 | human adjudicated; synthetic; none | 13 | some concerns |
| Santillana [195] | classification | 4 | 2,021 | administrative field; none | 13 | some concerns |
| Sautenkov et al. [196] | agent control | 1 | 255 | synthetic | 7 | high |
| Severo et al. [197] | classification | 1 | 6,000 | administrative field | 14 | high |
| Shankaranarayana et al. [198] | other; QA; classification; safety | 1 | 1,680 | task outcome; human adjudicated; synthetic | 24 | some concerns |
| Sharma and Lall [200] | memory | 4 | 778 | llm teacher; human single; administrative field | 17 | high |
| Sharma et al. [199] | classification | 3 | 500 | synthetic | 10 | high |
| Sheng et al. [201] | agent control | 1 | 100 | task outcome | 10 | some concerns |
| Shi et al. [202] | judging | 3 | 579 | human single; none | 13 | high |
| Song et al. [203] | classification | 4 | 231 | not reported; synthetic | 14 | some concerns |

| Study | Task family | Models | $n$ | Reference labels | Rows | RoB |
|---|---|---|---|---|---|---|
| Song et al. [204] | scientific workflow | 11 | 6,466 | human adjudicated; human crowd; llm teacher | 16 | high |
| Song et al. [205] | QA | 5 | 1,700 | human adjudicated | 18 | high |
| Sonthalia et al. [206] | classification | 1 | 1,000 | not reported | 10 | some concerns |
| Stambler [209] | other | 6 | 47 | synthetic; administrative field; human single | 19 | high |
| Steiner et al. [210] | classification | 7 | 30,225 | other: benchmark gold match labels (curated by benchmark authors) | 22 | some concerns |
| Su and Huang [211] | agent control | 2 | 100 | task outcome | 10 | some concerns |
| Sudjianto and Burakov [212] | classification | 7 | 10,000 | administrative field | 9 | some concerns |
| Sun et al. [213] | QA; retrieval | 2 | 105 | human adjudicated; none | 10 | high |
| Sun et al. [214] | classification | 4 | 1,200 | administrative field | 22 | some concerns |
| Tan et al. [215] | safety | 1 | 100 | llm teacher | 7 | high |
| Tang and Chen [216] | classification; extraction | 1 | 200 | human single | 14 | high |
| Teke [217] | classification | 4 | 84 | model consensus; human single | 15 | high |
| Teke [218] | classification | 3 | 4,275 | model consensus; none; human single | 20 | high |
| Teng et al. [219] | classification | 6 | 2,521 | not reported | 15 | high |
| Terven et al. [220] | retrieval | 6 | 40 | llm teacher; other: human-annotated reference evidence (QASPER); other: human-annotated unanswerable (QASPER) | 14 | some concerns |
| Tommasino and Rinaldi [222] | classification | 5 | 12,692 | human single | 16 | some concerns |
| Minh et al. [155] | classification | 2 | 163 | human single | 12 | high |
| Vats [233] | agent control | 1 | 72 | task outcome; none | 10 | some concerns |
| Wake and Wagle [235] | agent control | 2 | 60 | none; synthetic; task outcome | 16 | some concerns |
| Wang and Zang [244] | other | 3 | 200 | synthetic | 11 | high |
| Wang et al. [238] | classification; other | 1 | 86 | administrative field; task outcome | 14 | high |
| Wang et al. [243] | extraction | 2 | 1,953 | not reported | 25 | some concerns |
| Wang et al. [248] | classification | 7 | 207,900 | human crowd; none | 16 | some concerns |
| Wang et al. [240] | safety | 5 | 100 | synthetic; administrative field; llm teacher; vendor label | 15 | high |
| Wang et al. [242] | agent control | 3 | 278 | human single; none; task outcome | 7 | some concerns |
| Wang and Gao [245] | safety | 1 | 5,219 | administrative field | 12 | some concerns |
| Wang et al. [239] | agent control | 1 | 150 | task outcome; not reported; synthetic; none | 13 | high |
| Wang et al. [241] | classification | 5 | 19,477 | task outcome | 9 | some concerns |

| Study | Task family | Models | $n$ | Reference labels | Rows | RoB |
|---|---|---|---|---|---|---|
| Wang [236] | retrieval; memory | 4 | 1,540 | administrative field; llm teacher; none | 9 | high |
| Wang et al. [247] | other | 3 | 194 | administrative field; not reported | 10 | some concerns |
| Wang et al. [246] | QA | 3 | 198 | human adjudicated | 13 | high |
| Wang et al. [237] | other | 9 | 1,858 | administrative field | 16 | some concerns |
| multimodalart [158] | multi-benchmark leaderboard; intent classification | 5 | 3,080 | human assigned | 7 | not graded |
| Weng et al. [249] | classification | 8 | 111 | not reported; llm teacher; none | 11 | high |
| Wu et al. [254] | agent control | 8 | 100 | task outcome | 25 | some concerns |
| Wu and Lim [255] | safety | 1 | 510 | task outcome | 13 | high |
| Wu et al. [253] | safety | 1 | 60 | synthetic | 13 | high |
| Wu and Lim [256] | agent control | 8 | 100 | human adjudicated; task outcome | 14 | some concerns |
| Wu [257] | retrieval | 2 | 1,000 | administrative field; synthetic; none | 9 | high |
| Xie et al. [258] | classification; agent control | 7 | 500 | synthetic | 21 | high |
| Xu and Mei [260] | classification; other | 3 | 100 | administrative field | 11 | some concerns |
| Xu et al. [262] | safety | 3 | 2,657 | task outcome; human crowd | 11 | high |
| Xu et al. [259] | judging; QA | 1 | 192 | llm teacher; human single; task outcome; none | 12 | high |
| Xu et al. [261] | safety | 3 | 3,072 | administrative field; synthetic; human single; none | 12 | some concerns |
| Yadav [263] | safety | 1 | 142,658 | human crowd | 14 | high |
| Yamamoto and Kuroki [264] | judging | 4 | 188 | human adjudicated; human crowd; task outcome; none | 10 | high |
| Yan [265] | classification | 4 | 4,300 | administrative field; none | 12 | high |
| Yan [266] | classification | 1 | 48 | administrative field; human single | 7 | high |
| Yang et al. [269] | QA; agent control | 1 | 134 | human adjudicated; task outcome | 12 | some concerns |
| Yang et al. [268] | other | 4 | 1,120 | task outcome; administrative field | 16 | some concerns |
| Yang et al. [270] | safety | 7 | 1,440 | synthetic | 12 | high |
| Yang et al. [267] | other | 3 | 738 | synthetic; administrative field | 15 | some concerns |
| Ye et al. [271] | other | 5 | 512 | synthetic | 15 | high |
| Yilmaz et al. [272] | classification | 2 | 400 | synthetic; administrative field; human crowd; task outcome; none | 17 | some concerns |
| You et al. [273] | classification | 1 | 135 | administrative field; human crowd | 15 | high |
| Yu and Yao [274] | classification | 8 | 7,532 | human adjudicated | 10 | high |

| Study | Task family | Models | $n$ | Reference labels | Rows | RoB |
|---|---|---|---|---|---|---|
| Zhan et al. [275] | classification; agent control | 12 | 231 | not reported; task outcome | 20 | some concerns |
| Zhang et al. [279] | classification; other | 5 | 213 | human crowd; human single; none | 14 | high |
| Zhang et al. [282] | other; extraction | 1 | 14,262 | human single | 10 | some concerns |
| Zhang and Yu [283] | classification | 4 | 2,210 | human crowd | 15 | high |
| Zhang et al. [276] | classification | 2 | 963,408 | administrative field; human single; none; task outcome; llm teacher; model consensus | 15 | some concerns |
| Zhang et al. [280] | agent control | 1 | 1,192 | task outcome | 22 | some concerns |
| Zhang [281] | agent control | 1 | not reported | task outcome; none | 5 | high |
| Zhang et al. [278] | classification | 8 | 2,091 | human adjudicated | 22 | high |
| Zhang et al. [277] | classification; QA; safety | 6 | 5,059 | administrative field; human crowd; none | 23 | high |
| Zhao et al. [284] | other: graph anomaly detection | 3 | 10,224 | other: benchmark anomaly labels (injected and real); none | 7 | some concerns |
| Zheng and Chen [285] | QA | 2 | 768 | administrative field | 13 | high |
| Zhong et al. [287] | other | 1 | 128 | synthetic | 12 | high |
| Zhou et al. [288] | classification | 8 | 3,669 | human single; human crowd; none | 16 | some concerns |
| Zhou et al. [289] | agent control | 1 | 21 | task outcome; none | 10 | high |
| Zhu et al. [291] | classification | 5 | 111 | administrative field; synthetic; none | 14 | high |
| Zhu et al. [290] | agent control | 4 | 500 | synthetic; not reported; task outcome; none | 15 | high |
| Zhu et al. [292] | other; QA | 2 | 591 | human adjudicated | 10 | high |
| Zhuang et al. [293] | other | 8 | 32,233 | synthetic; administrative field | 15 | some concerns |
| Zhuang et al. [294] | classification | 6 | 7,800 | human adjudicated; synthetic; none | 15 | high |

**Table S10.** The seven application areas of Section 10, the ledger studies that support each one, the kind of reference label each study used and the risk-of-bias grades the area received.

| Area | Supporting studies | Reference types | Grade distribution |
|---|---|---|---|
| Document coding at population scale | [180], [278] | human adjudicated; none; administrative field | high (1), some concerns (1) |
| Annotation for science | [80], [44], [189], [105] | human adjudicated; none; human crowd | high (2), some concerns (2) |
| Judging and evaluation | [117], [76] | vendor label; none; human adjudicated; task outcome | some concerns (2) |
| Agent control and memory | [256], [84], [232], [51] | human adjudicated; task outcome; llm teacher; model consensus; none; vendor label | high (3), some concerns (1) |
| Guardrails, routing and edge orchestration | [102], [103], [187], [65], [186] | task outcome; administrative field; human adjudicated; llm teacher; none | high (2), some concerns (3) |

**Table S11.** The vendor's launch claims against their independent status. Squares count the independent records that agree with a claim (■), agree in part (◪) or contradict it (□).

| Vendor claim and source | Status and records | Independent evidence |
|---|---|---|
| Faster than frontier language models, by 40× to 200× on System One shaped queries in the launch post, and by 193.6× on the homepage, which the vendor expects to lie at the higher end of real-world gains [226, 231] | Supported in direction ■■■◪◪◪

[5] Bushra Asseri and Abdulaziz Asseri. 2026. Calibrated to Whom? Persona and Language Effects on Cultural Values in JEV. arXiv:2609.36399 [cs.CL] https://arxiv.org/abs/2609.36399

[6] Seyedarmin Azizi, Erfan Baghaei Potraghloo, and Massoud Pedram. 2026. Labels Override Definitions in Jev-Style Typed Decision Models. arXiv:2610.02586 [cs.AI] https://arxiv.org/abs/2610.02586

[7] Seyedarmin Azizi, Erfan Baghaei Potraghloo, and Massoud Pedram. 2026. One Word Opens the Gate: The Option-Channel Attack on Typed Decision Models as Agent Guardrails. arXiv:2610.12292 [cs.AI] https://arxiv.org/abs/2610.12292

[8] Gian Luca Bailo. 2026. System Switch: When Should a Fast Decision Model Stop and Think? arXiv:2610.09683 [cs.AI] https://arxiv.org/abs/2610.09683

[9] Balian, Rob. 2026. *rev: Reverse Engineering Jev Using Open Models.* Retrieved 2026-09-24 from https://github.com/robbalian/rev

[10] Stephen Bates, Anastasios Angelopoulos, Lihua Lei, Jitendra Malik, and Michael Jordan. 2021. Distribution-free, Risk-controlling Prediction Sets. *J. ACM* 68, 6 (2021), 1–34. arXiv:2101.02703 doi:10.1145/3478535

[11] Jaime Bellver-Soler, Iván Martín-Fernández, Anmol Guragain, and Luis Fernando D'Haro. 2026. Audio System One Model: Typed Probabilistic Perception of Emotion in Speech. arXiv:2610.22401 [cs.SD] https://arxiv.org/abs/2610.22401

[12] Gaston Besanson. 2026. Probabilistic Sensing, Deterministic Authority: Admitting Model-Produced Observations into Sufficiency-Checked Governance Contracts. arXiv:2610.10978 [cs.SE] https://arxiv.org/abs/2610.10978

[13] Bespoke Labs. 2026. *Bespoke-Nimble-9B Model Card.* Retrieved 2026-09-24 from https://huggingface.co/bespokelabs/Bespoke-Nimble-9B

[14] Bespoke Labs. 2026. *nimble: Local Typed Decisions, Contrastive Data Curation, and Model Evaluation.* Retrieved 2026-09-24 from https://github.com/bespokelabsai/nimble

[15] Glenn W. Brier. 1950. Verification of Forecasts Expressed in Terms of Probability. *Monthly Weather Review* 78, 1 (1950), 1–3. doi:10.1175/1520-0493(1950)078<0001:vofeit>2.0.co;2

[16] Pedro Carvalho Brom. 2026. Confidence Is Not a Promise: A Reference Audit of Typed Decision Models. arXiv:2610.36311 [cs.LG] https://arxiv.org/abs/2610.36311

[17] Yves Bru, Kamaldeep Singh Oberoi, and Benoit Gaudou. 2026. Towards Adaptive and Real-Survey-Aligned Simulated Urban Mobility Behaviour of Generative Agents. arXiv:2610.22407 [cs.MA] https://arxiv.org/abs/2610.22407

[18] Felix Buecheler, Gerardo Berbeglia, and Mingyu Guo. 2026. A Cue's Hidden Price: Auditing Seller Influence on AI Shoppers. arXiv:2610.25843 [cs.AI] https://arxiv.org/abs/2610.25843

[19] Syed Usama Khalid Bukhari, Syed Safwan Khalid, and Muhammad Aamir. 2026. System X: An LLM Decision Model That Replies from Its Own KV Cache. arXiv:2610.25456 [cs.AI] https://arxiv.org/abs/2610.25456

[20] Cai. 2026. *ZefanCai/Open-Jev-9B.* Retrieved 2026-09-24 from https://huggingface.co/ZefanCai/Open-Jev-9B

[21] Congfeng Cao, Lipeng Zuo, Konstantinos Papakostas, Qiwei Xu, Songwei Xu, Qianru Meng, Lun Zhou, Zhaochun Ren, Yougang Lyu, and Xiaohui Yan. 2026. SearchJev: A Calibrated System-1 Model for Search Agents. arXiv:2610.05107 [cs.IR] https://arxiv.org/abs/2610.05107

[22] Hao Chen. 2026. COGNIT-Guard: Calibrated Standalone Direct-Decision Guardrails with Heterogeneous CPU-NPU Confidence Cascading under Explicit Latency and False-Positive Constraints. arXiv:2609.33671 [cs.CR] https://arxiv.org/abs/2609.33671

[23] Han Chen and Yingrui Li. 2026. Probability Contracts: Accuracy, Coherence, and Decisions Across LLM Interfaces. arXiv:2609.37470 [cs.LG] https://arxiv.org/abs/2609.37470

[24] Jianbo Chen. 2026. The Company a Question Keeps: Auditing Open Jev-Style Models for Retrieval. arXiv:2610.14631 [cs.IR] https://arxiv.org/abs/2610.14631

[25] Josef Liyanjun Chen. 2026. RoboJev: An Open Vision-Language Judge for Robot Success Detection. arXiv:2610.33718 [cs.RO] https://arxiv.org/abs/2610.33718

[26] Man Chen, Antai Chen, Shuai Xu, Chengjie Gu, Huaping Zhou, Kelei Sun, Tao Wu, and Yongjie Huang. 2026. RSAJEV: Training-Free Abstaining Prototype Memory for Eliminating Silent Hallucination in JEV-Based Remote Sensing Classification. arXiv:2610.15742 [cs.CV] https://arxiv.org/abs/2610.15742

[27] Peixin Chen, Zhigao Chen, Zhiyun Fan, Ying Fang, Zhifu Gao, Qing Gu, Jiajun He, Kangqi Jing, Xiangang Li, Yalin Li, Baiji Liu, Ying Liu, Zhaoci Liu, Yuezhang Peng, Zhendong Peng, Yu Pu, Peiyao Wang, Wupeng Wang, Yuzhong Wu, Yunchong Xiao, Nan Yang, and Renjie Yu. 2026. Qwen-Audio-Jev: A Unified Interface for Audio Decisions. arXiv:2610.21614 [cs.SD] https://arxiv.org/abs/2610.21614

[28] Tianyu Chen, Xinyang Liu, Ruyi An, Zhendong Wang, and Mingyuan Zhou. 2026. System1-Arena: Which Decisions Can Be Left to System 1? arXiv:2610.21244 [cs.CL] https://arxiv.org/abs/2610.21244

[29] Xupeng Chen and Chenqian Le. 2026. Suggested Is Not Superseded: A Pre-Registered Evaluation of a System-One Model as a Memory-Retirement Gate. arXiv:2610.15710 [cs.AI] https://arxiv.org/abs/2610.15710

[30] Zheng Chen, Fei Yu, Haohao Huang, Yang Li, Anlong Chen, and Lei Chen. 2026. SecJev: Bringing Security Expertise to System One Decision Models. arXiv:2610.03073 [cs.CR] https://arxiv.org/abs/2610.03073

[31] Jianpeng Cheng, Guangyu Sun, Aashu Singh, Benyu Zhang, Haixing Dai, Hossein Mansour, Jiangfan Zhang, Shlok Kumar Mishra, Wei Sun, Xuanming Cui, Yanli Liu, Qi Guo, Max Xiangjun Fan, and Jun Xiao. 2026. MetaEncoder: Exploring the Limit of Bi-Encoders for Multimodal System One Decision Making with Natural Language Interface. arXiv:2610.11316 [cs.CL] https://arxiv.org/abs/2610.11316

[32] Zehua Cheng, Wei Dai, and Jiahao Sun. 2026. this-that-model-1.0: A typed decision model that decides in 30 ms, for a millionth of a cent. arXiv:2609.23886 [cs.CL] https://arxiv.org/abs/2609.23886

[33] Avdhesh Singh Chouhan and Jack Perry. 2026. Verdict: Encode Once, Decide Many. arXiv:2610.20778 [cs.CL] https://arxiv.org/abs/2610.20778

[34] C. Chow. 1970. On optimum recognition error and reject tradeoff. *IEEE Transactions on Information Theory* 16, 1 (1970), 41–46. doi:10.1109/tit.1970.1054406

[35] Kawai Chung, Chunkit Chan, Yuxuan Liu, Yauwai Yim, Xi Yang, Wenbin Hu, Huihao Jing, Chiu Yeung Tang, Changxuan Fan, Ki Sen Hung, Tsun On Kwok, and Haoran Li. 2026. Jev-ToM: Evaluating Theory of Mind in Typed Decision Models. arXiv:2610.18610 [cs.CL] https://arxiv.org/abs/2610.18610

[36] Gabriele Cinà. 2026. Jev Matches 7B Language Models for Speech-Neuroprosthesis Rescoring. arXiv:2609.33538 [cs.CL] https://arxiv.org/abs/2609.33538

[37] Cloudflare. 2026. *Introducing Clef: Our Open-Source Decision Models, and New RL Fine-Tuning Platform.* https://blog.cloudflare.com/clef-decision-models

[38] Convai Innovations. 2026. *convaiinnovations/laya-multilingual.* Retrieved 2026-09-24 from https://huggingface.co/convaiinnovations/laya-multilingual

[39] Convai Innovations. 2026. *Laya Model Card (convaiinnovations/laya).* Retrieved 2026-09-24 from https://huggingface.co/convaiinnovations/laya

[40] Shenghong Dai, Shiva Kumar Pentyala, Yingchi Liu, Shubham Mehrotra, Suman Banerjee, James Zhu, Bin Bi, Sitaram Asur, and Phil Mui. 2026. Koa-decision: Fast and Consistent Structured Decision Making with Generative LLMs. arXiv:2609.36115 [cs.LG] https://arxiv.org/abs/2609.36115

[41] Yuyang Dai, Yuting Tang, Futoshi Futami, and Takashi Ishida. 2026. ProbabilityBench: Model Evaluation and Calibration with Exact Ground-Truth Uncertainty. arXiv:2610.17016 [cs.LG] https://arxiv.org/abs/2610.17016

[42] Pritam Deka. 2026. From Retrieval to Typed Decisions: Calibrated System One Models from Biomedical Sentence Encoders. arXiv:2610.02486 [cs.CL] https://arxiv.org/abs/2610.02486

[43] M. Mikail Demir. 2026. Commit or Abstain? System One Decision Models, LLMs, and Missing Legal Authority. arXiv:2610.29961 [cs.AI] https://arxiv.org/abs/2610.29961

[44] Boyuan Deng, Shuyi Fan, Hongyang Zhang, and Xinhong Xie. 2026. Jev for Scientific Decisions: Evaluating Semantic Choices and Their Consequences. arXiv:2609.24965 [cs.CL] https://arxiv.org/abs/2609.24965

[45] Steven Denney and Matthew DiGiuseppe. 2026. JEV versus LLMs: Accuracy, Cost and Calibration on Seven Political Science Replications. arXiv:2610.06625 [cs.CL] https://arxiv.org/abs/2610.06625

[46] Tobias Deußer, Lorenz Sparrenberg, and Rafet Sifa. 2026. Evaluating and Benchmarking the System One Model Jev. arXiv:2609.37647 [cs.CL] https://arxiv.org/abs/2609.37647

[47] Li Ding, Haidi Jin, and Chen Ji. 2026. Bongard: Training Machine Intuition. arXiv:2609.39111 [cs.CL] https://arxiv.org/abs/2609.39111

[48] Shenghao Ding. 2026. JET: Justification Evaluation in Transformer. arXiv:2609.33874 [cs.LG] https://arxiv.org/abs/2609.33874

[49] Michael Dinzinger, Kanishka Ghosh Dastidar, and Michael Granitzer. 2026. System One models Are Not Better Rerankers. arXiv:2610.32318 [cs.CL] https://arxiv.org/abs/2610.32318

[50] Ben Dong, Tianyi Lu, Zhonghao Guo, and Qian Wang. 2026. DICE: Tilting the Odds through Interface Attacks on System One Model. arXiv:2610.14404 [cs.CR] https://arxiv.org/abs/2610.14404

[51] Joas Antonio dos Santos Barbosa. 2026. Calibrated Decision Models for Autonomous Penetration-Testing Harnesses: JEV and Laya as System One Decision Layers for LLM-Driven Pentest Agents. arXiv:2609.28940 [cs.CR] https://arxiv.org/abs/2609.28940

[52] Yanrui Du, Danyang Zhao, Sendong Zhao, Wenhao Li, Yibo Gao, Haochun Wang, Zhuoer Xu, Shiwen Cui, and Bing Qin. 2026. How Reliable Are System-One Decisions in Medicine? A Comparative Study of Jev, Jev-like Models, and LLMs. arXiv:2610.18529 [cs.CL] https://arxiv.org/abs/2610.18529

[53] Feiyu Duan, Jiayu Lin, Jia Wang, Jun Xiang, Jialiang Wu, Xinnong Zhang, Hanqi Yan, Siyuan Wang, and Zhongyu Wei. 2026. General Decision Models: Benchmarking and Insights Beyond Jev. arXiv:2610.03935 [cs.CL] https://arxiv.org/abs/2610.03935

[54] Charles Elkan. 2001. The foundations of cost-sensitive learning. (2001), 973–978.

[55] Edward S. Epstein. 1969. A Scoring System for Probability Forecasts of Ranked Categories. *Journal of Applied Meteorology* 8, 6 (1969), 985–987. doi:10.1175/1520-0450(1969)008<0985:assfpf>2.0.co;2

[56] Romi Fadli, Rusdah, Wahyu Ramadani Putri Utami, and Zulfa Malika Amana. 2026. Does System One Transfer? Calibrated Typed-Decision Models, Label Budgets, and Translation for Indonesian Regional Languages. arXiv:2610.14112 [cs.CL] https://arxiv.org/abs/2610.14112

[57] Yangyang Feng, Jianle Gan, Zhuoyan Feng, and Chengwei Qin. 2026. Jev-DLC: Decision-Level Continual Learning from Typed Feedback. arXiv:2610.31521 [cs.AI] https://arxiv.org/abs/2610.31521

[58] Leandro Carísio Fernandes and Jayr Pereira. 2026. Jev-as-a-Judge for Brazilian Portuguese Information Retrieval: Relevance Assessment and Reranking. arXiv:2610.23346 [cs.IR] https://arxiv.org/abs/2610.23346

[59] FLock.io. 2026. *flock-io/this-that-model-1.0.* Retrieved 2026-09-24 from https://huggingface.co/flock-io/this-that-model-1.0

[60] Shuyu Gan, Young-Jun Lee, and Dongyeop Kang. 2026. SanSi: A Looped Typed Decision Model for System 1.5 Thinking. arXiv:2610.07730 [cs.CL] https://arxiv.org/abs/2610.07730

[61] Tianxiang Gao, Jinzhe Li, Zhiyuan Li, Yi Chang, and Yuan Wu. 2026. More Choices, Fewer Decisions: Ordinal-Scale Bias in JEV-like Direct-Decision Models. arXiv:2609.38827 [cs.AI] https://arxiv.org/abs/2609.38827

[62] Rotem Gershon, Seffi Cohen, Dean Ariel, Havatzelet Bilavsky-Yarden, Amiel Sberro, Shai Yitzhaki, Osnat Tausky, Naama Golan, Maayan Rabinovitch, Ariel Avraham Hasidim, Itay Arianu, Maya Dagan, Ran Balicer, and Noa Dagan. 2026. Decision language models as affordable and rapid alternatives to LLM judges of clinical generative AI. arXiv:2610.28826 [cs.AI] https://arxiv.org/abs/2610.28826

[63] Jonathan Geuter, Andrew Cheng, and David Alvarez-Melis. 2026. Releasing the Inner Jev: A Simple Recipe for Open Decision Models. arXiv:2610.17205 [cs.AI] https://arxiv.org/abs/2610.17205

[64] Tilmann Gneiting and Adrian E Raftery. 2007. Strictly Proper Scoring Rules, Prediction, and Estimation. *J. Amer. Statist. Assoc.* 102, 477 (2007), 359–378. doi:10.1198/016214506000001437

[65] Ruoqi Guo, Yi Liu, Gelei Deng, Yuekang Li, Lida Zhao, Yutao Wu, Simin Chen, Ying Zhang, and Leo Yu Zhang. 2026. Just Ask Jev: Reinforcement Learning for Calibrated Decisions as a Zero-Shot Detector of AI Alignment Failures. arXiv:2609.29429 [cs.AI] https://arxiv.org/abs/2609.29429

[66] Xiaoguang Guo, Yaohao Long, and Chuxu Zhang. 2026. BLADE: Auditing Information Use for Failure Attribution in LLM Multi-Agent Systems. arXiv:2610.18780 [cs.AI] https://arxiv.org/abs/2610.18780

[67] Phat Huu Ha, Nguyen Xuan Phuc, Nong Nhut Quy, Trinh Tran Tran, Nguyen Minh Triet, and Dang Van Thin. 2026. How Well Do Decision Models Transfer to Vietnamese? An Empirical Study of Text Classification. arXiv:2610.31422 [cs.CL] https://arxiv.org/abs/2610.31422

[68] Jin Han, Mingfeng Xin, Feng Liang, and Jingtao Yu. 2026. NIOCIS: Typed-Decision Next-Hop Routing with Node-Conditioned Option Spaces for Tool-Use Agents. arXiv:2610.25985 [cs.CR] https://arxiv.org/abs/2610.25985

[69] Zhi Han, Zihan Guo, Chenxi Zeng, Zicai Cui, Yue Xin, Ming Zhou, Dongzhan Zhou, Weinan Zhang, and Yang Li. 2026. Embodied Skill Bench: Benchmarking How Well Agents with Embodied Skills Perform on Physical Tasks. arXiv:2610.16238 [cs.RO] https://arxiv.org/abs/2610.16238

[70] Mengxian He, Ziyue Gao, Chun Li, Shunyi Zhang, Hao Wei, Minqing Zhang, and Wu Yuan. 2026. Can JEV Support Clinical Trial Criteria Assessment? arXiv:2610.35721 [cs.LG] https://arxiv.org/abs/2610.35721

[71] Heman10x-NGU. 2026. *Verdict-open-jev: Non-Autoregressive Decision Engine on ModernBERT (151M) with Calibrated Uncertainty (RLCD).* Retrieved 2026-09-24 from https://github.com/Heman10x-NGU/Verdict-open-jev

[72] Jianyi Hu, Hangtao Zhang, Yi Liu, Yeqi Zeng, Li Zeng, Xianlong Wang, Rui Wang, and Leo Yu Zhang. 2026. JevAdvBench: A Benchmark and Black-Box Attacks for Reinforcement Learning for Calibrated Decisions Models. arXiv:2609.31142 [cs.CR] https://arxiv.org/abs/2609.31142

[73] Wenbin Hu, Huihao Jing, Haochen Shi, Yuxuan Liu, Changxuan Fan, Sirui Zhang, Kawai Chung, Hanyu Yang, Zhenhuan Wang, Ziyi Chen, Haoran Li, and Yangqiu Song. 2026. Jev-Guard: Fast Routing and Auditing Agent Actions over Editable Policy Trees. arXiv:2610.18326 [cs.CR] https://arxiv.org/abs/2610.18326

[74] Jerrold Huang, Junwei Quan, Saiyue Lyu, Zihan Guo, and Yingqiang Ge. 2026. SkillScreen: High-Recall Screening of Malicious Agent Skills with Decision Models. arXiv:2610.17727 [cs.CR] https://arxiv.org/abs/2610.17727

[75] Jianguo Huang, Yao Long Teng, Yanchen Deng, and Bo An. 2026. Consider, Then Choose: Order-Invariant Decisions in System One Models. arXiv:2610.18233 [cs.AI] https://arxiv.org/abs/2610.18233

[76] Jiaju Huang, Hao Yang, Xinyu Ma, Xinglong Liang, Kunyan Cai, Junqiang Ma, Shaobin Chen, Yue Sun, and Tao Tan. 2026. Can Jev Judge Radiology Reports? Evaluating a System One Model for Clinical Factuality. arXiv:2609.27607 [cs.CL] https://arxiv.org/abs/2609.27607

[77] Hume, Archer. 2026. *Jev's Architecture Unmasked.* Retrieved 2026-09-24 from https://archerhume.com/posts/jevs-architecture-unmasked/

[78] Wenhua Huo, Fenglei Han, Wangyuan Zhao, Jialin Wu, and Jiayi Han. 2026. NL2Hull: A Natural Language-Driven Constrained Ship Design Decision Framework. arXiv:2610.09896 [cs.AI] https://arxiv.org/abs/2610.09896

[79] iApp Technology. 2026. *iapp/OpenThai-SystemOne*. Retrieved 2026-09-24 from https://huggingface.co/iapp/OpenThai-SystemOne

[80] Hazem Ibrahim and Yasir Zaki. 2026. Evaluating Decision Models for Text Annotation in Computational Social Science. arXiv:2609.24574 [cs.CL] https://arxiv.org/abs/2609.24574

[81] Yuma Ichikawa. 2026. Decision Model Factory: Building Specialized Sovereign Decision Models. arXiv:2610.34956 [cs.AI] https://arxiv.org/abs/2610.34956

[82] Ilaria Imperatrice, Taisia Kameneva, Adam Eric Greenberg, and Alessandro Romano. 2026. Are AI Decision Models Biased? A Case Study of Jev. arXiv:2610.19619 [cs.AI] https://arxiv.org/abs/2610.19619

[83] Abdul Rahman Iqbal, Muhammad Fawad Nasim, and Amir Saleem. 2026. Typed Decision Models under Prevalence Shift: Decision Training, Calibration, and Implicit Priors. arXiv:2610.26325 [cs.LG] https://arxiv.org/abs/2610.26325

[84] Dongming Jiang, Yi Li, and Bingzhe Li. 2026. Jev-Mem: System-One-Controlled Agentic Memory for Efficient AI Agents. arXiv:2609.23986 [cs.AI] https://arxiv.org/abs/2609.23986

[85] Saman Sarker Joy. 2026. Do System One Decisions Add Up? A Study of Probabilistic Coherence. arXiv:2609.33971 [cs.CL] https://arxiv.org/abs/2609.33971

[86] Wooyoung Jung. 2026. Where Can a Decision Model Diagnose HVAC Faults? Reasoning Demand, Physical Representation, and Robustness Under Shift. arXiv:2610.09937 [cs.AI] https://arxiv.org/abs/2610.09937

[87] Parv Khatri, Harshul Jain, Mehak Kapoor, and Tanya Sah. 2026. Do We Need an LLM to Know Why Sources Conflict? Decision Models for Knowledge-Conflict Typing in RAG. arXiv:2610.36915 [cs.CL] https://arxiv.org/abs/2610.36915

[88] Tina Khezresmaeilzadeh, Seyedarmin Azizi, Erfan Baghaei Potraghloo, Mehdi Kamal, and Massoud Pedram. 2026. Claim Laundering: When Agent Decision Models Trust Records Over Reality. arXiv:2610.25947 [cs.AI] https://arxiv.org/abs/2610.25947

[89] Orhan Konak. 2026. More Features Are Not More Evidence: Limits of Training-Free Human Activity Recognition with Jev. arXiv:2609.36154 [cs.AI] https://arxiv.org/abs/2609.36154

[90] kotoba-lang. 2026. *com-kotobalabs/open-jev-deberta-v3-large*. Retrieved 2026-09-24 from https://huggingface.co/com-kotobalabs/open-jev-deberta-v3-large

[91] Michail-Alexandros Kourtis and George Xilouris. 2026. Type-Safe Decision Frameworks for Agentic 5G Control: A Theory-Driven Testbed Characterization of Where They Can Be Applied. arXiv:2609.33689 [cs.NI] https://arxiv.org/abs/2609.33689

[92] Bhawesh Kumar, Charlie Lu, Gauri Gupta, Anil Palepu, David Bellamy, Ramesh Raskar, and Andrew Beam. 2023. Conformal Prediction with Large Language Models for Multi-Choice Question Answering. arXiv:2305.18404 [cs.CL] https://arxiv.org/abs/2305.18404

[93] Ted Kwartler, Alan Aqrawi, and Arian Abbasi. 2026. Harness Tokenomics: A Router for the Enterprise Agentic Control Plane. arXiv:2609.28919 [cs.AI] https://arxiv.org/abs/2609.28919

[94] Tianyou Lai, Wentao Yue, Zhiying Deng, and Qilei Li. 2026. Correct Choices, Failed Sequences: Choice2Seq Benchmarks Correctness Retention Across Output Interfaces. arXiv:2610.16191 [cs.AI] https://arxiv.org/abs/2610.16191

[95] Tianyou Lai, Wentao Yue, Zhiwei Zuo, and Qilei Li. 2026. Which Differences Matter? Controlled Tests of Rule Transfer, Joint Reliability, and Information Use in Decision Models. arXiv:2610.30045 [cs.AI] https://arxiv.org/abs/2610.30045

[96] Qianlong Lan, Anuj Kaul, Vinothini Pandurangan, and Indranil Sanyal. 2026. From Detection to Decision: Calibration and Deferral for Prompt-Injection Detection. arXiv:2610.20907 [cs.CR] https://arxiv.org/abs/2610.20907

[97] Yifan Lan, Zhongye Liu, Yurui Chang, Hanyu Wang, Yongkang Du, Lu Lin, and Jinghui Chen. 2026. DecisionRobust: Benchmarking Robustness for JEV Style Decision Models Across Text and Vision. arXiv:2610.19118 [cs.CL] https://arxiv.org/abs/2610.19118

[98] Simon A. Lee, Jiahang Sha, Moonseong Jeong, Yunbei Pan, and Jeffrey N. Chiang. 2026. MedJev: Evaluating Zero-Shot System-One Decision Making in Medicine. arXiv:2610.36006 [cs.CL] https://arxiv.org/abs/2610.36006

[99] Unggi Lee and Haeun Park. 2026. Can a System-One LLM Perform Knowledge Tracing When Few or No Learners Are Logged? arXiv:2610.11135 [cs.CL] https://arxiv.org/abs/2610.11135

[100] Baoteng Li, Wenzhuo Wu, Kongming Liang, and Zhanyu Ma. 2026. Visual Jev Rewards: Reference-Bound Verification for Multi-Subject Image Generation. arXiv:2610.09328 [cs.CV] https://arxiv.org/abs/2610.09328

[101] Delong Li, Chen Li, Xu Wang, Haochen Gong, Rui Lang, and Guangsheng Yu. 2026. SoK: Semantic Decision Engines in Network Control Loops. arXiv:2610.06425 [cs.NI] https://arxiv.org/abs/2610.06425

[102] Delong Li, Xu Wang, Haochen Gong, Rui Lang, and Guangsheng Yu. 2026. Intent Interpretation at RIC Timescales: Jev Decision Models versus Large Language Models in 6G Open RAN. arXiv:2609.23136 [cs.NI] https://arxiv.org/abs/2609.23136

[103] Delong Li, Xu Wang, Haochen Gong, Rui Lang, and Guangsheng Yu. 2026. Replacing Large Language Models with Jev Decision Models for Low-Latency Edge Service Orchestration. arXiv:2609.22753 [cs.DC] https://arxiv.org/abs/2609.22753

[104] Fengxin Li. 2026. Seeing the Options: Typed Decisions over Visual Candidates with Reusable Option Memory. arXiv:2610.33702 [cs.AI] https://arxiv.org/abs/2610.33702
[105] Hengyu Li. 2026. KITE: Scaling Jev Population Experiments with Sparse Flagship Calibration. arXiv:2609.27535 [cs.MA] https://arxiv.org/abs/2609.27535
[106] Jiawei Li. 2026. Fast Models, Slow Evidence: A Paired and Self-Audited Evaluation of System-1 Decision Models for LLM Agent Harnesses. arXiv:2610.02267 [cs.AI] https://arxiv.org/abs/2610.02267
[107] Keyi Li, Yihao He, and Quanyi Li. 2026. Beyond Calibration: Do a Typed-Decision Model's Probabilities Obey the Probability Axioms? arXiv:2609.33209 [cs.CL] https://arxiv.org/abs/2609.33209
[108] Qi Li and Xinchao Wang. 2026. Jeva: System One Models from First Principles. arXiv:2610.18773 [cs.AI] https://arxiv.org/abs/2610.18773
[109] Qiaomu Li and Ying Xie. 2026. Can System-1-Style Decision Models Replace Dedicated Rerankers in RAG? A Systems Evaluation. arXiv:2610.34816 [cs.LG] https://arxiv.org/abs/2610.34816
[110] Qi Li, Jianjun Xu, and Pingtao Wei. 2026. DKnown-Jev: Fine-Tuning and Evaluation of a JEV-Style Model for Tasks Involving Normative Knowledge. arXiv:2610.24358 [cs.AI] https://arxiv.org/abs/2610.24358
[111] Ran Li and Lei Chen. 2026. JevCascade: Readout Stability and Inference-Time Compute Allocation for Prefill-Only Decision Models. arXiv:2610.07716 [cs.CL] https://arxiv.org/abs/2610.07716
[112] Xuechen Li. 2026. AgriJev: Efficient Agricultural Candidate Scoring with Multi-Scale Adapted Models. arXiv:2610.19478 [cs.CL] https://arxiv.org/abs/2610.19478
[113] Xing Li, Qingcheng Chang, Jinzhong Ning, Changfeng Xu, Shenlong Zhang, Yijia Zhang, Ling Luo, and Hongfei Lin. 2026. Specialized Decision Models vs. General-Purpose LLMs: Benchmarking Jev Across Knowledge, Reasoning, and Multilingual Tasks. arXiv:2610.11978 [cs.CL] https://arxiv.org/abs/2610.11978
[114] Xiang Li, Aichun Huang, Mingming Zhang, and Zheli Liu. 2026. Same Attack, Different Judge: A First Controlled Adversarial Comparison of Jev, LLM Judges, and Purpose-Built Safety Classifiers. arXiv:2610.17820 [cs.CR] https://arxiv.org/abs/2610.17820
[115] Xing Li, Jinzhong Ning, Yijia Zhang, Liang Yang, and Hongfei Lin. 2026. Can Decision Models Understand Stance? Evaluating Jev Against General-Purpose LLMs. arXiv:2610.11901 [cs.CL] https://arxiv.org/abs/2610.11901
[116] Yubo Li, Ramayya Krishnan, and Rema Padman. 2026. Reading Right, Acting Wrong: Diagnosing Decision Failures of System One Models in Agent Loops. arXiv:2610.18579 [cs.AI] https://arxiv.org/abs/2610.18579
[117] Yubo Li, Yidi Miao, Ramayya Krishnan, and Rema Padman. 2026. JEV-as-a-Judge: Accept When Confident, Escalate When Unsure. arXiv:2609.26550 [cs.AI] https://arxiv.org/abs/2609.26550
[118] Yinheng Li and Justin Wagle. 2026. LLM-as-Jev: LLMs Are Already Jev-Style Decision Models – When and How to Fine-Tune Them. arXiv:2610.02076 [cs.CL] https://arxiv.org/abs/2610.02076
[119] Yang Li, Yike Wang, Di Wan, Chujun He, Zongsi Xu, Yitao Yu, Quanfeng Lu, Xiyu Chen, Sheng Zhong, Deng Binjie, Yichen Guo, Zhenwei Guo, Hou Jun, Kunhan Guo, Weihao Lin, Tuo Zhou, Hai Liu, Chenwei Wu, Jianyuan Zhong, Xilin Dai, and Ye Luo. 2026. $S^2$-MAS: A Society-Scale Multi-Agent Simulation Framework with 500 Million Household Persona Agents. arXiv:2610.27746 [cs.MA] https://arxiv.org/abs/2610.27746
[120] Yida Lin. 2026. PACT: Pairwise-Anchored Calibrated Tuning for Single-Token Typed Decisions. arXiv:2609.35865 [cs.CL] https://arxiv.org/abs/2609.35865
[121] Guoming Ling, Muen Xue, and Zijian Ye. 2026. Jev in the Wild: A Data-Driven Analysis of the Jev Model's Functionality, Applications and Ecosystem. arXiv:2609.30216 [cs.SE] https://arxiv.org/abs/2609.30216
[122] Yuchen Ling, Shengcheng Yu, Zhenyu Chen, and Chunrong Fang. 2026. When Faster Decisions Do Not Make Better Agents: An Empirical Study of Jev in Agent Workflows. arXiv:2610.13092 [cs.AI] https://arxiv.org/abs/2610.13092
[123] Bo Liu, Lianyu Wang, Meng Wang, Ching-Yu Cheng, and Huazhu Fu. 2026. RetiJev: Fast and Source-Grounded Ophthalmic Decision Models. arXiv:2610.30947 [cs.CL] https://arxiv.org/abs/2610.30947
[124] Chenghao Liu, Wei Fan, Jindong Han, Dongjie Wang, Aniket Mahanti, Pengyang Wang, and Hao Liu. 2026. TimesJev: Thinking Fast on Time Series with System 1 Sufficiency. arXiv:2610.26002 [cs.AI] https://arxiv.org/abs/2610.26002
[125] Daoxuan Liu, Jiayi Liao, Jiancan Wu, An Zhang, Xiang Wang, and Xiangnan He. 2026. Decision-Native Recommendation with Large Language Models. arXiv:2610.34124 [cs.IR] https://arxiv.org/abs/2610.34124
[126] Fangcheng Liu, Yeqing Shen, Anda Cheng, Weishi Mi, Chao Tang, Chenyuan Liu, Yushun Xiang, Tingguang Li, Yong-Lu Li, and Yehui Tang. 2026. RoboICL: Embodied In-Context Learning with GPT-6 Astra. arXiv:2609.34261 [cs.RO] https://arxiv.org/abs/2609.34261
[127] Fangyuan Liu, Sirui Zhao, Xiaohao Wang, Guo Cheng, Peng Zhang, and Enhong Chen. 2026. PsyJev: Psychological Analysis via System-1 Judgment. arXiv:2610.36689 [cs.AI] https://arxiv.org/abs/2610.36689
[128] Hongliang Liu. 2026. Adversarial Cues in Decision Models Used as Judges: The Role of Request Presentation. arXiv:2610.11436 [cs.CL] https://arxiv.org/abs/2610.11436
[129] Haozheng Liu, Zhaoqian Xue, Zhongyin Wang, Junting Mu, Zihui Ma, Shuya Feng, and Lingyao Li. 2026. Decision Models as Judges for Hallucination Detection. arXiv:2610.37229 [cs.CL] https://arxiv.org/abs/2610.37229

[130] Yixuan Liu. 2026. Evaluating System One Models for Agent Security Decisions: Reliability, Calibration, and Selective Automation. arXiv:2609.33401 [cs.CR] https://arxiv.org/abs/2609.33401
[131] Zhuchenyang Liu, Yao Zhang, and Yu Xiao. 2026. Multimodal Reranking Is a System One Decision. arXiv:2610.28435 [cs.IR] https://arxiv.org/abs/2610.28435
[132] llm-semantic-router. 2026. *llm-semantic-router/Decision-1.0-Sol-2B.* Retrieved 2026-09-24 from https://huggingface.co/llm-semantic-router/Decision-1.0-Sol-2B
[133] LocalLLaMA. 2026. *LocalLLaMA/typed-decisions.* Retrieved 2026-09-24 from https://huggingface.co/datasets/LocalLLaMA/typed-decisions
[134] Michele Loi. 2026. The Argument and the Letterhead: Source-Position Coherence in AI Evaluation. arXiv:2609.35286 [cs.AI] https://arxiv.org/abs/2609.35286
[135] Jiawen Lu and Tongtong Wu. 2026. Benchmarking candidate coverage and rejection policy transfer in typed decision models. arXiv:2610.03387 [cs.AI] https://arxiv.org/abs/2610.03387
[136] Federico Lucca. 2026. Measure Before You Train: Typed Decision Models vs. a Classical Baseline vs. a Generative LLM for Routing a Personal Multilingual Inbox. arXiv:2610.32955 [cs.CL] https://arxiv.org/abs/2610.32955
[137] Fabian Lukassen, Christoph Weisser, and Alexander Silbersdorff. 2026. Cheap, Consistent, Calibrated, but Biased? Typed Decision Models as Judges. arXiv:2610.18122 [cs.CL] https://arxiv.org/abs/2610.18122
[138] Mantas Lukauskas and Viktorija Šarkauskaitė. 2026. Probable but Not Valid: A Psychometric Audit of Decision Models as Synthetic Survey Respondents. arXiv:2610.14912 [cs.AI] https://arxiv.org/abs/2610.14912
[139] Yang Luo, Tiantian Ji, Zifeng Kang, Yucheng Wang, Yong Liu, Zhiyi Yin, and Xinran Liu. 2026. Nudge the Judge: Uncovering Program Decision Hijacking in Real-World Jev Applications. arXiv:2610.18612 [cs.CR] https://arxiv.org/abs/2610.18612
[140] Hanjia Lyu and Yinglong Xia. 2026. Decision-Oriented Recommendation Reranking: An Empirical Study of Its Promise and Limitations. arXiv:2609.40241 [cs.IR] https://arxiv.org/abs/2609.40241
[141] Jie Ma, Jie Gao, Yihang Liu, Zhike Qiu, Junle Li, Chongyi Zhuang, Jiayi Ji, and Xiaoshuai Sun. 2026. FastJEV: Understanding Redundancy for Compact JEV Inference. arXiv:2610.11379 [cs.CV] https://arxiv.org/abs/2610.11379
[142] Linhai Ma, Yan Wang, Lingfei Qian, Yupeng Cao, and Victor Gutierrez Basulto. 2026. Judges Follow the Reference: The Derivation Gap in Verifying Tool-Call Arguments. arXiv:2610.18497 [cs.AI] https://arxiv.org/abs/2610.18497
[143] Weiyu Ma, Liangbing Zhao, Yongcheng Zeng, and Jian Zhao. 2026. JEV-Star: Fast, Low-Cost StarCraft II Control with Language-Model Planning. arXiv:2609.27331 [cs.GT] https://arxiv.org/abs/2609.27331
[144] Xiaoxiao Ma, Weiyang Jin, Yanwen Ma, Haoran Li, Zhixiang Wei, Songchun Zhang, Yaowei Li, Junhao Zhuang, Zeyue Xue, Yuming Li, Zheming Fu, Haoyang Huang, Nan Duan, and Feng Zhao. 2026. WorldStream: Streaming Interactive 3D Worlds with Hierarchical Planning and Persistent State. arXiv:2610.28827 [cs.CV] https://arxiv.org/abs/2610.28827
[145] Yi Ma, Tianpei Yang, Yaodong Yang, Weixun Wang, and Hongyao Tang. 2026. Can Jev be Your Q or Policy in Reinforcement Learning? arXiv:2610.11692 [cs.LG] https://arxiv.org/abs/2610.11692
[146] MachineFi. 2026. *Trio-Spark Model Card.* https://huggingface.co/MachineFi/Trio-Spark
[147] Alfredo Madrid-García and Beatriz Merino-Barbancho. 2026. Jev in Medicine: A Benchmark Evaluation. arXiv:2609.34024 [cs.AI] https://arxiv.org/abs/2609.34024
[148] Mapika. 2026. *Mapika/decider-2b.* Retrieved 2026-09-24 from https://huggingface.co/Mapika/decider-2b
[149] Federico Mazzoni and Andrea Failla. 2026. Benchmarking System One Models in Online Moderation. arXiv:2610.07953 [cs.SI] https://arxiv.org/abs/2610.07953
[150] Haocheng Mei, Yuchuan Tian, Ye Yuan, Enhua Wu, Chao Xu, Allen Chen, Kai Han, and Yunhe Wang. 2026. Improving JEV Entailment Reranking with Span Readouts and Selective Adaptation. arXiv:2610.35654 [cs.CL] https://arxiv.org/abs/2610.35654
[151] Soundouss Messoudi and Youness Mansar. 2026. Calibration and Risk-Budgeted Decisions with System One Models. arXiv:2610.19811 [stat.ML] https://arxiv.org/abs/2610.19811
[152] Microsoft. 2026. *Deploy and Use Microsoft-Decision-1 in Microsoft Foundry.* https://learn.microsoft.com/en-us/azure/foundry/foundry-models/how-to/use-foundry-models-microsoft-decision
[153] Microsoft. 2026. *Introducing Microsoft-Decision-1.* https://commandline.microsoft.com/microsoft-decision-1-model-foundry/
[154] Guanghui Min and Chen Chen. 2026. Prune the Summary, Not the History: Source-Judged Compaction for Long-Horizon Agents. arXiv:2610.20927 [cs.CL] https://arxiv.org/abs/2610.20927
[155] Tran Cao Minh, Hai Tran, and Ha Minh Tan. 2026. Can Multimodal Decision Models Classify Breast Ultrasound Images? Benchmarking CLEF and CLEF-Flash Across Prompts and Datasets. arXiv:2610.13675 [eess.IV] https://arxiv.org/abs/2610.13675
[156] Mohamad Mohebifar and Alex Bit. 2026. OneCodeReviewBench: Typed Decisions for Code Review and Search. arXiv:2610.33389 [cs.SE] https://arxiv.org/abs/2610.33389

[157] Tianwei Mu, Shengyan Jiang, Mingzhe Yuan, Qing Luo, Min Xiao, Wenhong Wang, Jun Li, and Manhong Huang. 2026. HydroJEV: A one-second, training-free screen for cyber-attack and fault attribution in water distribution networks. arXiv:2610.02048 [cs.AI] https://arxiv.org/abs/2610.02048
[158] multimodalart. 2026. *Jev Decision Index.* https://huggingface.co/spaces/multimodalart/jev-decision-index
[159] Rushab Munot. 2026. When Multiple Choices Are Correct: Asymmetric Probability Allocation in Jev and Other Decision Models. arXiv:2610.29217 [cs.AI] https://arxiv.org/abs/2610.29217
[160] Gowthamkumar Nandakishore. 2026. CLM-as-a-Judge: Evaluating an Open Contrastive Decision Model on Public Judge Benchmarks. arXiv:2610.07177 [cs.LG] https://arxiv.org/abs/2610.07177
[161] Gowthamkumar Nandakishore. 2026. Laya as a Typed Probabilistic Assessor: An Independent Reproduction and a Preregistered Study of Calibration and Selective Escalation. arXiv:2609.33843 [cs.AI] https://arxiv.org/abs/2609.33843
[162] Jared Palmer. 2026. *kev: Jev-Like Family of Decision Models Built on Qwen3.5/3.8.* Retrieved 2026-09-24 from https://github.com/jaredpalmer/kev
[163] Palmer, Jared. 2026. *jaredpalmer/kev-0.8b.* Retrieved 2026-09-24 from https://huggingface.co/jaredpalmer/kev-0.8b
[164] Palmer, Jared. 2026. *jaredpalmer/kev-9b.* Retrieved 2026-09-24 from https://huggingface.co/jaredpalmer/kev-9b
[165] Ningxin Pan, Hanyu Li, Yeqing Shen, Ning Ding, Yehui Tang, and Wentao Zhang. 2026. The World Won't Wait: Evaluating and Teaching Agents Under a Live Clock. arXiv:2610.20665 [cs.AI] https://arxiv.org/abs/2610.20665
[166] Ujjawal K. Panchal. 2026. FunDM: Cheap & Label-Free Decision Models from Frozen Language Models. arXiv:2610.17175 [cs.LG] https://arxiv.org/abs/2610.17175
[167] Balamurugan Paramasivam and Sudalai Rajkumar. 2026. RubriX: A Fast, Fine-Tunable Non-Autoregressive Rubric Judge. arXiv:2610.34875 [cs.CL] https://arxiv.org/abs/2610.34875
[168] Demetris Paschalides, George Pallis, and Marios D. Dikaiakos. 2026. To Jev or Not? Evaluating the Accuracy and Efficiency of Structured Decision Models for Hate-Speech Moderation. arXiv:2610.03324 [cs.CL] https://arxiv.org/abs/2610.03324
[169] Chengxuan Pei, Ziyao Wang, Teng Mei, and Zhe Li. 2026. Learning to Formalize: Bridging Open-Ended Workloads and Fast Decision Models. arXiv:2610.36595 [cs.AI] https://arxiv.org/abs/2610.36595
[170] Ismail Pelaseyed and Alan Zabihi. 2026. DFIP: Decision-Focused Inference Path for System One Models. arXiv:2610.36804 [cs.PF] https://arxiv.org/abs/2610.36804
[171] Vasilis Perifanis, Nikolaos Pavlidis, and Symeon Symeonidis. 2026. SeLMRoute: Probabilistic Semantic Evidence for Large Language Model Routing. arXiv:2609.34736 [cs.AI] https://arxiv.org/abs/2609.34736
[172] Perplexity. 2026. *pplx-decider-v1.1-27b Model Card.* https://huggingface.co/perplexity-ai/pplx-decider-v1.1-27b
[173] pngwn. 2026. *pngwn/system-one-qwen3.5-4b-scorer.* Retrieved 2026-09-24 from https://huggingface.co/pngwn/system-one-qwen3.5-4b-scorer
[174] Marco Polignano, Het Darshan Mehta, Pasquale Lops, Ernesto William De Luca, and Giovanni Semeraro. 2026. Decision4Rec: A Jev-Inspired Framework of Decision Models on Knowledge and Active Graphs for Multi-Agent Recommender Systems. arXiv:2610.26035 [cs.AI] https://arxiv.org/abs/2610.26035
[175] Riccardo Porcedda. 2026. Jev thinks "I don't know", but doesn't say it: Introducing Sys1Cal-v1 Dataset for Probability Calibration. arXiv:2609.35342 [cs.AI] https://arxiv.org/abs/2609.35342
[176] Ruizhi Qian, Lei Shi, Tianyu Hu, Bo Yan, Song Wang, and Yu Tian. 2026. SOMA: Continuous Monitoring and Intervention for System Two Reasoning with System One Models. arXiv:2610.26793 [cs.AI] https://arxiv.org/abs/2610.26793
[177] Luozheng Qin, Yuhan Zhu, Changhai Zhou, Qian Qiao, Jun Gao, Yuhua Zhou, Harry Zhang, Xiangyu Zeng, Yuxuan Liu, Yuxin Lu, Kaijie Chen, Andrew Chen, and Pony Ma. 2026. MJev-Spatial: System One Spatial Intelligence via Native Attention Matching. arXiv:2610.22276 [cs.CV] https://arxiv.org/abs/2610.22276
[178] Xukui Qin, Youting Wang, Xinjie He, Ziyang Luo, Runxiong Wu, Yan-Syuan Chen, and Zhongyao Chu. 2026. Decision Readouts for Text-Mediated Video Anomaly Detection: An Exploratory Evaluation of Jev and Qwen. arXiv:2609.34180 [cs.AI] https://arxiv.org/abs/2609.34180
[179] Amir Rafe and Subasish Das. 2026. Benchmarking System One Decision Models against Trained Classifiers and Language Models for Automated Decision Gates. arXiv:2610.00346 [cs.LG] https://arxiv.org/abs/2610.00346
[180] Amir Rafe and Subasish Das. 2026. Calibrated Decisions at Scale: Converting Police Crash Narratives into Probabilistic Crash Variables with a System One Model (Jev). arXiv:2609.24052 [cs.CL] https://arxiv.org/abs/2609.24052
[181] Amir Rafe and Subasish Das. 2026. Counting the Uncounted: Population-Level Surveillance of Documented Pregnancy and Fetal Harm in Police Crash Narratives with a System One Model (Jev). arXiv:2610.00213 [stat.AP] https://arxiv.org/abs/2610.00213
[182] Amir Rafe and Subasish Das. 2026. Estimating Uncoded Crash Factors with Tabular Foundation and System One Models: Kumo Tabular and Jev. arXiv:2610.10321 [stat.AP] https://arxiv.org/abs/2610.10321
[183] Masoud Rahimi, S. M. Matin Alemohammad, Hamid Behroozi, and Mahdi Nouri. 2026. System One Models for Wireless Decision-Making:Applications and Performance Evaluation. arXiv:2610.04345 [eess.SP] https://arxiv.org/

abs/2610.04345

[184] Dushyant Rajput, Nirdesh Chauhan, and Siddharth Kosaraju. 2026. Does a Hosted Decision Model Respect Irrelevant Alternatives? A Pre-Registered Test of Option-Set Dependence in Jev. arXiv:2610.16655 [cs.AI] https://arxiv.org/abs/2610.16655

[185] Delip Rao and Chris Callison-Burch. 2026. Decision Models vs. LLMs as Rubric Judges: Cheaper, Faster, and Wrong in the Same Places. arXiv:2609.29769 [cs.CL] https://arxiv.org/abs/2609.29769

[186] Rauch. 2026. *post on X about Jev latency in Vercel AI Gateway.* Retrieved 2026-09-24 from https://x.com/rauchg/status/2100307962262872105

[187] Simiao Ren, Kidus Zewde, Xingyu Shen, Yuchen Zhou, Dennis Ng, Ankit Raj, Tommy Duong, Yuxin Zhang, and Neo Tiangratanakul. 2026. Open-Jev Judgments on CallScreenBench: Calibrated One-Pass Scam Screening with a Small Language Model. arXiv:2609.23959 [cs.CL] https://arxiv.org/abs/2609.23959

[188] Arshak Rezvani, Sasha Behrouzi, and Ahmad-Reza Sadeghi. 2026. JevVibe: Efficient Classification-Guided Secure Code Generation. arXiv:2609.34963 [cs.CR] https://arxiv.org/abs/2609.34963

[189] Werner Robitza. 2026. JEVQA - Video Quality from Metadata, Bitstream, and Pixel Features with a General-Purpose Decision Model. arXiv:2609.24395 [eess.IV] https://arxiv.org/abs/2609.24395

[190] Yaniv Romano, Matteo Sesia, and Emmanuel J. Candès. 2020. Classification with Valid and Adaptive Coverage. arXiv:2006.02544 [stat.ME] https://arxiv.org/abs/2006.02544

[191] Alden Do Rosario and Kirollos Atef. 2026. Jev-as-a-Judge for RAG Claim Verification: Confidence-Gated Cascading Between a Non-Generative Verifier and a Frontier LLM. arXiv:2610.20634 [cs.CL] https://arxiv.org/abs/2610.20634

[192] Mohamad Yazan Sadoun, Sarah Sharif, and Yaser Mike Banad. 2026. From Probabilities to Decisions: Search and Multi-Teacher Distillation with Jev. arXiv:2610.09188 [cs.AI] https://arxiv.org/abs/2610.09188

[193] Muhammad Atif Saeed, Azka Atiq, Adarsh Kumar, Akhtar Jamil, Uzair Iqbal, and Roland Aydin. 2026. SHIFT-JEV: Certified Abstention and Gain-Gated Continual Adaptation for LLM-Based Decision Models under Distribution Shift. arXiv:2610.34329 [cs.LG] https://arxiv.org/abs/2610.34329

[194] Adib Sakhawat and Syed Rifat Raiyan. 2026. Literal Lock-In: How Test Language Shifts Literal Attraction in Typed Decision Models on Bengali Idioms. arXiv:2610.22526 [cs.CL] https://arxiv.org/abs/2610.22526

[195] Juan S. Santillana. 2026. VX-One: Typed, Calibrated Decision Heads for Real-Time Perimeter Triage. arXiv:2610.30090 [cs.CR] https://arxiv.org/abs/2610.30090

[196] Oleg Sautenkov, Yasheerah Yaqoot, Muhammad Ahsan Mustafa, Grigorii Kalinin, Chih-Yung Wen, and Dzmitry Tsetserukou. 2026. UAV-SwarmAgent: Scalable Multi-UAV Reconnaissance and Task Allocation via Code Generation and Vision-Language Reasoning. arXiv:2610.32559 [cs.RO] https://arxiv.org/abs/2610.32559

[197] Paulo Severo, Silvio E. Quincozes, and Amanda Dias. 2026. Jev-IDS: System One Models for Network Intrusion Detection. arXiv:2610.01079 [cs.CR] https://arxiv.org/abs/2610.01079

[198] Sharath M Shankaranarayana, Davor Runje, and Jan Jannink. 2026. Beyond Answer Confidence: A Controlled Audit of Self-Knowledge in a Black-Box Decision Model. arXiv:2610.01006 [cs.AI] https://arxiv.org/abs/2610.01006

[199] Rahul Sharma, Andrew B. Duncan, Gaétan Marceau Caron, and Sebastian J. Vollmer. 2026. TypedBench: A Benchmark for Calibration, Framing Sensitivity, and Cost in System One Decision Models. arXiv:2610.11392 [cs.AI] https://arxiv.org/abs/2610.11392

[200] Rishabh Sharma and Rishika Lall. 2026. When Does Selection Replace Extraction? A Pre-Registered Test of Agent Memory with a Typed Decision Model. arXiv:2609.34227 [cs.AI] https://arxiv.org/abs/2609.34227

[201] Kai Sheng, Liuyi Wang, Jinlong Li, Haojie Dai, Chengju Liu, and Qijun Chen. 2026. NavJev: Efficient Vision-Language Navigation via Action-Centric Visual Compression and Discriminative Action-Semantic Memory. arXiv:2609.34969 [cs.RO] https://arxiv.org/abs/2609.34969

[202] Xianglong Shi, Shifeng Liu, Sirui Zhao, Shengming Yuan, and Enhong Chen. 2026. Multi-Dimensional Comparative Scale Construction for Efficient Personalized Subjective Judgment in High-Traffic Applications. arXiv:2609.33282 [cs.AI] https://arxiv.org/abs/2609.33282

[203] Dingjie Song, Zhiling Yan, Yuxuan Zhang, and Lichao Sun. 2026. LEV: Thinking Fast and Deep with Looped Decision Models. arXiv:2610.20951 [cs.AI] https://arxiv.org/abs/2610.20951

[204] Dingjie Song, Zhiling Yan, Ziqian Zhang, Yuxuan Zhang, and Lichao Sun. 2026. PremiseCheck: Efficient Fact-Checking of Human and AI Peer Reviews. arXiv:2610.21046 [cs.CL] https://arxiv.org/abs/2610.21046

[205] Mingyang Song, Mao Zheng, Zhiyuan Ma, and Xinpeng Zhou. 2026. Understanding Jev-Style System One Models: Does Structure Reduce Selection Bias? arXiv:2610.35826 [cs.CL] https://arxiv.org/abs/2610.35826

[206] Ankit Sonthalia, Haritz Puerto, Alexander Rubinstein, Martin Gubri, and Seong Joon Oh. 2026. Agent in a Bottle: Can LLM Agents Turn Their Capabilities Into Cheap, Scalable Artifacts? arXiv:2610.08775 [cs.AI] https://arxiv.org/abs/2610.08775

[207] Viknesh Sounderajah, Hutan Ashrafian, Robert M Golub, Shravya Shetty, Jeffrey De Fauw, Lotty Hooft, Karel Moons, Gary Collins, David Moher, Patrick M Bossuyt, Ara Darzi, Alan Karthikesalingam, Alastair K Denniston, Bilal Akhter

Mateen, Daniel Ting, Darren Treanor, Dominic King, Felix Greaves, Jonathan Godwin, Jonathan Pearson-Stuttard, Leanne Harling, Matthew McInnes, Nader Rifai, Nenad Tomasev, Pasha Normahani, Penny Whiting, Ravi Aggarwal, Sebastian Vollmer, Sheraz R Markar, Trishan Panch, and Xiaoxuan Liu. 2021. Developing a reporting guideline for artificial intelligence-centred diagnostic test accuracy studies: the STARD-AI protocol. *BMJ Open* 11, 6 (2021), e047709. doi:10.1136/bmjopen-2020-047709

[208] Viknesh Sounderajah, Hutan Ashrafian, Sherri Rose, Nigam H. Shah, Marzyeh Ghassemi, Robert Golub, Charles E. Kahn, Andre Esteva, Alan Karthikesalingam, Bilal Mateen, Dale Webster, Dan Milea, Daniel Ting, Darren Treanor, Dominic Cushnan, Dominic King, Duncan McPherson, Ben Glocker, Felix Greaves, Leanne Harling, Johan Ordish, Jérémie F. Cohen, Jon Deeks, Mariska Leeflang, Matthew Diamond, Matthew D. F. McInnes, Melissa McCradden, Michael D. Abràmoff, Pasha Normahani, Sheraz R. Markar, Stephanie Chang, Xiaoxuan Liu, Susan Mallett, Shravya Shetty, Alastair Denniston, Gary S. Collins, David Moher, Penny Whiting, Patrick M. Bossuyt, and Ara Darzi. 2021. A quality assessment tool for artificial intelligence-centered diagnostic test accuracy studies: QUADAS-AI. *Nature Medicine* 27, 10 (2021), 1663–1665. doi:10.1038/s41591-021-01517-0

[209] Lev Stambler. 2026. P(Yes): 15× Improvements via Test-Time Scaling of Decision Models. arXiv:2610.25474 [cs.AI] https://arxiv.org/abs/2610.25474

[210] Aaron Steiner, Ralph Peeters, and Christian Bizer. 2026. Entity Matching using Decision Models. arXiv:2610.34626 [cs.CL] https://arxiv.org/abs/2610.34626

[211] Haoyang Su and Weiran Huang. 2026. JevSpawn: Adaptive Agentic Inference through Compositional Action Spaces. arXiv:2610.00437 [cs.AI] https://arxiv.org/abs/2610.00437

[212] Agus Sudjianto and Denis Burakov. 2026. Teacher Supervision, Fixed Representations and Calibration: Exact Risk Calculations for Candidate-Scoring Decision Models. arXiv:2610.26797 [stat.ML] https://arxiv.org/abs/2610.26797

[213] Yasheng Sun, Yanning Dai, Yimeng Chen, Nanbo Li, Firas Laakom, Yifan Xu, Piotr Piękos, Mateusz Ostaszewski, Wenyi Wang, Cheng Luo, Yuhui Wang, and Jürgen Schmidhuber. 2026. JevGPT: Thinking Fast and Slow in Autonomous Research. arXiv:2610.18272 [cs.CL] https://arxiv.org/abs/2610.18272

[214] Yu Sun, Junhao Xu, Jiajia Shi, and Zijin Yang. 2026. Type-Safe Is Not Error-Free: A Constrained Decision Head Follows the Option Name, Not the Rubric Bound to It. arXiv:2609.26758 [cs.AI] https://arxiv.org/abs/2609.26758

[215] Yixin Tan, Chia-Yi Hsu, Jiayang Liu, Chia-Mu Yu, and Rui Wen. 2026. Diagnose Before You Refine: Multi-Dimensional Judge Feedback for Query-Efficient Jailbreak Attacks. arXiv:2610.19971 [cs.CR] https://arxiv.org/abs/2610.19971

[216] Luyao Tang and Cheng Chen. 2026. OmniMed-Jev: Calibrating LVLM Confidence for Trustworthy Medical Multimodal Decisions via System One. arXiv:2610.00381 [cs.LG] https://arxiv.org/abs/2610.00381

[217] Sait Furkan Teke. 2026. HakemBench: A Turkish Benchmark of Typed Decisions. arXiv:2610.02293 [cs.CL] https://arxiv.org/abs/2610.02293

[218] Sait Furkan Teke. 2026. ufakzeka-karar: An Open Turkish Typed-Decision Model with Order-Invariant Option Scoring. arXiv:2610.06744 [cs.CL] https://arxiv.org/abs/2610.06744

[219] Yao Long Teng, Jianguo Huang, Jiayi Cai, Yanchen Deng, and Bo An. 2026. Prism-1: Position- and Rival-Independent Scoring for System One Models. arXiv:2610.22066 [cs.AI] https://arxiv.org/abs/2610.22066

[220] Juan Terven, Diana-Margarita Córdova-Esparza, Julio-Alejandro Romero-González, Edgar Chavez-Urbiola, Juan Irving Vasquez, Julian Andres Ramirez-Bautista, Silvia L. Chaparro-Cárdenas, and Gendry Alfonso-Francia. 2026. Scan or Index? large Evidence Coverage, Answer Quality, and Cost in Long-Document RAG. arXiv:2610.28957 [cs.CL] https://arxiv.org/abs/2610.28957

[221] TheoLeeCJ. 2026. *SemIf-OpenJev: Semantic Ifs from Open Models.* Retrieved 2026-09-24 from https://github.com/TheoLeeCJ/SemIf-OpenJev

[222] Cristian Tommasino and Antonio M. Rinaldi. 2026. PathJev: Decision-Native Vision-Language Modelling for Histopathology. arXiv:2610.32478 [cs.CV] https://arxiv.org/abs/2610.32478

[223] TypeSafe AI. 2026. *AI Primer.* Retrieved 2026-09-24 from https://docs.typesafe.ai/introduction/machine-learning-primer

[224] TypeSafe AI. 2026. *Box.* https://docs.typesafe.ai/primitives/box.md

[225] TypeSafe AI. 2026. *Confidence.* Retrieved 2026-09-24 from https://docs.typesafe.ai/confidence

[226] TypeSafe AI. 2026. *Introducing System One Models & Jev.* Retrieved 2026-09-24 from https://typesafe.ai/blog/introducing-system-one-models-and-jev

[227] TypeSafe AI. 2026. *Introduction.* Retrieved 2026-09-24 from https://docs.typesafe.ai/introduction

[228] TypeSafe AI. 2026. *Jev 1.13 jaggedness.* Retrieved 2026-09-24 from https://docs.typesafe.ai/model-jaggedness/jev-1.13

[229] TypeSafe AI. 2026. *Models.* https://docs.typesafe.ai/models.md

[230] TypeSafe AI. 2026. *Patterns.* Retrieved 2026-09-24 from https://docs.typesafe.ai/patterns

[231] TypeSafe AI. 2026. *TypeSafe AI Home Page.* Retrieved 2026-09-24 from https://typesafe.ai/

[232] TypeSafe AI. 2026. *Workflow evals.* Retrieved 2026-09-24 from https://evals.typesafe.ai/

[233] Naman Vats. 2026. Good Judgment, Bad Advice: Decision-Model Controllers Raise Agent Cost Without Improving Success. arXiv:2610.24649 [cs.AI] https://arxiv.org/abs/2610.24649

[234] Wadhwa. 2026. *OpenDecision: An Open-Source Semantic Decision Engine.* Retrieved 2026-09-24 from https://github.com/deepanwadhwa/OpenDecision

[235] Naoki Wake and Justin Wagle. 2026. SharedKV-BT: Node-Local Typed Decisions for Behavior-Tree Agents. arXiv:2610.07327 [cs.RO] https://arxiv.org/abs/2610.07327

[236] Guangren Wang. 2026. Mnemon: Raw Records, Fast Judgments, Slow Thoughts. arXiv:2609.36059 [cs.CL] https://arxiv.org/abs/2609.36059

[237] Jianing Wang, Youwen Jian, Derong Wang, Jinyang Yu, Qingyi Si, Chuanyu Qin, Yanghua Xiao, and Hongcheng Guo. 2026. UniJev: Separating Accuracy from Calibration in Trimodal System One Decision Models. arXiv:2610.25784 [cs.CV] https://arxiv.org/abs/2610.25784

[238] Jianye Wang, Kexin Zhang, Jiayin Xiong, and Hao Xue. 2026. Benchmarking System One Models for Time-Series Decision Making: A Case Study of Jev. arXiv:2610.33410 [cs.AI] https://arxiv.org/abs/2610.33410

[239] Kaixiang Wang, Zhaijiacheng Zhou, Jiong Lou, and Jie Li. 2026. Jev-LiteMAS: Separating Decisions from Generation in Multi-Agent Workflows. arXiv:2610.21411 [cs.AI] https://arxiv.org/abs/2610.21411

[240] Shang Wang, Tianqing Zhu, Huajie Chen, Jiayang Li, Meng Yang, and Bo Liu. 2026. Hidden Risks of Jev: An Empirical Study of Security, Privacy, and Dual Use. arXiv:2610.04985 [cs.CR] https://arxiv.org/abs/2610.04985

[241] Xiuying Wang, Jiahua Cheng, Shuotian Li, Yufan Cheng, Bowen Deng, Zhexuan Bai, and Yichen Li. 2026. JevSoup: System-One Routing for Training-Free LoRA Composition. arXiv:2609.30922 [cs.AI] https://arxiv.org/abs/2609.30922

[242] Yuxiang Wang, Shengbo Cai, Zhixian Zhao, Yingda Shen, Yuancheng Wang, Xueyao Zhang, Liqiang Zhang, Teddy Sun, Steve Yves, and Zhizheng Wu. 2026. Jarvis: Coordination Deserves a Brain of Its Own in Agentic Interactive Models. arXiv:2610.23804 [cs.SD] https://arxiv.org/abs/2610.23804

[243] Yang Wang, Hanlin Xiao, Yanan Ma, Chenghao Xiao, and Chenghua Lin. 2026. Calibrated Typed Decisions for Entity, Relation, and Event Extraction. arXiv:2610.17113 [cs.CL] https://arxiv.org/abs/2610.17113

[244] Yuhao Wang and Zelin Zang. 2026. ABACUS: Program-Guided Multistep Reasoning over Frozen Judgment Models. arXiv:2610.25963 [cs.AI] https://arxiv.org/abs/2610.25963

[245] Zhiqiang Wang and Yichao Gao. 2026. JEV as a Judge for Agent Trace Security: An Empirical Comparison with Generative LLM Judges. arXiv:2609.34862 [cs.CR] https://arxiv.org/abs/2609.34862

[246] Zhongyin Wang, Zhaoqian Xue, Junting Mu, Haozheng Liu, Ye Yuan, Haolun Wu, and Lingyao Li. 2026. Truncated Reasoning Under a Budget: Evaluating System-1 Models as Decision-Makers. arXiv:2610.25768 [cs.CL] https://arxiv.org/abs/2610.25768

[247] Zhengle Wang, Hanxu Yan, Fuheng Zhao, and Chunwei Liu. 2026. Prune First, Decide Fast: Scalable Semantic Query Processing with JEVDB. arXiv:2610.02046 [cs.DB] https://arxiv.org/abs/2610.02046

[248] Zexiao Wang, Zihao Zhang, Xudong Wang, Pan Wang, Ziyi Ye, Haoyu Zhao, Zuxuan Wu, and Shuicheng Yan. 2026. Chinese-Jev: Bringing System One Model to Chinese-Language Tasks. arXiv:2609.36965 [cs.CL] https://arxiv.org/abs/2609.36965

[249] Yuchuan Weng, Chi Liu, Xin Chen, and Srinivasan Manoharan. 2026. Our Own Jev: Typed Decisions in One Forward Pass, from an In-House Judge to Open LoRA Models. arXiv:2610.29052 [cs.CL] https://arxiv.org/abs/2610.29052

[250] wfzyx. 2026. *wfzyx/von · Hugging Face.* Retrieved 2026-09-24 from https://huggingface.co/wfzyx/von

[251] Penny F. Whiting, Anne W.S. Rutjes, Marie E. Westwood, Susan Mallett, Jonathan J. Deeks, Johannes B. Reitsma, Mariska M.G. Leeflang, Jonathan A.C. Sterne, Patrick M.M. Bossuyt, and the QUADAS-2 Group*. 2011. QUADAS-2: A Revised Tool for the Quality Assessment of Diagnostic Accuracy Studies. *Annals of Internal Medicine* 155, 8 (2011), 529–536. doi:10.7326/0003-4819-155-8-201110180-00009

[252] Robert F. Wolff, Karel G.M. Moons, Richard D. Riley, Penny F. Whiting, Marie Westwood, Gary S. Collins, Johannes B. Reitsma, Jos Kleijnen, Sue Mallett, and for the PROBAST Group†. 2019. PROBAST: A Tool to Assess the Risk of Bias and Applicability of Prediction Model Studies. *Annals of Internal Medicine* 170, 1 (2019), 51–58. doi:10.7326/m18-1376

[253] Chenkai Wu, Xing Chang, and Jun Yan. 2026. Poisoned into Action: Context Attacks on Typed Decision Workflows. arXiv:2610.15537 [cs.CR] https://arxiv.org/abs/2610.15537

[254] Pengying Wu, Zhejia Wen, Kang Ding, Kangjie Zhou, Chunxuan Jiao, Wei Pan, Xiangli Nie, and Chang Liu. 2026. CovNav: Conformal Prediction-Guided Adaptive Inference for Object Goal Navigation. arXiv:2610.27677 [cs.RO] https://arxiv.org/abs/2610.27677

[255] Tiantong Wu and Wei Yang Bryan Lim. 2026. Decision Hijacking: Prompt Injection Attacks on Jev's Typed Probabilistic Decisions. arXiv:2609.28613 [cs.CR] https://arxiv.org/abs/2609.28613

[256] Tiantong Wu and Wei Yang Bryan Lim. 2026. REFLEX with Jev for Efficient Selective Control in LLM Agents. arXiv:2609.26532 [cs.AI] https://arxiv.org/abs/2609.26532

[257] Yuchao Wu. 2026. SAG2: Embedding-Free Multi-Hop Retrieval with BM25 and JEV. arXiv:2610.22588 [cs.CL] https://arxiv.org/abs/2610.22588

[258] Yuanbo Xie, Mingli Zhu, Tianyun Liu, Yingjie Zhang, Haixiao Xiong, and Tingwen Liu. 2026. Lost in the Fallback: How Reliably Do Typed Decision Models Use Fallback Options? arXiv:2610.19856 [cs.CR] https://arxiv.org/abs/2610.19856
[259] Chuhong Xu, Bo Su, Ziyao Chen, Ruiyang Xu, Shimeng Dai, and Xinyu Qiu. 2026. Same-Number Citation Swaps: Stress-Testing Jev as a Financial Evidence Judge. arXiv:2610.08675 [cs.CL] https://arxiv.org/abs/2610.08675
[260] Shenghe Xu and Lifan Mei. 2026. A First Glance at Jev for Network Traffic Classification: Accuracy, Processing Time, and Cost. arXiv:2610.00376 [cs.LG] https://arxiv.org/abs/2610.00376
[261] Zhiwei Xu, Xuyang Liu, Xiaolin Peng, Weixian Deng, Jiabao Gao, Zirui Li, Tian Qiu, Boya Zhou, Wei Jiao, Hai Wan, and Xibin Zhao. 2026. TrustJev: Separating Policy Authority from Untrusted Evidence in LLM-Based Decisions. arXiv:2610.34826 [cs.AI] https://arxiv.org/abs/2610.34826
[262] Zixiang Xu, Zirui Song, Chiyu Zhang, Xiuying Chen, Xi Liu, Xiyang Hu, and Yue Zhao. 2026. JevOut: Natural Context Can Flip Decision Models. arXiv:2609.30243 [cs.CL] https://arxiv.org/abs/2609.30243
[263] Karan Yadav. 2026. Two Uncertainties Are Not One: Disagreement versus Decision-Risk in Cheap Structured Content Moderation. arXiv:2610.33258 [cs.CL] https://arxiv.org/abs/2610.33258
[264] Kakei Yamamoto and So Kuroki. 2026. PRISM: Calibrating Black-Box Judges with Counterfactual Probes. arXiv:2610.18389 [cs.LG] https://arxiv.org/abs/2610.18389
[265] Qiang Yan. 2026. Chinese Decision: A Family of Language Models for Single-Pass Probabilistic Decision-Making. arXiv:2610.23170 [cs.CL] https://arxiv.org/abs/2610.23170
[266] Yu Yan. 2026. JevForest: Path Voting for Budgeted Feature Acquisition. arXiv:2610.10615 [stat.ML] https://arxiv.org/abs/2610.10615
[267] Wang Yang, Xinpeng Li, Yanyan Zhang, Chuang Ma, Shouren Wang, Jianzhe Wei, Liqin Ye, Xiaoran Cai, Mohsen Hariri, Vipin Chaudhary, and Xiaotian Han. 2026. What Can't Jev Decide? Probing the Limits of One-Pass Decision Models. arXiv:2610.24929 [cs.CL] https://arxiv.org/abs/2610.24929
[268] Xianliang Yang, Yapu Zhang, and Li Zhao. 2026. GraphDecisionBench: Benchmarking System One Models on Graph Tasks. arXiv:2610.06354 [cs.AI] https://arxiv.org/abs/2610.06354
[269] Yaodong Yang, Hongyao Tang, Yi Ma, Xingyu Fan, Weixun Wang, Jinpeng Li, and Tianpei Yang. 2026. Code Owns the Simulation, Jev Owns the Evaluation. arXiv:2610.01834 [cs.AI] https://arxiv.org/abs/2610.01834
[270] Yiqu Yang, Qiaoyuan Zheng, Yang Tian, Yu Fan, and Elliott Ash. 2026. TUPLE-Bench: Evaluating and Mitigating Privacy-Utility Trade-offs in Typed Decision Models. arXiv:2610.23668 [cs.CR] https://arxiv.org/abs/2610.23668
[271] Weiwei Ye, Hangchen Liu, and Renhe Jiang. 2026. NumericJev: Jev-like LLM Numerical Decoding with Multiway Decision Trees. arXiv:2609.28587 [stat.ML] https://arxiv.org/abs/2609.28587
[272] Furkan Yilmaz, Habibe Aleyna Tasdemir, and Muhammed Faruk Gozay. 2026. LAVOIR: Teaching a Single-Pass Decision Encoder When and What to Ask with Amortized Value of Information. arXiv:2609.30706 [cs.AI] https://arxiv.org/abs/2609.30706
[273] Liang You, Zhiyin Zhou, Dawei Tang, Chuchu Wu, and Jingzhuo Hu. 2026. Native Probability Outputs for Clinical Triage: An Evaluation of Calibration and Decision Accuracy. arXiv:2610.24692 [cs.LG] https://arxiv.org/abs/2610.24692
[274] Guanxu Yu and Yuhang Yao. 2026. Visual Jev: Accurate and Efficient Decisions from Shared Visual Context. arXiv:2609.25845 [cs.CV] https://arxiv.org/abs/2609.25845
[275] Yundaichuan Zhan, Weishi Wang, Wenbiao Liu, Daniel Dahlmeier, Chengwei Qin, Juncheng Li, Fredrik D. Johansson, and Zhongqi Yue. 2026. Dyad: Extending Large Language Models with Native Typed Decision-Making. arXiv:2609.36116 [cs.LG] https://arxiv.org/abs/2609.36116
[276] Andrew Zhang, Trinh T. L. Vuong, Sophia J. Wagner, Dongmin Bang, Tong Ding, Yuchang Su, Mary Cipperman, Christina S. Chen, Judith Lefkes, Ramin Kahidi, Ming Y. Lu, Caiwei Tian, Tianhao Luo, Jingnan Ma, Rowland Pettit, Long Phi Le, and Faisal Mahmood. 2026. A general-purpose System One decision model for clinical records. arXiv:2610.27099 [cs.AI] https://arxiv.org/abs/2610.27099
[277] Baowen Zhang, Hangting Ye, and Hongyuan Zha. 2026. Typed Decision Models on Tabular Data. arXiv:2610.19536 [cs.CL] https://arxiv.org/abs/2610.19536
[278] Fan Zhang, Yankai Chen, Zhuohan Xie, Yixi Zhou, Sijia Peng, Lei Fan, Xinhua Ji, Cunyuan Zheng, Huangyong Shan, Philip S. Yu, Xue Liu, Yu Chen, Preslav Nakov, and Songwei He. 2026. Same Scores, Different Decisions: Evaluating JEV and Language Models for Legal Document Understanding. arXiv:2609.27678 [cs.CL] https://arxiv.org/abs/2609.27678
[279] Jiamu Zhang, Tianze Yang, Yucheng Shi, Evan Chen, Zixiang Nie, Kelly Wan, Liangjie Hong, Ninghao Liu, and Liang Wu. 2026. AnyJev Technical Report. arXiv:2610.00831 [cs.LG] https://arxiv.org/abs/2610.00831
[280] Jiahao Zhang, Yifan Zhang, and Yu Huang. 2026. JevCoder: When Does Decision Delegation Pay Off in Code Repair? arXiv:2610.19596 [cs.SE] https://arxiv.org/abs/2610.19596
[281] Linghua Zhang. 2026. Jev-Mobile: Jev as an Executor for Mobile GUI Agents. arXiv:2609.30186 [cs.AI] https://arxiv.org/abs/2609.30186
[282] Yiqun Zhang, Peidong Wang, Zihan Wang, and Shi Feng. 2026. Decide, Don't Generate: Competitive Dimensional ABSA with Jev's Typed Decisions. arXiv:2609.35293 [cs.CL] https://arxiv.org/abs/2609.35293

[283] Yazhou Zhang and Junhao Yu. 2026. Emo-Jev: Probabilistic Reasoning for Emotion Classification with Jev. arXiv:2610.08829 [cs.CL] https://arxiv.org/abs/2610.08829

[284] Xinyu Zhao, Qingyun Sun, Ziwei Zhang, Tianchen Zhu, Daqing Li, and Jianxin Li. 2026. One Pretrained Decision Model Is Enough for Training-Free Generalist Graph Anomaly Detection. arXiv:2610.30777 [cs.LG] https://arxiv.org/abs/2610.30777

[285] Bin Zheng and Zheng Chen. 2026. Selective Reasoning for Typed Decision Models: When to Start, Read, and Stop. arXiv:2610.19644 [cs.CL] https://arxiv.org/abs/2610.19644

[286] Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, Hao Zhang, Joseph Gonzalez, and Ion Stoica. 2023. Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena. In *Advances in Neural Information Processing Systems 36*. 46595–46623. arXiv:2306.05685 doi:10.52202/075280-2020

[287] Jike Zhong, Ming Li, and Yuxiang Lai. 2026. When the Right Answer Is Missing: An Arithmetic-Dependent Rejection Bottleneck in Jev. arXiv:2609.39496 [cs.LG] https://arxiv.org/abs/2609.39496

[288] Xunlan Zhou, Xianliang Yang, and Li Zhao. 2026. From Text Decisions to Pixels: An Study of Jev-Style Visual Choice Model. arXiv:2609.29283 [cs.AI] https://arxiv.org/abs/2609.29283

[289] Zihan Zhou, Xinzhe Hu, Hanxu Yang, Liangjian Wen, and Zhao Kang. 2026. Token-Efficient Multi-Agent Collaboration via System One-Guided Computational Division of Labor. arXiv:2610.08155 [cs.MA] https://arxiv.org/abs/2610.08155

[290] Kunlun Zhu, Tao Feng, Xu Han, Heng Wang, Ling Yang, Xiangru Tang, Jiaxuan You, and Heng Ji. 2026. JevAgentHarness: Benchmarking, Deploying and Training Decision Models That Share Control with LLMs. arXiv:2610.21412 [cs.AI] https://arxiv.org/abs/2610.21412

[291] Tong Zhu, Zhe Xu, Zefeng He, Yunkai Chai, Xuyang Hu, Dehong Zheng, Yun Luo, Yafu Li, Qi Zhang, and Yu Cheng. 2026. Intern-Decision: Efficient Multimodal Decision Making with Autoregressive Masked Language Modeling. arXiv:2610.22131 [cs.CL] https://arxiv.org/abs/2610.22131

[292] Yuhan Zhu, Xiangyu Zeng, Qingyi Si, Chenxu Yang, Yifei Li, Luozheng Qin, Junhao Zhou, Dingyu Yao, Jun Zhang, Chuanyu Qin, Zhiqiu Zhang, Yuandong Yang, Yuqi Xu, Tianyu Zhang, Hongcheng Guo, Jiaqi Wang, Nan Duan, and Limin Wang. 2026. VideoJev: System One Model for Video Understanding and Interaction. arXiv:2610.18615 [cs.CV] https://arxiv.org/abs/2610.18615

[293] Xialie Zhuang, Mingcong Lei, Zunhai Su, Ri Liu, Jianjin Li, Peixian Ma, Jia Pan, Ngai Wong, Guanhua Chen, and Chuan-Wei Kuo. 2026. DecisionPivot: A Diagnostic Benchmark for Decision Models in LLM Systems. arXiv:2610.28522 [cs.AI] https://arxiv.org/abs/2610.28522

[294] Xialie Zhuang, Zunhai Su, Jia Pan, Ngai Wong, Guanhua Chen, and Chuan-Wei Kuo. 2026. StartLux-Decision: Auto-Think Decision Models with Reinforcement Learning for Calibrated Deliberative Decisions. arXiv:2610.17309 [cs.CL] https://arxiv.org/abs/2610.17309