F 01R 10Y 776					
未注尺寸公差 GB/T 1804-m					
0.5 ...3	> 3 ...6	> 6 ...30	> 30 ..120	> 120 ..400	> 400 ..1000
± 0.1	± 0.1	± 0.2	± 0.3	± 0.5	± 0.8
未注圆角、倒角公差 GB/T 1804-m					
± 0.2	± 0.5	± 1	± 2	± 2	± 2
未注角度公差（短边尺寸）GB/T 1804-m					
0 ...10	> 10 ...50	> 50 ...120	> 120 ...400	> 400	
± 1°	± 30'	± 20'	± 10'	± 5'	
未注形位公差 GB/T 1184-K					

B-B
测量点为法兰面往下 14.21和28MM
DEPTH OF MEASURING 14.21 AND 28mm
C-C
测量点为Ø 33.88MM平面往上 2MM
MEASURING POINT 2MM FROM PLANE Ø 33.88MM
Y-Y
E-E
2:1
III
20:1
CONNECTING SURFACE FOR HOLDING PLATE VALID FOR BOTH DOMES
托板压板的连接接触面
A-A
I
5:1
CIRCULATION
测量区域
MEASURE AREA
测量面
在标记的宽度区域为功能面
MEASUREMENT PLANE
ON MARKED AREA WIDTH
FUNCTIONAL SURFACE
18:2 0.1 CZ PERMISSIBLE
用于M基准测量
FOR M MEASUREMENT
AB-AB
3D VIEW K
1:1
F..XXXXXX-TT.N01
毛坯零件号(F...776)
II
2:1
PRODUNCTION DATE YY-MM-DD
生产年月日
MEASURING AREA: ZONE w
测量区域：区域 w
MEASURING AREA: ZONE x
测量区域：区域 x
U-U
V-V
H-H
2:1
P-P
MEASUREMENT POSITION
测量位置
R-R
S-S
CLAMPING FACE
REFERENCE FACE
装夹面
参考面
SHAFT CENTER LINE
阀轴中心线
SECTION N-N
MACHINING DEPTH
机加深度
W AXIS
U AXIS
V AXIS

二维码：尺寸：6×6
类型：ECC200，按照规范“ISO/IEC 16022〈2011-02〉执行；
可读性：3级〈B〉按照规范“ISO/IEC15415〈2011-06〉”；
例子：474389XXX00023010100001；
机加壳体零件号后三位：776；
毛胚壳体零件号后三位：777；
供应商代码：XXX；产线号：000；
生产日期23年01月01日；
产线流水号：00001。
MATIX CODE:SIZE 6X6;
TYPE:ECC200,ACCORDING TO NORM 'ISO/IEC 16022(2011-02)':
READABILITY:GRADE 3(B) ACCORDING
"ISO/IEC 15415(2011-06)"
EXAMPLE:474389XXX00023010100001
MACHINING HOUSING PART NUMBER:776
CAST HOUSING PART NUMBER:777
SUPPLIER NUMBER: XXX
LINE NUMBER:000
PRODUCTION DATE:YY-23;MM-01;DD-01
RUNNING NUMBER PER PRODUCTION DAY
(THE NO.00001 HOUSING PRODUCED ON CERTAIN DAY)

测量坐标系UVW的建立规则：

1. 坐标系原点：基准A和基准B的公共轴线与基准面M的交点；
2. W基准线：基准A和基准B的公共轴线；
3. 坐标系的第一平面：平行于法兰端面基准E，并通过W基准线的平面；
4. V基准线：在坐标系的第一平面内，通过坐标系原点，并垂直于W基准线的轴线；
5. U基准线：通过坐标系原点和右手原则，根据V、W基准线建立笛卡尔坐标轴线；

MEASUREMENT COORDINATE SYSTEM:

1. ORIGIN OF COORDINATE SYSTEM:INTERSECTION OF DATUM M AND PUBLIC AXIS OF DATUM A AND DATUM B;
2. AXIS W:PUBLIC AXIS OF DATUM A AND DATUM B;
3. COORDINATE SYSTEM FIRST PLANE:A SURFACE CONTAIN AXIS W AND PARALLEL DATUM E;
4. AXIS V:A AXIS IN THE FIRST PLANE, AND PASS THROUGH ORIGIN OF COORDINATE SYSTEM; AND PERPENDICULAR AIXS W;
5. ASIS U:THROGH THE ORIGIN, BASED RIGHT-HAND PRINCIPLE AND AXES V AND W, ESTABLISH CARTESIAN AXIS;

技术要求

1. 避免含硅物料的使用：
   生产、加工、清洗和包装过程中不得使用含硅的产品及辅助性物料。
2. 测量规范见Y289 P00 017.
3. 若中、英文描述相矛盾，优先使用中文。
4. 未注形位公差参见GB/T 1184-H.
5. 材料符合N2580.
6. *使用成型刀机加

NOTE

1. EXEMPTION FROM SILICONE:
   FOR PRODUCTION; TREATMENT; CLEANING AND PACKAGING NO SILICONE CONTAINING SUBSTANCES OR PRODUCTOIN AUXILIARY MATERIALS MAY BE USED!
2. MEASURING SPECIFICATION SEE Y289 P00 017.
3. IN CASE OF A CONFLICT BETWEEN CHINESE AND THE ENGLISH LANGUAGE THE CHINESE LANGUAGE SHALL TAKE THE PRECEDENCE.
4. GEOMETRICAL TOLERANCE FOR FEATURES WITHOUT INDIVIDUAL TOLERANCE INDICATIONS ACCORDING TO GB/T 1184-H.
5. MATERIALS CORRESPOND TO N2580.
6. *WITH MULTI-STEP TOOL MANUFACTURED.

|F| = 与功能相关的特殊特性/FUNCTION RELEVANT SPECIAL CHARACTERISTICS

|S| = 与安全有关的特性/SAFETY-RELEVANT CHARACTERISTIC

.... |3| = SPC 控制根据使用标准，且要求CPK>1.33
SPC ACCORDING TO APPLICABLE STANDARDS WITH-cpk-RECORD>1.33

.... |5| = PPK(INITIAL SAMPLES CAPABILITY(PPK>1.67).
PPK(初始样品能力指数(PPK>1.67))

Rzmax 40 (✓)

满足GB/T 30512《汽车禁用物质要求》、2000/53/EC、Bosch N2580-1要求
COMPLY WITH THE REGULATIONS: GB/T 30512 ‹REQUIREMENTS FOR PROHIBITED SUBSTANCES ON AUTOMOBILES›, 2000/53/EC AND BOSCH N2580-1

EN 受控
EN CONTROL

详细数据见MISS. DETAILS					UAES 联合汽车电子有限公司 United Automotive Electronic Systems Co., Ltd.			
首次用于1ST APPLICAT. F 01R 00Y 369								
阶段标记STG: S A B					版本VERSION 01		比例SCALE 1:1	重量WEIGHT 302g
				设 计DSN	刘晟辰	260813	材料MATERIAL 5960 990 300 EN AC-AlSi12(Fe)	A0
				制 图DWG	刘晟辰	260813		
				校 对CHK	冯立梅	260813	名称DESIGNATION 机加工壳体 MACHINED HOUSING	
				审 核ADT	冯立梅	260813		
				工 艺MFR	李辉	260813		
				标准化STD	陈光	260813	图号DWG No. F 01R 10Y 776	页次 SHEET 1of1
序号No.	更 改REVISION	分区AREA	更改人DSN	日期DATE	批 准APP 周进	260813		

陆建平yuebai.chen@chinaflx.com