

Venice Municipal Airport (VNC)
120 West Airport Ave
Venice, FL 34285

N69MB

Date 3-1-24

Hobbs 907.1

Test ran engine for operational check of all systems and controls. Jacked aircraft, opened for inspection. Checked and cleaned fuel gascolator. Inspected engine air filter element. Lubed airframe and landing gear. Serviced hydraulic reservoir. Removed heater shroud and pressure checked entire exhaust system.

Removed hinge pin from inner MLG doors and removed doors. Drilled out loose cherry max rivets, opened holes to oversize and installed new CR3242-4-3 rivets. Reinstalled doors.

Removed LH main wheel assy. Disassembled, cleaned and inspected all parts. Reassembled with new Goodyear FCIII s/n 22950220 and new Goodyear tube. Serviced all tires with shop air.

Removed steering horn. Disassembled, cleaned and inspected. Reassembled, lubed and shimmed as required. Reinstalled and checked operation. Performed gear retraction and extension tests, checked over center tensions.

Replaced alternator field switch in instrument panel. Test run engine for operational check of charging system.
.....CONTINUED NEXT PAGE.....

Reattached TKS stall strips on RH and LH wings in accordance with CAV Ice Protection Systems instructions.


Installed new oxygen cylinder and valve assy 895-08077, bottle p/n 4110-200-3 s/n ALT281-55556, and repaired valve p/n 803216-03 s/n 1395. Reference Aerox WO# RS091522-02. Replaced missing system components cable bracket to regulator and copper fill tube from Tee to regulator. Filled bottle to 500 lbs and checked for leaks.

R&R'd tailpipe for turbocharger replacement, see engine log. Inspected all turbo clamps. Tailpipe clamp AD 2023-09-09 Not Applicable as this is a Rivetted clamp, not spot welded. AD 2004-23-17 not applicable to serial number of aircraft, rivetted clamp and proper heat shield etc. already installed at factory. This is the second documented removal and installation of this V-band coupling.

Inspected and tested ELT in accordance with FAR 91.207(d).

Checked AD's to current bi-weekly, all applicable are in compliance at this time, see AD listing. I certify this aircraft has been inspected in accordance with an annual inspection and is airworthy at this time.

IA2809540



Venice Municipal Airport (VNC)
120 West Airport Ave
Venice, FL 34285

N69MB

Date 3-1-24

Hobbs 907.1


Test ran engine for leak and operational check. Drained oil, changed filter. Checked sump suction screen. Serviced engine with Phillips XC 20W50. Compression 1-78, 2-76, 3-77, 4-73, 5-77, 6-79. Checked fuel servo inlet screen.

Removed tailpipe, waste gate, transition tube and #6 exhaust riser to facilitate maintenance. Removed defective turbocharger. Reinstalled overhauled unit p/n 46C19836 s/n FCL2091, reference ATC WO# 43158. Reinstalled wastegate, lubed shaft with mouse milk. Wastegate, transition tube and riser reinstalled with new gaskets 78084, 75845 and 77611. All V-band clamps inspected and reinstalled in CONTINUED NEXT PAGE.....

accordance with V-band clamp Best Practices Guide JASC 8100 and 8120. Tailpipe clamp AD 2023-09-09 Not Applicable as this is a Rivetted clamp, not spot welded. AD 2004-23-17 not applicable to serial number of aircraft, rivetted clamp and proper heat shield etc. already installed at factory. This is the second documented removal and installation of this V-band coupling. Complied with Kelly Aerospace SB no. 23. Turbo oil inlet filled with oil and compressor spun to lubricate bearings. Removed spark plugs and cranked engine until oil pressure came up and oil appeared in oil hose to turbo inlet. Engine run-up satisfactory.

Complied with AD 2015-19-07 by inspection of fuel injector lines and clamps for condition and security. Checked AD's to current bi-weekly, all applicable are in compliance at this time, see AD listing. I certify this engine has been inspected in accordance with an annual inspection and is airworthy at this time.

IA2809540



Venice Municipal Airport (VNC)
120 West Airport Ave
Venice, FL 34285

N69MB

Date 3-1-24

Hobbs 907.1

Test ran engine for operational check of prop and governor. R&R spinner to facilitate maintenance.
Inspected propeller, spinner and backing plates for condition and security.
Checked AD's to current bi-weekly, all applicable are in compliance at this time, see AD listing. I certify
this propeller has been inspected in accordance with an annual inspection and is airworthy at this time.

IA2809540