Android Concurrency: Overview of Java Synchronization & Scheduling Classes




Douglas C. Schmidt <u>d.schmidt@vanderbilt.edu</u> www.dre.vanderbilt.edu/~schmidt

> Institute for Software Integrated Systems Vanderbilt University Nashville, Tennessee, USA



Learning Objectives in this Part of the Module

 Recognize the key Java classes in Android that synchronize & schedule access to critical sections & interactions among threads in concurrent programs



We don't show any Java code yet – that's covered in subsequent parts

- Java provides many synchronization
 - & scheduling classes
 - e.g., java.util.concurrent & java.util.concurrent.lock

package Added in API level 1

java.util.concurrent.locks

Interfaces and classes providing a framework for locking and waiting for conditions that is distinct from built-in synchronization and monitors. The framework permits much greater flexibility in the use of locks and conditions, at the expense of more awkward syntax.

The Lock interface supports locking disciplines that differ in semantics (reentrant, fair, etc), and that can be used in non-block-structured contexts including hand-over-hand and lock reordering algorithms. The main implementation is ReentrantLock.

package Added in API level 1

java.util.concurrent

Utility classes commonly useful in concurrent programming. This package includes a few small standardized extensible frameworks, as well as some classes that provide useful functionality and are otherwise tedious or difficult to implement. Here are brief descriptions of the main components. See also the java.util.concurrent.locks and java.util.concurrent.atomic packages.

- Java provides many synchronization
 & scheduling classes
- We cover a subset of these classes

Java Class	Purpose
ReentrantLock	A reentrant mutual exclusion lock that extends the built-in monitor lock capabilities
ReentrantRead WriteLock	Improves performance when resources are read much more often than written
Semaphore	A non-negative integer that controls the access of multiple threads to a limited number of shared resources
ConditionObject	Block thread(s) until some condition(s) becomes true
CountDownLatch	Allows one or more threads to wait until a set of operations being performed in other threads complete

- Java provides many synchronization
 & scheduling classes
- We cover a subset of these classes

Java Class	Purpose
ReentrantLock	A reentrant mutual exclusion lock that extends the built-in monitor lock capabilities
ReentrantRead WriteLock	Improves performance when resources are read much more often than written
Semaphore	A non-negative integer that controls the access of multiple threads to a limited number of shared resources
ConditionObject	Block thread(s) until some condition(s) becomes true
CountDownLatch	Allows one or more threads to wait until a set of operations being performed in other threads complete

- Java provides many synchronization
 & scheduling classes
- We cover a subset of these classes

Java Class	Purpose	
ReentrantLock	A reentrant mutual exclusion lock that extends the built-in monitor lock capabilities	
ReentrantRead WriteLock	Improves performance when resources are read much more often than written	
Semaphore	A non-negative integer that controls the access of multiple threads to a limited number of shared resources	
ConditionObject	Block thread(s) until some condition(s) becomes true	
CountDownLatch	Allows one or more threads to wait until a set of operations being performed in other threads complete	

- Java provides many synchronization
 & scheduling classes
- We cover a subset of these classes

Java Class	Purpose
ReentrantLock	A reentrant mutual exclusion lock that extends the built-in monitor lock capabilities
ReentrantRead WriteLock	Improves performance when resources are read much more often than written
Semaphore	A non-negative integer that controls the access of multiple threads to a limited number of shared resources
ConditionObject	Block thread(s) until some condition(s) becomes true
CountDownLatch	Allows one or more threads to wait until a set of operations being performed in other threads complete


- Java provides many synchronization
 & scheduling classes
- We cover a subset of these classes

Java Class	Purpose
ReentrantLock	A reentrant mutual exclusion lock that extends the built-in monitor lock capabilities
ReentrantRead WriteLock	Improves performance when resources are read much more often than written
Semaphore	A non-negative integer that controls the access of multiple threads to a limited number of shared resources
ConditionObject	Block thread(s) until some condition(s) becomes true
CountDownLatch	Allows one or more threads to wait until a set of operations being performed in other threads complete


- Java provides many synchronization
 & scheduling classes
- We cover a subset of these classes

Java Class	Purpose
ReentrantLock	A reentrant mutual exclusion lock that extends the built-in monitor lock capabilities
ReentrantRead WriteLock	Improves performance when resources are read much more often than written
Semaphore	A non-negative integer that controls the access of multiple threads to a limited number of shared resources
ConditionObject	Block thread(s) until some condition(s) becomes true
CountDownLatch	Allows one or more threads to wait until a set of operations being performed in other threads complete

- Java provides many synchronization
 & scheduling classes
- We cover a subset of these classes
- These classes are distinct from Java's built-in monitor object mechanisms




- Java provides many synchronization
 & scheduling classes
- We cover a subset of these classes
- These classes are distinct from Java's built-in monitor object mechanisms
 - e.g., the synchronized keyword & the wait(), notify(), & notifyAll() methods




- Java provides many synchronization
 & scheduling classes
- We cover a subset of these classes
- These classes are distinct from Java's built-in monitor object mechanisms
- They are more fundamental & flexible, so we present them first





 The performance of these classes depends on details of the Java virtual machine, operating system, hardware, & program use cases



 The performance of these classes depends on details of the Java virtual machine, operating system, hardware, & program use cases



en.wikipedia.org/wiki/Spinlock has more on spin locks

 The performance of these classes depends on details of the Java virtual machine, operating system, hardware, & program use cases




en.wikipedia.org/wiki/Busy_waiting has more on busy waiting

 The performance of these classes depends on details of the Java virtual machine, operating system, hardware, & program use cases



See docs.oracle.com/javase/tutorial/essential/concurrency/guardmeth.html

 The performance of these classes depends on details of the Java virtual machine, operating system, hardware, & program use cases



 The performance of these classes depends on details of the Java virtual machine, operating system, hardware, & program use cases



"Engineering Concurrent Library Components"

Doug Lea

Day 2 - April 3, 2013 - 1:30 PM - Salon C

phillyemergingtech.com

- The performance of these classes depends on details of the Java virtual machine, operating system, hardware, & program use cases
- Some issues to consider when choosing between classes:



- The performance of these classes depends on details of the Java virtual machine, operating system, hardware, & program use cases
- Some issues to consider when choosing between classes:
 - ReentrantLocks have lower overhead than ReentrantReadWriteLocks



- The performance of these classes depends on details of the Java virtual machine, operating system, hardware, & program use cases
- Some issues to consider when choosing between classes:
 - ReentrantLocks have lower overhead than ReentrantReadWriteLocks
 - But ReentrantReadWriteLocks may enable more concurrency on multi-core or multi-processor hardware



- The performance of these classes depends on details of the Java virtual machine, operating system, hardware, & program use cases
- Some issues to consider when choosing between classes:
 - ReentrantLocks have lower overhead than ReentrantReadWriteLocks
 - ConditionObjects & Semaphores have higher overhead than ReentrantLocks & Reentrant ReadWriteLocks



- The performance of these classes depends on details of the Java virtual machine, operating system, hardware, & program use cases
- Some issues to consider when choosing between classes:
 - ReentrantLocks have lower overhead than ReentrantReadWriteLocks
 - ConditionObjects & Semaphores have higher overhead than ReentrantLocks & Reentrant ReadWriteLocks
 - But they are also more expressive
 & more flexible



- The performance of these classes depends on details of the Java virtual machine, operating system, hardware, & program use cases
- Some issues to consider when choosing between classes:
 - ReentrantLocks have lower overhead than ReentrantReadWriteLocks
 - ConditionObjects & Semaphores have higher overhead than ReentrantLocks & Reentrant ReadWriteLocks
 - But they are also more expressive
 & more flexible
 - e.g., they allow threads to coordinate their interactions



- The performance of these classes depends on details of the Java virtual machine, operating system, hardware, & program use cases
- Some issues to consider when choosing between classes:
 - ReentrantLocks have lower overhead than ReentrantReadWriteLocks
 - ConditionObjects & Semaphores have higher overhead than ReentrantLocks & Reentrant ReadWriteLocks
 - ConditionObjects have a different purpose than other locks



- The performance of these classes depends on details of the Java virtual machine, operating system, hardware, & program use cases
- Some issues to consider when choosing between classes:
 - ReentrantLocks have lower overhead than ReentrantReadWriteLocks
 - ConditionObjects & Semaphores have higher overhead than ReentrantLocks & Reentrant ReadWriteLocks
 - ConditionObjects have a different purpose than other locks
 - A thread uses a lock to keep other threads out of a critical section




- The performance of these classes depends on details of the Java virtual machine, operating system, hardware, & program use cases
- Some issues to consider when choosing between classes:
 - ReentrantLocks have lower overhead than ReentrantReadWriteLocks
 - ConditionObjects & Semaphores have higher overhead than ReentrantLocks & Reentrant ReadWriteLocks
 - ConditionObjects have a different purpose than other locks
 - A thread uses a lock to keep other threads out of a critical section
 - A thread uses a ConditionObject to keep itself out of a critical section until it can make forward progress





 All these Java synchronization & scheduling classes are used throughout Android



Download the Android source code from source.android.com


 All these Java synchronization & scheduling classes are used throughout Android


 Concurrent programs use these classes for several reasons







- All these Java synchronization & scheduling classes are used throughout Android
- Concurrent programs use these classes for several reasons
 - Protect against corruption due to race conditions





- All these Java synchronization & scheduling classes are used throughout Android
- Concurrent programs use these classes for several reasons
 - Protect against corruption due to race conditions
 - Schedule & control the order in which threads execute





```
% java PingPong
Ready...Set...Go!
Ping!(1)
Pong!(1)
Ping!(2)
Pong!(2)
Ping!(3)
Pong!(3)
Ping!(4)
Pong!(4)
Ping!(5)
Pong!(5)
Ping!(6)
Pong!(6)
Ping!(7)
Pong!(7)
Ping!(8)
Pong!(8)
Ping!(9)
Pong!(9)
Ping!(10)
Pong!(10)
Done!
```

All these Java synchronization & scheduling

classes are used throughout Android

 Concurrent programs use these classes for several reasons

 We devote more time to Java synchronization & scheduling mechanisms than to Java threading mechanisms



Thread coverage



Synchronization & scheduling coverage

All these Java synchronization & scheduling

classes are used throughout Android


- Concurrent programs use these classes for several reasons
- We devote more time to Java synchronization & scheduling mechanisms than to Java threading mechanisms
 - Complexity arises largely from coordinating interactions of multiple entities that run concurrently



 All these Java synchronization & scheduling classes are used throughout Android

- Concurrent programs use these classes for several reasons
- We devote more time to Java synchronization & scheduling mechanisms than to Java threading mechanisms
- Each Java synchronization & scheduling class is covered systematically

Java Class	Purpose
Reentrant Lock	A reentrant mutual exclusion lock that extends the built-in monitor lock capabilities
Reentrant Read WriteLock	Improves performance when resources are read much more often than written
Semaphore	A non-negative integer that controls the access of multiple threads to a limited number of shared resources
Condition Object	Block thread(s) until some condition(s) becomes true
CountDown Latch	Allows one or more threads to wait until a set of operations being performed in other threads complete



- We devote more time to Java synchronization & scheduling mechanisms than to Java threading mechanisms
- Each Java synchronization & scheduling class is covered systematically

