

Coding_challenge_7

Pankaj Gaonkar

2025-04-03

Contents

1. 4 pts. Read in the data called “PlantEmergence.csv” using a relative file path and load the following libraries. tidyverse, lme4, emmeans, multcomp, and multcompView. Turn the Treatment , DaysAfterPlanting and Rep into factors using the function as.factor	2
2. 5 pts. Fit a linear model to predict Emergence using Treatment and DaysAfterPlanting along with the interaction. Provide the summary of the linear model and ANOVA results.	4
3. 5 pts. Based on the results of the linear model in question 2, do you need to fit the interaction term? Provide a simplified linear model without the interaction term but still testing both main effects. Provide the summary and ANOVA results. Then, interpret the intercept and the coefficient for Treatment 2.	5
Answer:	5
4. 5 pts. Calculate the least square means for Treatment using the emmeans package and perform a Tukey separation with the compact letter display using the cld function. Interpret the results.	7
Answer:	7
5. 4 pts. The provided function lets you dynamically add a linear model plus one factor from that model and plots a bar chart with letters denoting treatment differences. Use this model to generate the plot shown below. Explain the significance of the letters.	8
Answer:	8
Function defined (from assignment)	8
6. 2 pts. Generate the gfm .md file along with a .html, .docx, or .pdf. Commit, and push the .md file to github and turn in the .html, .docx, or .pdf to Canvas. Provide me a link here to your github.	10

1. 4 pts. Read in the data called “PlantEmergence.csv” using a relative file path and load the following libraries. tidyverse, lme4, emmeans, multcomp, and multcompView. Turn the Treatment , DaysAfterPlanting and Rep into factors using the function as.factor

```
STANDTreatment <- as.factor(STANDTreatment) # example shown here.
```

```
#load libraries
#Load packages
library(tidyverse)
```

```
## Warning: package 'ggplot2' was built under R version 4.4.3
```

```
## Warning: package 'purrr' was built under R version 4.4.2
```

```
## Warning: package 'lubridate' was built under R version 4.4.2
```

```
## -- Attaching core tidyverse packages ----- tidyverse 2.0.0 --
```

```
## v dplyr      1.1.4      v readr      2.1.5
```

```
## v forcats    1.0.0      v stringr    1.5.1
```

```
## v ggplot2     3.5.1      v tibble     3.2.1
```

```
## v lubridate  1.9.4      v tidyr      1.3.1
```

```
## v purrr      1.0.4
```

```
## -- Conflicts ----- tidyverse_conflicts() --
```

```
## x dplyr::filter() masks stats::filter()
```

```
## x dplyr::lag()     masks stats::lag()
```

```
## i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to become errors
```

```
library(lme4)
```

```
## Warning: package 'lme4' was built under R version 4.4.2
```

```
## Loading required package: Matrix
```

```
## Warning: package 'Matrix' was built under R version 4.4.2
```

```
##
```

```
## Attaching package: 'Matrix'
```

```
##
```

```
## The following objects are masked from 'package:tidyr':
```

```
##
```

```
##      expand, pack, unpack
```

```
#install.packages("multcompView")
```

```
library(multcomp)
```

```
## Warning: package 'multcomp' was built under R version 4.4.2
```

```
## Loading required package: mvtnorm
```

```
## Warning: package 'mvtnorm' was built under R version 4.4.2
```

```
## Loading required package: survival
```

```
## Loading required package: TH.data
```

```
## Warning: package 'TH.data' was built under R version 4.4.2
```

```
## Loading required package: MASS
```

```
##
```

```
## Attaching package: 'MASS'
```

```
##
```

```
## The following object is masked from 'package:dplyr':
```

```
##
```

```
##      select
```

```
##
```

```
##
```

```
## Attaching package: 'TH.data'
```

```
##
```

```
## The following object is masked from 'package:MASS':
```

```
##
```

```
##      geyser
```

```
#install.packages("emmeans")
```

```
library(emmeans)
```

```
## Warning: package 'emmeans' was built under R version 4.4.3
```

```
## Welcome to emmeans.
```

```
## Caution: You lose important information if you filter this package's results.
```

```
## See '? untidy'
```

```
#load data
```

```
datum <- read.csv("PlantEmergence.csv")
```

```
head(datum)
```

```
##   Plot Treatment Rep Emergence DatePlanted DateCounted DaysAfterPlanting
## 1  101         1   1    180.5    9-May-22    16-May-22             7
## 2  102         2   1     54.5    9-May-22    16-May-22             7
## 3  103         3   1    195.0    9-May-22    16-May-22             7
## 4  104         4   1    198.5    9-May-22    16-May-22             7
## 5  105         5   1    202.0    9-May-22    16-May-22             7
## 6  106         6   1    184.0    9-May-22    16-May-22             7
```

```
#Turn the Treatment , DaysAfterPlanting and Rep into factors using the function as.factor
```

```
datum$Treatment <- as.factor(datum$Treatment)
```

```
datum$DaysAfterPlanting <- as.factor(datum$DaysAfterPlanting)
```

```
datum$Rep <- as.factor(datum$Rep)
```

2. 5 pts. Fit a linear model to predict Emergence using Treatment and DaysAfterPlanting along with the interaction. Provide the summary of the linear model and ANOVA results.

```
model1 <- lm(Emergence ~ Treatment + DaysAfterPlanting + Treatment:DaysAfterPlanting, data = datum)
summary(model1)
```

```
##
## Call:
## lm(formula = Emergence ~ Treatment + DaysAfterPlanting + Treatment:DaysAfterPlanting,
##     data = datum)
##
## Residuals:
```

	Min	1Q	Median	3Q	Max
	-21.250	-6.062	-0.875	6.750	21.875

```
##
## Coefficients:
```

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	1.823e+02	5.324e+00	34.229	<2e-16 ***
Treatment2	-1.365e+02	7.530e+00	-18.128	<2e-16 ***
Treatment3	1.112e+01	7.530e+00	1.477	0.142
Treatment4	2.500e+00	7.530e+00	0.332	0.741
Treatment5	8.750e+00	7.530e+00	1.162	0.248
Treatment6	7.000e+00	7.530e+00	0.930	0.355
Treatment7	-1.250e-01	7.530e+00	-0.017	0.987
Treatment8	9.125e+00	7.530e+00	1.212	0.228
Treatment9	2.375e+00	7.530e+00	0.315	0.753
DaysAfterPlanting14	1.000e+01	7.530e+00	1.328	0.187
DaysAfterPlanting21	1.062e+01	7.530e+00	1.411	0.161
DaysAfterPlanting28	1.100e+01	7.530e+00	1.461	0.147
Treatment2:DaysAfterPlanting14	1.625e+00	1.065e+01	0.153	0.879
Treatment3:DaysAfterPlanting14	-2.625e+00	1.065e+01	-0.247	0.806
Treatment4:DaysAfterPlanting14	-6.250e-01	1.065e+01	-0.059	0.953
Treatment5:DaysAfterPlanting14	2.500e+00	1.065e+01	0.235	0.815
Treatment6:DaysAfterPlanting14	1.000e+00	1.065e+01	0.094	0.925
Treatment7:DaysAfterPlanting14	-2.500e+00	1.065e+01	-0.235	0.815
Treatment8:DaysAfterPlanting14	-2.500e+00	1.065e+01	-0.235	0.815
Treatment9:DaysAfterPlanting14	6.250e-01	1.065e+01	0.059	0.953
Treatment2:DaysAfterPlanting21	3.500e+00	1.065e+01	0.329	0.743
Treatment3:DaysAfterPlanting21	-1.000e+00	1.065e+01	-0.094	0.925
Treatment4:DaysAfterPlanting21	1.500e+00	1.065e+01	0.141	0.888
Treatment5:DaysAfterPlanting21	2.875e+00	1.065e+01	0.270	0.788
Treatment6:DaysAfterPlanting21	4.125e+00	1.065e+01	0.387	0.699
Treatment7:DaysAfterPlanting21	-2.125e+00	1.065e+01	-0.200	0.842
Treatment8:DaysAfterPlanting21	-1.500e+00	1.065e+01	-0.141	0.888
Treatment9:DaysAfterPlanting21	-1.250e+00	1.065e+01	-0.117	0.907
Treatment2:DaysAfterPlanting28	2.750e+00	1.065e+01	0.258	0.797
Treatment3:DaysAfterPlanting28	-1.875e+00	1.065e+01	-0.176	0.861
Treatment4:DaysAfterPlanting28	3.264e-13	1.065e+01	0.000	1.000
Treatment5:DaysAfterPlanting28	2.500e+00	1.065e+01	0.235	0.815
Treatment6:DaysAfterPlanting28	2.125e+00	1.065e+01	0.200	0.842

```
## Treatment7:DaysAfterPlanting28 -3.625e+00 1.065e+01 -0.340 0.734
## Treatment8:DaysAfterPlanting28 -1.500e+00 1.065e+01 -0.141 0.888
## Treatment9:DaysAfterPlanting28 -8.750e-01 1.065e+01 -0.082 0.935
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 10.65 on 108 degrees of freedom
## Multiple R-squared:  0.9585, Adjusted R-squared:  0.945
## F-statistic: 71.21 on 35 and 108 DF,  p-value: < 2.2e-16
```

```
anova(model1)
```

```
## Analysis of Variance Table
##
## Response: Emergence
##
##           Df Sum Sq Mean Sq F value    Pr(>F)
## Treatment      8 279366    34921 307.9516 < 2.2e-16 ***
## DaysAfterPlanting 3   3116     1039   9.1603 1.877e-05 ***
## Treatment:DaysAfterPlanting 24    142        6   0.0522      1
## Residuals     108 12247      113
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

#OR

```
summary(aov(Emergence ~ Treatment + DaysAfterPlanting + Treatment:DaysAfterPlanting, data = datum))
```

```
##           Df Sum Sq Mean Sq F value    Pr(>F)
## Treatment      8 279366    34921 307.952 < 2e-16 ***
## DaysAfterPlanting 3   3116     1039   9.160 1.88e-05 ***
## Treatment:DaysAfterPlanting 24    142        6   0.052      1
## Residuals     108 12247      113
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

3. 5 pts. Based on the results of the linear model in question 2, do you need to fit the interaction term? Provide a simplified linear model without the interaction term but still testing both main effects. Provide the summary and ANOVA results. Then, interpret the intercept and the coefficient for Treatment 2.

Answer:

None of the interactions were significant so we can exclude the interactions. Lets consider with-interaction as 'complicated model'(model 1) and without-interaction as 'simple model'(model 2). So we will proceed with simple model for our analysis.

Interpretation:

- Intercept is showing that Emergence value is 182.163 units when other independent variables (Treatment, DaysAfterPlanting) are considered to be zero.
- Treatment 2: Plant that received treatment 2 had 134.531 units (SE +/- 3.42) lesser emergence. ($p < 2e-16$)

```
model2 <- lm(Emergence ~ Treatment + DaysAfterPlanting, data = datum)
summary(model2)
```

```
##
## Call:
## lm(formula = Emergence ~ Treatment + DaysAfterPlanting, data = datum)
##
## Residuals:
```

	Min	1Q	Median	3Q	Max
	-21.1632	-6.1536	-0.8542	6.1823	21.3958

```
##
## Coefficients:
```

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	182.163	2.797	65.136	< 2e-16 ***
Treatment2	-134.531	3.425	-39.277	< 2e-16 ***
Treatment3	9.750	3.425	2.847	0.00513 **
Treatment4	2.719	3.425	0.794	0.42876
Treatment5	10.719	3.425	3.129	0.00216 **
Treatment6	8.812	3.425	2.573	0.01119 *
Treatment7	-2.188	3.425	-0.639	0.52416
Treatment8	7.750	3.425	2.263	0.02529 *
Treatment9	2.000	3.425	0.584	0.56028
DaysAfterPlanting14	9.722	2.283	4.258	3.89e-05 ***
DaysAfterPlanting21	11.306	2.283	4.951	2.21e-06 ***
DaysAfterPlanting28	10.944	2.283	4.793	4.36e-06 ***

```
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 9.688 on 132 degrees of freedom
## Multiple R-squared:  0.958, Adjusted R-squared:  0.9545
## F-statistic: 273.6 on 11 and 132 DF, p-value: < 2.2e-16
```

```
anova(model2)
```

```
## Analysis of Variance Table
##
## Response: Emergence
```

	Df	Sum Sq	Mean Sq	F value	Pr(>F)
Treatment	8	279366	34921	372.070	< 2.2e-16 ***
DaysAfterPlanting	3	3116	1039	11.068	1.575e-06 ***
Residuals	132	12389	94		

```
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

4. 5 pts. Calculate the least square means for Treatment using the emmeans package and perform a Tukey separation with the compact letter display using the cld function. Interpret the results.

Answer:

Interpretation Based on multiple comparison we found that statistically significant differences were only observed between Treatment 2 and other treatment groups. There was lower Emergence in group 2 compared to other groups.

```
lsmeans <- emmeans(model2, ~ Treatment) # estimate lsmeans
Results_lsmeans <- cld(lsmeans, alpha = 0.05, reversed = TRUE, details = TRUE)
Results_lsmeans
```

```
## $emmeans
## Treatment emmean SE df lower.CL upper.CL .group
## 5          200.9 2.42 132    196.1    205.7    1
## 3          199.9 2.42 132    195.1    204.7    1
## 6          199.0 2.42 132    194.2    203.8    1
## 8          197.9 2.42 132    193.1    202.7   12
## 4          192.9 2.42 132    188.1    197.7   12
## 9          192.2 2.42 132    187.4    196.9   12
## 1          190.2 2.42 132    185.4    194.9   12
## 7          188.0 2.42 132    183.2    192.8    2
## 2           55.6 2.42 132     50.8     60.4    3
##
## Results are averaged over the levels of: DaysAfterPlanting
## Confidence level used: 0.95
## P value adjustment: tukey method for comparing a family of 9 estimates
## significance level used: alpha = 0.05
## NOTE: If two or more means share the same grouping symbol,
##       then we cannot show them to be different.
##       But we also did not show them to be the same.
##
## $comparisons
## contrast estimate SE df t.ratio p.value
## Treatment7 - Treatment2 132.344 3.43 132 38.638 <.0001
## Treatment1 - Treatment2 134.531 3.43 132 39.277 <.0001
## Treatment1 - Treatment7  2.188 3.43 132  0.639 0.9993
## Treatment9 - Treatment2 136.531 3.43 132 39.861 <.0001
## Treatment9 - Treatment7  4.188 3.43 132  1.223 0.9502
## Treatment9 - Treatment1  2.000 3.43 132  0.584 0.9997
## Treatment4 - Treatment2 137.250 3.43 132 40.071 <.0001
## Treatment4 - Treatment7  4.906 3.43 132  1.432 0.8832
## Treatment4 - Treatment1  2.719 3.43 132  0.794 0.9969
## Treatment4 - Treatment9  0.719 3.43 132  0.210 1.0000
## Treatment8 - Treatment2 142.281 3.43 132 41.540 <.0001
## Treatment8 - Treatment7  9.938 3.43 132  2.901 0.0978
## Treatment8 - Treatment1  7.750 3.43 132  2.263 0.3724
## Treatment8 - Treatment9  5.750 3.43 132  1.679 0.7583
## Treatment8 - Treatment4  5.031 3.43 132  1.469 0.8678
## Treatment6 - Treatment2 143.344 3.43 132 41.850 <.0001
```

```
## Treatment6 - Treatment7    11.000 3.43 132    3.212 0.0425
## Treatment6 - Treatment1     8.812 3.43 132    2.573 0.2083
## Treatment6 - Treatment9     6.812 3.43 132    1.989 0.5538
## Treatment6 - Treatment4     6.094 3.43 132    1.779 0.6957
## Treatment6 - Treatment8     1.062 3.43 132    0.310 1.0000
## Treatment3 - Treatment2   144.281 3.43 132   42.124 <.0001
## Treatment3 - Treatment7    11.938 3.43 132    3.485 0.0187
## Treatment3 - Treatment1     9.750 3.43 132    2.847 0.1120
## Treatment3 - Treatment9     7.750 3.43 132    2.263 0.3724
## Treatment3 - Treatment4     7.031 3.43 132    2.053 0.5099
## Treatment3 - Treatment8     2.000 3.43 132    0.584 0.9997
## Treatment3 - Treatment6     0.938 3.43 132    0.274 1.0000
## Treatment5 - Treatment2   145.250 3.43 132   42.406 <.0001
## Treatment5 - Treatment7    12.906 3.43 132    3.768 0.0074
## Treatment5 - Treatment1    10.719 3.43 132    3.129 0.0535
## Treatment5 - Treatment9     8.719 3.43 132    2.545 0.2204
## Treatment5 - Treatment4     8.000 3.43 132    2.336 0.3288
## Treatment5 - Treatment8     2.969 3.43 132    0.867 0.9943
## Treatment5 - Treatment6     1.906 3.43 132    0.557 0.9998
## Treatment5 - Treatment3     0.969 3.43 132    0.283 1.0000
##
## Results are averaged over the levels of: DaysAfterPlanting
## P value adjustment: tukey method for comparing a family of 9 estimates
```

5. 4 pts. The provided function lets you dynamically add a linear model plus one factor from that model and plots a bar chart with letters denoting treatment differences. Use this model to generate the plot shown below. Explain the significance of the letters.

Answer:

**Significance of letters: if the letters are same then there is no statically significant difference between groups. If letters are different between two groups then they are statistically significantly different from each other.

Example: Treament 2 (letter-c) versus Treamet 9 (letter- ab) – They are statically significantly different from each other.

Treatment 8 (letter-ab) versus Treament 9 (letter- ab) - There is NO statiically significant difference between them

Function defined (from assignment)

```
plot_cldbars_onefactor <- function(lm_model, factor) {
  data <- lm_model$model
  variables <- colnames(lm_model$model)
  dependent_var <- variables[1]
  independent_var <- variables[2:length(variables)]
```



```

lsmeans <- emmeans(lm_model, as.formula(paste("~", factor))) # estimate lsmeans
Results_lsmeans <- cld(lsmeans, alpha = 0.05, reversed = TRUE, details = TRUE, Letters = letters) # c

# Extracting the letters for the bars
sig.diff.letters <- data.frame(Results_lsmeans$emmeans[,1],
                              str_trim(Results_lsmeans$emmeans[,7]))
colnames(sig.diff.letters) <- c(factor, "Letters")

# for plotting with letters from significance test
ave_stand2 <- lm_model$model %>%
  group_by(!sym(factor)) %>%
  dplyr::summarize(
    ave.emerge = mean(.data[[dependent_var]], na.rm = TRUE),
    se = sd(.data[[dependent_var]]) / sqrt(n())
  ) %>%
  left_join(sig.diff.letters, by = factor) %>%
  mutate(letter_position = ave.emerge + 10 * se)

plot <- ggplot(data, aes(x = !! sym(factor), y = !! sym(dependent_var))) +
  stat_summary(fun = mean, geom = "bar") +
  stat_summary(fun.data = mean_se, geom = "errorbar", width = 0.5) +
  ylab("Number of emerged plants") +
  geom_jitter(width = 0.02, alpha = 0.5) +
  geom_text(data = ave_stand2, aes(label = Letters, y = letter_position), size = 5) +
  xlab(as.character(factor)) +
  theme_classic()


return(plot)
}

```

```

plot_cldbars_onefactor(model2, "Treatment") #I realized functions can make life easier

```



6. 2 pts. Generate the gfm .md file along with a .html, .docx, or .pdf. Commit, and push the .md file to github and turn in the .html, .docx, or .pdf to Canvas. Provide me a link here to your github.

Coding_challenge_7 Folder