

R documentation

of all in ‘man’

August 13, 2026

R topics documented:

audit_model_registry	1
available_provider_models	2
available_scales	3
build_scale_prompt	3
compare_training_iterations	3
extract_article_text	4
extract_pdf_text	4
parse_scale_scores	5
propose_prompt_revision	5
resolve_prompt	6
run_article	7
run_dataset	8
run_llm	9
strip_references_section	10
structure_article_markdown	11
Index	12

audit_model_registry	<i>Audit every registered scale and model prompt.</i>
----------------------	---

Description

Audit every registered scale and model prompt.

Usage

```
audit_model_registry(  
  registry_dir = NULL,  
  output_dir = NULL,  
  apply_unifications = FALSE  
)
```

Arguments

- registry_dir Optional registry root. Defaults to bundled prompts.
- output_dir Optional directory for audit and unification CSV reports.
- apply_unifications Move exact duplicate prompt folders to a timestamped backup directory. Defaults to FALSE.

Value

A list with checks, duplicate_groups, unification_plan, and backup_dir.

available_provider_models
<i>List models currently available to the configured provider.</i>

Description

List models currently available to the configured provider.

Usage

```
available_provider_models(  
  provider,  
  api_key = NULL,  
  timeout = 30,  
  supported_only = TRUE  
)
```

Arguments

- provider "gemini", "openai", "claude", or an alias.
- api_key Optional in-memory API key. Otherwise the provider's usual environment variables are used.
- timeout Request timeout in seconds.
- supported_only For Gemini, keep models supporting generateContent.

Value

A data frame with provider, model id, display name, and raw metadata.

available_scales	<i>List scales available in the local prompt registry.</i>
------------------	--

Description

List scales available in the local prompt registry.

Usage

```
available_scales(registry_dir = NULL)
```

Arguments

registry_dir	Optional registry root. Defaults to bundled package prompts.
--------------	--

build_scale_prompt	<i>Append article text to a scale prompt.</i>
--------------------	---

Description

Append article text to a scale prompt.

Usage

```
build_scale_prompt(prompt_text, article_text)
```

Arguments

prompt_text	Scale prompt text.
article_text	Extracted article text.

compare_training_iterations	<i>Compare local prompt-training iterations with a reviewed answer key.</i>
-----------------------------	---

Description

Each iteration directory must contain one timestamped *_Consensus_Report.csv produced by [run_dataset\(\)](#). The answer key must contain an ID column and columns named IT01, IT02, etc., or another IT-prefixed item scheme.

Usage

```
compare_training_iterations(ideal_csv, iterations_dir)
```

Arguments

ideal_csv	Path to the reviewed answer-key CSV.
iterations_dir	Directory containing iteration_1, iteration_2, etc.

Value

A list with comparison (item-level rows) and summary (accuracy by iteration).

extract_article_text	<i>Extract text from a supported article file.</i>
----------------------	--

Description

Extract text from a supported article file.

Usage

```
extract_article_text(  
    file_path,  
    filetype = "auto",  
    strip_references = TRUE,  
    tables_advanced = TRUE,  
    cache_markdown = TRUE  
)
```

Arguments

file_path	Path to a .pdf, .txt, or .md article file.
filetype	One of "auto", "pdf", "txt", or "md".
strip_references	Whether to remove the reference section before sending text to an LLM.

Details

Files are read from the local filesystem. PDF, TXT, and Markdown inputs are supported.

extract_pdf_text	<i>Extract text from a PDF article.</i>
------------------	---

Description

Extract text from a PDF article.

Usage

```
extract_pdf_text(  
    pdf_path,  
    strip_references = TRUE,  
    tables_advanced = TRUE,  
    cache_markdown = TRUE  
)
```

Arguments

pdf_path	Path to a PDF article.
strip_references	Whether to remove the reference section before sending text to an LLM.

parse_scale_scores	<i>Parse scale item scores from an LLM response.</i>
--------------------	--

Description

Parse scale item scores from an LLM response.

Usage

```
parse_scale_scores(text, items = 1:10, metadata = NULL)
```

Arguments

text	LLM response text.
items	Numeric item ids to parse. Defaults to 1:10.
metadata	Optional resolved scale metadata.

propose_prompt_revision	<i>Propose a revised prompt from the results of a training iteration.</i>
-------------------------	---

Description

This function does not modify files, execute articles, or replace the current prompt. It asks the selected provider to propose a complete revised prompt using the current prompt, item-level comparison, and audit logs from the latest iteration.

Usage

```
propose_prompt_revision(
  prompt_path,
  comparison,
  reason_files,
  provider = "gemini",
  model = "gemini-3.6-flash",
  api_key = NULL,
  project_id = NULL,
  temperature = 0,
  timeout = 300,
  output_path = NULL
)
```

Arguments

prompt_path	Path to the current prompt.md.
comparison	A comparison data frame, or path to comparison.csv.
reason_files	Character vector of audit-log or evidence files.
provider	LLM provider used to generate the proposal.
model	Model used to generate the proposal.
api_key	Optional in-memory API key.
project_id	Optional OpenAI project identifier.
temperature	Generation temperature. Defaults to 0.
timeout	Request timeout in seconds.
output_path	Optional path where the proposal is written as Markdown.

Value

A list with the proposed prompt, source paths, provider, and model.

resolve_prompt	<i>Resolve the best prompt registered for a scale and requested model.</i>
----------------	--

Description

Resolution order is exact model, same model family token, same numeric version, generic, and finally closest available folder name by edit distance.

Usage

```
resolve_prompt(scale, model, provider = NULL, registry_dir = NULL)
```

Arguments

scale	Scale name, for example "mqs".
model	Requested model name.
provider	Optional provider. When supplied, <provider>-generic is preferred after model-specific matching.
registry_dir	Optional registry root. Defaults to bundled package prompts.

Value

A list containing prompt path, model folder, match strategy, and metadata.

run_article

*Run one article file through a registered scale prompt.***Description**

Run one article file through a registered scale prompt.

Usage

```
run_article(
  article_path = NULL,
  scale = "mqs",
  provider = "gemini",
  model = "gemini-3.6-flash",
  registry_dir = NULL,
  filetype = "auto",
  strip_references = TRUE,
  tables_advanced = TRUE,
  cache_markdown = TRUE,
  items = NULL,
  output_dir = NULL,
  temperature = 0,
  top_p = 0.1,
  timeout = 300,
  api_key = NULL,
  project_id = NULL,
  pdf_path = NULL,
  max_retries = 3,
  retry_wait_seconds = 1,
  retry_backoff = 2,
  rate_limit_seconds = 0,
  reference_scores = NULL,
  validation_mode = c("free", "reference"),
  write_evidence = TRUE
)
```

Arguments

article_path	Article path. Supported extensions are .pdf, .txt, and .md.
scale	Scale name. Defaults to "mqs".
provider	LLM provider. Defaults to "gemini".
model	Requested model. Defaults to "gemini-3.6-flash".
registry_dir	Optional prompt registry root.
filetype	One of "auto", "pdf", "txt", or "md".
strip_references	Whether to remove references before the LLM call.
items	Item ids to parse. Defaults to 1:10.
output_dir	Optional output directory for an audit log.

temperature, top_p, timeout, api_key, project_id	Provider call settings.
pdf_path	Backward-compatible alias for article_path.
max_retries, retry_wait_seconds, retry_backoff, rate_limit_seconds	Reliability settings.
reference_scores	Optional reviewed scores for reference validation.
validation_mode	Either "free" or "reference".
write_evidence	Whether to write the per-article evidence CSV. Dataset workflows set this to FALSE because they write one consolidated report.

run_dataset	<i>Run article files in a directory through a registered scale prompt.</i>
-------------	--

Description

Existing *_AuditLog.txt files larger than 100 bytes are reused and skipped.

Usage

```
run_dataset(
  articles_dir,
  scale = "mqs",
  provider = "gemini",
  model = "gemini-3.6-flash",
  output_dir,
  registry_dir = NULL,
  filetype = "auto",
  strip_references = TRUE,
  tables_advanced = TRUE,
  cache_markdown = TRUE,
  max_articles = 0,
  items = NULL,
  temperature = 0,
  top_p = 0.1,
  timeout = 300,
  api_key = NULL,
  project_id = NULL,
  max_retries = 3,
  retry_wait_seconds = 1,
  retry_backoff = 2,
  rate_limit_seconds = 0,
  reference_csv = NULL,
  validation_mode = c("free", "reference")
)
```

Arguments

articles_dir	Directory containing articles.
scale	Scale name.
provider	LLM provider.
model	Requested model.
output_dir	Directory where audit logs and CSV are written.
registry_dir	Optional prompt registry root.
filetype	One of "auto", "pdf", "txt", or "md".
strip_references, items, temperature, top_p, timeout, api_key, project_id	Provider and parsing settings.
max_articles	Maximum pending PDFs to process. 0 means all.
max_retries, retry_wait_seconds, retry_backoff, rate_limit_seconds	Reliability settings.
reference_csv	Optional reviewed-score CSV.
validation_mode	Either "free" or "reference".

Value

A list containing the timestamped run directory, consensus report, consolidated evidence report, and errors when any occurred.

run_llm	<i>Call a supported LLM provider with user-owned API credentials.</i>
---------	---

Description

Call a supported LLM provider with user-owned API credentials.

Usage

```
run_llm(
    prompt,
    provider = "gemini",
    model = "gemini-3.6-flash",
    temperature = 0,
    top_p = 0.1,
    timeout = 300,
    api_key = NULL,
    project_id = NULL,
    max_retries = 3,
    retry_wait_seconds = 1,
    retry_backoff = 2,
    rate_limit_seconds = 0,
    response_schema = NULL
)
```

Arguments

prompt	Prompt text to send.
provider	"gemini", "openai", "chatgpt", "claude", or "anthropic".
model	Model id.
temperature	Sampling temperature.
top_p	Gemini nucleus-sampling value; ignored by OpenAI and Claude.
timeout	Maximum duration in seconds for each individual API attempt.
api_key	Optional in-memory API key.
project_id	Optional OpenAI project id.
max_retries	Maximum retries for transient failures.
retry_wait_seconds	Initial exponential-backoff delay.
retry_backoff	Multiplicative exponential-backoff factor.
rate_limit_seconds	Minimum delay between requests in this R process.
response_schema	Optional registered response schema.

`strip_references_section`*Remove reference sections from extracted article text.*

Description

Remove reference sections from extracted article text.

Usage

```
strip_references_section(article_text)
```

Arguments

article_text	Full extracted text.
--------------	----------------------

`structure_article_markdown`*Convert extracted text to Markdown headings, lists, and tables.*

Description

Convert extracted text to Markdown headings, lists, and tables.

Usage

```
structure_article_markdown(article_text, tables_advanced = TRUE)
```

Arguments

`article_text` Extracted article text.

`tables_advanced`
Whether to convert table-like blocks.

Index

`audit_model_registry`, [1](#)
`available_provider_models`, [2](#)
`available_scales`, [3](#)

`build_scale_prompt`, [3](#)

`compare_training_iterations`, [3](#)

`extract_article_text`, [4](#)
`extract_pdf_text`, [4](#)

`parse_scale_scores`, [5](#)
`propose_prompt_revision`, [5](#)

`resolve_prompt`, [6](#)
`run_article`, [7](#)
`run_dataset`, [8](#)
`run_dataset()`, [3](#)
`run_llm`, [9](#)

`strip_references_section`, [10](#)
`structure_article_markdown`, [11](#)