

Module: Problem 2 - Printing Out the User's Guess

This module implements a helper routine used in word-guessing games (e.g., Hangman). The core function builds a visual representation of the secret word, revealing the letters that have already been guessed and masking the rest with underscores.

Functions

`getGuessedWord(secretWord, lettersGuessed)`

Description

Constructs a string that shows which characters of `secretWord` have been guessed.

For each character in `secretWord`, the function appends the character itself if it appears in the `lettersGuessed` list; otherwise it appends an underscore (`'_'`). The resulting string reflects the current state of the game board.

Parameters

- `secretWord` (*str*): The target word the user is trying to guess.
- `lettersGuessed` (*list of str*): A collection of letters (or strings) that have been guessed so far. Membership is tested **exactly**; only single-character strings that match a character in `secretWord` will be revealed.

Returns

- *str*: A string of the same length as `secretWord` composed of correctly guessed letters and underscores for unknown letters.

Examples

```
# Example 1 - no guessed letters match
result = getGuessedWord('hello', ['apple', 'banana', 'cherry'])
# → '_____'

# Example 2 - one matching letter
result = getGuessedWord('test', ['a', 'b', 'c', 'd', 'e'])
# → '_e__'

# Example 3 - empty secret word
result = getGuessedWord('', [])
# → ''

# Example 4 - guessed entry is a whole word, not a single letter
result = getGuessedWord('a', ['hello'])
# → '_ '

# Example 5 - list contains only multi-character strings
result = getGuessedWord('abcdef', ['test', 'word', 'example', 'data', 'value'])
# → '_____'
```

Edge Cases / Notes - The function does **not** validate that items in `lettersGuessed` are single characters; any string longer than one character will never match a single character in `secretWord`. - An empty `secretWord`

yields an empty string regardless of `lettersGuessed` . - Duplicate entries in `lettersGuessed` have no additional effect because membership testing is idempotent. - The function assumes iterable inputs; passing non-iterable types will raise a `TypeError` .