

Prajit. M. V
192521088

[Signature]

SIMATS ENGINEERING ASSESSMENT TOOL 1

COURSE NAME: CSA07 COURSE CODE: Computer Networks

COURSE OUTCOME COVERED

CO1: Apply the functions of OSI layer in enabling reliable data transmission across networks. (BL2, BL3)

Assessment Tool Weightage: 40%

Description about the assessment tool:

Short-answer questions effectively measure conceptual understanding, logical reasoning, and the ability to apply theoretical knowledge without requiring lengthy descriptive responses. This assessment method is also efficient for evaluating multiple OSI-related concepts within a limited time while ensuring objective and consistent evaluation.

A31

Short Answer Test

1. A company needs to transfer a **150 MB** design file from a client computer to a remote server over a network with a bandwidth of **50 Mbps**. The Transport Layer divides the file into **1500-byte segments**, while the Data Link Layer encapsulates each segment into frames by adding **40 bytes of header and trailer**. Calculate the total number of segments and frames transmitted, the total transmission overhead introduced by the Data Link Layer, and estimate the total transmission time (ignoring propagation delay). Explain how the Transport and Data Link layers ensure reliable communication.

2. A Transport Layer protocol uses a **sliding window size of 6 frames**. Each frame carries **1024 bytes** of user data. If the sender transmits **48 frames**, calculate the number of transmission windows required. If one frame in every

window is lost and must be retransmitted, determine the total number of retransmissions. Explain how flow control improves communication efficiency.

3. A **12,000-byte** IP packet is transmitted through a router where the Maximum Transmission Unit (MTU) is **1500 bytes**. Assuming each fragment requires a **20-byte IP header**, calculate the total number of fragments created and the total header overhead introduced. Explain how the Network Layer ensures successful delivery of fragmented packets to the destination.

4. A Transport Layer protocol uses a **sliding window size of 6 frames**. Each frame carries **1024 bytes** of user data. If the sender transmits **48 frames**, calculate the number of transmission windows required. If one frame in every window is lost and must be retransmitted, determine the total number of retransmissions. Explain how flow control improves communication efficiency.

5. A multimedia application transfers a **600 MB** video file. The Session Layer inserts a synchronization checkpoint after every **60 MB** of transmitted data. During transmission, a failure occurs after **390 MB** has been transferred. Determine the number of checkpoints created before failure and calculate the amount of data that must be retransmitted after recovery. Explain the importance of synchronization in the Session Layer.

6. Before transmission, the Presentation Layer compresses a **900 MB** file by **40%**. The compressed data is encrypted, adding **5% overhead** to the compressed size. Calculate the compressed file size, the encrypted file size, and the total percentage reduction compared to the original file. Explain how the Presentation Layer improves transmission efficiency and security.

7. An FTP application transfers **3 GB** of data over a network with an effective throughput of **120 Mbps**. The Application Layer divides the data into requests of **3 MB** each. Calculate the total number of requests generated and estimate the total transmission time in seconds. Discuss how the Application Layer provides reliable services to users.

8. A packet experiences the following processing delays at different OSI layers: Application Layer = **4 ms**, Transport Layer = **3 ms**, Network Layer = **5 ms**, Data Link Layer = **2 ms**, and Physical Layer = **1 ms**. The propagation delay is **18 ms**, and the transmission delay is **12 ms**. Calculate the total end-to-end delay experienced by the packet and explain how each layer contributes to the communication process.

9. A network transfers **80 MB** of useful data using frames of **1600 bytes**, where each frame contains **80 bytes** of protocol overhead added by different OSI layers. Calculate the total number of frames required, the total overhead transmitted, and the transmission efficiency as a percentage. Explain how protocol overhead affects network performance.

10. A hospital transfers a patient's medical record of **240 MB** through an IoT-enabled healthcare network. The Presentation Layer compresses the data by **30%**, the Transport Layer divides the compressed data into **1400-byte segments**, and the Data Link Layer adds **60 bytes** of overhead to each frame. Calculate the compressed file size, the total number of segments transmitted, the total protocol overhead introduced, and the final amount of data transmitted across the Physical Layer. Explain how multiple OSI layers work together to ensure secure and reliable communication.

Given

- File size = 150 MB = 150,000,000 bytes
- segment size = 1500 bytes
- Data link layer overhead per frame = 40 bytes
- Bandwidth = 50 Mbps = 50,000,000 bits/s

1. Number of transport Layer segments

$$\text{Number of segments} = \frac{150,000,000}{1500} = 100,000$$

2. Number of Data Link Layer

Each segment is encapsulated into one frame

$$\text{Number of frames} = 100,000$$

3. Total Data link Layer frames

overhead per frame = 40 bytes

$$100,000 \times 40 = 4,000,000 \text{ bytes}$$

4. Total data transmitted

$$1500 + 40 = 1540 \text{ bytes}$$

Total transmitted data:

$$100,000 \times 1540 = 154,000,000$$

convert to bits

$$154,000,000 \times 8 = 1,232,000,000 \text{ bits}$$

5. Transmission time

$$\text{Bandwidth} = 50 \text{ Mbps} = 50,000,000 \text{ bits/s}$$

$$\text{Transmission time} = \frac{1,232,000,000}{50,000,000} = 24.64 \text{ seconds.}$$

2)

- Sliding window size = 6 frames
- Data per frame = 1024 bytes
- Total frames to transmit = 48 frames
- Number of transmission windows

$$\text{Number of windows} = \frac{48}{6} = 8$$

2. Total number of Retransmissions

- one frame is lost in every window
- Number of windows = 8

$$\text{Retransmission} = 8 \times 1 = 8$$

3. Flow control and communication Efficiency

- preventing the sender from transmitting data faster
- Avoiding receiver buffer overflow and data loss

Given :

- IP packet size = 12,000 bytes
- MTU = 1500 bytes
- IP header per fragment = 20 bytes

1. Maximum Data per fragment

Each fragment must include a 20-byte IP header,

So the maximum payload is

$$1500 - 20 = 1480 \text{ bytes}$$

2. Number of Fragments

$$\frac{12000}{1480} = 8.11 \approx 9$$

3. Total Header overhead

Each fragment has a 20 byte IP header

$$9 \times 20 = 180 \text{ bytes}$$

4)

Given :

- sliding window size = 6 frames
- Data per frame = 1024 bytes
- Total frames transmitted = 48 frames

1. number of transmission windows

$$\text{Number of windows} = \frac{48}{6} = 8$$

2. Total number of Retransmissions

- one frame is lost in each window
- Number of windows = 8

$$\text{Total Retransmissions} = 8 \times 1 = 8$$

3. Flow control and communication efficiency

by :

- preventing the sender from sending data faster than the receiver can process.
- Avoiding receiver buffer overflow and packet loss.
- Reducing unnecessary retransmission.

5) Given :

- video file size = 600 MB
- checkpoint interval = 60 MB
- Failure occurs after = 390 MB

1. Number of checkpoints created Before failure

checkpoints are inserted every 60 MB :

- 60 MB $\rightarrow$ checkpoint 1
- 120 MB $\rightarrow$ checkpoint 2
- 180 MB $\rightarrow$ checkpoint 3
- 240 MB $\rightarrow$ checkpoint 4

- 300 MB $\rightarrow$ checkpoint 5
- 360 MB $\rightarrow$ checkpoint 6


2. Data to be Retransmitted after recovery

- Last successful checkpoint = 360 MB
- Failure occurs at 390 MB

Data sent after the last checkpoint :

$$390 - 360 = 30 \text{ MB}$$

RS



Q₁ Q₂ Q₃ Q₄ Q₅ Q₆ Q₇ Q₈ Q₉ Q₁₀
 L3L2L1 L3L2L1 L3L2L1 L3L2L1 L3L2L1 L3L2L1 L3L2L1 L3L2L1 L3L2L1 L3L2L1

Understanding 2.25 2 2.25 2 2.25 — — — — —

Explanation 1 1.75 1.75 1 1.75 — — —

clarity 20% 1 1 0.5 1 1 — — —
 4.25 4.75 4.5 4 4

21.5 / 50

RUBRICS FOR CALCULATION

Criteria	Weightage	Level 4 – Exemplary	Level 3 – Proficient	Level 2 – Developing	Level 1 – Beginning
Understanding of Concepts	25%	Demonstrates a thorough, accurate understanding of concepts	Good understanding with minor gaps	Basic understanding with some misconceptions	Poor understanding; major misconceptions
Explanation	25%	Detailed, well-explained answers with relevant examples	Clear explanation with adequate details	Limited explanation; lacks depth	Poor or unclear explanation
Application	20%	Effectively applies concepts with strong analytical ability	Applies concepts with minor errors	Limited application with weak analysis	No application or incorrect analysis
Organization	15%	Well-structured answers with logical flow and coherence	Organized with minor issues in flow	Basic structure, lacks clarity	Poor organization, incoherent answers
Accuracy	10%	Completely accurate and covers all required points	Mostly accurate with minor omissions	Partially correct with missing points	Incorrect answers with major gaps
Clarity	5%	Clear, neat, professional presentation	Understandable with minor issues	Limited clarity, readability issues	Poorly written, difficult to understand