


A series







Fans - A series

Specifications: The Fan is of large volume flow design. The impeller is designed to give excellent performance characteristic with large airflow and low static pressure development.

Impellers: Flaktwoods aerofoil selection glass filled polypropylene impeller suited to more highly corrosive environments. The impellers are balanced according to ISO 1940

Motor: Manufactured to supply AS1359 high efficiency IE2 motor enclosure to feature IP55 protection. winding insulation are to incorporate thermal class 155 as standard.

Plate: Steel plate with powder coating finish. Impeller/motor assembly to be supported by a powder coated / galvanised steel. Motor side guards to be fit as standards.



Model	Mounting style	Discharge type	Impeller size	Pressure Range	Airflow Range	SWL Range	Power Range
100 series	Wall mounted	Horizontal discharge	—	0 - 218 Pa	0 - 1640 L/s	—	—
AFD-2200X	—	—	560 mm	0 - 183 Pa	0 - 1490 L/s	—	—
Fan-1	—	—	—	0 - 299 Pa	24 - 1450 L/s	—	—

A series - 100 series



Description

Rosenberg AC-Axial fans in combination with voltage-controllable external-rotor motor form a very compact, efficient and optimized fan unit. They impress with low installation depth and low noise level. Fast start-up is ensured because of well-integrated components.

Applications

Air heaters / Heat pumps / Condensers / Cooling units / Evaporators / Chillers

Sizes

400, 450, 500, 560, 630 mm diameter

Fan performance

The fan is of low noise and high static efficiency design. The impeller is designed to give excellent performance characteristic with high static pressure development without stall.

MAIN

Mounting style	Wall mounted
Discharge type	Horizontal discharge

IMPELLER


Size	—
Type	Backward curve
Material	—
Motor finish	—

MOTOR






Type	—
IP Rating	—
Insulation	—
Power	—
Power Supply	—
Speed	—
FLC	—
Capacitor	—
Control	—
Protection	—

FAN


Plate	—
Weight	—
Max. Temp	—



Speed (rpm)	Peak Pressure (Pa)	Peak Power (kW)	Running Frequency (Hz)	Sound Pressure Level (dB) @ 3 meters	Sound (Hz) Power Level (dB) SWL re 1pw							
					63	125	250	500	1k	2k	4k	8k
1200												
1800												
2400												



A series - AFD-2200X



Description

Rosenberg AC-Axial fans in combination with voltage-controllable external-rotor motor form a very compact, efficient and optimized fan unit. They impress with low installation depth and low noise level. Fast start-up is ensured because of well-integrated components.

Applications

Air heaters / Heat pumps / Condensers / Cooling units / Evaporators / Chillers

Sizes

Not provided.

Fan performance

Not provided.

IMPELLER


Size	560 mm
Type	Backward curve
Material	Steel
Motor finish	Powder coat

MOTOR


Type	IE2
IP Rating	55
Insulation	Class 155
Power	3 kW
Power Supply	400V/3PH/50Hz
Speed	1415 RPM
FLC	—
Capacitor	6.4 A
Control	Variable Speed Drive
Protection	Thermistor


FAN

Plate	Galvanised steel
Weight	139 kg
Max. Temp	50 °C



Speed (rpm)	Peak Pressure (Pa)	Peak Power (kW)	Running Frequency (Hz)	Sound Pressure Level (dB) @ 3 meters	Sound (Hz) Power Level (dB) SWL re 1pw							
					63	125	250	500	1k	2k	4k	8k
1000												
1500												
2100												





Description

Desc1 test

Applications

Desc2 test

Sizes

Desc3 test

Fan performance

Not provided.

IMPELLER


Size	—
Type	Backward curve
Material	—
Motor finish	—

MOTOR

Type	—
IP Rating	—
Insulation	—
Power	—
Power Supply	—
Speed	—
FLC	—
Capacitor	—
Control	—
Protection	—

FAN

Plate	—
Weight	—
Max. Temp	—



Speed (rpm)	Peak Pressure (Pa)	Peak Power (kW)	Running Frequency (Hz)	Sound Pressure Level (dB) @ 3 meters	Sound (Hz) Power Level (dB) SWL re 1pw							
					63	125	250	500	1k	2k	4k	8k
1000												
1500												
2000												

No product images available.

No product image available.