

SERIES OVERVIEW

Template Series Default
Products 3
Graph rule Highest and lowest line from each product

DESCRIPTION1

The Fan is of large volume flow design. The impeller is designed to give excellent performance characteristic with large airflow and low static pressure development.

DESCRIPTION4


Steel plate with powder coating finish. Impeller/motor assembly to be supported by a powder coated / galvanised steel. Motor side guards to be fit as standards.

Description2


Flaktwoods aerofoil selection glass filled polypropylene impeller suited to more highly corrosive environments. The impellers are balanced according to ISO 1940

Description3

Manufactured to supply AS1359 high efficiency IE2 motor enclosure to feature IP55 protection. winding insulation are to incorporate thermal class 155 as standard.



Model	Main: Mounting style	Main: Discharge type	Impeller: Size	Impeller: Type	Impeller: Material	Impeller: Motor finish
100 series	Wall mounted	Horizontal discharge	—	Backward curve	—	—
AFD-2200X	—	—	560 mm	Backward curve	Steel	Powder coat
Fan-1	—	—	—	Backward curve	—	—



PRODUCT TYPE


Fan

PRODUCTS

3

GRAPH RULE

Highest and lowest line from each product



Description

Description:
Rosenberg AC-Axial fans in combination with voltage-controllable external-rotor motor form a very compact, efficient and optimized fan unit. They impress with low installation depth and low noise level. Fast start-up is ensured because of well-integrated components.


Applications:
Air heaters / Heat pumps / Condensers / Cooling units / Evaporators / Chillers Sizes: 400, 450, 500, 560, 630mm diameter Fan Performance: The fan is of low noise and high static efficiency design. The impeller is designed to give excellent performance characteristic with high static pressure development without stall.

Applications
Not provided.

IMPELLER	
Size	—
Type	Backward curve
Material	—
Motor finish	—


MOTOR	
Type	—
IP Rating	—
Insulation	—
Power	—
Power Supply	—
Speed	—
FLC	—
Capacitor	—
Control	—
Protection	—

FAN	
Plate	—
Weight	—
Max. Temp	—



Fan Map Points

RPM Line	Point	Airflow	Pressure
1200	1	72	94
1200	2	293	96
1200	3	800	80
1200	4	958	50
1200	5	1106	0
1800	1	83	158
1800	2	516	158
1800	3	900	139
1800	4	1186	72
1800	5	1455	0
2400	1	96	218
2400	2	676	216
2400	3	1000	178
2400	4	1310	101
2400	5	1640	0




Online

FAN

AFD-2200X

Fan - A series



DESCRIPTION1

Rosenberg AC-Axial fans in combination with voltage-controllable external-rotor motor form a very compact, efficient and optimized fan unit. They impress with low installation depth and low noise level. Fast start-up is ensured because of well-integrated components.

DESCRIPTION2

Air heaters / Heat pumps /
Condensers / Cooling units /
Evaporators / Chillers

DESCRIPTION3

Not provided.

COMMENTS

Not provided.

GROUPED SPECIFICATIONS

Impeller

Size	560 mm
Type	Backward curve
Material	Steel
Motor finish	Powder coat

Motor

Type	IE2
IP Rating	55
Insulation	Class 155
Power	3 kW
Power Supply	400V/3PH/50Hz
Speed	1415 RPM
FLC	—

Capacitor
Control
Protection


6.4 A
Variable Speed Drive
Thermistor

Fan


Plate
Weight
Max. Temp

Galvanised steel
139 kg
50 °C


PRODUCT GRAPH



PRODUCT IMAGES



Primary image



Description

Desc1 test

Applications

Desc2 test

IMPELLER


- Size
- TypeBackward curve
- Material
- Motor finish

MOTOR

- Type
- IP Rating
- Insulation
- Power
- Power Supply
- Speed
- FLC
- Capacitor
- Control
- Protection

FAN

- Plate
- Weight
- Max. Temp



Fan Map Points

RPM Line	Point	Airflow	Pressure
1000	1	24	134
1000	2	306	121
1000	3	557	100
1000	4	772	72
1000	5	1081	22
1000	6	1160	0
1500	1	38	222
1500	2	537	218
1500	3	781	197
1500	4	1091	140
1500	5	1179	107
1500	6	1336	0
2000	1	42	299
2000	2	614	297
2000	3	977	275
2000	4	1116	244
2000	5	1238	204
2000	6	1450	0

