


Online

FAN

AFD-2200X

Fan - A series



DESCRIPTION1

Rosenberg AC-Axial fans in combination with voltage-controllable external-rotor motor form a very compact, efficient and optimized fan unit. They impress with low installation depth and low noise level. Fast start-up is ensured because of well-integrated components.

DESCRIPTION2

Air heaters / Heat pumps /
Condensers / Cooling units /
Evaporators / Chillers

DESCRIPTION3

Not provided.

COMMENTS

Not provided.

GROUPED SPECIFICATIONS

Impeller

Size	560 mm
Type	Backward curve
Material	Steel
Motor finish	Powder coat

Motor

Type	IE2
IP Rating	55
Insulation	Class 155
Power	3 kW
Power Supply	400V/3PH/50Hz
Speed	1415 RPM
FLC	—
Capacitor	6.4 A
Control	Variable Speed Drive


Protection	Thermistor
Fan	
Plate	Galvanised steel
Weight	139 kg
Max. Temp	50 °C

FAN ACOUSTIC TABLE


Speed (rpm)	Peak Pressure (Pa)	Peak Power (kW)	Runni ng Freque ncy	Sound Pressure Level dB @ 3 meters	Sound Power Level SWL dB re 1pw							
					63	125	250	500	1k	2k	4k	8k

2100
1500
1000

PRODUCT GRAPH



PRODUCT IMAGES



Primary image