
RS PRO Aluminium/Steel Dome Head Blind Rivet, 4 mm Diameter x 25 mm long

Supplier Part Number: OJASD4025



FEATURES

- **Aluminium Body:** Offers lightweight yet durable fastening.
- **Steel Mandrel:** Ensures strong and secure installation.
- **Dome Head:** Provides a neat and smooth finish.
- **4 mm Diameter:** Suitable for a range of applications.
- **25 mm Length:** Accommodates thicker materials.
- **Trivalent Chromate Finish:** Enhances corrosion resistance.

RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

The RS PRO Aluminium Blind Rivet is designed for secure fastening in applications where access is only available from one side. With a robust aluminium body and steel mandrel, it provides reliable performance in various industrial settings. Ideal for joining materials with a grip range between 18 mm and 20 mm.

General Specifications

Finish	Clear, Trivalent Chromate, Zinc
Head Type	Dome
Product Type	Blind Rivet
Rivet Type	Blind
Fixing Hole Diameter	4.1 mm
Mandrel Material	Steel
Maximum Grip	20 mm
Minimum Grip	18 mm


Mechanical Specifications


Head Diameter	8 mm
Rivet Body Material	Aluminium
Rivet Diameter	4 mm
Rivet Length	25 mm
Shear Strength	1200 N
Tensile Strength	1600 N

Approvals

Standards/Approvals	DIN 7337, ISO 9001:2015, ISO 14001:2015, ISO 14589, ISO TS 16949:2009

Technical Diagrams





Nominal Diameter mm	Body Length mm	Grip Range Min mm	Grip Range Max mm	Hole Size mm	Flange Diameter mm	Flange Thickness mm	Nom. Mandrel Diameter mm	Min Mandrel Length mm	Shear Strength N	Tensile Strength N	Box Quantity
D	L				dk	K	dm	L2			
4.0	6.0	1.0	2.0	4.1	8.0	1.0	2.10	27.0	1200	1600	1000
	8.0	2.0	4.0	4.1	8.0	1.0	2.10	27.0	1200	1600	750
	10.0	4.0	6.0	4.1	8.0	1.0	2.10	27.0	1200	1600	500
	12.0	6.0	8.0	4.1	8.0	1.0	2.10	27.0	1200	1600	500
	14.0	8.0	10.0	4.1	8.0	1.0	2.10	27.0	1200	1600	500
	16.0	10.0	12.0	4.1	8.0	1.0	2.10	27.0	1200	1600	500
	18.0	12.0	14.0	4.1	8.0	1.0	2.10	27.0	1200	1600	500
	20.0	14.0	15.5	4.1	8.0	1.0	2.10	27.0	1200	1600	500
	25.0	18.0	20.0	4.1	8.0	1.0	2.10	27.0	1200	1600	350
	30.0	21.5	26.0	4.1	8.0	1.0	2.10	27.0	1200	1600	250
4.8	6.0	1.0	2.0	4.9	9.5	1.1	2.70	28.0	1700	2250	500
	8.0	2.0	3.5	4.9	9.5	1.1	2.70	28.0	1700	2250	500
	10.0	3.5	5.5	4.9	9.5	1.1	2.70	28.0	1700	2250	500
	12.0	5.5	7.5	4.9	9.5	1.1	2.70	28.0	1700	2250	500
	14.0	7.5	9.5	4.9	9.5	1.1	2.70	28.0	1700	2250	500
	16.0	9.0	11.0	4.9	9.5	1.1	2.70	28.0	1700	2250	500
	18.0	11.0	13.0	4.9	9.5	1.1	2.70	28.0	1700	2250	250
	20.0	13.0	15.0	4.9	9.5	1.1	2.70	28.0	1700	2250	250
	22.0	15.0	17.0	4.9	9.5	1.1	2.70	28.0	1700	2250	250