
RS PRO Aluminium/Steel Dome Head Blind Rivet, 3.2 mm Diameter x 12 mm long

Supplier Part Number: OJASDP3212



FEATURES

- **Dome Head:** Provides a neat and low-profile finish.
- **Aluminium Body:** Offers corrosion resistance and lightweight properties.
- **Steel Mandrel:** Ensures high tensile strength and secure fastening.
- **3.2 mm Rivet Diameter:** Suitable for a range of applications.
- **12 mm Rivet Length:** Accommodates materials with a grip range of 3 mm to 5 mm.
- **Trivalent Chromate Finish:** Enhances corrosion resistance.
- **Compliance with DIN 7337:** Meets industry standards for quality and reliability.

RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

RS PRO offers a high-quality aluminium blind rivet designed for secure fastening in a variety of applications. With a dome head and steel mandrel, this rivet provides reliable performance and ease of installation. Ideal for use where access is only available from one side, it ensures a strong and durable connection.

General Specifications

Finish	Clear, Trivalent Chromate, Zinc
Head Type	Dome
Product Type	Blind Rivet
Rivet Type	Blind
Fixing Hole Diameter	3.7 mm
Mandrel Material	Steel
Maximum Grip	5 mm
Minimum Grip	3 mm


Mechanical Specifications


Head Diameter	6 mm
Rivet Body Material	Aluminium
Rivet Diameter	3.2 mm
Rivet Length	12 mm
Shear Strength	765 N
Tensile Strength	700 N

Approvals

Standards/Approvals	DIN 7337, ISO 9001:2015, ISO 14001:2015, ISO 14589, ISO TS 16949:2009

Technical Diagrams





Nominal Diameter mm	Body Length mm	Grip Range Min mm	Grip Range Max mm	Hole Size mm	Flange Diameter mm	Flange Thickness mm	Nom. Mandrel Diameter mm	Min Mandrel Length mm	Shear Strength N	Tensile Strength N	Box Quantity
D	L				dk	K	dm	L2			
3.2	8.0	0.5	1.0	3.5-3.7	6.0	0.8	1.90	26.0	765	700	1000
	10.0	1.0	3.0	3.5-3.7	6.0	0.8	1.90	26.0	765	700	1000
	12.0	3.0	5.0	3.5-3.7	6.0	0.8	1.90	26.0	765	700	1000
	16.0	7.0	9.0	3.5-3.7	6.0	0.8	1.90	26.0	765	700	800
4.0	10.0	1.5	4.5	3.5-3.7	6.0	0.8	1.90	26.0	765	700	800
	12.0	4.0	6.5	4.3-4.5	8.0	1.2	2.30	27.0	1260	1150	800
	14.0	5.0	8.5	4.3-4.5	8.0	1.2	2.30	27.0	1260	1150	500
	16.0	8.0	10.5	4.3-4.5	8.0	1.2	2.30	27.0	1260	1150	500
	18.0	10.0	12.5	4.3-4.5	8.0	1.2	2.30	27.0	1260	1150	500
	20.0	12.0	14.5	4.3-4.5	8.0	1.2	2.30	27.0	1260	1150	500
4.8	10.0	0.5	4.0	4.3-4.5	8.0	1.2	2.30	27.0	1260	1150	500
	12.0	2.0	6.0	5.1-5.3	9.5	1.3	2.60	28.0	2400	2200	500
	14.0	4.0	8.0	5.1-5.3	9.5	1.3	2.60	28.0	2400	2200	500
	16.0	6.0	9.5	5.1-5.3	9.5	1.3	2.60	28.0	2400	2200	400
	18.0	8.0	11.0	5.1-5.3	9.5	1.3	2.60	28.0	2400	2200	400
	20.0	10.0	14.0	5.1-5.3	9.5	1.3	2.60	28.0	2400	2200	350
	22.0	12.0	16.0	5.1-5.3	9.5	1.3	2.60	28.0	2400	2200	300
	25.0	16.0	19.0	5.1-5.3	9.5	1.3	2.60	28.0	2400	2200	250
	30.0	19.0	24.0	5.1-5.3	9.5	1.3	2.60	28.0	2400	2200	250
	35.0	24.0	28.0	5.1-5.3	9.5	1.3	2.60	28.0	2400	2200	200