
RS PRO Aluminium/Steel Dome Head Blind Rivet, 4.8 mm Diameter x 10 mm long

Supplier Part Number: OJCLASD4810WH



FEATURES

- **Aluminium Body:** Offers a lightweight yet durable fastening solution.
- **Steel Mandrel:** Provides additional strength and reliability during installation.
- **Dome Head Type:** Ensures a neat and flush finish for aesthetic applications.
- **Trivalent Chromate Finish:** Enhances corrosion resistance for longer-lasting performance.
- **Wide Grip Range:** Accommodates material thicknesses from 4 mm to 6 mm, offering versatility.
- **Compliance with Standards:** Meets DIN 7337 and ISO standards for quality assurance.

RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

The RS PRO Aluminium Blind Rivet is designed for secure fastening in a variety of applications. With a 4.8 mm diameter and a 10 mm length, it provides reliable performance in both light and heavy-duty tasks. Its aluminium body ensures durability while maintaining a lightweight profile, making it ideal for use in construction and manufacturing.

General Specifications

Finish	Clear, Trivalent Chromate, Zinc
Head Type	Dome
Product Type	Blind Rivet
Rivet Type	Blind
Fixing Hole Diameter	4.9 mm
Mandrel Material	Steel
Maximum Grip	6 mm
Minimum Grip	4 mm


Mechanical Specifications


Head Diameter	9.5 mm
Rivet Body Material	Aluminium
Rivet Diameter	4.8 mm
Rivet Length	10 mm
Shear Strength	1700 N
Tensile Strength	2250 N

Approvals

Standards/Approvals	DIN 7337, ISO 9001:2015, ISO 14001:2015, ISO 14589, ISO TS 16949:2009

Additional Image 1





Nominal Diameter mm	Body Length mm	Grip Range Min mm	Grip Range Max mm	Hole Size mm	Flange Diameter mm	Flange Thickness mm	Nom. Mandrel Diameter mm	Min Mandrel Length mm	Shear Strength N	Tensile Strength N	Box Quantity
D	L				dk	K	dm	L2			
4.8	6.0	1.0	2.5	4.9	9.5	1.1	2.70	28.0	1700	2250	500
	8.0	2.5	4.0	4.9	9.5	1.1	2.70	28.0	1700	2250	500
	10.0	4.0	6.0	4.9	9.5	1.1	2.70	28.0	1700	2250	500
	12.0	6.0	8.0	4.9	9.5	1.1	2.70	28.0	1700	2250	500
	14.0	8.0	10.0	4.9	9.5	1.1	2.70	28.0	1700	2250	500
	16.0	10.0	12.0	4.9	9.5	1.1	2.70	28.0	1700	2250	250
	18.0	12.0	14.0	4.9	9.5	1.1	2.70	28.0	1700	2250	250
	20.0	14.0	16.0	4.9	9.5	1.1	2.70	28.0	1700	2250	250
	22.0	16.0	18.0	4.9	9.5	1.1	2.70	28.0	1700	2250	250
	25.0	18.0	21.0	4.9	9.5	1.1	2.70	28.0	1700	2250	250
	28.0	21.0	23.5	4.9	9.5	1.1	2.70	28.0	1700	2250	250
	30.0	23.0	25.0	4.9	9.5	1.1	2.70	28.0	1700	2250	250
	35.0	25.0	30.0	4.9	9.5	1.1	2.70	28.0	1700	2250	200
	40.0	30.0	35.0	4.9	9.5	1.1	2.70	28.0	1700	2250	150