
RS PRO Aluminium/Steel Dome Head Blind Rivet, 4.8 mm Diameter x 15 mm long

Supplier Part Number: OJCLASDM4815BL



FEATURES

- **Rivet Diameter:** 4.8 mm for precise fitting
- **Rivet Length:** 15 mm suitable for thicker materials
- **Mandrel Material:** Steel for enhanced durability
- **Head Type:** Dome for a smooth finish
- **Finish:** Trivalent Chromate for corrosion resistance
- **Maximum Grip:** 10 mm accommodating thicker joints
- **Minimum Grip:** 5 mm for versatility in application

RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

This RS PRO Aluminium Blind Rivet is designed for secure fastening in a variety of applications. With a 4.8 mm diameter and a 15 mm length, it is ideal for joining materials where access is only available from one side. The rivet features a steel mandrel for added strength and reliability.

General Specifications

Finish	Clear, Trivalent Chromate, Zinc
Head Type	Dome
Product Type	Blind Rivet
Rivet Type	Blind
Fixing Hole Diameter	4.9 mm
Mandrel Material	Steel
Maximum Grip	10 mm
Minimum Grip	5 mm


Mechanical Specifications

Head Diameter	9.5 mm
Rivet Body Material	Aluminium
Rivet Diameter	4.8 mm
Rivet Length	15 mm
Shear Strength	1500 N
Tensile Strength	2350 N

Approvals

Standards/Approvals	DIN 7337, ISO 9001:2015, ISO 14001:2015, ISO 14589, ISO TS 16949:2009

Additional Image 1





Nominal Diameter mm	Grip Range Min mm	Grip Range Max mm	Hole Size mm	Flange Diameter mm	Flange Thickness mm	Nom. Mandrel Diameter mm	Min Mandrel Length mm	Shear Strength N	Tensile Strength N	Box Quantity
D				dk	K	dm	L2			
4.8	5.0	10.0	4.9	9.5	2.0	2.78	28.0	1500	2350	500