
RS PRO Stainless Steel/Stainless Steel Flange Head Blind Rivet, 4 mm Diameter x 8 mm long

Supplier Part Number: OJSSL4008



FEATURES

- **Flange Head:** Provides a larger bearing surface for increased load distribution.
- **Stainless Steel Mandrel:** Ensures high strength and resistance to corrosion.
- **Wide Grip Range:** Accommodates material thicknesses from 2 mm to 4 mm.

RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

The RS PRO 4 mm Blind Rivet is designed for secure fastening in applications where access is limited to one side. Made from high-quality stainless steel, it offers excellent corrosion resistance and durability, making it ideal for both indoor and outdoor use.

General Specifications

Head Type	Flange
Product Type	Blind Rivet
Rivet Type	Blind
Fixing Hole Diameter	4.1 mm
Mandrel Material	Stainless Steel
Maximum Grip	4 mm
Minimum Grip	2 mm


Mechanical Specifications


Head Diameter	12 mm
Rivet Body Material	Stainless Steel
Rivet Diameter	4 mm
Rivet Length	8 mm
Shear Strength	2895 N
Tensile Strength	3650 N

Approvals

Standards/Approvals	DIN 7337, ISO 9001:2015, ISO 14001:2015, ISO 14589, ISO TS 16949:2009

Technical Diagrams





Nominal Diameter mm	Body Length mm	Grip Range Min mm	Grip Range Max mm	Hole Size mm	Flange Diameter mm	Flange Thickness mm	Nom. Mandrel Diameter mm	Min Mandrel Length mm	Shear Strength N	Tensile Strength N	Box Quantity
D	L				dk	K	dm	L2			
	6.0	1.0	3.5	3.3	9.5	1.3	1.90	26.0	1875	2360	1000
	8.0	3.5	5.0	3.3	9.5	1.3	1.90	26.0	1875	2360	1000
3.2	10.0	5.0	7.0	3.3	9.5	1.3	1.90	26.0	1875	2360	500
	12.0	7.0	9.0	3.3	9.5	1.3	1.90	26.0	1875	2360	500
	14.0	9.0	11.0	3.3	9.5	1.3	1.90	26.0	1875	2360	500
	6.0	1.0	2.0	4.1	12.0	1.6	2.50	27.0	2895	3650	500
	8.0	2.0	4.0	4.1	12.0	1.6	2.50	27.0	2895	3650	500
4.0	10.0	4.0	6.0	4.1	12.0	1.6	2.50	27.0	2895	3650	500
	12.0	6.0	8.0	4.1	12.0	1.6	2.50	27.0	2895	3650	500
	16.0	10.0	12.0	4.1	12.0	1.6	2.50	27.0	2895	3650	500
	8.0	2.5	4.0	4.9	16.0	1.7	3.00	28.0	4230	5335	250
	10.0	4.0	6.0	4.9	16.0	1.7	3.00	28.0	4230	5335	250
	12.0	6.0	8.0	4.9	16.0	1.7	3.00	28.0	4230	5335	250
4.8	14.0	8.0	9.5	4.9	16.0	1.7	3.00	28.0	4230	5335	250
	16.0	9.5	11.0	4.9	16.0	1.7	3.00	28.0	4230	5335	250
	20.0	12.0	15.0	4.9	16.0	1.7	3.00	28.0	4230	5335	250
	25.0	16.0	20.0	4.9	16.0	1.7	3.00	28.0	4230	5335	200