
RS PRO Stainless Steel/Stainless Steel Flange Head Blind Rivet, 4 mm Diameter x 12 mm long

Supplier Part Number: OJSSL4012



FEATURES

- **Stainless Steel Construction:** Provides excellent corrosion resistance and durability.
- **Blind Rivet Design:** Allows for fastening where only one side is accessible.
- **4 mm Diameter:** Suitable for a variety of applications requiring this specific size.
- **Flange Head:** Ensures a secure fit and distributes load effectively.
- **12 mm Rivet Length:** Accommodates materials with a thickness between 6 and 8 mm.
- **Compliance with Standards:** Meets DIN 7337 and ISO standards for quality and reliability.

RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

The RS PRO Stainless Steel Blind Rivet is designed for secure fastening in applications where access is only possible from one side. Made from durable stainless steel, this rivet offers excellent corrosion resistance, making it ideal for use in harsh environments. With a 4 mm diameter and a grip range of 6 to 8 mm, it provides reliable and robust fastening solutions.

General Specifications

Head Type	Flange
Product Type	Blind Rivet
Rivet Type	Blind
Fixing Hole Diameter	4.1 mm
Mandrel Material	Stainless Steel
Maximum Grip	8 mm
Minimum Grip	6 mm


Mechanical Specifications


Head Diameter	12 mm
Rivet Body Material	Stainless Steel
Rivet Diameter	4 mm
Rivet Length	12 mm
Shear Strength	2895 N
Tensile Strength	3650 N

Approvals

Standards/Approvals	DIN 7337, ISO 9001:2015, ISO 14001:2015, ISO 14589, ISO TS 16949:2009

Technical Diagrams





Nominal Diameter mm	Body Length mm	Grip Range Min mm	Grip Range Max mm	Hole Size mm	Flange Diameter mm	Flange Thickness mm	Nom. Mandrel Diameter mm	Min Mandrel Length mm	Shear Strength N	Tensile Strength N	Box Quantity
D	L				dk	K	dm	L2			
	6.0	1.0	3.5	3.3	9.5	1.3	1.90	26.0	1875	2360	1000
	8.0	3.5	5.0	3.3	9.5	1.3	1.90	26.0	1875	2360	1000
3.2	10.0	5.0	7.0	3.3	9.5	1.3	1.90	26.0	1875	2360	500
	12.0	7.0	9.0	3.3	9.5	1.3	1.90	26.0	1875	2360	500
	14.0	9.0	11.0	3.3	9.5	1.3	1.90	26.0	1875	2360	500
	6.0	1.0	2.0	4.1	12.0	1.6	2.50	27.0	2895	3650	500
	8.0	2.0	4.0	4.1	12.0	1.6	2.50	27.0	2895	3650	500
4.0	10.0	4.0	6.0	4.1	12.0	1.6	2.50	27.0	2895	3650	500
	12.0	6.0	8.0	4.1	12.0	1.6	2.50	27.0	2895	3650	500
	16.0	10.0	12.0	4.1	12.0	1.6	2.50	27.0	2895	3650	500
	8.0	2.5	4.0	4.9	16.0	1.7	3.00	28.0	4230	5335	250
	10.0	4.0	6.0	4.9	16.0	1.7	3.00	28.0	4230	5335	250
	12.0	6.0	8.0	4.9	16.0	1.7	3.00	28.0	4230	5335	250
4.8	14.0	8.0	9.5	4.9	16.0	1.7	3.00	28.0	4230	5335	250
	16.0	9.5	11.0	4.9	16.0	1.7	3.00	28.0	4230	5335	250
	20.0	12.0	15.0	4.9	16.0	1.7	3.00	28.0	4230	5335	250
	25.0	16.0	20.0	4.9	16.0	1.7	3.00	28.0	4230	5335	200