
RS PRO Aluminium Flat Head Blind Rivet Nut, M12 x 25mm long

Supplier Part Number: RNAFH1240



FEATURES

- **Material:** Aluminium construction offers a lightweight yet durable solution.
- **Thread Size:** M12 thread size ensures compatibility with a wide range of bolts and screws.
- **Fixing Hole Diameter:** 16 mm fixing hole diameter allows for easy installation.
- **Length:** 25 mm length provides ample grip for secure fastening.

RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

The RS PRO M12 Aluminium Rivet Nut is designed for secure fastening in applications where a strong, lightweight solution is required. Ideal for use in thin materials, it provides a reliable threaded connection without the need for welding or tapping.


General Specifications


Material	Aluminium
Product Type	Rivet Nut
Sub Type	Nut
Thread Size	M12
Fixing Hole Diameter	16 mm
Head Type	Flat


Mechanical Specifications

Diameter	15.9 mm
Length	25 mm
Maximum Grip	4 mm
Minimum Grip	1 mm
Shear Strength	
Tensile Strength	28000 N
Maximum Tightening Torque	45 Nm

Technical Diagrams







Thread Size mm	Grip Range Min mm	Grip Range Max mm	Hole Size mm	Body Diameter mm	Flange Diameter mm	Flange Thickness mm	Body Overall Length mm	Max Tightening Torque Nm	Tensile Strength N	Box Quantity
A	G	G		B	H	T	L			
M3	0.5	1.5	5.0	4.9	8.0	1.0	9.0	0.7	2500	2000
M4	0.5	2.0	6.0	5.9	9.0	1.0	10.5	2.0	3600	1500
	0.5	2.5	6.0	5.9	9.0	1.0	13.0	2.0	3600	1000
M5	5.5	8.0	7.0	6.9	10.0	1.0	20.0	4.0	5500	500
M6	0.5	2.5	9.0	8.9	12.3	1.0	15.0	6.0	8300	500
	2.5	4.5	9.0	8.9	12.3	1.0	19.5	6.0	8300	400
	4.5	6.5	9.0	8.9	12.3	1.0	21.0	6.0	8300	300
M8	1.0	3.0	11.0	10.9	14.5	1.0	16.5	15.0	13000	300
	3.0	5.5	11.0	10.9	14.5	1.0	21.0	15.0	13000	250
	5.5	8.0	11.0	10.9	14.5	1.0	23.5	15.0	13000	200
M10	0.5	4.0	13.0	12.9	16.5	1.6	19.0	27.0	20000	150
	4.0	6.5	13.0	12.9	16.5	1.6	24.0	27.0	20000	100
M12	1.0	4.0	16.0	15.9	22.0	2.0	25.0	45.0	28000	100