RS PRO A2/304 Stainless Steel Countersunk Head Blind Rivet Nut, M3 x 8.5mm long

Supplier Part Number: RNSSCH0330



FEATURES

- **Material:** A2/304 stainless steel provides high corrosion resistance and durability.
- **Thread Size:** M3 thread size ensures compatibility with a wide range of bolts and screws.
- **Fixing Hole Diameter:** 5 mm fixing hole diameter allows for easy installation.
- **Length:** 8.5 mm length suitable for thin material applications.

RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

The RS PRO M3 Rivet Nut is designed for secure fastening in various industrial applications. Made from A2/304 stainless steel, it offers excellent corrosion resistance and durability. This rivet nut is ideal for creating strong, reliable threads in thin materials.


General Specifications


Material	A2/304 Stainless Steel
Product Type	Rivet Nut
Sub Type	Nut
Thread Size	M3
Fixing Hole Diameter	5 mm
Head Type	Countersunk


Mechanical Specifications

Diameter	4.9 mm
Length	8.5 mm
Maximum Grip	3 mm
Minimum Grip	1.6 mm
Shear Strength	900 N
Tensile Strength	3900 N
Maximum Tightening Torque	1 Nm

Technical Diagrams







Thread Size mm	Grip Range Min mm	Grip Range Max mm	Hole Size mm	Body Diameter mm	Flange Diameter mm	Flange Thickness mm	Body Overall Length mm	Max Tightening Torque Nm	Tensile Strength N	Box Quantity
A	G	G		B	H	T	L			
M3	1.6	3.0	5.0	4.9	7.5	1.5	8.5	1.0	3900	2000
	1.5	3.0	5.0	4.9	7.5	1.5	12.0	1.0	3900	1000
M4	3.0	4.5	6.0	5.9	9.0	1.5	13.0	3.0	6800	1500
M5	1.5	3.5	7.0	6.9	10.0	1.5	13.0	6.0	10000	500
	3.5	5.0	7.0	6.9	10.0	1.5	15.0	6.0	10000	500
M6	1.5	4.0	9.0	8.9	12.0	1.5	15.5	10.0	15000	500
	4.0	6.0	9.0	8.9	12.0	1.5	17.0	10.0	15000	400
M8	2.0	4.5	11.0	10.9	14.0	1.7	18.5	24.0	27000	250
	4.5	6.0	11.0	10.9	14.0	1.7	19.0	24.0	27000	250
M10	2.0	5.0	13.0	12.9	16.0	1.7	21.0	32.0	28500	250
	5.0	6.5	13.0	12.9	16.0	1.7	24.0	32.0	28500	100
M12	1.7	5.0	16.0	15.9	18.0	1.8	24.0	44.0	48000	100
	4.5	7.5	16.0	15.9	18.0	1.8	27.5	44.0	48000	100