RS PRO A2/304 Stainless Steel Countersunk Head Blind Rivet Nut, M10 x 30mm long

Supplier Part Number: RNSSCHC1050



FEATURES

- **Material:** A2/304 stainless steel provides corrosion resistance and durability.
- **Diameter:** 12.9 mm diameter ensures a secure fit in pre-drilled holes.
- **Thread Size:** M10 thread size for compatibility with standard fittings.
- **Fixing Hole Diameter:** 13 mm for easy installation.
- **Length:** 30 mm length suitable for a range of applications.

RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

This RS PRO M10 Rivet Nut is designed for secure fastening in a variety of industrial applications. Made from A2/304 stainless steel, it offers excellent corrosion resistance and durability. Ideal for use in environments where strength and reliability are paramount.


General Specifications


Material	A2/304 Stainless Steel
Product Type	Rivet Nut
Sub Type	Nut
Thread Size	M10
Fixing Hole Diameter	13 mm
Head Type	Countersunk


Mechanical Specifications

Diameter	12.9 mm
Length	30 mm
Maximum Grip	5 mm
Minimum Grip	1.5 mm
Shear Strength	5000 N
Tensile Strength	28500 N
Maximum Tightening Torque	32 Nm

Technical Diagrams







Thread Size mm	Grip Range Min mm	Grip Range Max mm	Hole Size mm	Body Diameter mm	Flange Diameter mm	Flange Body Overall Thickness mm Length mm (T) (L)	Max Tightening Torque Nm	Tensile Strength N	Box Quantity
A	G	G		B	H				
M4	1.5	3.5	6.0	5.9	9.0	17.5	3.0	6800	1000
M5	1.5	3.5	7.0	6.9	10.0	20.0	6.0	10000	500
M6	1.5	4.0	9.0	8.9	12.0	23.0	10.0	15000	500
M8	1.5	4.5	11.0	10.9	14.0	26.5	24.0	27000	250
M10	1.5	5.0	13.0	12.9	16.0	1.7 30.0	32.0	28500	100