RS PRO 13A Circular Connector, 17.5 mm Plug

Supplier Part Number: SA1210/P2IG-NP

RS Stock No:



FEATURES

- **Push Pull Mating Type:** Provides secure and quick connections.
- **IP67 Rating:** Offers protection against dust and water ingress.
- **Gold-Plated Contacts:** Ensures low contact resistance and high conductivity.
- **Anodised Aluminium Housing:** Provides corrosion resistance and durability.
- **Wide Operating Temperature Range:** Suitable for environments from -40 °C to 85 °C.
- **Solder Termination:** Allows for secure and reliable connections.
- **500 Mating Cycles:** Ensures long-lasting performance.

RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

The RS PRO 13A Circular Connector is designed for reliable and efficient electrical connections in demanding environments. With a robust anodised aluminium housing and gold-plated copper alloy contacts, this connector ensures excellent conductivity and durability. Ideal for industrial applications, it supports a current rating of 13 A and a voltage of 250 V ac.

General Specifications

Cable Diameter Range	4 to 6.5 mm
Coding	SA12
Colour	Green
Connector Length	46 mm
Contact Diameter	1.6 mm
Contact Gender	Male
Contact Material	Copper Alloy
Contact Plating	Gold
Mating Cycle	500 cycles
Mating Type	Push Pull
Maximum Insulation Resistance	2000 MΩ
Maximum Wire Size (mm^2)	≤2
Number of Contacts	2
Orientation	Straight
Product Type	Circular Connector
Series	SA12
Shell Size	12 mm

Mechanical Specifications

Connector Size	17.5 mm
Housing Material	Anodised Aluminium
Insert Material	PPS
Mount Type	Cable
Termination Type	Solder

Approvals

Standards/Approvals	EN61984;CE

Electrical Specifications

Contact Resistance	2.5 mΩ
Current	13 A
Plug/Socket	Plug
Pole Format	2P
Test Voltage	1500 V ac
Voltage	250 V ac

Protection Category

IP Rating	IP67

Operation Environment Specifications

Maximum Operating Temperature	85 °C
Minimum Operating Temperature	-40 °C

Specifications

{"section":"headers":["1","| 2","[ES","Column 4","Column 5","Column 6"],"rows":[["Rated current (A)","13","13","5","5","3"],["Contact diameter","21.6X2","21.6X3","21X4","21X5","20.7X9"],["Rated voltage (AC.V)","250","250","200","180","125"],["Test voltage(AC.V) 1 min","1500","1500","1500","1000","1000"],["Contact resistance (MQ)","25","25","5","5","10"],["Wire size AWG)","=2/14","=2/14","","=075/18 <075/18","=0.75/18 =05/20"]])