RS PRO 26.5 mm Circular Connector, 12P

Supplier Part Number: SA2010/P12IIG-1-NP

RS Stock No:



FEATURES

- **Push Pull Mating Type:** Provides quick and secure connections.
- **IP67 Rating:** Ensures protection against dust and water ingress.
- **Gold-Plated Contacts:** Enhances conductivity and corrosion resistance.
- **Anodised Aluminium Housing:** Offers durability and resistance to environmental factors.
- **12 Contacts:** Supports multiple connections in a compact form.
- **Wide Temperature Range:** Operates effectively from -40 °C to 85 °C.
- **Solder Termination:** Allows for secure and reliable wire connections.

RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

The RS PRO Circular Connector is designed for robust and reliable connections in demanding environments. With a push-pull mating type and IP67 rating, it ensures secure and waterproof connections suitable for industrial applications. This connector supports a current rating of 5 A and a voltage rating of 400 V AC, making it ideal for high-performance electrical systems.

General Specifications

Cable Diameter Range	8 to 12 mm
Coding	SA20
Colour	Green
Connector Length	66 mm
Contact Diameter	1 mm
Contact Gender	Male
Contact Material	Copper Alloy
Contact Plating	Gold
Mating Cycle	500 cycles
Mating Type	Push Pull
Maximum Insulation Resistance	2000 MΩ
Maximum Wire Size (mm^2)	≤0.75
Number of Contacts	12
Orientation	Straight
Product Type	Circular Connector
Series	SA20
Shell Size	20 mm

Mechanical Specifications

Connector Size	26.5 mm
Housing Material	Anodised Aluminium
Insert Material	PPS
Mount Type	Cable
Termination Type	Solder

Approvals

Standards/Approvals	EN61984;CE

Electrical Specifications

Contact Resistance	5 mΩ
Current	5 A
Plug/Socket	Plug
Pole Format	12P
Test Voltage	1200 V ac
Voltage	400 V ac

Protection Category

IP Rating	IP67

Operation Environment Specifications

Maximum Operating Temperature	85 °C
Minimum Operating Temperature	-40 °C

Specifications

{"section":"headers":["contactspec ee Rated current (A) Contact diameter(mm)","025X2","25 025X3","6 25 025X4","6) 10","W Crimp contact spec see P20 6 2","©)","8 10","10 015X8","% Screw contact spec see P21 69 5 o1X9","85 5 01X12","5 01X15"],"rows":[["Rated voltage (AC.V)","500","500","500","500","500","500","500","500","400","400","400"],["Test voliage(AC.Y) | min","1500","1500","1500","1500","1500","1500","1500","1500","1200","1200","1200"],["Contact resistance","1","1","1","2.5",":",":","25","25","5","5","5"], ["Termination","","","solder/screw","solder","solder","solder","solder","solder","solder","solder"], ["Wire size for screw termination (mm:/AWG)| =1515","","=1515","=15/15","/","/","/","/","/","/","/","/"]]}