

Sparse $\ell_2 - \ell_0$ image reconstruction

Laure Blanc-Feraud

Projet MORPHEME - UCA, CNRS, INRIA -

M2 MScDAI

-
1. Introduction and examples
 2. ℓ_1 promotes sparsity
 3. Algorithms for $\ell_2 - \ell_1$ optimization
 4. Algorithms for $\ell_2 - \ell_0$ optimization
 5. Results on super-resolution Microscopy by Single Molecule Localization.
-

1.Introduction

Many signal processing areas are concerned with

- ▶ Linear observation : $Ax = d$
 - ▶ d : observed data, vector in \mathbb{R}^M
 - ▶ x unknown data to be estimated in \mathbb{R}^N
 - ▶ A observation matrix, $M \times N$ matrix.

where we have **few observations** for a **large explicative unknown variables** x $M \ll N$

The system is undertermined, A is ill-conditioned, observations are noisy

- ▶ Least square solution $\hat{x} = \arg \min_{x \in \mathbb{R}^N} \|Ax - d\|_2^2$

$$(\|x\|_2^2 = \|x\|^2 = \sum_{i=1}^N x_i^2)$$

- ▶ Regularization: **sparse** signal hypothesis modeled by considering ℓ_1 -norm or ℓ_0 semi-norm constraints:

$$\|x\|_1 \leq K \text{ where } \|x\|_1 = \sum_{i=1}^N |x_i|$$


$$\|x\|_0 \leq K \text{ where } \|x\|_0 = \# \{x_i, i = 1, \dots, N : x_i \neq 0\}$$

NB: ℓ_0 -norm **is NOT** a norm as $\|\lambda x\|_0 = \|x\|_0 \neq \lambda \|x\|_0$.

1.0 Dictionary representation in image processing


- Image are non-stationary, they exhibit smooth areas, oscillations, edges, textures,...

Let's $d \in \mathbb{R}^M$ be a patch of an image or a signal:



- Each part is represented by given waveforms which best match the image structure, for example Basis B_i as Haar, smooth wavelets, sine/cosine transform,...

Let's $A = [a_1, \dots, a_N] \in \mathbb{R}^{M \times N}$ be a set of basis vectors, or normalized vectors



1.0 Dictionary representation in image processing

- ▶ Such A is a redundant **dictionary** (succession of representative waveforms, possibly a succession of bases)
- ▶ The dictionary A is adapted to the signal d if d can be represented by a **few** number of vectors of the dictionary A , that is $d \approx Ax$ with x is a **sparse** vector, that is $\|x\|_0 \leq K$, where $K \ll N$.

$$\begin{bmatrix} d \end{bmatrix} = \begin{bmatrix} a_{i1} & a_{i2} & a_{i3} \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \\ x_3 \end{bmatrix} = x_1 \begin{bmatrix} a_{i1} \end{bmatrix} + x_2 \begin{bmatrix} a_{i2} \end{bmatrix} + x_3 \begin{bmatrix} a_{i3} \end{bmatrix} + \dots$$

1.1 Examples in Signal/image Processing

- ▶ signal is a sum of pulses, spikes, modeled by a sum of Dirac $\sum_{r=1}^K x_r \delta_{t_r}$.
- ▶ acquisition system, channel, is modeled as a linear system, e.g. convolution by a Gaussian function:
$$d(\cdot) = h * \sum_{r=1}^K x_r \delta_{t_r} = \sum_{r=1}^K x_r h(\cdot - t_r).$$

By assuming the Dirac locations t_r are on a regular grid indexed by $i = 1, \dots, N$

$$\begin{bmatrix} \vdots \\ \vdots \\ \vdots \end{bmatrix} = \begin{bmatrix} \text{ } & \text{ } & \text{ } \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \\ x_3 \end{bmatrix} \begin{matrix} -t_1 \\ -t_2 \\ -t_3 \end{matrix} + \begin{bmatrix} \vdots \\ \vdots \\ \vdots \end{bmatrix}$$

$\mathbf{d} = \mathbf{A} \mathbf{x} + \mathbf{n}$


1D example: Channel estimation in communications, ...

2D example: Single Molecule Localization in super-resolution microscopy , ...

2D example in Super-resolution microscopy: SMLM (continued)

Conventional fluorescence microscopy limits

- ▶ physical diffraction limit of optical systems
- ▶ Airy patch = impulse response of the microscope (PSF: *Point Spread Function*)
- ▶ overlapping patches limit at $\approx 200\text{nm}$ the distance between two molecules to be resolved (Rayleigh limit)



Super-resolution by single molecule localization

- ▶ **Photo-activable molecules:** PALM *Photo Activated Localisation Microscopy* ([Betzig & al 06, Hess & al, 2006]) et STORM *STochastic Optical Reconstruction Microscopy* ([Rust & al, 2006])
- ▶ Sequentially activate and image a small random set of fluorescent molecules.

2D example in Super-resolution microscopy: SMLM (continued)

- ▶ activation
- ▶ imaging
- ▶ localization
- ▶ assembling



Figure: PALM microscopy principle. From Zeiss tutorials
[<http://zeiss-campus.magnet.fsu.edu/tutorials/index.html>]

2D example in Super-resolution microscopy: SMLM (continued)

- ▶ activation
- ▶ imaging
- ▶ localization
- ▶ assembling




Figure: PALM microscopy principle. From Zeiss tutorials
[<http://zeiss-campus.magnet.fsu.edu/tutorials/index.html>]

2D example in Super-resolution microscopy: SMLM (continued)

- ▶ activation
- ▶ imaging
- ▶ localization
- ▶ assembling




Figure: PALM microscopy principle. From Zeiss tutorials
[<http://zeiss-campus.magnet.fsu.edu/tutorials/index.html>]

2D example in Super-resolution microscopy: SMLM (continued)

- ▶ activation
- ▶ imaging
- ▶ localization
- ▶ assembling




Figure: PALM microscopy principle. From Zeiss tutorials
[<http://zeiss-campus.magnet.fsu.edu/tutorials/index.html>]

2D example in Super-resolution microscopy: SMLM (continued)

- ▶ activation
- ▶ imaging
- ▶ localization
- ▶ assembling




Figure: PALM microscopy principle. From Zeiss tutorials
[<http://zeiss-campus.magnet.fsu.edu/tutorials/index.html>]

2D example in Super-resolution microscopy: SMLM (continued)

- ▶ activation
- ▶ imaging
- ▶ localization
- ▶ assembling




Figure: PALM microscopy principle. From Zeiss tutorials
[<http://zeiss-campus.magnet.fsu.edu/tutorials/index.html>]

2D example in Super-resolution microscopy: SMLM (continued)

- ▶ activation
- ▶ imaging
- ▶ localization
- ▶ assembling




Figure: PALM microscopy principle. From Zeiss tutorials
[<http://zeiss-campus.magnet.fsu.edu/tutorials/index.html>]

2D example in Super-resolution microscopy: SMLM (continued)

- ▶ activation
- ▶ imaging
- ▶ localization
- ▶ assembling




Figure: PALM microscopy principle. From Zeiss tutorials
[<http://zeiss-campus.magnet.fsu.edu/tutorials/index.html>]

2D example in Super-resolution microscopy: SMLM (continued)

- ▶ activation
- ▶ imaging
- ▶ localization
- ▶ assembling






Figure: PALM microscopy principle. From Zeiss tutorials
[<http://zeiss-campus.magnet.fsu.edu/tutorials/index.html>]

2D example in Super-resolution microscopy: SMLM (continued)



$$\hat{\mathbf{x}} \in \arg \min_{\mathbf{x}} \frac{1}{2} \|A\mathbf{x} - \mathbf{d}\|_2^2 + \lambda \|\mathbf{x}\|_0$$

2D example in Super-resolution microscopy: SMLM (continued)





$$\hat{\mathbf{x}} \in \arg \min_{\mathbf{x}} \frac{1}{2} \|\mathbf{Ax} - \mathbf{d}\|_2^2 + \lambda \|\mathbf{x}\|_0$$

2D example in Super-resolution microscopy: SMLM (continued)

Image formation model PALM / STORM

$\mathbf{d} \in \mathbb{R}^{M \times M}$ one acquisition.

$\mathbf{X} \in \mathbb{R}^{ML \times ML}$ an image where each pixel of \mathbf{d} is divided in $\mathbf{L} \times \mathbf{L}$ pixels.





2D example in Super-resolution microscopy: SMLM (continued)

Image formation model PALM / STORM

$\mathbf{d} \in \mathbb{R}^{M \times M}$ one acquisition.

$\mathbf{X} \in \mathbb{R}^{ML \times ML}$ an image where each pixel of \mathbf{d} is divided in $\mathbf{L} \times \mathbf{L}$ pixels.





2D example in Super-resolution microscopy: SMLM (continued)

Image formation model PALM / STORM

$\mathbf{d} \in \mathbb{R}^{M \times M}$ one acquisition.

$\mathbf{X} \in \mathbb{R}^{ML \times ML}$ an image where each pixel of \mathbf{d} is divided in $\mathbf{L} \times \mathbf{L}$ pixels.





2D example in Super-resolution microscopy: SMLM (continued)

Image formation model PALM / STORM

$\mathbf{d} \in \mathbb{R}^{M \times M}$ one acquisition.

$\mathbf{X} \in \mathbb{R}^{ML \times ML}$ an image where each pixel of \mathbf{d} is divided in $\mathbf{L} \times \mathbf{L}$ pixels.





2D example in Super-resolution microscopy: SMLM (continued)

Image formation model PALM / STORM

$\mathbf{d} \in \mathbb{R}^{M \times M}$ one acquisition.

$\mathbf{X} \in \mathbb{R}^{ML \times ML}$ an image where each pixel of \mathbf{d} is divided in $\mathbf{L} \times \mathbf{L}$ pixels.



Model



$$\mathbf{d} = \mathbf{M}_L(\mathbf{H}(\mathbf{X})) + \eta,$$

2D example in Super-resolution microscopy: SMLM (continued)

Image formation model PALM / STORM

$\mathbf{d} \in \mathbb{R}^{M \times M}$ one acquisition.

$\mathbf{X} \in \mathbb{R}^{ML \times ML}$ an image where each pixel of \mathbf{d} is divided in $\mathbf{L} \times \mathbf{L}$ pixels.



Problem $\ell_2 - \ell_0$

$$\hat{\mathbf{X}} \in \arg \min_{\mathbf{X}} \frac{1}{2} \|\mathbf{d} - \mathbf{M}_L(\mathbf{H}(\mathbf{X}))\|_2^2 + \lambda \|\mathbf{X}\|_0$$

$\|\mathbf{X}\|_0 = \#\{X_i / X_i \neq 0\}$ is the number of non zero components of \mathbf{X} .

1.3 ℓ_2 - ℓ_0 optimization problems

Noisy problem: two constrained forms ($\epsilon > 0, K > 0$)

$$\hat{x} = \arg \min_{x \in \mathbb{R}^N} \frac{1}{2} \|Ax - d\|_2^2 \quad \text{subject to} \quad \|x\|_0 \leq K$$

$$\hat{x} = \arg \min_{x \in \mathbb{R}^N} \|x\|_0 \quad \text{subject to} \quad \|Ax - d\|_2^2 \leq \epsilon$$

Noisy problem : penalized form ($\lambda > 0$)

$$\hat{x} = \arg \min_{x \in \mathbb{R}^N} G_{\ell_0}(x) := \frac{1}{2} \|Ax - d\|_2^2 + \lambda \|x\|_0$$

$$A \in \mathbb{R}^{M \times N} \quad \text{with} \quad M \ll N$$

- ▶ Non equivalent formulations
- ▶ Existence of an optimal solution and relationships between optimal solutions in [Nikolova 16]
- ▶ Intensive work in signal and image processing, and in statistics.
- ▶ **non-continuous**, **non-convex** and **NP-hard** optimization problem. [Natarajan 95] [Davis & al 97]. Roughly speaking, *a solution cannot be verified in polynomial time w.r.t the dimension of the problem*

\

-
1. Iterative Hard Thresholding,
 2. Continuous relaxation,
 3. Greedy algorithms,
 4. Exact reformulation.
-

Penalized form

$$\hat{\mathbf{x}} = \arg \min_{\mathbf{x} \in \mathbb{R}^N} \frac{1}{2} \|A\mathbf{x} - d\|_2^2 + \lambda \|\mathbf{x}\|_0$$

- ▶ $\frac{1}{2} \|A\mathbf{x} - d\|_2^2$ is L -gradient Lipschitz ($L = \|A\|^2$)
- ▶ Proximal of $\|\cdot\|_0$ has explicit expression, this is the Hard Threshold

Iterative Hard Thresholding

(IHT): Forward-Backward Splitting (FBS) algorithm

$$\mathbf{x}^{k+1} = \text{prox}_{\gamma\lambda\|\cdot\|_0} \left(\mathbf{x}^k - \gamma A^t (A\mathbf{x}^k - d) \right)$$

$\gamma < \frac{1}{L}$ is the gradient step.

Computation of $\text{prox}_{\gamma\lambda\|\cdot\|_0}$:

$$\text{prox}_{\gamma\lambda\|\cdot\|_0}(y) = \arg \min_{x \in \mathbb{R}^N} \left\{ \frac{1}{2} \|x - y\|^2 + \gamma\lambda \|x\|_0 \right\}$$

$$\frac{1}{2} (x - y)^2 + \gamma\lambda \|x\|_0 = \sum_{i=1}^N (x_i - y_i)^2 + \gamma\lambda |x_i|_0$$

where $|u|_0 = 1$ if $u \neq 0$, 0 elsewhere.

Then it is sufficient to compute in 1D

$$\arg \min_{u \in \mathbb{R}} \{g(u) := \frac{1}{2}(u - y)^2 + \gamma\lambda |u|_0\}$$

IHT Algorithm (continued)

Computation of $\arg \min_{u \in \mathbb{R}} \{g(u) := \frac{1}{2}(u - y)^2 + \gamma\lambda|u|_0\}$



- ▶ if $u = 0$ then

$$g(0) = \frac{1}{2}(y)^2$$

- ▶ The minimum could be reached at $\hat{u} = 0$, the value is

$$g(\hat{u}) = \frac{1}{2}(y)^2$$

- ▶ if $u \neq 0$ then

$$g(u) = \frac{1}{2}(u - y)^2 + \lambda$$


- ▶ The minimum is reached at $\hat{u} = y$ and the value is $g(\hat{u}) = \lambda$

if $|y| \leq \sqrt{2\lambda}$ then $\hat{u} = 0$

if $|y| \geq \sqrt{2\lambda}$ then $\hat{u} = y$

The solution is given by the Hard Threshold function

$$\hat{u} = \begin{cases} y & \text{if } |y| > \sqrt{2\lambda}, \\ 0 & \text{if } |y| \leq \sqrt{2\lambda}. \end{cases}$$



non convex

Find the solution of the optimal problem

$$\hat{x} = \arg \min_{x \in \mathbb{R}^N} \frac{1}{2} \|Ax - d\|_2^2 + \lambda \|x\|_0$$

by Forward Backward Splitting algorithm (Iterative Hard Thresholding)

$$x^{k+1} = \text{prox}_{\gamma\lambda\|\cdot\|_0} \left(x^k - \gamma A^t (Ax^k - d) \right)$$

- ▶ IHT algorithm converges to a critical point [Blumensath and Davies 08, Attouch et al 13].
- ▶ **Initialization** point is important, for example initialize with the solution with the ℓ_1 -norm problem:

$$\arg \min_{x \in \mathbb{R}^N} \left\{ \frac{1}{2} \|Ax - y\|^2 + \gamma\lambda \|x\|_1 \right\}. \text{ It is not guaranty that this}$$

solution is sparse.

4.3 ℓ_2 - ℓ_0 optimization by continuous relaxation

Continuous separable relaxation (convex and non-convex)

$$\frac{1}{2}\|Ax - d\|_2^2 + \lambda\|\mathbf{x}\|_0 \rightarrow \frac{1}{2}\|Ax - d\|_2^2 + \lambda\sum_{i \in \mathbb{I}_N} \phi(x_i)$$

Continuous approximation of the ℓ_0 -norm function:

- ▶ ℓ_1 -norm: Lasso [Tibshirani 96] ; Basic Pursuit [Chen et al 98] ; Compressed Sensing [Donoho 06, Candes et al 06]
- ▶ Adaptive Lasso [Zou 06] ;
- ▶ Nonnegative Garrote [Breiman 95] ;
- ▶ Exponential approximation [Mangasarian 96] ;
- ▶ Log-Sum Penalty [Candes et al 08] ;
- ▶ Smoothly Clipped Absolute Deviation (SCAD) [Fan and Li 01] ;
- ▶ Minimax Concave Penalty (MCP) [Zhang 10] ;
- ▶ ℓ_p -norms $0 < p < 1$ [Chartrand 07, Foucart and Lai 09] ;
- ▶ Smoothed ℓ_0 -norm Penalty (SL0) [Mohimani et al 09] ;


Are they *good* approximations?
Which one to use?

4.3 ℓ_2 - ℓ_0 optimization by continuous relaxation

Continuous separable relaxation (convex and non-convex)

$$\frac{1}{2}\|Ax - d\|_2^2 + \lambda\|x\|_0 \rightarrow \frac{1}{2}\|Ax - d\|_2^2 + \lambda\sum_{i \in \mathbb{I}_N} \phi(x_i)$$

Continuous approximation of the ℓ_0 -norm function:



Are they *good* approximations?
Which one to use?

4.3 ℓ_2 - ℓ_0 optimization by continuous relaxation

Example of continuous approximation functions of the ℓ_0 -norm:

- ▶ ℓ_1 -norm: $\phi(t) = |t|$
- ▶ Log-Sum Penalty [Candes et al 08] $\phi_{Log}(\theta; t) := \log(1 + |t|\theta)$, with $\theta \in \mathbb{R}_+^*$.
- ▶ Minimax Concave Penalty (MCP) [Zhang 10]
 $\phi_{MCP}(\gamma, \lambda; t) = \lambda \left(\frac{\gamma\lambda}{2} \mathbb{1}_{\{|t| > \gamma\lambda\}} + \left(|t| - \frac{t^2}{2\gamma\lambda} \right) \mathbb{1}_{\{|t| \leq \gamma\lambda\}} \right)$
with $\mathbb{1}_{\{x \in C\}} = 1$ if $x \in C$ and 0 otherwise.

$$G_{\ell_0}(x) := \frac{1}{2} \|Ax - d\|_2^2 + \lambda \|x\|_0 \rightarrow \tilde{G}(x) := \frac{1}{2} \|Ax - d\|_2^2 + \sum_{i=1}^N \phi(x_i)$$

Definition of a *good* continuous approximation

- ▶ $G_{\ell_0}(x)$ and $\tilde{G}(x)$ have **same global** minimizers

$$\arg \min_{x \in \mathbb{R}^N} \tilde{G}(x) = \arg \min_{x \in \mathbb{R}^N} G_{\ell_0}(x) \quad (\text{P1})$$

- ▶ $\tilde{G}(x)$ has **less local** minimizers than $G_{\ell_0}(x)$

$$\hat{x} \text{ minimiseur de } \tilde{G} \implies \hat{x} \text{ minimiseur de } G_{\ell_0} \quad (\text{P2})$$

ℓ_2 - ℓ_0 optimization by continuous relaxation


ϕ depends on $\|a_i\|$ and λ when applied on x_i :

$$\tilde{G}(x) := \frac{1}{2} \|Ax - d\|_2^2 + \sum_{i \in \mathbb{I}_N} \phi(\|a_i\|, \lambda, x_i)$$

The one which removes the most of local minimizers is $\phi_{MCP}(\frac{1}{\|a_i\|}, \lambda, t)$ that we call ϕ_{CELO} :

$$\phi_{CELO}(\|a_i\|, \lambda, x) = \lambda - \frac{\|a_i\|^2}{2} \left(|x| - \frac{\sqrt{2\lambda}}{\|a_i\|} \right)^2 \mathbb{1}_{\{|x| \leq \frac{\sqrt{2\lambda}}{\|a_i\|}\}}$$

where $\mathbb{1}_{\{x \in D\}} = 1$ if $x \in D$; 0 otherwise.



The $\ell_2 - \ell_0$ and ℓ_2 -CEL0 functionals :

$$G_{\ell_0}(x) := \frac{1}{2} \|Ax - d\|^2 + \lambda \|x\|_0$$

$$G_{\text{CEL0}}(x) = \frac{1}{2} \|Ax - d\|^2 + \sum_{i \in \mathbb{I}_N} \phi_{\text{CEL0}}(\|a_i\|, \lambda, x_i)$$

where $\phi_{\text{CEL0}}(\|a_i\|, \lambda, x) = \lambda - \frac{\|a_i\|^2}{2} \left(|x| - \frac{\sqrt{2\lambda}}{\|a_i\|} \right)^2 \mathbb{1}_{\{|x| \leq \frac{\sqrt{2\lambda}}{\|a_i\|}\}}$

Properties of $G_{\text{CEL0}}(x)$

- ▶ **Limit inf** of the functions satisfying (P1) and (P2) ; the one which removes the most of local minimizers
- ▶ **Continuity**
- ▶ **Non convex** in the general case (for any A)
- ▶ but **convexity** with respect to each **component**

Nonsmooth nonconvex algorithms

The **continuity of G_{CELO}** allows to use recent *nonsmooth nonconvex* algorithms to minimize (indirectly) G_{ℓ_0} ,

- ▶ *Difference of Convex* (DC) functions programming [[Gasso et al 09](#)]
- ▶ *Majorization-Minimization* (MM) algorithms (*e.g.* Iteratively Reweighted ℓ_1 (IRL1) [[Ochs et al 2015](#)])
- ▶ *Forward-Backward splitting* (GIST [[Gong et al 13](#)], [[Attouch et al 13](#)])

ℓ_2 - ℓ_0 optimization by continuous relaxation

Forward-Backward Splitting Algorithm

$$\mathbf{x}^{k+1} \in \text{prox}_{\gamma \Phi_{\text{CELO}}(\cdot)} \left(\mathbf{x}^k - \gamma^k A^T (A \mathbf{x}^k - d) \right),$$

where $0 < \gamma < \frac{1}{\|A\|^2}$ and

$$\text{prox}_{\gamma \phi_{\text{CELO}}(a, \lambda; \cdot)}(u) = \begin{cases} \text{sign}(u) \min \left(|u|, (|u| - \sqrt{2\lambda}\gamma a)_+ / (1 - a^2\gamma) \right) & \text{if } \underline{a^2\gamma} < 1 \\ u \mathbf{1}_{\{|u| > \sqrt{2\gamma\lambda}\}} + \{0, u\} \mathbf{1}_{\{|u| = \sqrt{2\gamma\lambda}\}} & \text{if } a^2\gamma \geq 1 \end{cases}$$




Figure: Proximal operators. Red: ℓ_0 , Blue: ℓ_1 , Green: Φ_{CELO} (depends on $a = \|a_i\|$ at component $u = x_i$).



Forward-Backward Splitting Algorithm

$$\mathbf{x}^{k+1} \in \text{prox}_{\gamma \Phi_{\text{CELO}}(\cdot)} \left(\mathbf{x}^k - \gamma^k A^T (A \mathbf{x}^k - d) \right),$$

where $0 < \gamma < \frac{1}{\|A\|^2}$ and

$$\text{prox}_{\gamma \phi_{\text{CELO}}(a, \lambda; \cdot)}(u) = \begin{cases} \text{sign}(u) \min \left(|u|, (|u| - \sqrt{2\lambda}\gamma a)_+ / (1 - a^2\gamma) \right) & \text{if } a^2\gamma < 1 \\ u \mathbb{1}_{\{|u| > \sqrt{2\gamma\lambda}\}} + \{0, u\} \mathbb{1}_{\{|u| = \sqrt{2\gamma\lambda}\}} & \text{if } a^2\gamma \geq 1 \end{cases}$$

- Convergence to a critical point under Kurdyka-Lojaseiwicz (KL) property [Attouch et al 13].
- Accelerated algorithm in the non convex case [Li Lin 15]

5.1 Results, ISBI challenge 2013, simulated dataset




Figure: Simulated images (among the 361 simulated high density images for this sample). Data from IEEE ISBI Challenge 2013.

<http://bigwww.epfl.ch/smlm/datasets/index.html>

8 simulated tubes of 30nm diameter

Camera of 64×64 pixels of size 100nm.

Gaussian PSF, FWHM = 258.21 nm (full width at half maximum)

80932 molecules activated on 361 frames.

5.1 Results, ISBI challenge 2013, simulated dataset




Figure: Reconstruction from simulated data set, reduction ratio $L = 4$.

Greedy algorithms (continued)

Matching Pursuit principle

It is assumed without loss of generality that A has unit norm columns, $\|A_{:,i}\| = \|a_i\| = 1$.

The **first component** $i^1 \in \{1, \dots, N\}$ will be such that the **correlation** between d and atom i is maximum: $i^1 = \arg \max_{j \in \{1, \dots, N\}} |\langle a_j, d \rangle|$.

Then the **optimal solution** is $x^1 = (0, 0, \dots, \langle a_{i^1}, d \rangle, 0, \dots, 0)$, where the non null component is at index i^1 , which is written as $x^1 = \langle a_{i^1}, d \rangle \cdot e_{i^1}$, $e_i \in \mathbb{R}^N$, $i \in \{1, \dots, N\}$ is the canonical basis in \mathbb{R}^N .

The criterion is $\|A \cdot x^1 - d\|^2 = \|d\|^2 - (\langle a_{i^1}, d \rangle)^2$.

The **residual** is $r = d - A \cdot x^1 = d - \langle a_{i^1}, d \rangle a_{i^1}$, and the process is repeated.

Matching Pursuit Algorithm

Input: A (with unit norm column), d , K .

Initialize: $r^0 = d, \sigma^0 = \emptyset, (x^0 = 0)$.

Repeat, while $\#\sigma^k \leq K$: (or while $\|r^k\| > \epsilon$)

$$\begin{aligned} i^k &= \arg \max_{j \in \{1, \dots, N\}} |\langle r^k, a_j \rangle| \\ \sigma^{k+1} &= \sigma^k \cup \{i^k\} \\ r^{k+1} &= r^k - \langle r^k, a_{i^k} \rangle a_{i^k} \end{aligned}$$

(1)

σ^k is the support of the current solution x^k , that is the indexes of the non-zero components. $\#\sigma^k$ is the cardinal of σ^k . The initial value of $\#\sigma^0$ is 0 and it increases by 1 at each iteration.

The optimal solution at current iteration is $x^{k+1} = x^k + \langle r^k, a_{i^k} \rangle a_{i^k}$.

- ▶ The residual $\|r^k\|$ converges exponentially to 0 [Mallat et al 93].
- ▶ Sub-optimal solution: retro-project the residual onto $\text{Span}\{(a_i)_{i \in \sigma^k}\}$ reduce the approximation error ($\|A x^k - d\|^2$).

Greedy algorithms (continued)

Orthogonal Matching Pursuit [Pati et al 93, Tropp 04]: at each iteration, optimally estimate the intensities with the current support of the solution fixed, by $\mathbf{x}^{k+1} = \arg \min_{\{\mathbf{x} / \sigma_{\mathbf{x}} \subset \sigma^{k+1}\}} \|\mathbf{A}\mathbf{x} - \mathbf{d}\|^2$.

Orthogonal Matching Pursuit (OMP) Algorithm Input: \mathbf{A} (with

unit norm column), \mathbf{d} , K .

i = intensity

Initialize: $\mathbf{r}^0 = \mathbf{d}$, $\sigma^0 = \emptyset$

Repeat, while $\#\sigma^k \leq K$:

$$i^k = \arg \max_{j \notin \sigma^k} |\langle \mathbf{r}^k, \mathbf{a}_j \rangle|$$

$$\sigma^{k+1} = \sigma^k \cup \{i^k\}$$

$$\mathbf{x}^{k+1} = \arg \min_{\{\mathbf{x} / \sigma_{\mathbf{x}} \subset \sigma^{k+1}\}} \|\mathbf{A}\mathbf{x} - \mathbf{d}\|^2$$

$$\mathbf{r}^{k+1} = \mathbf{d} - \mathbf{A}\mathbf{x}^{k+1}$$

- Convergence in N iterations at most (at each iteration a **new** component is selected),
- Exact sparse recovery results (under conditions on \mathbf{A}) [Tropp 04].

Greedy algorithms (continued)

Further algorithms:

At each iteration, several strategies for one component to be


- ▶ added,
- ▶ removed,
- ▶ replaced.

Orthogonal Least Squares (OLS) [Chen et al 89], *Bayesian OMP* [Herzet et al 10], *Single Best Replacement* [Soussen et al 11] and further variants [Jain & al 11, Soussen et al 15]...

The more complex is the strategy, the best is the solution and the longest is the computing time.

Exact reformulation

- ▶ *Class of continuous nonconvex penalties* → asymptotic connections with the ℓ_2 - ℓ_0 criteria [Chouzenoux et al 13]
- ▶ *Reformulation using Difference of Convex functions* → asymptotic or local minimizer results [Le Thi et al 14, Le Thi et al 15]
- ▶ *Equivalence of ℓ_0 - and ℓ_p -norm ($0 < p \leq 1$) minimization under linear equalities or inequalities (e.g. exact reconstruction problem)* [Fung and Mangasarian 11]
- ▶ *Reformulation and optimization through Mixed-Integer Programs (MIPs)* → global optimum for problems of reasonable size (a few hundred variables) [Bourguignon et al 15]
- ▶ **Exact reformulation** ([Bi et al 14, Yuan & Ghanem 16, Liu et al 18], ...)



Exact reformulation of ℓ_0 : Penalized reformulation

Lemma 1 [Liu et al 18, Yuan & Ghanem 16]

$$\|x\|_0 = \min_{-1 \leq u \leq 1} \|u\|_1 \text{ s.t. } \|x\|_1 = \langle u, x \rangle$$

Exact reformulation for the $\ell_2 - \ell_0$ penalized problem

Initial problem:

$$\min_x \frac{1}{2} \|Ax - d\|_2^2 + \lambda \|x\|_0$$

Penalized reformulation:

$$\min_{x,u} G_\rho(x, u) := \frac{1}{2} \|Ax - d\|_2^2 + \iota_{\{-1 \leq \cdot \leq 1\}}(u) + \lambda \|u\|_1 + \rho (\|x\|_1 - \langle x, u \rangle)$$

with $\iota_{\{x \in D\}}(x) = 0$ if $x \in D$, $+\infty$ otherwise.

Theorem [Bechensteen, et al.]

If $\rho > \sigma_{\max}(A) \|d\|_2$, and A is of full rank. Then:

1. If (x_ρ, u_ρ) is a local (respectively global) minimizer of G_ρ , then x_ρ is a local (respectively global) minimizer of the initial problem.
2. If \hat{x} is a global minimizer of the initial problem, then (\hat{x}, \hat{u}) is a global minimizer of G_ρ with \hat{u} associated with Lemma 1.

Exact reformulation of ℓ_0 : Constrained reformulation

Lemma 1 [Liu et al 18, Yuan & Ghanem 16]

$$\|x\|_0 = \min_{-1 \leq u \leq 1} \|u\|_1 \text{ s.t. } \|x\|_1 = \langle u, x \rangle$$

Exact reformulation for the $\ell_2 - \ell_0$ constrained problem

Initial problem:

$$\min_x \frac{1}{2} \|Ax - d\|_2^2 + \iota_{\{\|\cdot\|_0 \leq K\}}(x)$$

Constrained reformulation:

$$\min_{x,u} G_\rho(x, u) := \frac{1}{2} \|Ax - d\|^2 + \iota_{\{\cdot \geq 0\}}(x) + \iota_{\{-1 \leq \cdot \leq 1\}}(u) + \iota_{\{\|\cdot\|_1 \leq K\}}(u) + \rho(\|x\|_1 - \langle x, u \rangle)$$

Theorem [Bechensteen, et al.]

If $\rho > \sigma_{\max}(A)\|d\|_2$, and A is of full rank. Then:

1. If (x_ρ, u_ρ) is a local (respectively global) minimizer of G_ρ , then x_ρ is a local (respectively global) minimizer of the initial problem.
2. If \hat{x} is a global minimizer of the initial problem, then (\hat{x}, \hat{u}) is a global minimizer of G_ρ with \hat{u} associated with Lemma 1.

Why minimize the constrained or penalized reformulation instead of their initial formulation?

Constrained reformulation:

$$\min_{\mathbf{x}, \mathbf{u}} \frac{1}{2} \|A\mathbf{x} - d\|^2 + \iota_{\{\cdot \geq 0\}}(\mathbf{x}) + \iota_{\{-1 \leq \cdot \leq 1\}}(\mathbf{u}) + \iota_{\{\|\cdot\|_1 \leq K\}}(\mathbf{u}) + \rho(\|\mathbf{x}\|_1 - \langle \mathbf{x}, \mathbf{u} \rangle)$$

Penalized reformulation:

$$\min_{\mathbf{x}, \mathbf{u}} \frac{1}{2} \|A\mathbf{x} - d\|^2 + \iota_{\{\cdot \geq 0\}}(\mathbf{x}) + \iota_{\{-1 \leq \cdot \leq 1\}}(\mathbf{u}) + \lambda \|\mathbf{u}\|_1 + \rho(\|\mathbf{x}\|_1 - \langle \mathbf{x}, \mathbf{u} \rangle)$$

- ▶ Biconvex
- ▶ Non-convexity linked to the coupling term $\langle \mathbf{x}, \mathbf{u} \rangle$
- ▶ Minimizing the reformulation is equivalent to minimize the initial problem regarding local and global minimizers

Exact reformulation of ℓ_0 : Algorithm

We add a positivity constraint on x and we finally define

$$G_\rho(x, u) = \frac{1}{2} \|Ax - d\|^2 + \iota_{\{x \geq 0\}}(x) + \rho \|x\|_1 + \iota_{\{\|\cdot\|_1 \leq K\}}(u) + \iota_{\{-1 \leq \cdot \leq 1\}}(u) - \rho < x, u$$

The global optimization scheme is (continuation method)

Initialize: $\rho^0 > 0, n = 0$

Repeat: Solve the problem G_{ρ^n} :

$$\{x^{n+1}, u^{n+1}\} = \arg \min_{x, u} G_{\rho^n}(x, u)$$

Update: $\rho^{n+1} = \alpha \rho^n, \alpha > 1$

Until: $\rho^{n+1} > \sigma_{\max}(A) \|d\|_2$

Exact reformulation of ℓ_0 : Algorithm

$$G_{\rho^n}(x, u) = \frac{1}{2} \|Ax - d\|^2 + \iota_{\{\cdot \geq 0\}}(x) + \rho^n \|x\|_1 + \iota_{\{\|\cdot\|_1 \leq K\}}(u) + \iota_{\{-1 \leq \cdot \leq 1\}}(u) - \rho^n < \infty$$

At fixed ρ^n we apply the Proximal Alternate Minimization (PAM) algorithm [Attouch & al 10]

Initialize: $u^0 = 0 \in \mathbb{R}^M$

Repeat: $\arg \min G_{\rho^n}$ using alternate minimizations


$$\begin{aligned} \blacktriangleright \{x^{n+1}\} &= \arg \min_x G_{\rho^n}(x, u^n) + \frac{1}{2c^n} \|x - x^n\|^2 \\ &\rightarrow \text{FISTA Algorithm [Beck et al 09]} \end{aligned}$$

$$\begin{aligned} \blacktriangleright \{u^{n+1}\} &= \arg \min_u G_{\rho^n}(x^{n+1}, u) + \frac{1}{2d^n} \|u - u^n\|^2 \\ &\rightarrow \text{Algorithm [Stefanov, 2004]} \end{aligned}$$

Until: convergence


Convergence of the algorithm towards a critical point of G_{ρ^n} for c^n and d^n such that $0 < r_- < c^n, d^n < r_+$ and under KL condition on G_{ρ^n} and assuming that x_n and u_n are bounded [Attouch & al 10].

Results: Single-Molecule Localization Microscopy



$$\hat{\mathbf{x}} \in \arg \min_{\mathbf{x}} \frac{1}{2} \|A\mathbf{x} - d\|_2^2 + \iota_{\{\cdot \geq 0\}}(\mathbf{x}) + R(\mathbf{x})$$

Results: Single-Molecule Localization Microscopy



$$\hat{x} \in \arg \min_x \frac{1}{2} \|Ax - d\|_2^2 + \iota_{\{x \geq 0\}}(x) + R(x)$$




Figure: Simulated images (among the 361 simulated high density images for this sample). Data from IEEE ISBI Challenge 2013.

<http://bigwww.epfl.ch/smlm/datasets/index.html>

8 simulated tubes of 30nm diameter

Camera of 64×64 pixels of size 100nm.

Gaussian PSF, FWHM = 258.21 nm (full width at half maximum)

80932 molecules activated on 361 frames.

Results, ISBI challenge 2013, simulated dataset





Figure: Reconstruction from simulated data set, reduction ratio $L = 4$.

Jaccard index calculus




$$\text{Jaccard index} = \frac{\text{DC}}{\text{DC} + \text{FA} + \text{ND}}$$

Jaccard index results

	Jaccard index (%)			
Method - Tolerance (nm)	50	100	150	200
IHT	20.1	35.9	40.4	41.3
CEL0	29.3	41.3	42.4	42.6
Constrained reformulation	25.2	40.0	43.2	43.9
Penalized reformulation	25.0	39.3	42.2	42.8
Deep-STORM	×	×	×	×

Table: The Jaccard index obtained and the tolerance

Jaccard index calculus



$$\text{Jaccard index} = \frac{\text{DC}}{\text{DC} + \text{FA} + \text{ND}}$$

Jaccard index results

	Jaccard index (%)			
Method - Tolerance (nm)	50	100	150	200
IHT	20.1	35.9	40.4	41.3
CEL0	29.3	41.3	42.4	42.6
Constrained reformulation	25.2	40.0	43.2	43.9
Penalized reformulation	25.0	39.3	42.2	42.8
Deep-STORM	×	×	×	×

Table: The jaccard index obtained and the tolerance

Results, ISBI challenge 2013, Real dataset




Figure: Real images (among the 500 real high density images for this sample).
Data from IEEE ISBI Challenge 2013.

<http://bigwww.epfl.ch/smlm/datasets/index.html>

Camera of 128×128 pixels of size 100nm.

Gaussian PSF, FWHM = 358.1 nm (full width at half maximum)

Results, ISBI challenge 2013, Real dataset




Figure: Reconstruction from the real data set, reduction ratio $L = 4$.

References I



HEDY ATTOUCH, JÉRÔME BOLTE, PATRICK REDONT AND ANTOINE SOUBEYRAN, *Proximal alternating minimization and projection methods for nonconvex problems. An approach based on the Kurdyka-Lojasiewicz inequality*, Mathematics of operation research, 35(2), (2010), pp. 438–457.



HEDY ATTOUCH, JEROMME BOLTE, AND BENAR FUX SVAITER, *Convergence of descent methods for semi-algebraic and tame problems: proximal algorithms, forward-backward splitting, and regularized gauss-seidel methods*, Mathematical Programming, 137 (2013), pp. 91–129.



ARNE BECHENSTEEN, LAURE BLANC-FERAUD AND GILLES AUBERT, *Reformulation of l_2 - l_0 constrained criterion for SMLM*, preprint, 2018.



AMIR BECK AND MARC TEBoulLE, *A fast iterative shrinkage-thresholding algorithm for linear inverse problems*, SIAM Journal on Imaging Sciences, 2 (2009), pp. 183–202.



S. BI, X. LIU, AND S. PAN, *Exact penalty decomposition method for zero-norm minimization based on MPEC formulation*, SIAM Journal on Scientific Computing, 36(4) (2014).



THOMAS BLUMENSATH AND MIKE E DAVIES, *Iterative thresholding for sparse approximations*, Journal of Fourier Analysis and Applications, 14 (2008), pp. 629–654.



J. BIOUCAS-DIAS AND M. FIGUEIREDO, *A new TwIST: Two-step iterative shrinkage/thresholding algorithms for image restoration*, IEEE Transactions on Image processing 16 (12), (2007), pp.2992-3004



LÉON BOTTOU, FRANK E. CURTIS AND JORGE NOCEDAL, *Optimization Methods for Large-Scale Machine Learning*, SIAM Review, 60(2), (2018), pp.223-311.



S. BOYD, N. PARIKH, E. CHU, B. PELEATO, AND J. ECKSTEIN, *Distributed optimization and statistical learning via the alternating direction method of multipliers. Foundations and Trends in Machine Learning*, 3(1), (2011), pp.1-122.

References II



SÉBASTIEN BOURGUIGNON, JORDAN NININ, HERVÉ CARFANTAN AND MARCEL MONGEAU, *Optimisation exacte de critères parcimonieux en norme ℓ_0 par programmation mixte en nombres entiers*, Colloque GRETSI 2015.



LEO BREIMAN, *Better subset regression using the nonnegative garrote*, Technometrics, 37 (1995), pp. 373–384.



BETZIG, ERIC AND PATTERSON, GEORGE H AND SOUGRAT, RACHID AND LINDWASSER, O WOLF AND OLENYCH, SCOTT AND BONIFACINO, JUAN S AND DAVIDSON, MICHAEL W AND LIPPINCOTT-SCHWARTZ, JENNIFER AND HESS, HARALD F, *Imaging intracellular fluorescent proteins at nanometer resolution*, Science, 5793 (2006), pp. 1642-1645.



L. BREGMAN, *A Relaxation Method of Finding a Common Point of Convex Sets and its Application to Problems of Optimization*, Dokl. Akad. Nauk SSSR, 171(5), (1966) pp. 1019-1022. (English translation: Soviet Math. Dokl., v. 7, 1966, p.p. 1578-1581).



EMMANUEL J CANDÉS, JUSTIN ROMBERG, AND TERENCE TAO, *Robust uncertainty principles: Exact signal reconstruction from highly incomplete frequency information*, Information Theory, IEEE Transactions on, 52 (2006), pp. 489–509.



EMMANUEL J CANDÉS, MICHAEL B WAKIN, AND STEPHEN P BOYD, *Enhancing sparsity by reweighted ℓ_1 minimization*, Journal of Fourier analysis and applications, 14 (2008), pp. 877–905.



EMMANUEL J CANDÉS, AND MICHAEL B WAKIN, *An introduction to compressive sampling*, IEEE Signal Processing Magazine, 25(2), (2008), pp. 21–30.



P. CATALA, V. DUVAL AND G. PEYRE, *A low - rank approach to off - the - grid sparse deconvolution*, NCMIP conf 2017, arXiv 2019.



RICK CHARTRAND, *Exact reconstruction of sparse signals via nonconvex minimization*, Signal Processing Letters, IEEE, 14 (2007), pp. 707–710.

References III



S. CHEN, S. BILLINGS AND W. LUO, *Orthogonal least squares methods and their application to non-linear system identification*, International journal of Control, 50(5) (1989), pp. 1873–1896.



SCOTT SHAOBING CHEN, DAVID L DONOHO, AND MICHAEL A SAUNDERS, *Atomic decomposition by Basis Pursuit*, SIAM journal on scientific computing, 20 (1998), pp. 33–61.



EMILIE CHOUZENOUX, ANNA JEZIERSKA, JEAN-CHRISTOPHE PESQUET AND HUCUES TALBOT, *A majorize-minimize subspace approach for ℓ_2 - ℓ_0 image regularization*, SIAM Journal on Imaging Sciences, 6 (2013), pp.563–591.



FRANK H CLARKE, *Optimization and nonsmooth analysis*, vol. 5, Siam, 1990.



PATRICK COMBETTES AND V. WAJS, *Signal recovery by proximal forward-backward splitting*, Multiscale Modeling and Simulation, 4(4), (2005), pp. 1168-1200.



INGRID DAUBECHIES, MICHEL DEFRISE, AND CHRISTINE DE MOL, *An iterative thresholding algorithm for linear inverse problems with a sparsity constraint*, Communications on Pure and Applied Mathematics, 57 (2004), pp. 1413–1457.



GEOFF DAVIS, STEPHANE MALLAT AND MARCO AVELLANEDA *Adaptive greedy approximations*, Constructive approximation, 13 (1997), pp. 57–98.



DAVID L DONOHO AND MICAEL ELAD, *Optimally sparse representation in general (nonorthogonal) dictionaries via ℓ_1 minimization*, in Proceedings of the National Academy of Sciences 100(5) (2003), pp. 72–76.



DAVID L DONOHO, *For most large underdetermined systems of linear equations the minimal ℓ_1 -norm solution is also the sparsest solution*, Communications on Pure and Applied Mathematics, 59 (2006), pp. 797–829.



DAVID L DONOHO, *Compressed sensing*, IEEE Transactions on Information Theory. 52 (4), (2006), pp. 1289?1306.

References IV



M. ELAD, B. MATALON, AND M. ZIBULEVSKY, *Subspace optimization methods for linear least squares with non-quadratic regularization*, Appl. Comput. Harmon. Anal., 23 (2007), pp. 346–367.



JON THAN ECKSTEIN, *Augmented Lagrangian and Alternating Direction Methods for Convex Optimization: A tutorial and some illustrative computational results*, Rutcor Resaerch Report, RRR 32-2012 (2012).



JIANQING FAN AND RUNZE LI, *Variable selection via nonconcave penalized likelihood and its oracle properties*, Journal of the American Statistical Association, 96 (2001), pp. 1348–1360.



SIMON FOUCART AND MINC-JUN LAI, *Sparsest solutions of underdetermined linear systems via ℓ_q -minimization for $0 < q \leq 1$* , Applied and Computational Harmonic Analysis, 26 (2009), pp. 395–407.



G.M. FUNG AND O.L. MANGASARIAN, *Equivalence of minimal ℓ_0 - and ℓ_p -norm solutions of linear equalities, inequalities and linear programs for sufficiently small p* , Journal of optimization theory and applications, 151 (2011), pp. 1–10.



GILLES GASSO, ALAIN RAKOTOMAMONJY, AND STÉPHANE CANU, *Recovering sparse signals with a certain family of nonconvex penalties and DC programming*, Signal Processing, IEEE Transactions on, 57 (2009), pp. 4686–4698.



R. GLOWINSKI AND A. MARROCO, *Sur l'approximation par éléments finis d'ordre un et la résolution, par pénalisation-dualité, d'une classe de problèmes de Dirichlet non linéaires*, Revue Francaise d'Automatique, Informatique, et Recherche Opérationnelle, 9, (1975) pp.41-76.



T. GOLDSTEIN AND S. OSHER *The split Bregman method for ℓ_1 -regularization problems*, SIAM Journal of Imaging Sciences, 2(2) (2009), pp. 323–343.

References V



PINGHUA GONG, CHANGSHUI ZHANG, ZHAOSONG LU, JIANHUA HUANG, AND JIEPING YE, *A General Iterative Shrinkage and Thresholding Algorithm for Non-convex Regularized Optimization Problems*, in Proceedings of The 30th International Conference on Machine Learning (2013), pp. 37–45.



REMI GRIBONVAL AND MORTEN NIELSEN, *Sparse representation in unions of bases*, IEEE Transactions on Information Theory, 49(12), (2003), pp. 73–76.



HESS, SAMUEL T AND GIRIRAJAN, THANU PK AND MASON, MICHAEL D *Ultra-high resolution imaging by fluorescence photoactivation localization microscopy* Biophysical journal, 11 (2006), Elsevier, pp. 4258-4272.



CÉDRIC HERZET AND ANGÉLIQUE DRÉMEAU, *Bayesian Pursuit Algorithms* , in Proceedings of European Signal Processing conference (EUSIPCO), Aalborg, Danemark, August 2010.



SEAMUS J HOLDEN, STEPHAN UPHOFF AND ACHILLEFS N KAPANIDIS *DAOSTORM: an algorithm for high-density super-resolution microscopy* Nature Methods, 8 (2011), pp. 279–280.



P. JAIN, A. TEWARI AND I.S.DHILLON *Orthogonal Matching Pursuit with Replacement* Advanced in Neural Information Processing Systems, 24 (2011), pp. 1215–1223.



HOAI AN LE THI, HOAI MINH LE AND TAO PHAM DINH, *Feature selection in machine learning: an exact penalty approach using a Difference of Convex function Algorithm*, Machine Learning, 2014, pp. 1–24.



HOAI AN LE THI, TAO PHAM DINH, HOAI MINH LE AND XUAN THANH VO, *DC approximation approaches for sparse optimization*, European Journal of Operational Research, 244 (2015), pp. 26-46.



HUAN LI AND ZHOUCHE LIN, *Accelerated Proximal Gradient Methods for Nonconvex Programming*, Part of: Advances in Neural Information Processing Systems 28 (NIPS 2015), pp. 679-704.

References VI



YULAN LIU, SHUJUN. BI, AND SHOAHUA PAN, *Equivalent Lipschitz surrogates for zero-norm and rank optimization problems.*, Journal of Global Optimization, 72 (4), (2018), pp. 679?704.



STÉPHANE G MALLAT AND ZHIFENG ZHANG, *Matching pursuits with time-frequency dictionaries*, Signal Processing, IEEE Transactions on, 41 (1993), pp. 3397–3415.



OL MANCASARIAN *Machine learning via polyhedral concave minimization* Applied Mathematics and Parallel Computing (1996), pp. 175–188.



MIN, J. AND VONESCH, C. AND KIRSHNER, H. AND CARLINI, L. AND OLIVIER, N. AND HOLDEN, S. AND UNSER, M. *FALCON: fast and unbiased reconstruction of high-density super-resolution microscopy data*. Scientific Reports, 4 (2014), pp. 4577.



HOSEIN MOHIMANI, MASSOUD BABAIE-ZADEH AND CHRISTIAN JUTTEN, *A fast approach for overcomplete sparse decomposition based on smoothed ℓ_0 norm*, Signal Processing, IEEE Transactions on, 57 (2008), pp. 289–301.



BALAS KAUSIK NATARAJAN *Sparse approximate solutions to linear systems*, SIAM journal on computing, 24 (1995), pp. 227–234.



YURI NESTEROV *Gradient methods for minimizing composite functions*, Mathematical Programming, 140(1), (2013), pp 125?161



MILA NIKOLOVA, *Description of the minimizers of least squares regularized with ℓ_0 -norm. Uniqueness of the global minimizer*, SIAM Journal on Imaging Sciences, 6 (2013), pp. 904–937.



MILA NIKOLOVA, *Relationship between the optimal solutions of least squares regularized with L_0 -norm and constrained by k -sparsity*, Appl. Comput. Harmon. Anal., 41(1), (2016), pp. 237–265.



JORGE NOCEDAL AND STEPHEN J. WRIGHT, *Numerical Optimization* , Springer, 2 edition (2006).

References VII



P. OCHS, A. DOSOVITSKIY, T. BROX, AND T. POCK, *An iteratively reweighted Algorithm for Non-smooth Non-convex Optimization in Computer Vision*, SIAM Journal on Imaging Sciences, 8(1), 2015.



YACYENSH CHANDRA PATI, RAMIN REZAIIFAR, AND PS KRISHNAPRASAD, *Orthogonal matching pursuit: Recursive function approximation with applications to wavelet decomposition*, in Signals, Systems and Computers, 1993. 1993 Conference Record of The Twenty-Seventh Asilomar Conference on, IEEE, 1993, pp. 40–44.



R. T. ROCKAFELLAR, *Convex analysis* Princeton Landmarks in Mathematics. Princeton University Press, Princeton, NJ, (1997). Reprint of the 1970 original, Princeton Paperbacks.



RUST, MICHAEL J AND BATES, MARK AND ZHUANG, XIAOWEI *Sub-diffraction-limit imaging by stochastic optical reconstruction microscopy (STORM)*, Nature methods, 10 (2006), pp. 793-796.



DANIEL SAGE, HACAI KIRSHNER, THOMAS PENCO, NICO STUURMAN, JUNHONG MIN, SULIANA MANLEY AND MICHAEL UNSER, *Quantitative evaluation of software packages for single-molecule localization microscopy*, in Nature methods, 2015, pp. 717–724.



STEFAN M. STEFANOV *Convex quadratic minimization subject to a linear constraint and box constraints* Applied Mathematics Research Express, 1 (2004), pp. 17-42.



EMMANUEL SOUBIES, LAURE BLANC-FERAUD AND GILLES AUBERT *A Continuous Exact l_0 Penalty (CEL0) for Least Squares Regularized Problem*, SIAM Journal on Imaging Sciences, 8(3), 2015.



EMMANUEL SOUBIES, LAURE BLANC-FERAUD AND GILLES AUBERT *A Unified View of Exact Continuous Penalties for l_2 - l_0 Minimization*, SIAM Journal of Optimization, 27(3), 2017.



CHARLES SOUSSEN, JEROME IDIER, DAVID BRIE, AND JUNBO DUAN, *From Bernoulli–Gaussian deconvolution to sparse signal restoration*, Signal Processing, IEEE Transactions on, 59 (2011), pp. 4572–4584.

References VIII



CHARLES SOUSSEN, JEROME IDIER, JUNBO DUAN AND DAVID BRIE, *Homotopy Based Algorithms for ℓ_0 -Regularized Least-Squares*, Signal Processing, IEEE Transactions on, 63(13) (2015), pp. 3301–3316.



R. TIBSHIRANI, *Regression shrinkage and selection via the lasso*, Journal of the Royal Statistical Society, 46 (1996), pp. 431–439.



JOEL A TROPP, *Greed is good: Algorithmic results for sparse approximation*, Information Theory, IEEE Transactions on, 50 (2004), pp. 2231–2242.



GANZHAO YUAN AND BERNARD GHANEM, *Sparsity Constrained Minimization via Mathematical Programming with Equilibrium Constraints*, arXiv:1608.04430 (2016).



CUN-HUI ZHANG, *Multi-stage convex relaxation for learning with sparse regularization*, Advances in Neural Information Processing Systems, (2009), pp. 1929–1936.



CUN-HUI ZHANG, *Nearly unbiased variable selection under minimax concave penalty*, The Annals of Statistics, (2010), pp. 894–942.



HUI ZOU, *The adaptive lasso and its oracle properties*, Journal of the American statistical association, 101 (2006), pp. 1418–1429.