

1. Aging is a solution to the starvation problem

1 Point

- ☒ True
- ☐ False

2. 4 processes A,B,C,D have estimated burst times of 4,5,6,7 ns respectively. They are scheduled in round robin fashion and the time slice is of 2ns. The processes A,B,C,D arrive at the 0,0.1,0.2,0.3 ns respectively. At what time will the process A complete? _____

1 Point

14

3. 4 processes A,B,C,D have estimated burst times of 4,5,6,7 ns respectively. They are scheduled in round robin fashion and the time slice is of 2ns. The processes A,B,C,D arrive at the 0,0.1,0.2,0.3 ns respectively. At what time will all the processes complete? _____

1 Point

22

4. 4 processes A,B,C,D have estimated time of completion of 5,7,9,11 ns each. They are scheduled in round robin fashion and the time slice is of 2ns. The processes A,B,C,D arrive at the 0,1,2,3 ns respectively. At what time will the process C complete? _____

1 Point

29

5. 4 processes A,B,C,D have estimated time of completion of 5,7,9,11 ns each. They are scheduled in round robin fashion and the time slice is of 2ns. The processes A,B,C,D arrive at the 0,1,2,3 ns respectively. At what time will the processes complete execution? _____

1 Point

32

6. In Question 4, what will be the completion time of process C, if Shortest Job First was used instead of Round Robin._____

1 Point

21

7. Many more context switches occur when using (non-pre-emptive) Shortest Job First scheduling instead of Round Robin scheduling

1 Point

☐ True

☒ False

8. A Round Robin Scheduling algorithm with a large time slice will behave similar to a First-Come-First-Serve algorithm.

1 Point

☒ True

☐ False

9. The overhead due to context switches is less if the time slice durations are small

1 Point

☐ True

☒ False

10. Starvation can occur in the Shortest Remaining Time First (SRTF) algorithm and Shortest Job First (SJF) algorithm.

1 Point

☒ True

☐ False

You may submit any number of times before the due date. The final submission will be considered for evaluation.

Submit Answers