



Greedy Method

It is one of strategy to solve the problems

This method is used for solving Optimisation Problem
 either min or Max



P: 4 → B minimising cost



** For any problem, there is only one optimal solⁿ

- 1 Greedy method
2. Dynamic programming
3. Branch and Bound

* Above three strategies are used to solve optimisation Problem, Approach is different for solving Problem by different strategies

General method of Greedy

Algorithm Greedy(a, n)

$n=5$
a

q_1	q_2	q_3	q_4	q_5
1	2	3	4	5

For $i=1$ to n do -

$x = \text{select}(a);$

IF Feasible(x) then

solution = solution + x;

Greedy method statement

- Problem should be solved in stages
- In each stage we will consider input from given problem
- If that input is Feasible, we will include it into solution
- by including all those Feasible we will get optimal solution.

ex:-

For selecting one ^{best} person among 1000

- written Test
- Technical Test / Group Discussion
- Technical interview / HR interview

Knapsack p

$n=7$ 06

$m=15$

Fill

Constraint

15 kg


soln:-

highest profit
lowest

→ we should
Profit

Knapsack Problem

$n=7$ Objects: 0 1 2 3 4 5 6 7
 $m=15$ Profits: P 10 5 15 7 6 18 3
 weights: w 2 8 5 7 1 4 1




Assumption:- Objects are divisible

Fill such that profit is Maximized

Constraint $\rightarrow$ Total weight should be less than 15 kg

Soln:- x ($x_1, x_2, x_3, x_4, x_5, x_6, x_7$)



$\rightarrow$ we should select object having highest profit per kg weights


P	5	1.3	3	1	6	4.5	3
w							

Greedy method:-

First you decide how you are going to select an input & go on selecting input one by one.

P	10	5	15	7	6	18	3
w	2	3	5	7	1	4	1

P/w	5	1.3	3	1	6	4.5	3
quantity	2	1	3	1	3	4	3
	②	③	④	⑤	①	③	⑤



$$15 - 1 = 14 \text{ kg}$$

$$14 - 2 = 12$$

$$12 - 1 = 8$$

$$8 - 5 = 3$$

$$3 - 1 = 2$$

$$* 2 - 2 = 0 \times$$

$\Sigma (x_i \cdot w_i)$

weight Profit: $1 \times 2 + 2 \times 3 + 1 \times 5 + 0 \times 7 + 1 \times 1$

$$= 2 + 2 + 5 + 0 + 1 + 1 = 15 \text{ kg}$$

$\Sigma x_i \cdot P_i$

Profit $\rightarrow 1 \times 10 + 2 \times 5 + 1 \times 15 + 1 \times 6 + 1 \times 18$

$$= 54.6$$

0.1 Knapsack

$\rightarrow$ It is a things r y

Job Sequencing

$n = 5$
Jobs
Profits
deadlines

Assume $\rightarrow$ each job

Complete their dead

Optimisation

0 $\downarrow$
14 9 $\downarrow$
 $\downarrow$
 $\downarrow$

First gone to M

0.1 Knapsack problem

→ It is Container loading with indivisible things [you can't take part of it]

Job Sequencing with deadlines

$n=5$

Jobs	J_1	J_2	J_3	J_4	J_5
Profits	20	15	10	5	1
deadlines	2	2	1	3	3

3 hrs

Assume → each job take one unit of time on completion

Job → Machine → 1 unit

Complete each job set of jobs done within their deadline such that profit is maximized.

Optimisation problem → Greedy method

always select max one & check slot is empty or not

AM 9 ↓ 10 ↓ 11 ↓ 12
 J_2 J_1 J_4

↓ J_2, J_1, J_4

First gone to Max²

Ans → $J_1 \rightarrow J_2 \rightarrow J_4$

$J_2 \rightarrow J_4 \rightarrow J_1$ having same order

0-1-2-3

Job Consider	slot assign	solution	Profit
J_1	$[1,2]$	0	0
J_2	$[0,1], [1,2]$	J_1	20
$J_3 \times$	$[0,1], [1,2]$	J_1, J_2	20+15
J_4	$[0,1], [1,2], [2,3]$	J_1, J_2, J_4	20+15
$J_5 \times$	"	"	40

Optimal

List $\rightarrow A$
 sizes $\rightarrow 6$

Greedy selection

Optimization problem

↓
 Greedy method


3 2 1 0

2 1 0 1 2 3 4 5 6


Find optimal
 answer

Optimal Merge Pattern

tion	Profit
1	0
2	20
3	20+15
4	20+15+10
5	40



List $\rightarrow$ A B C D
 sizes $\rightarrow$ 6 5 2 3




$11+8+16 \text{ steps}$
 $= 40$

Find optimal way so that, it can be merged into least steps

Huffman

it is the size

Message $\rightarrow$ 8




$$11 + 5 + 16 = 32$$

$$16 + 10 + 5 = 31$$

Greedy method

$\rightarrow$ always select a pair of small size list to get best result

2. list $\rightarrow x_1, x_2, x_3, x_4, x_5$
 sizes $\rightarrow 20, 30, 10, 5, 30$



$$15 + 35 + 45 + 60 = 205$$

$$3 \times 5 + 3 \times 10 + 2 \times 20 + 2 \times 30 = 205$$

heights $\times$ distances

$$\sum d_i \times x_i$$

Huffman Coding

it is compression technique used for reducing the size of data or message.

Message $\rightarrow$ B C C A B B D D A E C C B B A E D D C C

length = 20

ASCII - 8-bits

A	65	01000001
B	66	01000010
C	67	
D	68	
E	69	

8x20 = 160 bits

size without coding

$$= 205$$

$$20 + 2 \times 80 = 205$$

* * *

B C C A B B D D A E C C B B A E D D C C

20 bits = 3x05

Message - B C C A B B D A E C C B B A E D D C C

⇒ Fixed size coding

Character	Count/Frequency	Code
A	8 $\frac{3}{40}$	000
B	5 $\frac{5}{20}$	001
C	6 $\frac{6}{20}$	010
D	4 $\frac{4}{20}$	011
E	2 $\frac{2}{20}$	100
For 128 Symbols		20

we are using only 5 characters so not 8 bits will be required, 8 bit is required

1 bit → 0/1

2 bit → 00
01
10
11

3 bit → 000
001
010
011
100
101
110
111

Message - B C C A B B D A E C C B B A E D D C C
001 010

$$20 \times 3 = 60 \text{ bits}$$

we have to

5x

⇒ Huffman

?

1 have given

any other three bits

can

0

6

7

we have to also send table correspond to character for Decoding

$5 \times 8 \text{ bits}$

5×3

character symbols

codes

$100 + 15 = 115$

Msg - 60 bits


Table - 55 bits

115 bits

Huffman Coding [Variable size Coding]

We don't have to take Fixed size Codes, some character may be appearing some time & some may be appearing more time.

If you give small size Code for more appearing character the size of entire message can be reduced



Message - B C C A B B D D A E C C B B A E D D C C

Step 4 → F

From

A →

B →

Message

Me

Along with
chart / Tree

Alpha

8 bits

=

Me

Tree

Char	Count	Code	Size
A	3	001	$3 \times 3 = 9$
B	5	10	$5 \times 2 = 10$
C	6	11	$6 \times 2 = 12$
D	4	01	$4 \times 2 = 8$
E	2	000	$2 \times 3 = 6$
F	2		45 bits


Step 1 → Arrange all alphabets into increasing number of their

Count

[2] F [3] A [4] D [4] B [5] C [6] E

Step 2 → Optimal Merge Pattern should be

Followed on this one [Greedy approach]



$$\sum d_i \cdot f_i$$

$$= 2 \times 2 + 3 \times 3$$

$$+ 4 \times 2 + 5 \times 4 + 6 \times 6$$


$$= 41 \text{ bits}$$

Step 3 → left side edges Mark them as 0

& right side edges mark them as 1

Message $\rightarrow$ B C C D A C C B D A B C C D E A A E D A

001 11 11 01 10 11 11 00 01 10 00 11 11 0



Decode = ? $\rightarrow$ Do by self

$\rightarrow$ Do with help of tree

B C C D - - -

Revised it [As]

Q: N meeting

what is meeting

in one room

$N = 6$

start $[] = \{1,$

end $[] = \{2,$

OP: - 4

(1,2), (3,4), (5,

$S() = 1, 0$

$F() = 2, 6$

1, 2

if 2 is

that

① ③

strict meeting

not

not

not

not

not

not

not

not

not

not

void maxMeetings (int s[], int e[], int n) {
 struct meeting meet[n];

for (int i = 0; i < n; i++) {

meet[i].start = s[i], meet[i].end = e[i], meet[i].pos =

sort (meet, meet+n, Comparator);

vector<int> answer;

int limit = meet[0].end;

answer.push_back (meet[0].pos);

for (int i = 1; i < n; i++) {

if (meet[i].start > limit) {

limit = meet[i].end;

answer.push_back (meet[i].pos);

for (int i = 0; i < answer.size(); i++) {

cout << answer[i] << " ";

Q. Minimum Platforms

Given arrival and departure times of all trains that reach a railway station. Find minimum number of platforms required for railway station

So that no train is kept waiting

Input: n = 6

arr[] = {0900, 0940, 0950, 1100, 1500, 1800}

dep[] = {1000, 1200, 1120, 1180, 1900, 2000}

o/p:- 3

return result;

0) {

arr[i].pos;

);

};

1 = 02

2 = 04

arr[i].pos;

); i++) {

};

If all trains
ind minion
railway sta
iting

1800

10, 2000

start = { 120, 50, 550, 200, 700, 850 }

end = { 600, 550, 700, 500, 900, 1000 }

sort both
start and
end array

start[] = { 50, 120, 200, 550, 700, 850 }

end[] = { 500, 550, 600, 700, 900, 1000 }


sorted

plat = 1 2 3

2 8 2

1 2 1 2

max = 1 2 3



Railway station

TC $\rightarrow O(\log n) + O(n)$

Sorting array $\rightarrow$ pointer approach

SC $\rightarrow O(1)$

int findPlatform (int arr[], int dep[], int n)

{

sort (arr, arr+n);

sort (dep, dep+n);

int plat-needed = 1, result = 1;

int i = 1, j = 0;

while (i < n && j < n) {

if (arr[i] <= dep[j]) {

plat-needed++;

i++;

else if (arr[i] > dep[j]) {

plat-needed--;

j++;

if (plat-needed > result) {

result = plat-needed;

return result;

}

Q. Job - Sequencing Problem [each take unit time]
 N = 4
 Jobs = { (1, 4, 20), (2, 1, 10), (3, 1, 40), (4, 1, 30) }

coins[] = [

O/P:- 2 GO
 no of Job Profit
 By Putting static
 Passed on GFG

Pair (int, int) Jobscheduling (Job arr[], int n)

sort (arr, arr+n, mycomp);
 int Prof=0;
 int Count=0;
 int A[n]=0;

Think by this

1	4	50
2	1	10
3	1	40
4	1	30

for (int i=0; i<n; i++)

for (int j = min(0, arr[i]-dead-1); j<=arr[i]; j++)

if (A[j] == 0)
 {
 A[j]++;
 Count++;

Profit += arr[i];
 break;

Pair (int, int) P;

P = max_Pair (Count, Profit);
 return P;

}

Unit time

$(1, 30)$

arr, probarr

Profit $< arr[1] \cdot arr[0]$

intn)

$arr[1] \cdot arr[0]$

$arr[1] \cdot arr[0]$

$arr[1] \cdot arr[0]$

Profit

Min² - 20. OF Coins needed to make 5400
coins[] = [1, 2, 5, 10, 20, 50, 100, 500, 1000], v = 49

v = 49 29 9 4 20

20
20
5
2
2

↓
here greedy Fails

[1, 5, 6, 9]

v = 11

→ greedy 9 1 1 1

Dynamic

5 | 2
6 | 2

$$\begin{matrix} e & 1 \\ 2 & 1 \end{matrix}$$

Dominic

$$\begin{bmatrix} 1 & 2 & e & a \\ 1 & 1 & 1 & 1 \end{bmatrix} \xrightarrow{R_2 - R_1} \begin{bmatrix} 1 & 2 & e & a \\ 0 & 0 & 0 & 0 \end{bmatrix}$$

per 8 days trip

$$\begin{matrix} 1 & 2 & e & a \\ 1 & 1 & 1 & 1 \end{matrix}$$

$$\begin{bmatrix} 1 & 2 & e & a \\ 1 & 1 & 1 & 1 \end{bmatrix} \xrightarrow{R_2 - R_1} \begin{bmatrix} 1 & 2 & e & a \\ 0 & 0 & 0 & 0 \end{bmatrix}$$

per 8 days trip