International Journal of Scientific Research in Computer Science, Engineering and Information Technology

ISSN : 2456-3307 OPEN ACCESS

Available Online at : www.ijsrcseit.com

doi : https://doi.org/10.32628/CSEIT25112433

AI and Machine Learning in Payment Systems: Unlocking Higher Approval Rates and Lower Fees

Krishna Chaitanya Saride

Andhra University, India

ARTICLEINFO

Article History:

Accepted : 07 March 2025

Published: 09 March 2025

Publication Issue

Volume 11, Issue 2

March-April-2025

Page Number

858-877

ABSTRACT

This article explores the implementation of artificial intelligence and machine learning techniques in payment processing systems to optimize transaction routing decisions. In the modern payments ecosystem, merchants face significant challenges with varying approval rates across different processing paths based on factors, including card type, issuing bank, transaction geography, and merchant category. Through analyzing several machine learning approaches—ranging from decision trees to advanced neural networks and reinforcement learning—the article demonstrates how intelligent routing systems can significantly enhance approval rates while simultaneously reducing processing costs. The article evaluates the effectiveness of various ML models in identifying optimal routing paths based on historical performance data and transaction attributes, highlighting strategies such as issuer-specific routing, prevention of futile authorization attempts, dynamic fee optimization, adaptive retry mechanisms, and cross-border transaction handling. Additionally, the article addresses critical implementation challenges, including latency requirements, data quality

Copyright © 2025 The Author(s) : This is an open access article under the CC BY license (http://creativecommons.org/licenses/by/4.0/)

concerns, regulatory compliance, and concept drift, offering practical frameworks for deploying these systems in high-volume production environments.

Keywords: Payment optimization, machine learning, transaction routing, approval rates, dynamic fee optimization

Introduction

In the global payments ecosystem, merchants face significant challenges in optimizing transaction approvals and minimizing processing costs. With the proliferation of payment methods and the complexity of financial networks, merchants often rely on multiple acquirers to process transactions. However, approval rates can vary dramatically based on numerous factors, including card type, issuing bank, transaction geography, and merchant category.

The digital payments market has experienced remarkable growth, valued at USD 95.2 billion in 2023, and is projected to expand at a compound annual growth rate (CAGR) of 15.7% from 2024 to 2030, according to Grand View Research's comprehensive market analysis [1]. This substantial growth is driven by the increasing adoption of smartphones, the proliferation of e-commerce platforms, and the shifting consumer preference toward digital and contactless payment solutions. Within this expanding landscape, merchants encounter substantial disparities in authorization success rates, with the report highlighting that approval rate variations of 10-20% can be observed across different acquirers for identical transaction profiles, particularly when comparing traditional bank-based systems with emerging digital wallet solutions.

The optimization challenge is particularly pronounced in cross-border transactions, where McKinsey's Global Payments Report 2024 indicates that approval rates typically decrease by 5-8% compared to domestic transactions due to increased fraud concerns, regulatory differences, and technical integration challenges [2]. The report emphasizes that large enterprises employing sophisticated payment orchestration can achieve average approval rate improvements of 7.6% and cost reductions of 11.2% through intelligent routing mechanisms. This translates to a significant bottom-line impact, as McKinsey's analysis reveals that a mere one percentage point increase in approval rates can generate approximately 0.9-1.1% additional revenue for merchants, representing millions in recovered sales for high-volume processors. The study further notes that global payments revenue reached $2.2 trillion in 2023, with transaction banking and payments processing constituting approximately 40% of this value, highlighting the enormous financial incentive for optimization.

This paper explores how artificial intelligence and machine learning techniques can revolutionize transaction routing decisions, enabling merchants to select the optimal processing path for each authorization request. These intelligent systems can significantly enhance approval rates while reducing transaction costs by analyzing historical approval patterns and transaction attributes in real-time. Recent implementations of machine learning-based routing systems have demonstrated approval rate improvements of 5.8-8.7% and processing cost reductions of 10.5-13.8% compared to traditional static routing approaches, according to McKinsey's analysis of payment infrastructure investments across 150+ financial institutions and payment processors [2]. The report further suggests that institutions

implementing advanced data analytics and machine learning capabilities for payment routing can expect to reduce their total cost of operations by 15-20% while simultaneously improving customer experience through higher transaction success rates.

The Challenge of Payment Processing Optimization

2.1. Complexity of the Payment Ecosystem

Modern payment processing involves a complex ecosystem of interconnected stakeholders, creating a multifaceted network that processes billions of daily transactions across global markets. According to Giraldo Mora et al.'s comprehensive analysis of global payment infrastructure, this ecosystem includes merchants, payment gateways, payment processors, acquiring banks, card networks (Visa, Mastercard, etc.), issuing banks, and alternative payment methods [3]. Their research reveals that across 54 countries studied, over 70 instant payment systems were operational by 2020, with an additional 40 systems in various stages of development or implementation. The study further indicates that transaction processing times have decreased from an industry average of 3-5 seconds in 2010 to sub-second response times in mature markets by 2020, increasing demands on routing optimization systems to make decisions within extremely tight timeframes.

Giraldo Mora et al. note that while card-based payments remain dominant in North America and Europe (accounting for 61% and 47% of non-cash transactions, respectively), alternative payment methods have gained significant market share in Asia-Pacific regions, where mobile wallet transactions represented 56% of e-commerce payments in 2019 [3]. The research highlights that this heterogeneity in payment methods creates significant integration challenges, with the average enterprise merchant integrating with 4-6 distinct payment processors to ensure adequate market coverage. The study further reveals that each payment transaction typically traverses between 6-8 distinct processing entities before completion, with each entity applying its own risk assessment algorithms and approval criteria. This multi-layered ecosystem increases complexity for merchants, who must contend with fragmented payment landscapes where approval rates can vary by 12-18% across different processing paths for otherwise identical transactions. Merchants seeking to maximize approval rates must navigate this complexity effectively, with the research demonstrating that enterprises employing sophisticated payment orchestration layers achieve 7-9% higher overall approval rates than those utilizing single-processor approaches.

2.2. Factors Affecting Transaction Approval

Transaction approvals are influenced by numerous attributes that collectively determine the likelihood of successful processing. According to Cognizant's comprehensive analysis of real-time settlement systems, transaction-specific factors such as amount, currency, and type (authorization, verification, capture, reversal) significantly impact approval rates [4]. Their research indicates that high-value transactions (exceeding $1,000) experience 9-14% lower approval rates than transactions under $100, widening this gap to 16-22% for cross-border high-value transactions. The Cognizant study further reveals that currency conversion introduces an additional 4-7% decline in approval rates for international transactions, with particular challenges for emerging market currencies where forex volatility can trigger additional risk assessments.

Card details, including brand (Visa, Mastercard, etc.), type (credit, debit, gift), issuing bank, and country of issuance, create substantial variance in approval patterns. Giraldo Mora et al.'s research demonstrates that credit products generally achieve 6-9% higher approval rates than debit products for identical transaction parameters, with premium card products showing an additional 3-5% approval advantage over standard offerings [3]. Their analysis of 23 major markets reveals that approval rate disparities between the highest and lowest-performing issuers within individual markets can exceed 15%, creating

significant challenges for merchants operating in multiple geographies. The research further indicates that issuer approval rates can fluctuate by 5-8% over a fiscal quarter due to internal risk policy adjustments, requiring continual recalibration of routing algorithms to maintain optimal performance.

Merchant factors, including industry category code, reputation, and chargeback history, create another layer of complexity. Cognizant's analysis indicates that merchants in high-risk categories (such as gambling, travel, and digital goods) experience average approval rates 10-16% lower than those in traditional retail, regardless of other transaction attributes [4]. Their study shows that merchants with chargeback ratios exceeding 1% of transactions face an additional 6-9% reduction in approval rates across all card types. Furthermore, the research demonstrates that merchant category codes (MCCs) significantly influence interchange rates and approval probabilities, with variations of up to 120 basis points in processing costs between favorable and unfavorable categorizations. Cognizant's data indicates that large enterprises utilizing multiple MCCs for different business units can experience approval rate variations of 7-11% between these units despite identical risk profiles, highlighting the importance of optimizing merchant categorization.

Entry method (manually entered, magnetic stripe, EMV chip, contactless, tokenized), authentication details (card security code availability, 3D Secure usage), point of sale environment (in-store, e-commerce, MOTO, unattended, recurring), cardholder verification (none, PIN, biometrics, offline verification), and transaction initiation (customer-initiated or merchant-initiated) each introduce their own approval variances. Giraldo Mora et al. highlight that card-present transactions utilizing EMV chip technology achieve approval rates 13.6% higher than manually entered online transactions without strong authentication [3]. Their research shows that implementing 3D Secure 2.0 protocols has increased approval rates by 9.2% for participating merchants compared to non-authenticated transactions, though this comes at the cost of a 2.5% increase in cart abandonment rates during the authentication process. For mobile transactions, the study indicates that tokenized payments through digital wallets achieve 11.4% higher approval rates than traditional card-not-present methods, reflecting the enhanced security and reduced fraud associated with these transaction types.

The interplay of these factors creates a multi-dimensional decision space that Cognizant's research estimates encompass over 18,000 distinct transaction routing scenarios [4]. Their analysis reveals that traditional rule-based routing approaches typically address only 200-300 routing scenarios and fail to adapt to changing network conditions or issuer behavior patterns. According to their findings, static routing approaches leave an estimated 5-8% of potential approval rate improvements unrealized, representing billions in lost sales globally. The research further demonstrates that real-time machine learning models evaluating 30+ transaction variables can improve approval rates by 4.3-6.7% compared to rule-based systems, with particularly strong performance for cross-border transactions where approval uplift can reach 9.1%. This complexity underscores the need for sophisticated, data-driven routing solutions that can continuously adapt to the dynamic payment ecosystem.

Factor	Category	Approval Rate Difference (%)
Processing Path	Different paths for identical transactions	12-18%
Orchestration	Sophisticated vs. single-processor	7-9%
Transaction Value	High-value ($1000+) vs. low-value	9-14%

Factor	Category	Approval Rate Difference (%)
	(<$100)	
Transaction Value (Cross-border)	High-value vs. low-value	16-22%
Currency Conversion	International vs. domestic	4-7%
Card Type	Credit vs. debit	6-9%
Card Tier	Premium vs. standard	3-5%
Issuer Performance	Highest vs. lowest performing in market	>15%
Merchant Category	Traditional retail vs. high-risk	10-16%
Chargeback Ratio	Low vs. high (>1%)	6-9%
Entry Method	EMV chip vs. manual entry	13.6%
Authentication	3D Secure 2.0 vs. non-authenticated	9.2%
Payment Method	Tokenized wallets vs. traditional CNP	11.4%
Routing Technology	ML models vs. rule-based systems	4.3-6.7%
Routing Technology (Cross-border)	ML models vs. rule-based systems	9.1%

Table 1: Payment Processing Approval Rate Variations by Factor [3, 4]

Machine Learning Approach to Payment Routing

3.1. Decision Trees for Transaction Routing

Decision trees provide an intuitive and effective approach for transaction routing optimization. These supervised learning algorithms partition the transaction attribute space to identify optimal routing paths based on historical performance. According to Sinap's comprehensive comparative analysis of machine learning techniques in payment processing, decision tree models analyzing payment transaction attributes achieved an average accuracy of 82.7% in predicting successful authorizations across a dataset of 284,807 transactions, significantly outperforming logistic regression models, which achieved only 76.9% accuracy on the same dataset [5]. His research demonstrated that decision tree models incorporating 22 distinct transaction attributes consistently outperformed traditional rule-based routing systems by 3.8-5.2% in overall fraud detection rates, with particularly significant performance improvements observed for high-value transactions exceeding $500 (+6.9%). The study further revealed that decision trees demonstrated superior interpretability compared to other machine learning approaches, with an average of 16.3 decision nodes providing a clear understanding of authorization patterns across different transaction types. This interpretability advantage makes decision trees particularly valuable in regulated financial environments where oversight authorities often require explainability of decision-making processes.

3.1.1. Classification Trees

Classification trees predict discrete outcomes (approval/decline) by analyzing patterns in historical transaction data. These models can identify which combination of transaction attributes and routing paths leads to the highest probability of approval. Inampudi et al.'s extensive research on machine learning applications in payment gateway optimization demonstrated that classification tree models achieved a mean accuracy of 86.4% in predicting transaction approvals, with a precision of 0.83 and a recall of 0.81 across diverse transaction types [6]. Their analysis of implementation results across three major e-commerce platforms revealed that classification tree models reduced false decline

rates by an average of 26.2% compared to traditional scoring approaches. Their study of 1.97 million transactions processed through an intelligent routing system showed that classification-tree-based routing increased successful transactions from 89.7% to 94.2%, representing approximately $2.8 million in recovered revenue annually for a mid-sized online merchant processing 35,000 transactions daily. The research further indicated that classification trees demonstrated particular strength in identifying approval patterns for transactions with foreign-issued payment instruments, achieving a 37.8% improvement in approval rates for international cards compared to static routing approaches.

3.1.2. Regression Trees

Regression trees predict continuous values such as the probability of approval, expected processing time, anticipated interchange fees, and likelihood of fraud. Combining these predictions allows the system to select the optimal routing path for each transaction. Sinap found that regression tree models predicting fraud probability achieved a mean absolute error (MAE) of 0.089 across his test dataset, significantly outperforming naive Bayes (MAE 0.124) approaches [5]. His research demonstrated that regression trees accurately identified high-risk transactions with an Area Under the ROC Curve (AUC) of 0.823, enabling more precise routing of suspicious transactions through enhanced verification pathways. For the crucial problem of handling highly imbalanced datasets typical in payment processing (where fraudulent transactions represented only a tiny fraction of the dataset at 0.172% in his study), regression tree-based techniques achieved F1 scores of 0.795, significantly outperforming basic classification approaches. Sinap's analysis further revealed that regression trees accurately identified high-probability approval paths that reduced processing costs by 22.6 basis points per transaction when routing flexibility existed between multiple viable processing paths, representing significant savings for high-volume merchants.

3.2. Advanced ML Techniques for Routing Optimization

Beyond basic decision trees, more sophisticated approaches offer enhanced performance in payment routing optimization. Inampudi et al.'s analysis of advanced machine learning deployments across multiple payment processors revealed that sophisticated ML approaches delivered an average incremental gain of 3.2-5.1% in approval rates compared to basic decision tree implementations, with particular strength shown in handling complex cross-border payment scenarios [6]. Their research demonstrated that advanced machine learning models reduced transaction failures by 31.7% compared to traditional routing mechanisms, translating to significant revenue recovery for implementing merchants.

3.2.1. Ensemble Methods

Random Forests, which combine multiple decision trees to reduce overfitting and improve prediction accuracy, demonstrated especially strong performance in Sinap's comparative analysis, achieving a 4.1% improvement in fraud detection accuracy compared to single decision tree implementations [5]. His study revealed that Random Forest models incorporating 100 trees reached optimal performance, beyond which returns diminished while computational complexity increased exponentially. For payment systems requiring real-time decision-making, Sinap's timing analysis indicated that Random Forest models increased processing latency by only 12.7 milliseconds compared to single decision tree implementations, making them viable for real-time routing decisions in all but the most latency-sensitive payment environments.

Gradient Boosting approaches, which sequentially build trees that correct errors from previous models, achieved even stronger performance in Inampudi et al.'s study, with improvement margins of 5.2% over single decision trees in transaction approval prediction [6]. Their analysis of 2.38 million transactions processed through gradient boosting

models revealed that these approaches reduced misrouting events (transactions sent to sub-optimal processors) by 38.7% compared to random forest implementations. XGBoost, an optimized gradient boosting implementation with regularization, demonstrated the strongest overall performance among ensemble methods in their experimental evaluation, with their research showing that XGBoost models achieved 6.3% higher approval rates than baseline decision trees while simultaneously reducing computational requirements by 41.5% compared to standard gradient boosting implementations, making XGBoost particularly suitable for high-throughput payment environments processing upwards of 500 transactions per second.

3.2.2. Reinforcement Learning

Reinforcement learning enables the routing system to adapt continuously by learning from the outcomes of its decisions. The model optimizes a reward function that balances approval rates, processing costs, and other business objectives. Inampudi et al.'s pioneering implementation of reinforcement learning for payment routing demonstrated that these systems achieved a 7.1% improvement in overall approval rates compared to static models after 60 days of operation [6]. Their study revealed that reinforcement learning models were particularly effective at adapting to sudden changes in processor performance, reducing the approval impact of processor outages or degradations by 68.4% compared to traditional routing approaches. The research further indicated that reinforcement learning models optimized for a balance of approval rates and processing costs achieved a 5.3% reduction in overall processing expenses while simultaneously improving approval rates by 4.2%, representing a dual optimization not achievable with static models. Their analysis highlighted the value of Q-learning algorithms in payment routing, which achieved convergence to optimal routing policies after processing approximately 175,000 transactions, representing just 5 days of operation for a mid-sized e-commerce merchant.

3.2.3. Neural Networks

Deep learning approaches can capture complex non-linear relationships between transaction attributes and approval outcomes, especially when dealing with high-dimensional data or when strong interaction effects exist between variables. While Sinap's research focused primarily on fraud detection rather than approval optimization, his findings regarding neural network performance remain relevant to the routing domain [5]. His implementation of deep neural networks for transaction classification achieved an accuracy of 85.9% in identifying fraudulent transactions, compared to 82.7% for decision trees and 84.2% for random forests. The neural network approach demonstrated particular strength in identifying subtle patterns in consumer behavior that indicated elevated fraud risk, achieving a 27.6% improvement in early fraud detection compared to traditional methods. For complex transaction patterns, Sinap's neural network implementation with 3 hidden layers (containing 128, 64, and 32 neurons respectively) and dropout regularization (p=0.3) achieved the highest overall performance among all methods tested.

Inampudi et al.'s implementation of neural network models for payment routing optimization revealed that these approaches achieved an average approval rate improvement of 6.7% compared to decision tree baselines for complex transaction types involving 25+ attributes [6]. Their analysis demonstrated that deep neural networks with 2-3 hidden layers and 64-128 neurons per layer achieved optimal performance for payment routing, with particular strength in identifying approval patterns for recurring transactions and subscription payments, where neural networks improved successful billing rates by 9.4% compared to traditional routing mechanisms. The research indicated that neural networks were especially effective at capturing temporal patterns in authorization behavior, automatically adapting to

time-based approval variations without explicit programming. Their most significant finding showed that neural networks correctly identified 67.9% of transactions that would benefit from retries after initial decline, compared to 38.5% for decision tree approaches, creating significant revenue recovery opportunities for implementing merchants. Additionally, their research demonstrated that neural network approaches reduced false declines for legitimate high-value transactions by 43.2%, addressing a critical pain point for merchants in luxury goods and high-ticket service categories.



Fig. 1: Effectiveness Analysis of Advanced ML Algorithms for Transaction Processing Enhancement [5, 6]

Implementation Framework

4.1. Data Collection and Preprocessing

Effective ML-based routing requires comprehensive historical transaction data that captures the full lifecycle of payment processes. According to research by Moreira et al. on predictive assessment of fraud in banking systems, successful payment routing implementations require a minimum dataset of 478,787 transactions to achieve baseline model performance, with optimal results observed when training on datasets exceeding 1.2 million records [7]. Their experimental results revealed that models trained on smaller datasets showed performance degradation of up to 14.3% compared to those trained on more comprehensive datasets. The study emphasized the critical importance of transaction logs containing complete records of authorization requests and responses. Moreira's research indicates that feature sets containing at least 30 distinct transaction attributes yielded optimal predictive accuracy. Their analysis demonstrated that the financial sector could save approximately $1.1 million per case of fraud detected by implementing comprehensive data collection protocols for transaction analysis.

Comprehensive routing decision data, capturing the historical record of which the acquirer processed each transaction, provides essential context for model training. According to Jutur's extensive work on scaling real-time payment systems, implementations incorporating full acquirer routing histories achieved average response times of 54 milliseconds compared to 83 milliseconds for systems with limited historical context [8]. His research revealed that resilient payment architectures incorporating detailed outcome data (approval/decline status, specific response codes, and settlement information) consistently achieved system availability of 99.99%, compared to 99.95% for systems with less comprehensive data integration. The study further demonstrated that fully instrumented processing systems capable of capturing and analyzing transaction costs (interchange fees, network fees, and processor fees) achieved 27% higher throughput

during peak loads while maintaining consistent 60ms response times within the industry standard threshold of 200ms.

Data preprocessing represents a critical foundation for effective machine learning implementation. Moreira et al. found that normalization of continuous variables using min-max scaling improved model performance by 7.2% compared to models trained on raw values [7]. Their analysis showed that proper encoding of categorical variables significantly improved fraud detection rates, with optimized encoding approaches achieving F1 scores of 0.89 compared to 0.76 for models using standard encoding techniques. The research further indicated that feature engineering to create derived attributes (including time-based, frequency-based, and amount-based features) yielded a 12.9% increase in model performance. Jutur's work complemented these findings, demonstrating that sophisticated approaches to handling missing values in payment routing data reduced transaction failure rates by 3.7% compared to systems using simple data replacement strategies [8]. His research showed that implementations employing effective data preprocessing pipelines achieved 99.98% transaction integrity during high-volume periods, compared to 99.87% for systems with limited preprocessing capabilities.

4.2. Model Training and Evaluation

The model training process follows a structured methodology to ensure optimal performance. Moreira et al.'s research on fraud detection frameworks revealed that data partitioning strategies significantly impact model quality, with their experimental results demonstrating that a 60/20/20 split between training, validation, and test sets yielded the best balance between model accuracy and generalizability [7]. Their work showed that stratified sampling techniques preserving the distribution of fraud cases (which represented only 0.173% of their dataset) improved model performance significantly, with properly stratified datasets achieving AUC scores of 0.9902 compared to 0.9514 for random sampling approaches. The researchers noted that addressing class imbalance through techniques such as the Synthetic Minority Over-sampling Technique (SMOTE) improved fraud detection rates by 23.7% while maintaining false positive rates below 3%.

Feature selection represents another critical element in the modeling process. Jutur's comprehensive analysis of feature importance in payment system resilience demonstrated that most effective models utilized between 25-40 key features, with his research showing that systems monitoring 32 distinct transaction metrics achieved optimal performance in predicting transaction failures [8]. His study revealed that implementations focusing on the most predictive transaction attributes achieved 99.89% routing accuracy during normal operations and maintained 99.56% accuracy during degraded conditions. The research further showed that the most significant metrics for payment routing optimization included transaction velocity (transactions per second), response time percentiles (50th, 95th, 99th), error rates across different processing nodes, and historical approval rates for specific transaction types.

Hyperparameter tuning plays a crucial role in optimizing model performance. Moreira et al.'s experimental results demonstrated that grid search approaches to hyperparameter tuning yielded models with detection rates of 83% and precision rates of 93% when properly optimized [7]. Their research identified optimal hyperparameter ranges for payment fraud detection models, including tree depths 8 for decision tree implementations and 350 estimators for random forest models. The study revealed that appropriate hyperparameter selection reduced false positive rates to 0.3%, significantly lower than the industry average of 1.2% for comparable systems. Jutur's research complemented these findings, demonstrating that properly tuned routing algorithms maintained 97.2% of their optimal performance even when transaction volumes increased by 400% during peak processing periods [8].

Performance evaluation encompasses multiple metrics to provide a complete assessment of model quality. Moreira et al.'s research emphasized the importance of balanced evaluation approaches, showing that models optimized for comprehensive metrics achieved fraud detection rates of 83% with precision rates of 93% [7]. Their analysis revealed that effective evaluation frameworks must consider the significant cost imbalance between false positives and false negatives in financial transactions, with their study estimating that each undetected fraudulent transaction costs approximately 50 times more than a false positive. The research further demonstrated that the Matthews Correlation Coefficient (MCC) provided more meaningful evaluation than accuracy for imbalanced financial datasets. MCC-optimized models achieved 18.7% better performance on fraud detection with minimal impact on legitimate transaction processing.

4.3. Real-time Decision Engine

The operational system for payment routing incorporates several critical components designed to ensure optimal performance under the strict latency constraints of payment processing. According to Jutur's real-time payment system architecture analysis, feature extraction systems must process incoming transaction data with average latencies below 30 milliseconds to meet industry standards [8]. His research showed that implementations utilizing optimized data processing pipelines achieved average transaction processing times of 54 milliseconds, with 95th percentile response times remaining below 110 milliseconds even during peak loads. The study revealed that systems implementing parallel processing architectures handled up to 2,500 transactions per second while maintaining consistent response times, representing a 340% improvement over sequential processing approaches.

The prediction service component generates routing recommendations based on trained models, with Jutur's research demonstrating that containerized microservice architectures achieved 99.99% availability for prediction services compared to 99.95% for monolithic implementations [8]. His analysis of high-throughput payment systems showed that architectures implementing appropriate horizontal scaling mechanisms successfully maintained consistent response times below 60 milliseconds even when transaction volumes increased to 5,000 transactions per second. The research further revealed that distributed prediction services implementing proper load balancing handled sustained transaction volumes of 8,000 TPS with degradation of only 15%, compared to 74% degradation for non-distributed approaches. Implementing redundant processing nodes across multiple availability zones achieved 99.999% overall availability, representing approximately 5 minutes of total downtime annually.

Decision execution systems implement routing decisions through payment gateway APIs, with Moreira et al.'s research indicating that optimized execution frameworks successfully processed 98.7% of transactions without manual intervention [7]. Their study showed that implementing automated decisioning systems reduced the need for manual review to just 1.3% of transactions, representing significant operational cost savings while maintaining high-security standards. Jutur's research complemented these findings, demonstrating that resilient execution frameworks implementing circuit breaker patterns maintained 99.2% of normal transaction throughput during degraded conditions, compared to 67.8% for systems lacking these resilience features [8]. His analysis further revealed that systems implementing retry mechanisms with exponential backoff successfully completed 99.87% of transactions during network instability periods, compared to 97.32% for systems with fixed retry approaches.

The feedback loop capturing transaction outcomes to refine future routing decisions is critical for long-term system performance. Moreira et al.'s research showed that feedback-optimized models maintained detection performance above 80% even as fraud patterns evolved over time [7]. Their analysis demonstrated

that continuous learning systems incorporating recent transaction outcomes identified 93% of novel fraud patterns within the first 100 occurrences, compared to 41% for static models. Jutur's work further revealed that systems implementing real-time feedback loops maintained routing optimization within 2.7% of theoretical maximums despite processor performance fluctuations of up to 40% [8]. His research showed that feedback-optimized systems reduced transaction failure rates during holiday shopping peaks by 47% compared to systems without dynamic adaptation capabilities.

Performance monitoring systems tracking approval rates, costs, and model drift provide essential oversight of the routing system. Moreira et al.'s research showed that implementations with comprehensive monitoring identified 87% of anomalous transaction patterns within the first 50 occurrences [7]. Their analysis demonstrated that rule-based monitoring combined with machine learning anomaly detection achieved a 14.7% higher sensitivity in identifying suspicious patterns than either approach. Jutur's study complemented these findings, revealing that comprehensive monitoring frameworks successfully detected 97.8% of system degradation events within 30 seconds of onset [8]. His research demonstrated that implementations employing distributed tracing across the full transaction lifecycle reduced mean time to diagnosis (MTTD) by 64% compared to systems with limited observability. Organizations implementing comprehensive performance dashboards tracking 32 key metrics achieved mean time to resolution (MTTR) of 17 minutes for critical incidents, 73% faster than the industry average of 63 minutes.

Implementation Component	Metric	Performance Value	Comparison/Baseline
Dataset Size	Minimum Transactions Required	478,787	Baseline performance
Dataset Size	Optimal Transactions	1.2 million+	For best results
Data Integration	Response Time	54 ms	vs. 83 ms for limited history
Data Integration	System Availability	99.99%	vs. 99.95% for limited integration
Data Integration	Peak Load Throughput Increase	27%	For fully instrumented systems
Data Preprocessing	Performance Improvement	7.2%	Min-max vs. raw values
Data Preprocessing	F1 Score	0.89	vs. 0.76 for standard encoding
Data Preprocessing	Feature Engineering Impact	12.9%	Performance increase
Data Preprocessing	Transaction Integrity	99.98%	vs. 99.87% for limited preprocessing
Model Training	AUC Score (Stratified)	0.9902	vs. 0.9514 for random sampling
Model Training	Fraud Detection Improvement	23.7%	Using SMOTE techniques
Feature Selection	Routing Accuracy (Normal)	99.89%	Using 32 transaction metrics
Feature Selection	Routing Accuracy (Degraded)	99.56%	During system degradation
Hyperparameter Tuning	Detection Rate	83%	With grid search optimization
Hyperparameter Tuning	Precision Rate	93%	With grid search optimization

Implementation Component	Metric	Performance Value	Comparison/Baseline
Hyperparameter Tuning	False Positive Rate	0.3%	vs. 1.2% industry average
Peak Performance	Volume Resilience	97.2%	At 400% normal volume
Decision Engine	Transaction Processing	54 ms	Average processing time
Decision Engine	Peak Processing Capacity	2,500 TPS	Using parallel architecture
Decision Engine	Processing Improvement	340%	vs. sequential processing
Prediction Service	Service Availability	99.99%	For containerized microservices
Prediction Service	Response Time Under Load	<60 ms	At 5,000 TPS
Prediction Service	High Volume Degradation	15%	At 8,000 TPS
Prediction Service	Overall Availability	99.999%	With redundant nodes
Decision Execution	Automated Processing	98.7%	Without manual intervention
Decision Execution	Throughput Maintenance	99.2%	During degraded conditions
Decision Execution	Transaction Completion	99.87%	During network instability
Feedback Loop	Novel Pattern Detection	93%	vs. 41% for static models
Feedback Loop	Optimization Maintenance	2.7%	Of theoretical maximum
Feedback Loop	Failure Rate Reduction	47%	During peak shopping periods
Performance Monitoring	Anomaly Detection	87%	Within first 50 occurrences
Performance Monitoring	System Degradation Detection	97.8%	Within 30 seconds
Performance Monitoring	MTTD Reduction	64%	vs. limited observability
Performance Monitoring	MTTR	17 minutes	vs. 63 minutes industry average

Table 2: Performance Metrics for ML-Based Payment Routing Implementation Components [7, 8]

Key Optimization Strategies

5.1. Issuer-Specific Routing

Some card issuers, such as Chase or specific debit networks like STAR, can authorize transactions without going through the main card networks. The ML model can identify and route these opportunities accordingly to reduce fees and improve approval rates. According to Ferreira's comprehensive analysis of dynamic payment routing, transactions processed through direct issuer connections experience approval rates up to 8.5% higher than those routed through traditional network paths, representing a significant opportunity for revenue enhancement [9]. His research demonstrates that merchants implementing intelligent issuer-specific routing can reduce processing costs by up to 35 basis points per transaction, with these savings being particularly pronounced for debit transactions where fee differentials between network and direct routing can exceed 100 basis points. For large enterprises processing 20+ million monthly transactions, these optimizations translate to annual savings of $7-10 million while improving customer experience through higher approval rates.

The operational impact of issuer-specific routing extends beyond mere cost savings. Dao Thu's analysis of AI applications in payment security reveals that intelligent routing to issuer-direct processing paths can reduce transaction abandonment rates by up to 5.2% in time-sensitive merchant categories [10]. Her research indicates that direct issuer connections enable faster processing times, with average authorization response times decreasing from 1.8 seconds to 0.7 seconds for transactions routed through

direct issuer paths. This improvement has particular significance for mobile commerce, where each additional second of processing time increases cart abandonment by 7%. The research further demonstrates that for large issuers with substantial market share in specific regions, direct routing can improve overall payment success rates by 4-7%, representing millions in recovered revenue for enterprise merchants. Her analysis shows sophisticated machine learning systems can predict which transactions would benefit from direct issuer routing with 94.2% accuracy based on historical performance patterns, bank identification number (BIN) analysis, and real-time network performance metrics.

5.2. Preventing Futile Authorization Attempts

Many merchants waste resources by repeatedly attempting authorizations on cards with a negligible approval probability. ML models can identify these patterns and implement "stand-in" processing, where the system returns a decline response without submitting the authorization to the network, thereby saving fees and avoiding potential penalties for excessive retry attempts. Ferreira's analysis of transaction processing efficiency reveals that approximately 12.3% of all authorization attempts represent futile retries with less than a 3% probability of success, generating unnecessary costs and potential reputation damage with card networks [9]. His research indicates that these futile retry attempts cost merchants an average of €0.18-€0.27 (approximately $0.20-$0.30) per attempt in processing fees, network charges, and operational overhead. For large enterprise merchants processing millions of transactions monthly, these unnecessary attempts can represent €350,000-€500,000 in annual wasted expenditure, creating a compelling business case for intelligent stand-in processing.

The machine learning approach to identifying futile authorization patterns shows remarkable effectiveness compared to traditional methods. Dao Thu's research on AI applications in payment optimization demonstrates that properly trained predictive models can identify transactions with negligible approval probability with up to 93% accuracy [10]. Her analysis reveals that by implementing intelligent stand-in processing for these futile attempts, merchants can reduce their declined transaction ratio by 5-7% while simultaneously decreasing authorization expenses. The study shows that properly implemented stand-in processing has minimal impact on legitimate transactions, with false positive rates (declining potentially approvable transactions) below 0.8%. Furthermore, advanced machine learning models incorporating 120+ transaction variables demonstrate 41% greater accuracy in predicting futile authorization attempts than rule-based systems. According to the research, merchants implementing AI-driven stand-in processing experience up to 46% reduction in network non-compliance fees for excessive authorization attempts, avoiding the penalties that can reach $10,000+ per month for large merchants exceeding network thresholds for declined-to-approved ratios.

5.3. Dynamic Fee Optimization

By incorporating interchange fee structures into the decision model, the system can optimize approval rates and processing costs. This multiobjective optimization balances the revenue benefit of approved transactions against the cost of processing. Ferreira's detailed examination of payment economics reveals that the cost variance between optimal and sub-optimal routing decisions averages 40-60 basis points per transaction, with this differential widening to over 120 basis points for premium credit products and cross-border transactions [9]. His analysis demonstrates that large merchants implementing sophisticated dynamic fee optimization can achieve average processing cost reductions of 13-15%, with these savings being achieved through intelligent routing decisions that leverage real-time data on interchange rates, network fees, and processor pricing tiers. For a mid-sized enterprise processing €500

million annually, these optimizations translate to €2.6-€3.0 million in direct cost savings that contribute directly to bottom-line profitability.

The machine learning approach to fee optimization demonstrates significant advantages over traditional methods. Dao Thu's research shows that neural network models analyzing 87+ distinct transaction attributes can identify optimal routing paths with up to 96% accuracy, consistently selecting processing channels that maximize the value ratio between approval probability and processing costs [10]. Her analysis reveals that reinforcement learning approaches are particularly effective for optimizing the balance between approval rates and fees, with these systems achieving 22% higher performance than traditional supervised learning approaches when evaluating long-term value maximization. The research further indicates that payment optimization systems incorporating fee structures can reduce overall processing costs by 8-12% while maintaining equivalent approval rates, with particularly strong performance observed for merchants with diverse product offerings spanning multiple merchant category codes (MCCs). According to the study, implementing dynamic fee optimization enables merchants to generate an average of 8.3% higher net revenue per transaction (transaction value minus processing costs) than systems focused exclusively on approval optimization.

5.4. Adaptive Retry Strategies

When transactions are declined, ML models can determine whether to retry the transaction, which alternative routing path to use, the optimal timing for the retry attempt, and whether to modify any transaction parameters. Ferreira's comprehensive analysis of decline recovery strategies reveals that 22-27% of initially declined transactions can be successfully recovered through properly optimized retry approaches [9]. His research indicates that the timing of retry attempts significantly influences success probability, with data showing that attempts made within specific recovery windows achieve 32-41% higher approval rates than immediate retries. The study demonstrates that routing retries through alternative processing paths improves recovery rates by up to 36% compared to retrying through the same path, with this improvement being particularly pronounced when using direct-to-issuer connections for transactions initially declined at the network level. According to the analysis, every 1% improvement in decline recovery rates translates to approximately €1.4 million in annual recovered revenue for merchants processing €500 million yearly.

The differentiated approach to retry strategies based on decline reason codes yields impressive results. Dao Thu's research on AI-driven payment optimization reveals that machine learning models analyzing 35+ distinct decline codes achieve 30-35% retry success rates, significantly outperforming the 15-18% recovery rates achieved through generic retry strategies [10]. Her analysis demonstrates that recovery rates can reach up to 65% when appropriate retry timing and routing are applied for specific soft decline categories, such as insufficient funds and temporary holds. The research further indicates that sophisticated AI systems can successfully predict whether a transaction should be retried and identify the optimal retry path, timing window, and parameter modifications necessary to maximize approval probability. According to the study, implementing intelligent retry orchestration can recover revenue equivalent to 3-5% of a merchant's annual transaction volume, representing millions in sales that would otherwise be permanently lost. For subscription businesses and recurring billing models, where customer retention is paramount, proper retry optimization has been shown to reduce involuntary churn by 7-12%, significantly enhancing lifetime customer value.

5.5. Cross-Border Transaction Optimization

International transactions face additional complexity due to currency conversion, regional regulations, and cross-border fees. ML models can identify optimal routing paths for these transactions based on the

specific countries and currencies involved. Ferreira's detailed analysis of cross-border payment dynamics reveals that approval rate variations between optimal and sub-optimal routing paths for international transactions can exceed 15%, compared to 5-8% variations for domestic transactions [9]. His research demonstrates that transactions routed through local acquiring entities in the cardholder's region can achieve approval rates 10-14% higher than those processed through international acquiring paths, primarily due to reduced triggering of fraud monitoring systems that often flag cross-regional transactions. The study further indicates that optimized cross-border routing can reduce processing costs by 70-110 basis points per transaction, with these savings being particularly significant for transactions between certain currency pairs where foreign exchange margins and cross-border fees are substantial. For merchants with significant international customer bases, these optimizations can improve overall approval rates by 4-6%, translating to millions in recovered revenue.

The specialized nature of cross-border transaction processing creates unique optimization opportunities. Dao Thu's analysis of AI applications in payment routing reveals that machine learning systems incorporating regional regulatory requirements, currency considerations, and local processing capabilities can improve cross-border approval rates by 11-15% compared to standard international routing [10]. Her research demonstrates that AI-driven routing decisions can successfully navigate the complexity of cross-border payments by analyzing 180+ transaction attributes to determine optimal processing paths based on card type, issuing region, and transaction characteristics. The study indicates that intelligent cross-border routing reduces transaction abandonment rates by 17% by minimizing the additional friction often associated with international payments, such as stepped-up authentication and verification processes. According to the research, merchants implementing AI-optimized international payment routing experience 22% fewer payment-related customer service inquiries for cross-border transactions, reflecting the improved payment experience. For large global enterprises, where international customers may represent 30-50% of total revenue, these optimizations create significant competitive advantage through improved payment accessibility and customer experience.



Fig. 2: Performance Benchmarks for Machine Learning Applications in Payment Routing: Strategy-by-Strategy Analysis [9, 10]

Implementation Challenges

Several challenges must be addressed when implementing ML-based routing systems to ensure their effectiveness in production environments. These challenges span technical, operational, and regulatory dimensions and require careful consideration during system design and implementation.

6.1. Latency Requirements

Payment authorization requires near-instantaneous decisions. The ML system must deliver routing recommendations within milliseconds to avoid adding perceptible delay to the transaction process. According to Gujalwar's comprehensive analysis of AI applications in payment systems, transaction decisions must be rendered within 200-300 milliseconds of total processing time to meet industry standards, with the ML-based routing component needing to deliver results in under 50 milliseconds to accommodate network transmission times and other processing steps [11]. His research indicates that in high-volume e-commerce environments, each additional 100 milliseconds of processing latency correlates with a 1.5-3% increase in cart abandonment, representing a significant potential revenue impact for merchants. The study further highlights that production-grade payment systems must maintain 99.95% availability while handling transaction volumes that can surge 300-400% during peak shopping periods like Black Friday, placing extraordinary demands on ML infrastructure. Gujalwar notes that while cloud-based ML deployments offer scalability advantages, many financial institutions still prefer on-premises deployments for sensitive payment workloads, with 43% of surveyed organizations citing security concerns as the primary factor in this decision.

The architectural considerations for managing latency extend beyond model optimization. Sousa's detailed analysis of payment routing systems for high-volume e-commerce environments reveals that distributed deployment architectures can reduce average response times to 37 milliseconds for pre-trained ML models, compared to 176 milliseconds for traditional rule-based routing systems that must evaluate complex conditional logic [12]. His research demonstrates that optimized decision tree models specifically pruned to minimize node traversal time achieved the best balance between accuracy and performance, with average inference times of 24.6 milliseconds while maintaining a prediction accuracy of 92.8%. The study further shows that implementing batch prediction for recurring transactions reduced processing overhead by 64% while maintaining authorization performance within 0.3% of real-time predictions. Perhaps most significantly, Sousa's analysis revealed that proper load balancing across redundant processing nodes maintained 99.98% system availability during the holiday shopping season, where transaction volumes reached 450 transactions per second, more than quadrupling the normal processing rate of 110 transactions per second. His research emphasizes that effective payment routing systems must maintain consistent performance not just under average conditions but during extreme traffic spikes.

6.2. Data Quality and Availability

Historical transaction data may be incomplete or inconsistently formatted. Robust data pipelines and cleansing processes are essential for maintaining model accuracy. Gujalwar's examination of data challenges in payment AI implementations reveals that financial institutions typically observe data quality issues in 15-20% of transaction records, with missing values, inconsistent formatting, and erroneous categorizations representing the most common problems [11]. His research indicates that improving data quality can boost model performance by 25-30%, making data preparation the single most impactful factor in successful implementation. The study highlights that payment processors must contend with rapidly growing data volumes, with the average processor seeing 35-45% year-over-year growth in transaction data volume, placing increasing strain on data management systems. Gujalwar notes that organizations implementing real-time data quality

monitoring detect 74% of data anomalies within minutes of occurrence, compared to just 23% for those relying on periodic batch analysis. According to his research, banking and payment systems typically encounter data quality issues from multiple sources, with 32% attributed to poor data entry at origination, 27% to system integration issues, and 22% to inconsistent data transformation processes across disparate systems.

Data availability challenges extend beyond quality concerns to encompass access restrictions and integration complexities. Sousa's comprehensive study of payment routing optimization found that effective ML models required access to a minimum dataset of 800,000 transactions to achieve adequate performance, with optimal results observed after training on approximately 3.5 million transactions [12]. His research revealed that organizations implementing payment routing systems typically needed to integrate data from 5-7 distinct internal systems, including authorization platforms, fraud management systems, customer relationship management databases, and historical transaction repositories. The study demonstrated that data historicization represented a significant challenge, with 68% of payment service providers maintaining less than 12 months of detailed transaction data in readily accessible formats, despite evidence showing that models trained on 24+ months of historical patterns outperformed those with shorter historical windows by 17.3% in approval prediction accuracy. Perhaps most significantly, Sousa's analysis highlighted the challenges of data imbalance in payment datasets, where declined transactions typically represent only 8-12% of total volume but are precisely the cases that routing optimization aims to address. His research showed that implementing synthetic minority oversampling techniques (SMOTE) improved prediction accuracy for decline cases by 28.7% compared to models trained on unbalanced datasets, highlighting the importance of specialized data preparation techniques for payment applications.

6.3. Regulatory Compliance

Payment routing decisions must comply with network rules, geographic regulations, and data privacy requirements. The model must incorporate these constraints as part of its decision logic. Gujalwar's examination of regulatory challenges in payment innovation revealed that financial institutions operate under 12-15 distinct regulatory frameworks simultaneously, with multinational organizations facing even greater complexity [11]. His research indicates that compliance-related constraints account for approximately 40% of the business rules governing payment routing decisions, creating significant implementation overhead. The study highlights that regulatory requirements vary substantially across jurisdictions, with European payment processors subject to PSD2 requirements spending 23-35% more on compliance technologies than their North American counterparts. Gujalwar notes that explainability has become a critical requirement for AI systems in payments, with 68% of surveyed financial institutions citing regulatory demands for transparent decision-making as a significant challenge in ML implementation. According to his analysis, organizations implementing "compliance-by-design" approaches, which incorporate regulatory constraints directly into model training and evaluation processes, reduce compliance incidents by 64% compared to those that treat compliance as a post-processing step.

The regulatory landscape places particular emphasis on data protection and privacy considerations. Sousa's comprehensive analysis of payment routing systems found that processors typically handle 18-22 distinct personal data elements per transaction, including sensitive payment instrument details, location data, and customer identifiers [12]. His research demonstrated that effective anonymization techniques could reduce personally identifiable information exposure by 87.2% while maintaining 97.1% of predictive performance, addressing key regulatory requirements under frameworks like

GDPR. The study highlighted the challenges of cross-border transactions, which must simultaneously comply with regulations in both the originating and receiving jurisdictions, creating complex compliance requirements that vary depending on the specific country pairs involved. Sousa noted that payment systems must also comply with network-specific rules that change frequently, with MasterCard and Visa collectively implementing 30-45 rule updates annually, potentially impacting routing decisions. His analysis revealed that maintenance of compliance rule sets consumed approximately 23% of total development resources for payment routing systems, representing a significant ongoing operational burden. Perhaps most significantly, the research demonstrated that machine-learning approaches could improve compliance rates by identifying patterns in transaction data that indicate potential regulatory issues, with ML-enhanced compliance monitoring reducing regulatory violations by 34.6% compared to traditional rule-based approaches.

6.4. Concept Drift

Due to new regulations, fee structures, and issuer policies, payment ecosystem dynamics change over time. The model must continuously adapt to maintain optimal performance. Gujalwar's detailed analysis of AI performance in financial services revealed that payment models typically experience accuracy degradation of 3-5% per quarter without regular updates, representing a significant cumulative impact on business outcomes [11]. His research indicated that concept drift in payment systems stems from multiple sources, with consumer behavior shifts accounting for 35% of observed drift, issuer policy changes representing 25%, technological evolution contributing 20%, and seasonal patterns accounting for the remaining 20%. The study highlighted that adaptive model architectures utilizing ensemble methods demonstrated 40-45% greater resilience to concept drift than single-model approaches. Gujalwar noted that effective model monitoring requires tracking at least 12-15 distinct performance metrics to detect degradation before it impacts business outcomes, with leading organizations implementing real-time dashboards that alert operations teams when key indicators deviate from expected ranges. According to his analysis, organizations implementing continuous learning approaches, where models are regularly retrained on recent transaction data, maintained accuracy levels within 5% of initial performance even after 12 months, compared to degradation exceeding 15% for static models.

The operational implications of concept drift extend beyond model performance to encompass monitoring and governance requirements. Sousa's comprehensive examination of payment routing systems found that effective drift detection required establishing statistical control limits for key performance indicators, with deviations exceeding two standard deviations serving as reliable early warnings of changing payment patterns [12]. His research revealed that payment routing models typically required full retraining every 6-8 weeks to maintain optimal performance, with incremental updates performed weekly to incorporate the most recent transaction patterns. The study demonstrated that A/B testing frameworks, which gradually introduced updated models to production traffic, reduced performance-related incidents by 78.4% compared to direct replacement approaches. Sousa highlighted the challenge of distinguishing between systemic pattern shifts and temporary anomalies, noting that payment volumes can fluctuate by 300-500% during promotional events or seasonal shopping periods without representing true concept drift. His analysis revealed that effective model governance frameworks, including comprehensive version control, performance logging, and retraining triggers, reduced the average time to address performance degradation from 18.3 days to 4.2 days. Perhaps most significantly, the research demonstrated that concept drift varies significantly across different segments of the payment ecosystem, with credit card transactions showing much greater stability in approval patterns (3.8%

quarterly drift) compared to alternative payment methods like digital wallets and buy-now-pay-later options (7.2% quarterly drift), necessitating segment-specific monitoring and update strategies.

Conclusion

Implementing machine learning-based payment routing systems represents a significant advancement in transaction processing optimization, offering merchants powerful tools to maximize approval rates and minimize costs in an increasingly complex payment ecosystem. By leveraging various ML techniques to analyze transaction attributes and historical performance data, these systems can make intelligent routing decisions that adapt to changing market conditions, processor performance, and consumer behavior patterns. The article demonstrates that sophisticated approaches like reinforcement learning and neural networks provide substantial advantages over traditional rule-based routing, particularly for complex scenarios such as cross-border transactions and high-value authorizations. While implementation challenges exist—including strict latency requirements, data quality issues, regulatory constraints, and concept drift—these can be effectively addressed through proper system architecture, robust data management practices, compliance-by-design approaches, and continuous model monitoring. As payment technologies evolve and diversify globally, adaptive ML-based routing optimization will become increasingly essential for merchants seeking to enhance customer experience, reduce transaction failures, and improve financial performance across their payment operations.

References

[1]. Grand View Research, "Digital Payment Market Size, Share & Trends Analysis Report By Solution, By Mode Of Payment (Bank Cards, Digital Currencies, Digital Wallets), By Deployment, By Enterprise Size, By End-use, By Region, And Segment Forecasts, 2024 - 2030." [Online]. Available: https://www.grandviewresearch.com/industry-analysis/digital-payment-solutions-market

[2]. Philip Bruno et al., "Global payments in 2024: Simpler interfaces, complex reality," McKinsey & Company, October 18, 2024. [Online]. Available: https://www.mckinsey.com/industries/financial-services/our-insights/global-payments-in-2024-simpler-interfaces-complex-reality

[3]. Juan Camilo Giraldo Mora et al., "The Evolution of Global Instant Payment Infrastructure," Innovation in Digital Banking, ResearchGate, June 2020. [Online]. Available: https://www.researchgate.net/publication/341821819_The_Evolution_of_Global_Instant_Payment_Infrastructure

[4]. Cognizant, "Real-time settlement for card-based payments." [Online]. Available: https://www.cognizant.com/en_us/industries/documents/real-time-settlement-for-card-based-payments.pdf

[5]. Vahid Sinap, "Comparative analysis of machine learning techniques for credit card fraud detection: Dealing with imbalanced datasets," Turkish Journal of Engineering – 2024, 8(2), 196-208. [Online]. Available: https://dergipark.org.tr/en/download/article-file/3517135

[6]. Rama Krishna Inampudi, et al., "Machine Learning in Payment Gateway Optimization: Automating Payment Routing and Reducing Transaction Failures in Online Payment Systems," J. of Art. Int. Research, vol. 2, no. 2, pp. 276–321, Oct. 2022. [Online]. Available: https://thesciencebrigade.com/JAIR/article/view/458

[7]. Miguel Ângelo Lellis Moreira et al., "Exploratory analysis and implementation of machine learning techniques for predictive assessment of fraud in banking systems,"

Procedia Computer Science 214 (2022) 117–124. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S1877050922018634

[8]. Abhinav Reddy Jutur, "Scaling Real-Time Payment Systems: A Deep Dive into Resilient Architectures," International Journal of Computer Engineering and Technology (IJCET), Volume 16, Issue 1, Jan-Feb 2025, pp. 3926-3952. [Online]. Available: https://iaeme.com/MasterAdmin/Journal_uploads/IJCET/VOLUME_16_ISSUE_1/IJCET_16_01_271.pdf

[9]. Pedro Ferreira, "Dynamic Payment Routing: Optimizing Cost Efficiency in Transaction Processing," Finance Magnates, 04/03/2024. [Online]. Available: https://www.financemagnates.com/fintech/dynamic-payment-routing-optimizing-cost-efficiency-in-transaction-processing/

[10]. Ha Dao Thu, "AI: The Keystone of Modern Payment Security Architecture," SmartDev, 15 December 2024. [Online]. Available: https://smartdev.com/ai-the-keystone-of-modern-payment-security-architecture/

[11]. Ashish Gujalwar, "AI in payments: balancing innovation with practicality," Volante. [Online]. Available: https://www.volantetech.com/ai-in-payments-industry/

[12]. Tiago Cardoso dos Santos Pinto de Sousa, "A Payments Routing Heuristic based on Machine Learning for High Volume E-Commerce Environments," July 2018. [Online]. Available: https://repositorio-aberto.up.pt/bitstream/10216/113823/2/276745.pdf