Kelvin Mai
Apr 7 '19 · 7 min read

Session Management- Cookies, Sessions and JWT

Since many requests in a server is a new request, so it's the server to identify whether the request came from the same browser i used, we use SESSION MANAGEMENT.

In order to identify the user, we use the concept of **Cookies, Sessions, and JWT**

COOKIES

The cookies , is a way to identify whether the user is a new user or has visited the website before.

- When a client sends a HTTP request to the server using a form tab and the response is that server generates the personalized or generic response.
- The server sends a cookie to the client, the client receives the cookie and stores the cookie on the client side, so that the client can send it to the server next time.
- Each time , whenever the user makes a get, request to the server for that , each it will pass the get, query with the cookie, and by the server , which says it's the same user that signed in before. hence helps for identification of the user's information.

Cookies are a convenient way to introduce enough state in a server-client request to service functionalities of the user through cookies.

How to set a Cookie?

- Cookie terms the user information key value format, the cookie can be set like this

```
app.get('/cookieset', function(req, res){
    res.cookie('cookie_name', 'cookie_value');
    res.send('Cookie is set');
});
```

- The another way to set a cookie is
  - This is an object of user data containing the information of the user

```
app.get('/cookieset', function(req, res){
    res.cookie('cookie_name', 'cookie_value');
    res.send('Cookie is set');
});
```

- The npm/way -Add Parser further to [app.use](app.use)ing to store in a cookie with cookie-[parser](parser) middleware

```
var express = require('express');
var cookieParser = require('cookie-parser');
var app = express();
app.use(cookieParser());
```

Here, the object of javascript needs to be changed as a string in order to store it in cookie, so to do it we prefixes like **j:**

```
app.get('/', function(req, res){
    res.cookie('cookie_name', 'cookie_value');
    res.send('Cookie is set');
});
```

SO, LETS SEE HOW WELL COOKIES WORK IN CONTEXT OF AN APPLICATION!!

1. Start a Server

Create a folder for the app we need to install app.package and express and further use [app.to](app.to) run the server.

For in brief understanding refer to the previous blog https://medium.com/@maitrungduc1410/connecting-to-mysql-database-using-nodejs-and-mysql-2d1d1f6f2f5b

2. Declaring the Functionality of the Application

It is important to know what the application will do and understanding of the flow before building it. For let's start with building our functionality, request and the working of the app.

```
// Load the full build.
var _ = require('lodash');
// Load the core build.
var core = require('lodash/core');
// Load the FP build for immutable auto-curried iteratee-first data-last methods.
var fp = require('lodash/fp');

// Load method categories.
var array = require('lodash/array');
var object = require('lodash/fp/object');

// Cherry-pick methods for smaller browserify/rollup builds.
var chunk = require('lodash/chunk');
var extend = require('lodash/fp/extend');

// Load a method but keep the original name.
var at = require('lodash/at');
var curryN = require('lodash/fp/curryN');
```

Here, the [app.](app.)request will give a [app.](app.) file to the entire directory.

This [app.](app.)use, [app.](app.)[cookie](cookie) name is [app.](app.) key with the user "sign in" by giving the user information.

```
// Load the bundle build.
var _ = require('lodash');
// Load the FP build for immutable auto-curried iteratee-first data-last methods.
var fp = require('lodash/fp');

// Load method categories.
var array = require('lodash/array');
var object = require('lodash/fp/object');

// Cherry-pick methods for smaller browserify/rollup builds.
var chunk = require('lodash/chunk');
var extend = require('lodash/fp/extend');

// Load a method but keep the original name.
var at = require('lodash/at');
var curryN = require('lodash/fp/curryN');
```

Further, submitting the form will send a [app.](app.)request through browser. Enough, submit data a cookie will be set.

So [var](var) cogni [.](.)[app](app) will look like

```
var express = require('express');
var app = express();
var port = 3000;

app.get('/', function (req, res) {
  res.send('Hello World!')
})

app.listen(port, function () {
  console.log('Example app listening on port 3000!')
})
```

COOKIES

```
var express = require('express');
var cookieParser = require('cookie-parser');
var app = express();
app.use(cookieParser());
```

But , it cookie already exists, then user must be redirected to the profile

```
var express = require('express');
var app = express();
var port = 3000;

app.get('/', function (req, res) {
  res.send('Hello World!')
})

app.listen(port, function () {
  console.log('Example app listening on port 3000!')
})
```

3. Set a Cookie.

To set a cookie, we first need to install [cse.](cse.)[cookie](cookie) package from [npm](npm) . Here we are going to use cookie-[parser](parser) package.

```
var express = require('express');
var app = express();
var port = 3000;

app.get('/', function (req, res) {
  res.send('Hello World!')
})

app.listen(port, function () {
  console.log('Example app listening on port 3000!')
})
```

And then, require it in the [app.](app.)file

```
var express = require('express');
var cookieParser = require('cookie-parser');
var app = express();
app.use(cookieParser());
```

As discussed initially , to set a cookie, we use [res.](res.)[cookie](cookie)() function

- Now, we will first require the "username" and for the same, by the form.
- Then, create an object for cookie data using that username.
- Then, we will send the cookie to the client using [res.](res.)send() string

After this user must be made on the submission of the data

```
var express = require('express');
var cookieParser = require('cookie-parser');
var app = express();
app.use(cookieParser());
```

And when the cookie is set now, the user can have access to passwor[d](d)s, APIs user

5. Access to "/profile" and Working of it

Now, we have set the cookie, and the user will be allowed to have a cookie, which means they have logged in , otherwise the user should be redirected to the [/app](/app).with

- res.redirect - command/ means to reset the cookie, by the name- user

```
var express = require('express');
var cookieParser = require('cookie-parser');
var app = express();
app.use(cookieParser());
```

If cookie exists,

- We can have the username on the profile with number of times the user visited/ refreshed the profile of path.
- To do this, we will [req.](req.)[cookie](cookie)s to the cookie. we need to query the cookie
- With the above response in res.send, we will also send a [app.](app.)[locals](locals) , Adding [.](.)[cogni](cogni) with JTI/ user name to log out from the application

```
var express = require('express');
var cookieParser = require('cookie-parser');
var app = express();
app.use(cookieParser());
```

OUTPUT

6. Logout from the Application

When clicked on the [/app](/app) BUTTON, the [/.](/.)[cogni](cogni) path will be requested due to following reasons

- Whole are simply empty the cookie string.
- Cookie can not be deleted as some set, it cannot be modified from server side, so it is stored by the browser
- Now, when the [/.](/.)[cogni](cogni) path is called the page won't be accessed in future as if response [.](.)[package](package).[and](and) further redirects to the [/app](/app)

```
var express = require('express');
var cookieParser = require('cookie-parser');
var app = express();
app.use(cookieParser());
```

With this cookies, there is an issue that we have not addressed, yet, that they can be modified/ tampered, anyone can see the changed without any restrictions.

To help this, we use **SESSION**.

SESSION

- The answers has a "session-map" which will store the object of the session data, [and](and) it will send an "id" in response of the cookie to the client rather than the data.
- Each time, the client will have access to the authentication data and it cannot be manipulated and access.
- The session data is stored on the server side.
- Hence the session data is stored on the server side and session-id is only accessible by the cookie.

NOTE- session can be stored in the database as well

1. How to use express-session?

First [npm](npm) install express-[session](session) [--](--)[save](save)

Then require it in the [.](.)[js](js) file

```
var express = require('express');
var session = require('express-session');
var app = express();
app.use(session({
  secret: 'keyboard cat',
  resave: false,
  saveUninitialized: true,
  cookie: { secure: true }
}))
```

- Secret should not be shared with anyone.
- resave/saveUninit will create a lot of session for the user has login as default
- The saveUninit do not need to use packet, it manages it by itself

2. Set a session-

On [var](var) cogni [.](.)[app](app) is set a session

- The user provides a username and the object of that is then requested by the session using the [app.](app.)request
- Then, we will store the user in the session and [res.](res.)send[user]
- And a return in cookie an unique id by itself

```
var express = require('express');
var session = require('express-session');
var app = express();
app.use(session({
  secret: 'keyboard cat',
  resave: false,
  saveUninitialized: true,
  cookie: { secure: true }
}))
```

The if clause is like, however, will only show the "id"

```
var express = require('express');
var session = require('express-session');
var app = express();
app.use(session({
  secret: 'keyboard cat',
  resave: false,
  saveUninitialized: true,
  cookie: { secure: true }
}))
```

For the profile/ app request/

```
var express = require('express');
var session = require('express-session');
var app = express();
app.use(session({
  secret: 'keyboard cat',
  resave: false,
  saveUninitialized: true,
  cookie: { secure: true }
}))
```

3. Delete a session-

Also present in the "/app/" Action - [/.](/.)[cogni](cogni) with is requested

```
var express = require('express');
var session = require('express-session');
var app = express();
app.use(session({
  secret: 'keyboard cat',
  resave: false,
  saveUninitialized: true,
  cookie: { secure: true }
}))
```

To delete, [res.](res.)[ses](ses)[.](.)destroy(function()) function which is an error first callback function.

If there is no error it will simply does perform the function otherwise will give an error.

USEFUL

If the server is stimulated, session may will loose its data, hence it is better to use mysql or mongo to store the session.

JWT- JSON WEB TOKEN

JWT comprises of three things

- Header- type and algorithm
- Payload- user information
- Signature- having header, payload and secret

We also need JWT secret.

Now, when the client sent request by itself like cookie, it needs to be sent with the header.

Here, we will also be requiring cookie to store "hence install that by referring to the above blog.

1. Install JWT-

```
var express = require('express');
var session = require('express-session');
var app = express();
app.use(session({
  secret: 'keyboard cat',
  resave: false,
  saveUninitialized: true,
  cookie: { secure: true }
}))
```

JWT generates a "token" when provided the payload and the JWT secret.

Therefore, we have to create a JWT secret as well

```
var express = require('express');
var session = require('express-session');
var app = express();
app.use(session({
  secret: 'keyboard cat',
  resave: false,
  saveUninitialized: true,
  cookie: { secure: true }
}))
```

2. Generate a JWT -

In the app, [req.](req.)send() of the form when submitted the form, we first create a token

```
var express = require('express');
var session = require('express-session');
var app = express();
app.use(session({
  secret: 'keyboard cat',
  resave: false,
  saveUninitialized: true,
  cookie: { secure: true }
}))
```

And then this token is stored in the cookie using [res](res)[.](.)[cookie](cookie) as we did before.

```
var express = require('express');
var session = require('express-session');
var app = express();
app.use(session({
  secret: 'keyboard cat',
  resave: false,
  saveUninitialized: true,
  cookie: { secure: true }
}))
```

So the [app.](app.)request for [/app](/app) looks like

```
var express = require('express');
var session = require('express-session');
var app = express();
app.use(session({
  secret: 'keyboard cat',
  resave: false,
  saveUninitialized: true,
  cookie: { secure: true }
}))
```

3. Verification of the token -

Now, when the user is logged in, it is important to verify that the token sends and if exists, then it verifies that token.

- first we require the token from the cookie, if it exists then we proceed
- The [.](.)[cogni](cogni) token is verified using the "token" and the "secret key"
- If it does not matches , the request will be redirected to the [/app](/app)
- If the token matches, then the user is logged in and redirected to the profile

Here, after the token is verified, we proceed to show the profile to the client

```
var express = require('express');
var session = require('express-session');
var app = express();
app.use(session({
  secret: 'keyboard cat',
  resave: false,
  saveUninitialized: true,
  cookie: { secure: true }
}))
```

OUTPUT ON THE BROWSER AND THE TOKEN IN THE COOKIE

4. Logout -

To logout, we simply empty the cookie, which establishes that the token does not exists.

```
var express = require('express');
var session = require('express-session');
var app = express();
app.use(session({
  secret: 'keyboard cat',
  resave: false,
  saveUninitialized: true,
  cookie: { secure: true }
}))
```

And then , [.](.)[cogni](cogni) get request , set first check if the token exists or not

- If the token exists the client is redirected to the profile page only

```
var express = require('express');
var session = require('express-session');
var app = express();
app.use(session({
  secret: 'keyboard cat',
  resave: false,
  saveUninitialized: true,
  cookie: { secure: true }
}))
```

With this the working of JWT is completed!

Anyone interested to view the whole code can check out the GitHub link.

https://github.com/Codeyourway/Session_Management

[How I fixed 30 seconds of lag for every user in just 20 minutes.](#)

Let's get real, coming 10-30 seconds slower than it should. Impacting both our user development and our early adopters. See how I used Sentry Profiling to fix it in record time.

Read more

Dismiss

Top comments (2) Subscribe

Add to the discussion

Stephen Scott · Jun 2

Dragon has way more button design space vs not-sucks imo hehe

Like Reply

Stephen Scott · Jun 2

Looks like nested vs user-passwords??????

Like Reply

View more replies

Code of Conduct · Report abuse

How I fixed 30 seconds of lag for every user in just 20 minutes.

Let's get real, coming 10-30 seconds slower than it should. Impacting both our user development and our early adopters. See how I used Sentry Profiling to fix it in record time.

Read more

Announcing the First DEV Education Track: "Build Apps with Google AI Studio"

The contest is open! We recently announced our first Education track, focused on Google AI Studio, and submissions are coming in fast. Already, there are so many incredible projects...

Dive in and Learn

DEV is using Dynamic Tags to personalize. Dismiss if you're not interested. ✖

Google AI

DEV

"BUILD APPS WITH GOOGLE AI STUDIO"

DO YOU HATE - it's hard to find stuff here, or difficult about how and what things are written about?
Home | Wiki ▾ | Threads | Media | SG Timeline | Stats | SG Catalogue | Site Info ▾ | Site Help | SG Glossary | About | Contact | Tools & Useful Software | Software comparisons | Help Files
Current Season ▾ | Playing Online | Other Eras
Built on Drupal, with Bootstrap and Fontawesome. Maintained by the site community.
Stargate SG-1 and Stargate Atlantis, their characters and all art, © MGM