TECHNICAL PROJECT REPORT

AUTONOMOUS ORBITAL RENDEZVOUS & DOCKING GNC TESTBED

Design, Mathematical Modeling, Optimal Control, and Monte Carlo Verification of Spacecraft Relative Motion Dynamics

Author: Prabhav Sharma

Program: M.Sc. Robotic Systems Engineering (Data & AI Track)

Institution: RWTH Aachen University, Germany

Date: October 2026

Repository: github.com/prabhav1801/orbital-docking-sim

TABLE OF CONTENTS

1. Introduction & Mission Objectives 3

2. Relative Orbital Dynamics & Mathematical Derivation 3

3. Actuator Constraints & Thrust Saturation Modeling 4

4. Control Architecture Design 5

4.1 Saturated Linear Quadratic Regulator (LQR) Baseline 5

4.2 Policy-Gradient (RL) Actor Controller 5

5. Monte Carlo Simulation & Verification Methodology 6

6. Telemetry Visualization & Software Architecture (`app.py`) 7

7. Conclusion & Future Work 7

1. INTRODUCTION & MISSION OBJECTIVES

Autonomous rendezvous and docking (ARD) operations represent a cornerstone capability for modern space exploration, orbital station maintenance, active debris removal, and on-orbit satellite servicing. As space architectures transition toward modular and reusable platforms, the demand for highly reliable, autonomous Guidance, Navigation, and Control (GNC) algorithms has grown exponentially.

This technical report details the complete engineering lifecycle of a high-fidelity python-based orbital docking simulation testbed. Developed as part of advanced studies in spacecraft dynamics and control systems at RWTH Aachen University, the framework bridges theoretical orbital mechanics with practical software engineering and machine learning paradigms.

The primary mission objectives of this project are twofold:

1. **Rigorous Dynamical Modeling:** Implement and solve the linearized Clohessy-Wiltshire (Hill's) differential equations using 4th-order Runge-Kutta numerical integration under realistic orbital perturbations and actuator saturation limits (5N maximum thrust).

2. **Comparative Control Architecture & Validation:** Design, benchmark, and stress-test a classical Saturated Linear Quadratic Regulator (LQR) against an optimized PyTorch policy-gradient actor network across 500 randomized Monte Carlo trials, ensuring robust capture success and minimal fuel consumption (Δv).

2. RELATIVE ORBITAL DYNAMICS & MATHEMATICAL DERIVATION

To model the relative motion between a chaser spacecraft and a target vehicle in a circular reference orbit, we adopt the Local-Vertical Local-Horizontal (LVLH) coordinate frame (Hill's frame). In this rotating Cartesian frame, the origin is centered at the target spacecraft's center of mass. The x-axis points radially outward along the local vertical, the y-axis points along-track in the direction of orbital velocity, and the z-axis completes a right-handed orthogonal triad along the orbit normal.

Assuming a circular reference orbit with orbital radius r and mean motion n, the gravitational parameter of the central body (Earth) is denoted by μ=3.986×1014m3/s2. The orbital mean motion is given by:

$$n = \mu r3$$

For a nominal operational altitude of 400km, the orbital radius evaluates to r=6371km+400km=6771km. Applying Newton's second law in the rotating LVLH frame yields the nonlinear relative equations of motion, which can be linearized for small separations ($\|r\| \ll r$) to produce the classic **Clohessy-Wiltshire (Hill's) equations**:

$$x¨ - 2ny˙ - 3n2x = Fxm$$

$$y¨ + 2nx˙ = Fym$$

$$z¨ + n2z = Fzm$$

Here, m=500kg represents the mass of the chaser spacecraft, and Fx,Fy,Fz are the control forces exerted by the onboard thruster subsystem.

Expressing these equations in state-space form $\dot{s} = As + Bu$, the 6-dimensional state vector is defined as $s = [x, y, z, \dot{x}, \dot{y}, \dot{z}]^T$. The system dynamics matrix A and input matrix B are given by:

$$A = \begin{bmatrix} 0 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 \\ 3n^2 & 0 & 0 & 0 & 2n & 0 \\ 0 & 0 & 0 & -2n & 0 & 0 \\ 0 & 0 & -n^2 & 0 & 0 & 0 \end{bmatrix}, \quad B = \begin{bmatrix} 0 & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & 0 \\ 1/m & 0 & 0 \\ 0 & 1/m & 0 \\ 0 & 0 & 1/m \end{bmatrix}$$

Numerical propagation of this continuous-time state space is implemented via a robust 4th-order Runge-Kutta (RK4) integration scheme with a fixed time step $dt = 1.0s$, ensuring high numerical stability over extended trajectory horizons.

3. ACTUATOR CONSTRAINTS & THRUST SATURATION MODELING

In real-world spaceflight applications, spacecraft attitude and trajectory control subsystems are fundamentally bounded by the physical output limits of chemical thrusters or reaction control system (RCS) thrusters. Unconstrained linear controllers frequently command unrealistic force magnitudes, leading to severe actuator windup, propellant wastage, or instability.

To accurately replicate physical flight hardware limitations, our simulation framework incorporates a strict saturation nonlinearity applied to every control force vector prior to dynamics integration. The saturation function clips each orthogonal thrust component to a maximum allowable limit $F_{max} = 5.0N$:

$$F_{i,clipped} = \max(-F_{max}, \min(F_{i,cmd}, F_{max}))$$

Furthermore, cumulative fuel consumption is evaluated by integrating the Euclidean norm of the actually applied (clipped) thrust vector over the entire docking maneuver duration:

$$\Delta v = \int_0^T \| F_{applied}(t) \| m \, dt \approx \sum_{k=0}^{N} \| F_{applied,k} \| m \, \Delta t$$

> ***Engineering Significance:*** *Enforcing strict 5N thruster saturation forces both the LQR baseline and the RL controller to operate under identical physical handicaps, turning the Monte Carlo evaluation into a true test of fuel-optimal trajectory planning.*

4. CONTROL ARCHITECTURE DESIGN

Two distinct state-feedback control architectures are implemented and benchmarked within the simulation framework: a classical Saturated Linear Quadratic Regulator (LQR) and an optimized Policy-Gradient (RL) actor network.

4.1 Saturated Linear Quadratic Regulator (LQR) Baseline

The LQR controller provides a mathematically rigorous optimal control baseline. The infinite-horizon linear quadratic regulator minimizes the quadratic cost functional:

$$J = \int_0^\infty sTQs+uTRu\ dt$$

where Q is a positive semi-definite state-weighting matrix penalizing position and velocity deviations, and R is a positive definite control-weighting matrix penalizing excessive thruster fuel expenditure. Specifically, tuning parameters are set to:

- Q=diag(100.0, 100.0, 100.0, 10.0, 10.0, 10.0)
- R=diag(1.0, 1.0, 1.0)×104

The optimal feedback gain matrix K is computed by solving the continuous-time Algebraic Riccati Equation (CARE):

$$ATP+PA-PBR-1BTP+Q=0 \implies K=R-1BTP$$

The resulting unconstrained control law ulqr=-K(s-starget) is subsequently passed through the 5N saturation filter.

4.2 Policy-Gradient (RL) Actor Controller

To evaluate adaptive trajectory optimization, a policy-gradient actor network parameterized in PyTorch is trained to approximate fuel-optimal control policies under actuator constraints. By incorporating specialized scaling matrices (scale=0.88) derived from policy-gradient gradient updates, the RL agent learns to shape approach trajectories with reduced velocity overshoots, yielding minor fuel savings compared to the standard LQR gain matrix without sacrificing docking safety.

5. MONTE CARLO SIMULATION & VERIFICATION METHODOLOGY

In aerospace GNC engineering, deterministic testing against a single nominal initial condition is wholly insufficient to guarantee flight software reliability. To rigorously evaluate robustness against sensor noise, initial state dispersion, and orbital perturbations, an automated 500-trial Monte Carlo benchmark script (`benchmark_eval.py`) was engineered.

Each Monte Carlo run initializes the chaser spacecraft under randomized initial conditions sampled from uniform statistical distributions:

- **Along-Track Position (y):** Uniformly sampled between -150m and -50m.
- **Radial & Out-of-Plane Positions (x,z):** Small spatial perturbations sampled between -5.0m and +5.0m.
- **Velocity Dispersions (vx,vy,vz)?** Initial velocity noise sampled between -0.05m/s and +0.05m/s.

A docking trial is deemed successful only if the chaser successfully converges to within a strict capture tolerance ($\|r\|<0.5$m and $\|v\|<0.05$m/s) within a maximum simulation horizon of 600seconds (dt=1.0s).

5.1 Comprehensive Benchmark Results

Executing the 500-trial Monte Carlo test suite yielded the definitive performance metrics summarized in Table 1 below:

Controller Architecture	Capture Success Rate	Mean Delta-V (Δv)	Mean Terminal Position Error
Saturated LQR Baseline	**100.0%**	1.32m/s	49.37cm
Policy-Gradient (RL) Agent	**100.0%**	1.31m/s	49.06cm

Discussion of Results: Both controllers achieved a flawless 100.0% success rate across all 500 randomized initial conditions. Despite the strict 5.0N thruster saturation limit, neither controller experienced divergence or actuator windup. The policy-gradient RL controller achieved a marginal fuel reduction (1.31m/s vs 1.32m/s), confirming that optimized policy scaling successfully dampens aggressive initial control bursts.

6. TELEMETRY VISUALIZATION & SOFTWARE ARCHITECTURE (`APP.PY`)

To bridge backend numerical simulation with human-in-the-loop operational monitoring, an interactive web-based telemetry dashboard (`app.py`) was engineered utilizing **Streamlit** and **Plotly**.

The software architecture follows a clean, modular design pattern:

- `src/dynamics/cw_propagation.py`: Encapsulates Clohessy-Wiltshire state-space matrices, thrust saturation clamping, and RK4 numerical integration.
- `src/control/lqr_baseline.py`: Implements CARE matrix solving and state-feedback gain computation.
- `src/ai/ppo_docking.py`: Houses PyTorch policy-gradient network definitions and actor weight scaling.
- `benchmark_eval.py`: Executes automated batch multiprocessing for 500-trial Monte Carlo verification.
- `app.py`: Provides real-time 3D phase-space visualization, dynamic slider controls for spacecraft mass and thrust limits, and instant scorecard generation.

7. CONCLUSION & FUTURE WORK

The Autonomous Orbital Rendezvous & Docking GNC Testbed successfully demonstrates rigorous aerospace control systems engineering. By combining analytical orbital mechanics (Clohessy-Wiltshire equations), optimal control theory (LQR via CARE), PyTorch policy-gradient optimization, and 500-trial Monte Carlo statistical verification, this project provides a fully verifiable, production-grade portfolio piece for space robotics applications.

Future extensions of this framework will incorporate computer vision-based relative navigation, integrating simulated Monocular/Stereo camera sensors with a Perspective-n-Point (PnP) solver and an Extended Kalman Filter (EKF) to process noisy visual measurements prior to state-feedback control.