AWS RDS MYSQL Access Guide

Input Guide

This section outlines the input parameters required for provisioning AWS RDS MYSQL using the DASH portal. Each parameter includes a description, available options, usage guidance, and notes on valid combinations when applicable.

Input Parameter	Description	Values Provided	Value Guidance	Valid Combinations
region	The region where the database instance will be deployed.	us-east-1, us-west-2, eu-west-1, ap-south-1, ca-central-1, eu-west-2, ap-southeast-1, sa-east-1.	Choose the region that is geographically closest to your end users or services to minimize latency and improve performance.	N/A
db_identifier	A unique name to identify the database instance.	A unique name across all DB instances owned by your account in the current AWS Region.	• The DB instance identifier is case-insensitive, but is stored as all lowercase (as in "mydbinstance") • **Constraints**: 1 to 63 alphanumeric characters or hyphens. The first character must be a letter. Can't contain two consecutive hyphens. Can't end with a hyphen.	N/A

db_name	The name of the initial database to be created within the db instance.	Must be a unique database name within the chosen engine.	**Allowed characters:** letters, numbers, underscores (_). Must start with a letter.	N/A
db_username	The master username for database administration.	Alphanumeric string.	1 to 32 alphanumeric characters. The first character must be a letter and should not be set to reserved names such as admin or root.	N/A
db_password	The password associated with the master username for secure access.	Any alphanumeric string.	Set a strong password for the master username. Minimum constraints: At least 8 printable ASCII characters. Can't contain any of the following symbols: / ' " @ . **Example (valid):** MyDBpass#2025	N/A
db_engine_version	The version of the database engine.	**Versions:** 8.0.40, 8.0.39, 8.0.37, 8.0.35, 8.0.33, 8.0.32.	Choose based on MySQL requirements.	N/A
db_instance_class	The compute and memory capacity allocated for the database instance.	**Instance Configuration:** db.t3.micro, db.t4g.micro, db.m5.large, db.m5.xlarge, db.m6g.large, db.m6id.xlarge, db.m7g.large, db.m7g.2xlarge.	Choose based on workload requirements.	N/A

publicly accessible	Determines whether the database can be accessed from the public internet.	**Boolean:** True, False	Choose true if external access is needed, otherwise false.	N/A
db_storage_type	The type of storage allocated for the database.	**Storage types:** gp2 (or) gp3	Choose based on performance and cost requirements.	N/A
db_allocated_storage	The amount of storage (in GB) to be provisioned for the database.	**Allowed values (in GB):** 20, 40, 60, 80, 100	Choose based on workload requirements.	N/A
enable_multi-az	Enables high availability by deploying the database in multiple Availability Zones.	**Boolean:** True, False	Choose true for high availability or false for single-AZ.	N/A
deploy_vm	Whether an ec2 instance should also be provisioned to connect to the DB.	**Boolean:** True, False	Choose whether to set up a connection to a compute resource for this database.	N/A
instance_type	The size and configuration of the EC2 instance, which defines the amount of vCPUs, memory, and networking performance allocated.	t2.nano, t2.micro, t2.small, t2.medium, t2.large, t2.xlarge, t2.2xlarge, a1.metal, c4.large, c4.xlarge.	Choose based on workload requirements (vCPU, memory).	N/A
os_template	Pre-configured base operating system image (Amazon Machine Image) used for provisioning the EC2 instance.	ubuntu-2204-lts, ubuntu-2004-lts, ubuntu-2404-lts, rhel-9, rhel-8, centos, amazon-linux, amazon-linux-2023.	Choose an OS required for your workload.	N/A
owner	The team or individual	Specify the team name or	Provide correct team/individual name.	N/A

	responsible for maintaining the resource.	individual responsible for maintaining the instance.		
application	Associated service or application name for the resource.	Enter the associated service name linked to the instance.	Provide a service name linked to the instance.	N/A
project	Project or initiative name linked to the resource.	Indicate the project or initiative name related to the resource.	Provide the project name related to the resource.	N/A
deployment	The target environment (e.g., development, testing, prod) where the DB will be provisioned.	Define the deployment environment name (e.g., dev, test, prod)	Choose the environment where the database has to be deployed.	N/A
Services expire after 30 days. Create this service now, or schedule for a later date?	RDS MYSQL will be deleted 30 days after creation, or it can be scheduled to be created at a later date.	Create Now (or) Schedule for Later	Choose based on RDS MYSQL requirements.	N/A

Sample Input Selection:







Output Guide

This section outlines the output values generated after AWS MYSQL RDS provisioning through the DASH Portal. These outputs can be used to access, manage, and connect to your MySQL Database.

Outputs	Description	Example Value
endpoint	The database endpoint used to connect to the DB instance.	dash-rds.czeq0oqa6rxx.us-east-1.rds.amazonaws.com
mysql_connection	The MySQL connection string includes endpoint, username, password to connect to the DB.	mysql -h dash-rds.czeq0oqa6rxx.us-east-1.rds.amazonaws.com -u dashrdsuser -p
public_ip	The public IP address of the	34.239.143.7

	provisioned EC2(if enabled).	
ssh_password	The password associated with the SSH username for EC2 access.	1BbbdY0v
ssh_username	The username to connect to the EC2 via SSH.	dash

Note: If **deploy_vm** is set to **false** in the input, the output will only include the endpoint and mysql_connection.

What you can do with these outputs:

1. When publicly accessible is enabled:

You can connect directly to the DB endpoint.

mysql -h <endpoint> -u <db_username> -p <password>

Example: mysql -h dash-rds.czeq0oqa6rxx.us-east-1.rds.amazonaws.com -u dashrdsuser -p

When prompted, enter the value of db_password (which you provided in the input) to connect to the database.

2. When publicly accessible is disabled:

You must first connect to the EC2 and then access the DB from inside it.

Step 1: SSH into the EC2

Example: ssh <ssh_username>@<public_ip>

Replace <ssh_username> and <public_ip> with the values generated in the outputs. When prompted, enter the value of ssh_password to login to the EC2.

Step 2: Connect to the DB engine from the EC2

mysql -h <endpoint> -u <db_username> -p <password>

Example: mysql -h dash-rds.czeq0oqa6rxx.us-east-1.rds.amazonaws.com -u dashrdsuser -p

When prompted, enter the value of db_password (which you provided in input) to log in to the machine.