DASH Azure Container Instances

Input Guide

This section outlines the input parameters required for provisioning Azure Container Instances using the DASH Portal. Each parameter includes a description, available options, guidance on usage, and notes for valid combinations when applicable.

Input Parameter	Description	Values Provided	Value Guidance	Valid Combinations / Notes
region	Azure region where the container will be deployed	East US, Central US, West US 2, Central India, UK South, Canada Central, East Asia, South Central US	Choose the region closest to users or dependent services	N/A
os_type	Operating system for the container	Linux, Windows	Use Linux unless your image explicitly requires Windows	Windows requires Windows-compatible base images
memory_in_gb	Memory (in GB) to allocate to the container	1, 2, 3, 4, 5, 6	Choose based on the memory requirements of the app/image	Some image types may have minimum memory requirements
cpu_cores	Number of CPU cores to allocate	1, 2, 3, 4	Choose based on expected workload; 2+ cores for higher concurrency	More cores = better multi-thread performance

container_name	Container instance name (combined with a random suffix for uniqueness)	Any alphanumeric string	Use `appname-xyz1` format to ensure uniqueness	Must be unique in the subscription
dns_name_label	Public DNS name prefix	Any valid DNS-compatible string	Used to form FQDN like `**myapp.eastus.azurecontainer.io**`	Must be globally unique
image	Container image to deploy	E.g., nginx: latest, myregistry.azurecr.io/myimage:v1	Use Docker Hub or fully qualified Azure Container Registry (ACR) paths	For private registries, `server`, `username` and `password` are required
port	Port to expose on the container	Any valid port (e.g., 80, 443)	The application in the container must be listening on this port	Common values: 80 for HTTP, 443 for HTTPS
server	Docker Hub or ACR registry URL	E.g., index.docker.io, myregistry.azurecr.io	Required only if pulling private images	Docker Hub/Azure registry server
username	Registry username	Your Docker Hub or ACR login	Required for authentication to private container registries	Username for Docker Hub/ACR
Password	Password for ACR or Docker Hub	Your Docker Hub or ACR Password/Key	Required for authentication to private container registries	Password/Key for Docker Hub/ACR
owner	The team or individual responsible for provisioning, managing, and	Specify the team name or individual responsible for maintaining the container instance.	Provide correct team/individual name.	N/A

	maintaining the resource.			
application	Associated service or application name for the resource.	Enter the associated service name linked to the container instance.	Provide a service name linked to the container instance.	N/A
project	Project or initiative name linked to the resource.	Indicate the project or initiative name related to the resource.	Provide the project name related to the resource.	N/A
deployment	The target environment (e.g., development, testing, prod) where the resource will be provisioned.	Define the deployment environment name (e.g., dev, test, prod)	Choose the environment where the container instance has to be deployed.	N/A
Services expire after 30 days. Create this service now, or schedule for a later date?	ACI will be deleted 30 days after creation, or it can be scheduled to be created at a later date.	Create Now (or) Schedule for Later	Choose based on ACI requirements.	N/A

Sample Input Selection:

CONTAINER NAME	azureaci
REGION	East US
OS TYPE	Linux
MEMORY IN GB	2
CPU CORES	2
DNS NAME LABEL	acidash
IMAGE	dashacrnew.azurecr.io/my-html-website:latest
PORT	80
SERVER	dashacrnew.azurecr.io
USERNAME	dashacrnew
PASSWORD	WYGBi8VXongjYNTHPhl4rW+VjmZZEhB3xwzLV58ICu+ACRBp8c
OWNER	dashuser
APPLICATION	dashapp

PROJECT	dash
DEPLOYMENT	dev

Services expire after 30 days. Create this service now, or schedule for a later date?

Create Now Schedule for Later

ADD SERVICE CANCEL

Output Guide

This section outlines the output values generated after provisioning an Azure Container Instance through the DASH Portal. These outputs can be used to access, manage, and connect to your virtual machine.

Name	Description	Example Value
container_group_fqdn	The Fully Qualified Domain Name (FQDN) of the Azure Container Group, accessible over the internet	newdemo.eastus.azurecontainer.io
container_ipv4_address	The public IPv4 address assigned to the Azure Container Group	52.226.98.112

What You Can Do with These Outputs

Follow the steps below to access and verify your Azure Container Instance deployment. Replace any placeholders like `<container_group_fqdn>` with actual values from the outputs provided after provisioning.

Access the Application URL

Open your browser and go to:

`http://<container_group_fqdn>`

Example:
`http://newdemo.eastus.azurecontainer.io`

- This is the public DNS address of your container instance.