

Package ‘SIHR’

June 14, 2022

Type Package

Title Statistical Inference in High Dimensional Regression

Version 0.1.0

Description Inference procedures in the high-dimensional setting for

- (1) linear functionals in generalized linear regression ('Cai et al.' (2019) <[arXiv:1904.12891](#)>, 'Guo et al.' (2020) <[arXiv:2012.07133](#)>, 'Cai et al.' (2021)),
- (2) quadratic functionals in linear regression ('Guo et al.' (2019) <[arXiv:1909.01503](#)>)
- (3) individual treatment effects in generalized linear regression.

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.2.0

Maintainer Zhenyu Wang <zw425@stat.rutgers.edu>

URL <https://github.com/prabrishar1/SIHR>

BugReports <https://github.com/prabrishar1/SIHR/issues>

Imports CVXR,
glmnet,
stats

R topics documented:

ITE	2
LF	3
print.summary.ITE	5
print.summary.LF	6
print.summary.QF	6
QF	7
summary.ITE	8
summary.LF	9
summary.QF	10
Index	11

ITE

Inference for difference of linear combinations of the regression vectors in high dimensional generalized linear regressions

Description

Computes the bias-corrected estimator of the difference of linear combinations of the regression vectors for the high dimensional generalized linear regressions and the corresponding standard error.

Usage

```
ITE(
  X1,
  y1,
  X2,
  y2,
  loading.mat,
  model = "linear",
  intercept = TRUE,
  intercept.loading,
  lambda = NULL,
  mu = NULL,
  init.step = NULL,
  resol = 1.5,
  maxiter = 6,
  alpha = 0.05,
  verbose = TRUE
)
```

Arguments

X1	Design matrix for the first sample, of dimension $n_1 \times p$
y1	Outcome vector for the first sample, of length n_1
X2	Design matrix for the second sample, of dimension $n_2 \times p$
y2	Outcome vector for the second sample, of length n_1
loading.mat	Loading matrix, $nrow=p$
model	The high dimensional regression model, either linear or logistic or logistic alternative or probit
intercept	Should intercept(s) be fitted for the initial estimators (default = TRUE)
intercept.loading	Should intercept be included for the loading (default = TRUE)
lambda	lambda The tuning parameter in fitting model (default = NULL)
mu	The dual tuning parameter used in the construction of the projection direction (default = NULL)
init.step	The initial step size used to compute mu; if set to NULL it is computed to be the number of steps (maxiter) to obtain the smallest mu

resol	The factor by which mu is increased/decreased to obtain the smallest mu such that the dual optimization problem for constructing the projection direction converges (default = 1.5)
maxiter	Maximum number of steps along which mu is increased/decreased to obtain the smallest mu such that the dual optimization problem for constructing the projection direction converges (default = 6)
alpha	Level of significance to construct two-sided confidence interval (default = 0.05)
verbose	Should intermediate message(s) be printed (default = TRUE)

Value

est.plugin.vec	The vector of plugin(biased) estimators for the linear combination of regression coefficients, length of ncol(loading.mat); corresponding to different column in loading.mat
est.debias.vec	The vector of bias-corrected estimators for the linear combination of regression coefficients, length of ncol(loading.mat); corresponding to different column in loading.mat
se.vec	The vector of standard errors of the bias-corrected estimators, length of ncol(loading.mat); corresponding to different column in loading.mat
ci.mat	The matrix of two.sided confidence interval for the linear combination, of dimension ncol(loading.mat) x 2; the row corresponding to different column in loading.mat

Examples

```

X1 = matrix(rnorm(100*120), nrow=100, ncol=120)
y1 = -0.5 + X1[,1] * 0.5 + X1[,2] * 1 + rnorm(100)
X2 = matrix(rnorm(90*120), nrow=90, ncol=120)
y2 = -0.4 + X2[,1] * 0.48 + X2[,2] * 1.1 + rnorm(90)
loading.mat = cbind(c(1, 1, rep(0, 118), c(-0.5, -1, rep(0, 118))))
Est = ITE(X1, y1, X2, y2, loading.mat, model="linear")
Est$est.plugin.vec ## plugin(biased) estimators
Est$est.debias.vec ## bias-corrected estimators
Est$se.vec ## standard errors for bias-corrected estimators
Est$ci.mat ## two-sided confidence interval for bias-corrected estimators
## Not run:
summary(Est)

## End(Not run)

```

LF

Inference for linear combination of the regression vector in high dimensional generalized linear regression

Description

Inference for linear combination of the regression vector in high dimensional generalized linear regression

Usage

```

LF(
  X,
  y,
  loading.mat,
  model = c("linear", "logistic", "logistic_alternative", "probit"),
  intercept = TRUE,
  intercept.loading = TRUE,
  lambda = NULL,
  mu = NULL,
  init.step = NULL,
  resol = 1.5,
  maxiter = 6,
  alpha = 0.05,
  verbose = TRUE
)

```

Arguments

<code>X</code>	Design matrix, of dimension $n \times p$
<code>y</code>	Outcome vector, of length n
<code>loading.mat</code>	Loading matrix, $nrow=p$
<code>model</code>	The high dimensional regression model, either linear or logistic or logistic_alternative or probit
<code>intercept</code>	Should intercept be fitted for the initial estimator (default = TRUE)
<code>intercept.loading</code>	Should intercept be included for the loading (default = TRUE)
<code>lambda</code>	The tuning parameter in fitting model (default = NULL)
<code>mu</code>	The dual tuning parameter used in the construction of the projection direction (default = NULL)
<code>init.step</code>	The initial step size used to compute μ ; if set to NULL it is computed to be the number of steps (<code>maxiter</code>) to obtain the smallest μ
<code>resol</code>	The factor by which μ is increased/decreased to obtain the smallest μ such that the dual optimization problem for constructing the projection direction converges (default = 1.5)
<code>maxiter</code>	Maximum number of steps along which μ is increased/decreased to obtain the smallest μ such that the dual optimization problem for constructing the projection direction converges (default = 6)
<code>alpha</code>	Level of significance to construct two-sided confidence interval (default = 0.05)
<code>verbose</code>	Should intermediate message(s) be printed (default = TRUE)

Value

<code>est.plugin.vec</code>	The vector of plugin(biased) estimators for the linear combination of regression coefficients, length of <code>ncol(loading.mat)</code> ; corresponding to different column in <code>loading.mat</code>
<code>est.debias.vec</code>	The vector of bias-corrected estimators for the linear combination of regression coefficients, length of <code>ncol(loading.mat)</code> ; corresponding to different column in <code>loading.mat</code>

se.vec	The vector of standard errors of the bias-corrected estimators, length of ncol(loading.mat); corresponding to different column in loading.mat
ci.mat	The matrix of two.sided confidence interval for the linear combination, of dimension ncol(loading.mat) x 2; the row corresponding to different column in loading.mat

Examples

```
X = matrix(rnorm(100*120), nrow=100, ncol=120)
y = -0.5 + X[,1] * 0.5 + X[,2] * 1 + rnorm(100)
loading.mat = cbind(c(1, 1, rep(0, 118), c(-0.5, -1, rep(0, 118))))
Est = LF(X, y, loading.mat, model="linear")
Est$est.plugin.vec ## plugin(biased) estimators
Est$est.debias.vec ## bias-corrected estimators
Est$se.vec ## standard errors for bias-corrected estimators
Est$ci.mat ## two-sided confidence interval for bias-corrected estimators
## Not run:
summary(Est)

## End(Not run)
```

print.summary.ITE	<i>Summarizing ITE</i>
-------------------	------------------------

Description

‘summary’ method for class ‘ITE’

Usage

```
## S3 method for class 'summary.ITE'
print(obj, digits = 5)
```

Arguments

obj	An object of class ‘summary.ITE’, a result of a call to ‘summary.ITE’
digits	The number of digits to use when printing

Examples

```
## Not run:
#' ##-- Continuing the ITE(.) example:
summary(Est)

## End(Not run)
```

print.summary.LF	<i>Summarizing LF</i>
------------------	-----------------------

Description

‘summary’ method for class ‘LF’

Usage

```
## S3 method for class 'summary.LF'
print(obj, digits = 5)
```

Arguments

obj	An object of class ‘summary.LF’, a result of a call to ‘summary.LF’
digits	The number of digits to use when printing

Examples

```
## Not run:
#' ##-- Continuing the LF(.) example:
summary(Est)

## End(Not run)
```

print.summary.QF	<i>Summarizing QF</i>
------------------	-----------------------

Description

‘summary’ method for class ‘QF’

Usage

```
## S3 method for class 'summary.QF'
print(obj, digits = 5)
```

Arguments

obj	An object of class ‘summary.QF’, a result of a call to ‘summary.QF’
digits	The number of digits to use when printing

Examples

```
## Not run:
#' ##-- Continuing the QF(.) example:
summary(Est)

## End(Not run)
```

QF

Inference for quadratic forms of the regression vector in high dimensional linear and logistic regressions

Description

Inference for quadratic forms of the regression vector in high dimensional linear and logistic regressions

Usage

```
QF(
  X,
  y,
  G,
  A = NULL,
  model = c("linear", "logistic", "logistic_alternative"),
  intercept = TRUE,
  tau.vec = c(0.5, 1),
  lambda = NULL,
  mu = NULL,
  init.step = NULL,
  resol = 1.5,
  maxiter = 6,
  alpha = 0.05,
  verbose = TRUE
)
```

Arguments

X	Design matrix, of dimension $n \times p$
y	Outcome vector, of length n
G	The set of indices, G in the quadratic form
A	The matrix A in the quadratic form, of dimension $ G \times G $. If NULL A would be set as the $ G \times G $ submatrix of the population covariance matrix corresponding to the index set G (default = NULL)
model	The high dimensional regression model, either linear or logistic or logistic_alternative
intercept	Should intercept be fitted for the initial estimator (default = TRUE)
tau.vec	The vector of enlargement factors for asymptotic variance of the bias-corrected estimator to handle super-efficiency (default = $c(0.5, 1)$)
lambda	The tuning parameter in fitting model (default = NULL)
mu	The dual tuning parameter used in the construction of the projection direction (default = NULL)
init.step	The initial step size used to compute mu; if set to NULL it is computed to be the number of steps ($< \text{maxiter}$) to obtain the smallest mu such that the dual optimization problem for constructing the projection direction converges (default = NULL)

resol	Resolution or the factor by which mu is increased/decreased to obtain the smallest mu such that the dual optimization problem for constructing the projection direction converges (default = 1.5)
maxiter	aximum number of steps along which mu is increased/decreased to obtain the smallest mu such that the dual optimization problem for constructing the projection direction converges (default = 6)
alpha	Level of significance to construct two-sided confidence interval (default = 0.05)
verbose	Should intermediate message(s) be printed (default = TRUE)

Value

est.plugin	The plugin(biased) estimator for the quadratic form of the regression vector restricted to G
est.debias	The bias-corrected estimator of the quadratic form of the regression vector
se.vec	The vector of standard errors of the bias-corrected estimator, length of tau.vec; corresponding to different values of tau.vec
ci.mat	The matrix of two.sided confidence interval for the quadratic form of the regression vector; row corresponds to different values of tau.vec

Examples

```

X = matrix(rnorm(100*120), nrow=100, ncol=120)
y = X[,1] * 0.5 + X[,2] * 1 + rnorm(100)
G = c(1,2)
A = matrix(c(1.5, 0.8, 0.8, 1.5), nrow=2, ncol=2)
Est = QF(X, y, G, A, model="linear")
Est$est.plugin ## plugin(biased) estimator
Est$est.debias ## bias-corrected estimator
Est$se.vec ## standard errors for bias-corrected estimators for each tau
Est$ci.mat ## two-sided confidence interval for bias-corrected estimator for each tau
## Not run:
summary(Est)

## End(Not run)

```

summary.ITE

*Summarizing ITE***Description**

‘summary’ method for class ‘ITE’

Usage

```

## S3 method for class 'ITE'
summary(obj, alpha = 0.05, alternative = c("two.sided", "less", "greater"))

```


Arguments

obj	An object of class 'ITE', a result of a call to 'ITE'
alpha	Level of significance to construct confidence interval
alternative	indicates the alternative hypothesis to construct confidence interval and must be one of "two.sided" (default), "less", or "greater".

Value

The function 'summary.ITE' computes and returns a list of summary statistics of LF given 'obj'

output.est	a $ncol(\text{loading.mat})$ x 5 matrix with columns for the plugin(biased) estimators, bias-corrected estimators, its standard error, z-statistic and corresponding (two-sided) p-value; Each row corresponds to each loading.
output.ci	a $ncol(\text{loading.mat})$ x 2 matrix with columns for lower and upper of (two-sided) confidence intervals; Each row corresponds to each loading.

Examples

```
## Not run:
##-- Continuing the ITE(.) example:
sEst = summary(Est)
sEst

## End(Not run)
```

summary.LF	<i>Summarizing LF</i>
------------	-----------------------

Description

'summary' method for class 'LF'

Usage

```
## S3 method for class 'LF'
summary(obj, alpha = 0.05, alternative = c("two.sided", "less", "greater"))
```

Arguments

obj	An object of class 'LF', a result of a call to 'LF'
alpha	Level of significance to construct confidence interval
alternative	indicates the alternative hypothesis to construct confidence interval and must be one of "two.sided" (default), "less", or "greater".

Value

The function 'summary.LF' computes and returns a list of summary statistics of LF given 'obj'

output.est	a $ncol(\text{loading.mat})$ x 5 matrix with columns for the plugin(biased) estimators, bias-corrected estimators, its standard error, z-statistic and corresponding (two-sided) p-value; Each row corresponds to each loading.
output.ci	a $ncol(\text{loading.mat})$ x 2 matrix with columns for lower and upper of (two-sided) confidence intervals; Each row corresponds to each loading.

Examples

```
## Not run:
##-- Continuing the LF(.) example:
sEst = summary(Est)
sEst

## End(Not run)
```

summary.QF

*Summarizing QF***Description**

‘summary’ method for class ‘QF’

Usage

```
## S3 method for class 'QF'
summary(obj, alpha = 0.05, alternative = c("two.sided", "less", "greater"))
```

Arguments

obj	An object of class ‘QF’, a result of a call to ‘QF’
alpha	Level of significance to construct confidence interval
alternative	indicates the alternative hypothesis to construct confidence interval and must be one of "two.sided" (default), "less", or "greater".

Value

The function ‘summary.QF’ computes and returns a list of summary statistics of LF given ‘obj’

output.est	a $length(\tau.vec)$ x 5 matrix with columns for the plugin(biased) estimators, bias-corrected estimators, its standard error, z-statistic and corresponding (two-sided) p-value; Each row corresponds to each tau.
output.ci	a $length(\tau.vc)$ x 2 matrix with columns for lower and upper of (two-sided) confidence intervals; Each row corresponds to each tau.

Examples

```
## Not run:
##-- Continuing the QF(.) example:
sEst = summary(Est)
sEst

## End(Not run)
```

Index

ITE, [2](#)

LF, [3](#)

print.summary.ITE, [5](#)

print.summary.LF, [6](#)

print.summary.QF, [6](#)

QF, [7](#)

summary.ITE, [8](#)

summary.LF, [9](#)

summary.QF, [10](#)