

GITHUB + PLAYWRIGHT + ALLURE SETUP

=====

Step 1: Install Allure packages

Run these commands in your Playwright project:

```
npm install -D allure-commandline
npm install -D allure-playwright
```

Step 2: Modify GitHub Actions YAML file

Update your .github/workflows/playwright.yml file:

name: Playwright Tests

on:

push:

branches: [main, master]

schedule:

12:30 UTC = 6:00 PM IST (UTC+5:30)

Runs every day at 6:00 PM IST

- cron: '30 12 * * *'

workflow_dispatch:

jobs:

test:

timeout-minutes: 60

runs-on: ubuntu-latest

steps:

- uses: actions/checkout@v4

- uses: actions/setup-node@v4

with:

node-version: lts/*

- name: Install dependencies

run: npm ci

- name: Install Playwright Browsers
run: npx playwright install --with-deps
- name: Install Allure CI
run: npm install -g allure-commandline
- name: Run Playwright tests
run: npx playwright test
- name: Generate Allure Report
run: allure generate allure-results --clean --single-file -o allure-report
if: \${{ !cancelled() }}
- name: Upload Playwright Report
uses: actions/upload-artifact@v4
if: \${{ !cancelled() }}
with:
 name: playwright-report
 path: playwright-report/
 retention-days: 30
- name: Upload Allure Report
uses: actions/upload-artifact@v4
if: \${{ !cancelled() }}
with:
 name: allure-report
 path: allure-report/
 retention-days: 30

Step 3: Modify Playwright config

In playwright.config.ts, add the Allure reporter:

```
reporter: [
  ['html'],
  ['list'],
  ['allure-playwright']
],
```

Example:

```
import { defineConfig } from '@playwright/test';

export default defineConfig({
  testDir: './tests',

  reporter: [
    ['html'],
    ['list'],
    ['allure-playwright']
  ],

  use: {
    trace: 'on-first-retry'
  }
});
```

Step 4: Add allure-results to .gitignore

Open your .gitignore file and add:

```
/allure-results/
```

Step 5: Push the code to GitHub

Run:

```
git add .
git commit -m "Add Allure reporting to Playwright"
git push origin main
```

Step 6: Check GitHub Actions

1. Open your GitHub repository.
2. Click the "Actions" tab.
3. Select "Playwright Tests".
4. Open the latest workflow run.
5. Check whether the tests passed.

6. After the workflow finishes, go to the "Artifacts" section.

You should see:

playwright-report
allure-report

Step 7: View Allure Report

Download the "allure-report" artifact from GitHub Actions.

The generated report will contain the Allure HTML report.

IMPORTANT:

You do NOT need to commit /allure-results/ to GitHub.

The flow is:

Playwright Tests



allure-playwright



allure-results/



allure generate



allure-report/



GitHub Actions Artifact



Download and view Allure Report