Experiment No.6							
Perform POS ta	agging	on	the	given	English	and	Indian
Language Text							
Date of Performance:							
Date of Submissi	on:						



Vidyavardhini's College of Engineering and Technology Department of Artificial Intelligence & Data Science

Aim: Perform POS tagging on the given English and Indian Language Text

Objective: To study POS Tagging and tag the part of speech for given input in english and an Indian Language.

Theory:

The primary target of Part-of-Speech (POS) tagging is to identify the grammatical group of a given word. Whether it is a NOUN, PRONOUN, ADJECTIVE, VERB, ADVERBS, etc. based on the context. POS Tagging looks for relationships within the sentence and assigns a corresponding tag to the word.

POS Tagging (Parts of Speech Tagging) is a process to mark up the words in text format for a particular part of a speech based on its definition and context. It is responsible for text reading in a language and assigning some specific token (Parts of Speech) to each word. It is also called grammatical tagging.

Steps Involved in the POS tagging example:

- Tokenize text (word tokenize)
- apply pos_tag to above step that is nltk.pos_tag(tokenize_text)

Code:

```
import nltk
nltk.download('punkt')
nltk.download('averaged_perceptron_tagger')
[nltk_data] Downloading package punkt to /root/nltk_data...
[nltk_data] Unzipping tokenizers/punkt.zip.
[nltk_data] Downloading package averaged_perceptron_tagger to
[nltk_data] /root/nltk_data...
[nltk_data] Unzipping taggers/averaged_perceptron_tagger.zip.
True

from nltk.chunk import RegexpParser
from nltk.tokenize import word_tokenize
sentence = "Education is the transmission of knowledge, skills, and character traits."
```

CSDL7013: Natural Language Processing Lab



Vidyavardhini's College of Engineering and Technology Department of Artificial Intelligence & Data Science

```
### Tokenization
tokens = word tokenize(sentence)
['Education', 'is', 'the', 'transmission', 'of', 'knowledge',
'skills', ',', 'and', 'character', 'traits', '.']
### POS tagging
pos tags = nltk.pos tag(tokens)
pos tags
[('Education', 'NN'), ('is', 'VBZ'), ('the', 'DT'), ('transmission',
'NN'), ('of', 'IN'), ('knowledge', 'NN'), (',', ','), ('skills', 'NNS'),
(',', ','), ('and', 'CC'), ('character', 'NN'), ('traits', 'NNS'), ('.',
'.')]
### Chunking patterns
chunk patterns = r"""
   NP: {<DT>?<JJ>*<NN>} # Chunk noun phrases
   VP: {<VB.*><NP|PP>} # Chunk verb phrases
11 11 11
chunk patterns
\n NP: {<DT>?<JJ>*<NN>} # Chunk noun phrases\n VP: {<VB.*><NP|PP>} #
Chunk verb phrases\n
### Create a chunk parser
chunk parser = RegexpParser(chunk patterns)
chunk parser
<chunk.RegexpParser with 2 stages>
### Perform chunking
result = chunk parser.parse(pos tags)
print(result)
  (NP Education/NN)
  (VP is/VBZ (NP the/DT transmission/NN))
 of/IN
  (NP knowledge/NN)
  ,/,
 skills/NNS
 ,/,
  and/CC
  (NP character/NN)
 traits/NNS
  ./.)
```



Vidyavardhini's College of Engineering and Technology Department of Artificial Intelligence & Data Science

Conclusion:

POS tagging (Part-of-Speech tagging) involves labeling words in a text with their grammatical categories (e.g., noun, verb, adjective). For English text, widely available libraries like NLTK or spaCy provide accurate tagging due to well-defined grammar. Indian languages pose greater challenges due to their diversity, script variations, and limited resources. Building accurate POS taggers for Indian languages often requires language-specific models and extensive linguistic knowledge.