

Name:Prachi Mehta

Roll No:28

UID:2018130025

Batch:B

CEL 51, DCCN, Monsoon 2020

## Lab 2: Basic Network Utilities

---

This lab introduces some basic network monitoring/analysis tools. There are a few exercises along the way. You should write up answers to the *ping* and *traceroute* exercises and turn them in the next lab. (You should try out each tool, whether it is needed for an exercise or not!).

Prerequisite: Basic understanding of command line utilities of Linux Operating system.

**Aim:** To study basic computer networking commands such as ping,traceroute,whois,netstat.

### Some Basic command line Networking utilities

Start with a few of the most basic command line tools. These commands are available on Unix, including Linux (and the first two, at least, are also for Windows). Some parameters or options might differ on different operating systems. Remember that you can use `man <command>` to get information about a command and its options.

**ping** — The command `ping <host>` sends a series of packets and expects to receive a response to each packet. When a return packet is received, ping reports the round trip time (the time between sending the packet and receiving the response). Some routers and firewalls block ping requests, so you might get no response at all. Ping can be used to check whether a computer is up and running, to measure network delay time, and to check for dropped packets indicating network congestion. Note that `<host>` can be either a domain name or an IP address. By default, ping will send a packet every second indefinitely; stop it with Control-C

Network latency, specifically round trip time (RTT), can be measured using `ping`, which sends ICMP packets. The syntax for the command in Linux or Mac OS is:

```
ping [-c <count>] [-s <packetsize>] <hostname>
```

The syntax in Windows is:

```
ping [-n <count>] [-l <packetsize>] <hostname>
```

The default number of ICMP packets to send is either infinite (in Linux and Mac OS) or 4 (in Windows). The default packet size is either 64 bytes (in Linux) or 32 bytes (in Windows). You can specify either a hostname (e.g., spit.ac.in) or an IP address.

To save the output from `ping` to a file, include a greater than symbol and a file name at the end of the command. For example:

```
ping -c 10 google.com > ping_c10_s64_google.log
```

### EXPERIMENTS WITH PING

1. Ping the any hosts 10 times (i.e., packet count is 10) with a packet size of 64 bytes, 100 bytes, 500 bytes, 1000 bytes, 1400 bytes

Ans:

```
C:\Users\LENOVO>ping -n 10 -l 64 www.amazon.com

Pinging d3ag4hukkh62yn.cloudfront.net [13.227.137.166] with 64 bytes of data:
Reply from 13.227.137.166: bytes=64 time=36ms TTL=244
Reply from 13.227.137.166: bytes=64 time=28ms TTL=244
Reply from 13.227.137.166: bytes=64 time=40ms TTL=244
Reply from 13.227.137.166: bytes=64 time=35ms TTL=244
Reply from 13.227.137.166: bytes=64 time=30ms TTL=244
Reply from 13.227.137.166: bytes=64 time=24ms TTL=244
Reply from 13.227.137.166: bytes=64 time=34ms TTL=244
Reply from 13.227.137.166: bytes=64 time=33ms TTL=244
Reply from 13.227.137.166: bytes=64 time=21ms TTL=244
Reply from 13.227.137.166: bytes=64 time=49ms TTL=244

Ping statistics for 13.227.137.166:
    Packets: Sent = 10, Received = 10, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 21ms, Maximum = 49ms, Average = 33ms
```

```
C:\Users\LENOVO>ping -n 10 -l 100 www.amazon.com
```

```
Pinging d3ag4hukkh62yn.cloudfront.net [13.227.137.166] with 100 bytes of data:
```

```
Reply from 13.227.137.166: bytes=100 time=31ms TTL=244  
Reply from 13.227.137.166: bytes=100 time=36ms TTL=244  
Reply from 13.227.137.166: bytes=100 time=19ms TTL=244  
Reply from 13.227.137.166: bytes=100 time=32ms TTL=244  
Reply from 13.227.137.166: bytes=100 time=46ms TTL=244  
Reply from 13.227.137.166: bytes=100 time=36ms TTL=244  
Reply from 13.227.137.166: bytes=100 time=49ms TTL=244  
Reply from 13.227.137.166: bytes=100 time=34ms TTL=244  
Reply from 13.227.137.166: bytes=100 time=49ms TTL=244  
Reply from 13.227.137.166: bytes=100 time=33ms TTL=244
```

```
Ping statistics for 13.227.137.166:
```

```
    Packets: Sent = 10, Received = 10, Lost = 0 (0% loss),  
Approximate round trip times in milli-seconds:  
    Minimum = 19ms, Maximum = 49ms, Average = 36ms
```

```
C:\Users\LENOVO>ping -n 10 -l 500 www.amazon.com
```

```
Pinging d3ag4hukkh62yn.cloudfront.net [13.227.137.166] with 500 bytes of data:
```

```
Reply from 13.227.137.166: bytes=500 time=38ms TTL=244  
Reply from 13.227.137.166: bytes=500 time=53ms TTL=244  
Reply from 13.227.137.166: bytes=500 time=46ms TTL=244  
Reply from 13.227.137.166: bytes=500 time=29ms TTL=244  
Reply from 13.227.137.166: bytes=500 time=54ms TTL=244  
Reply from 13.227.137.166: bytes=500 time=29ms TTL=244  
Reply from 13.227.137.166: bytes=500 time=44ms TTL=244  
Reply from 13.227.137.166: bytes=500 time=55ms TTL=244  
Reply from 13.227.137.166: bytes=500 time=28ms TTL=244  
Reply from 13.227.137.166: bytes=500 time=43ms TTL=244
```

```
Ping statistics for 13.227.137.166:
```

```
    Packets: Sent = 10, Received = 10, Lost = 0 (0% loss),  
Approximate round trip times in milli-seconds:  
    Minimum = 28ms, Maximum = 55ms, Average = 41ms
```



```
C:\Users\LENOVO>ping -n 10 -l 1000 www.amazon.com

Pinging d3ag4hukkh62yn.cloudfront.net [13.227.137.166] with 1000 bytes of data:
Reply from 13.227.137.166: bytes=1000 time=39ms TTL=244
Reply from 13.227.137.166: bytes=1000 time=37ms TTL=244
Reply from 13.227.137.166: bytes=1000 time=56ms TTL=244
Reply from 13.227.137.166: bytes=1000 time=50ms TTL=244
Reply from 13.227.137.166: bytes=1000 time=71ms TTL=244
Reply from 13.227.137.166: bytes=1000 time=30ms TTL=244
Reply from 13.227.137.166: bytes=1000 time=43ms TTL=244
Reply from 13.227.137.166: bytes=1000 time=76ms TTL=244
Reply from 13.227.137.166: bytes=1000 time=40ms TTL=244
Reply from 13.227.137.166: bytes=1000 time=49ms TTL=244

Ping statistics for 13.227.137.166:
    Packets: Sent = 10, Received = 10, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 30ms, Maximum = 76ms, Average = 49ms
```

```
C:\Users\LENOVO>ping -n 10 -l 1400 www.amazon.com

Pinging e15316.e22.akamaiedge.net [104.90.201.153] with 1400 bytes of data:
Reply from 104.90.201.153: bytes=1400 time=37ms TTL=57
Reply from 104.90.201.153: bytes=1400 time=28ms TTL=57
Reply from 104.90.201.153: bytes=1400 time=47ms TTL=57
Reply from 104.90.201.153: bytes=1400 time=64ms TTL=57
Reply from 104.90.201.153: bytes=1400 time=49ms TTL=57
Reply from 104.90.201.153: bytes=1400 time=48ms TTL=57
Reply from 104.90.201.153: bytes=1400 time=35ms TTL=57
Reply from 104.90.201.153: bytes=1400 time=53ms TTL=57
Reply from 104.90.201.153: bytes=1400 time=50ms TTL=57
Reply from 104.90.201.153: bytes=1400 time=41ms TTL=57

Ping statistics for 104.90.201.153:
    Packets: Sent = 10, Received = 10, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 28ms, Maximum = 64ms, Average = 45ms
```

```
C:\Users\LENOVO>ping -n 10 -l 64 www.youtube.com

Pinging youtube-ui.l.google.com [2404:6800:4002:803::200e] with 64 bytes of data:
Reply from 2404:6800:4002:803::200e: time=59ms
Reply from 2404:6800:4002:803::200e: time=66ms
Reply from 2404:6800:4002:803::200e: time=59ms
Reply from 2404:6800:4002:803::200e: time=53ms
Reply from 2404:6800:4002:803::200e: time=82ms
Reply from 2404:6800:4002:803::200e: time=42ms
Reply from 2404:6800:4002:803::200e: time=56ms
Reply from 2404:6800:4002:803::200e: time=51ms
Reply from 2404:6800:4002:803::200e: time=64ms
Reply from 2404:6800:4002:803::200e: time=58ms

Ping statistics for 2404:6800:4002:803::200e:
    Packets: Sent = 10, Received = 10, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 42ms, Maximum = 82ms, Average = 59ms
```

```
C:\Users\LENOVO>ping -n 10 -l 100 www.youtube.com

Pinging youtube-ui.l.google.com [2404:6800:4002:803::200e] with 100 bytes of data:
Reply from 2404:6800:4002:803::200e: time=62ms
Reply from 2404:6800:4002:803::200e: time=52ms
Reply from 2404:6800:4002:803::200e: time=75ms
Reply from 2404:6800:4002:803::200e: time=59ms
Reply from 2404:6800:4002:803::200e: time=54ms
Reply from 2404:6800:4002:803::200e: time=48ms
Reply from 2404:6800:4002:803::200e: time=63ms
Reply from 2404:6800:4002:803::200e: time=58ms
Reply from 2404:6800:4002:803::200e: time=52ms
Reply from 2404:6800:4002:803::200e: time=47ms

Ping statistics for 2404:6800:4002:803::200e:
    Packets: Sent = 10, Received = 10, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 47ms, Maximum = 75ms, Average = 57ms
```



```
C:\Users\LENOVO>ping -n 10 -l 500 www.youtube.com
```

```
Pinging youtube-ui.l.google.com [2404:6800:4002:803::200e] with 500 bytes of data:
```

```
Reply from 2404:6800:4002:803::200e: time=61ms  
Reply from 2404:6800:4002:803::200e: time=60ms  
Reply from 2404:6800:4002:803::200e: time=74ms  
Reply from 2404:6800:4002:803::200e: time=69ms  
Reply from 2404:6800:4002:803::200e: time=67ms  
Reply from 2404:6800:4002:803::200e: time=61ms  
Reply from 2404:6800:4002:803::200e: time=75ms  
Reply from 2404:6800:4002:803::200e: time=64ms  
Reply from 2404:6800:4002:803::200e: time=83ms  
Reply from 2404:6800:4002:803::200e: time=81ms
```

```
Ping statistics for 2404:6800:4002:803::200e:
```

```
    Packets: Sent = 10, Received = 10, Lost = 0 (0% loss),
```

```
Approximate round trip times in milli-seconds:
```

```
    Minimum = 60ms, Maximum = 83ms, Average = 69ms
```

```
C:\Users\LENOVO>ping -n 10 -l 1000 www.youtube.com
```

```
Pinging youtube-ui.l.google.com [2404:6800:4002:803::200e] with 1000 bytes of data:
```

```
Reply from 2404:6800:4002:803::200e: time=77ms  
Reply from 2404:6800:4002:803::200e: time=59ms  
Reply from 2404:6800:4002:803::200e: time=75ms  
Reply from 2404:6800:4002:803::200e: time=78ms  
Reply from 2404:6800:4002:803::200e: time=63ms  
Reply from 2404:6800:4002:803::200e: time=56ms  
Reply from 2404:6800:4002:803::200e: time=50ms  
Reply from 2404:6800:4002:803::200e: time=55ms  
Reply from 2404:6800:4002:803::200e: time=54ms  
Reply from 2404:6800:4002:803::200e: time=80ms
```

```
Ping statistics for 2404:6800:4002:803::200e:
```

```
    Packets: Sent = 10, Received = 10, Lost = 0 (0% loss),
```

```
Approximate round trip times in milli-seconds:
```

```
    Minimum = 50ms, Maximum = 80ms, Average = 64ms
```

```

C:\Users\LENOVO>ping -n 10 -l 1400 www.youtube.com

Pinging youtube-ui.l.google.com [2404:6800:4002:803::200e] with 1400 bytes of data:
Reply from 2404:6800:4002:803::200e: time=65ms
Reply from 2404:6800:4002:803::200e: time=89ms
Reply from 2404:6800:4002:803::200e: time=73ms
Reply from 2404:6800:4002:803::200e: time=67ms
Reply from 2404:6800:4002:803::200e: time=89ms
Reply from 2404:6800:4002:803::200e: time=74ms
Reply from 2404:6800:4002:803::200e: time=72ms
Reply from 2404:6800:4002:803::200e: time=63ms
Reply from 2404:6800:4002:803::200e: time=95ms
Reply from 2404:6800:4002:803::200e: time=59ms

Ping statistics for 2404:6800:4002:803::200e:
    Packets: Sent = 10, Received = 10, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 59ms, Maximum = 95ms, Average = 74ms

```

## QUESTIONS ABOUT LATENCY

Now look at the results you gathered and answer the following questions about latency. Store your answers in a file named `ping.txt`.

1. Does the average RTT vary between different hosts? What aspects of latency (transmit, propagation, and queueing delay) might impact this and why?
  - We can conclude from the output that average RRT varies between different hosts. Propagation delay might impact this because Propagation delay is the time it takes a bit to propagate from one router to the next. If the distance between the routers is increased and where the server is located, it will take longer time to propagate, that is, there would be more propagation delay.
2. Does the average RTT vary with different packet sizes? What aspects of latency (transmit, propagation, and queueing delay) might impact this and why?
  - RTT increases with increase in packet size, on performing experiments we can observe and get the same results.
  - Transmission delay is the time taken to transmit a packet size and bandwidth. Since we are using different packet size RTT for different packet sizes will be impacted because of transmission delay.



**Exercise 1:** Experiment with ping to find the round trip times to a variety of destinations. Write up any interesting observations, including in particular how the round trip time compares to the physical distance. Here are a few places from who to get replies: www.uw.edu, www.cornell.edu, berkeley.edu, www.uchicago.edu, www.ox.ac.uk (England), www.u-tokyo.ac.jp (Japan).

```
C:\Users\LENOVO>ping -n 10 -l 64 www.uw.edu

Pinging www.washington.edu [128.95.155.198] with 64 bytes of data:
Reply from 128.95.155.198: bytes=64 time=295ms TTL=47
Reply from 128.95.155.198: bytes=64 time=308ms TTL=47
Reply from 128.95.155.198: bytes=64 time=286ms TTL=47
Reply from 128.95.155.198: bytes=64 time=303ms TTL=47
Reply from 128.95.155.198: bytes=64 time=297ms TTL=47
Reply from 128.95.155.198: bytes=64 time=295ms TTL=47
Reply from 128.95.155.198: bytes=64 time=284ms TTL=47
Reply from 128.95.155.198: bytes=64 time=278ms TTL=47
Reply from 128.95.155.198: bytes=64 time=292ms TTL=47
Reply from 128.95.155.198: bytes=64 time=286ms TTL=47

Ping statistics for 128.95.155.198:
    Packets: Sent = 10, Received = 10, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 278ms, Maximum = 308ms, Average = 292ms
```

```
C:\Users\LENOVO>ping -n 10 -l 64 berkeley.edu

Pinging berkeley.edu [35.163.72.93] with 64 bytes of data:
Reply from 35.163.72.93: bytes=64 time=295ms TTL=38
Reply from 35.163.72.93: bytes=64 time=303ms TTL=38
Reply from 35.163.72.93: bytes=64 time=286ms TTL=38
Reply from 35.163.72.93: bytes=64 time=275ms TTL=38
Reply from 35.163.72.93: bytes=64 time=299ms TTL=38
Reply from 35.163.72.93: bytes=64 time=285ms TTL=38
Reply from 35.163.72.93: bytes=64 time=298ms TTL=38
Reply from 35.163.72.93: bytes=64 time=272ms TTL=38
Reply from 35.163.72.93: bytes=64 time=287ms TTL=38
Reply from 35.163.72.93: bytes=64 time=290ms TTL=38

Ping statistics for 35.163.72.93:
    Packets: Sent = 10, Received = 10, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 272ms, Maximum = 303ms, Average = 289ms
```



```

C:\Users\LENOVO>ping -n 10 -l 64 www.ox.ac.uk

Pinging www.ox.ac.uk [151.101.2.133] with 64 bytes of data:
Reply from 151.101.2.133: bytes=64 time=46ms TTL=57
Reply from 151.101.2.133: bytes=64 time=65ms TTL=57
Reply from 151.101.2.133: bytes=64 time=62ms TTL=57
Reply from 151.101.2.133: bytes=64 time=64ms TTL=57
Reply from 151.101.2.133: bytes=64 time=58ms TTL=57
Reply from 151.101.2.133: bytes=64 time=54ms TTL=57
Reply from 151.101.2.133: bytes=64 time=65ms TTL=57
Reply from 151.101.2.133: bytes=64 time=66ms TTL=57
Reply from 151.101.2.133: bytes=64 time=59ms TTL=57
Reply from 151.101.2.133: bytes=64 time=51ms TTL=57

Ping statistics for 151.101.2.133:
    Packets: Sent = 10, Received = 10, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 46ms, Maximum = 66ms, Average = 59ms

```

- www.uw.edu, berkeley.edu has a country code from USA they have average RTT 442,467 respectively. Since they are located in the same country the difference between average RTT is low.
- www.ox.ac.uk has a domain name uk and belongs to the United Kingdom has an average RTT of 72 which is less than the USA since the distance of the UK is less than the USA from us.

**nslookup** — The command nslookup <host> will do a DNS query to find and report the IP address (or addresses) for a domain name or the domain name corresponding to an IP address. To do this, it contacts a "DNS server." Default DNS servers are part of a computer's network configuration. (For a static IP address in Linux, they are configured in the file /etc/network/interfaces that you encountered in the last lab.) You can specify a different DNS server to be used by nslookup by adding the server name or IP address to the command: nslookup <host> <server>

```

C:\Users\LENOVO>nslookup www.spit.ac.in
Server:    UnKnown
Address:   192.168.43.1

Non-authoritative answer:
Name:      www.spit.ac.in
Address:   43.252.193.19

```

**ifconfig** — You used ifconfig in the previous lab. When used with no parameters, ifconfig reports some information about the computer's network interfaces. This usually includes lo which stands for localhost; it can be used for communication between programs running on the same computer. Linux often has an interface named eth0, which is the first ethernet card. The information is different on Mac OS and Linux, but includes the IP or "inet" address and ethernet or "hardware" address for an ethernet card. On Linux, you get the number of packets received (RX) and sent (TX), as well as the number of bytes transmitted and received. (A better place to monitor network bytes on our Linux computers is in the GUI program System Monitor, if it is installed!!!.)

C:\Windows\system32\cmd.exe

```
C:\Users\LENOVO>ipconfig
```

```
Windows IP Configuration
```

```
Ethernet adapter Ethernet:
```

```
Media State . . . . . : Media disconnected
Connection-specific DNS Suffix . :
```

```
Ethernet adapter VirtualBox Host-Only Network:
```

```
Connection-specific DNS Suffix . :
Link-local IPv6 Address . . . . . : fe80::d544:d209:c7cb:ef68%13
IPv4 Address. . . . . : 192.168.56.1
Subnet Mask . . . . . : 255.255.255.0
Default Gateway . . . . . :
```

```
Wireless LAN adapter Local Area Connection* 1:
```

```
Media State . . . . . : Media disconnected
Connection-specific DNS Suffix . :
```

```
Wireless LAN adapter Local Area Connection* 10:
```

```
Media State . . . . . : Media disconnected
Connection-specific DNS Suffix . :
```

```
Wireless LAN adapter Wi-Fi:
```

```
Connection-specific DNS Suffix . :
IPv6 Address. . . . . : 2401:4900:1af1:621:880:9c83:243a:9e98
Temporary IPv6 Address. . . . . : 2401:4900:1af1:621:1834:fc22:d77f:3248
Link-local IPv6 Address . . . . . : fe80::880:9c83:243a:9e98%19
IPv4 Address. . . . . : 192.168.43.174
Subnet Mask . . . . . : 255.255.255.0
Default Gateway . . . . . : fe80::4bd:bfff:fe86:db3a%19
                            192.168.43.1
```

```
Ethernet adapter Bluetooth Network Connection:
```

```
Media State . . . . . : Media disconnected
Connection-specific DNS Suffix . :
```

**netstat** — The netstat command gives information about network connections. I often use netstat -t -n which lists currently open TCP connections (that's the "-t" option) by IP address rather than domain name (that's the "-n" option). Add the option "-l" (lower case ell) to list listening sockets, that is sockets that have been opened by server programs to wait for connection requests from clients: netstat -t -n -l. (On Mac, use netstat -p tcp to list tcp connections, and add "-a" to include listening sockets in the list.)

```
C:\Windows\system32\cmd.exe
C:\Users\LENOVO>netstat -a

Active Connections

Proto Local Address           Foreign Address         State
TCP   0.0.0.0:135             DESKTOP-007I7FD:0      LISTENING
TCP   0.0.0.0:445             DESKTOP-007I7FD:0      LISTENING
TCP   0.0.0.0:5040            DESKTOP-007I7FD:0      LISTENING
TCP   0.0.0.0:7070            DESKTOP-007I7FD:0      LISTENING
TCP   0.0.0.0:38000           DESKTOP-007I7FD:0      LISTENING
TCP   0.0.0.0:39000           DESKTOP-007I7FD:0      LISTENING
TCP   0.0.0.0:49664           DESKTOP-007I7FD:0      LISTENING
TCP   0.0.0.0:49665           DESKTOP-007I7FD:0      LISTENING
TCP   0.0.0.0:49666           DESKTOP-007I7FD:0      LISTENING
TCP   0.0.0.0:49667           DESKTOP-007I7FD:0      LISTENING
TCP   0.0.0.0:49668           DESKTOP-007I7FD:0      LISTENING
TCP   0.0.0.0:49675           DESKTOP-007I7FD:0      LISTENING
TCP   127.0.0.1:1434          DESKTOP-007I7FD:0      LISTENING
TCP   127.0.0.1:15292         DESKTOP-007I7FD:0      LISTENING
TCP   127.0.0.1:15393         DESKTOP-007I7FD:0      LISTENING
TCP   127.0.0.1:16494         DESKTOP-007I7FD:0      LISTENING
TCP   127.0.0.1:45623         DESKTOP-007I7FD:0      LISTENING
TCP   127.0.0.1:49702         DESKTOP-007I7FD:0      LISTENING
TCP   127.0.0.1:49914         DESKTOP-007I7FD:0      LISTENING
TCP   127.0.0.1:49914         DESKTOP-007I7FD:49933  ESTABLISHED
TCP   127.0.0.1:49915         DESKTOP-007I7FD:0      LISTENING
TCP   127.0.0.1:49933         DESKTOP-007I7FD:49914  ESTABLISHED
TCP   127.0.0.1:52645         DESKTOP-007I7FD:0      LISTENING
TCP   192.168.43.174:139      DESKTOP-007I7FD:0      LISTENING
TCP   192.168.43.174:49800    13.75.106.0:https      ESTABLISHED
```



**traceroute** — Traceroute is discussed in man utility. The command `traceroute <host>` will show routers encountered by packets on their way from your computer to a specified `<host>`. For each  $n = 1, 2, 3, \dots$ , traceroute sends a packet with "time-to-live" (ttl) equal to  $n$ . Every time a router forwards a packet, it decreases the ttl of the packet by one. If the ttl drops to zero, the router discards the packet and sends an error message back to the sender of the packet. (Again, as with ping, the packets might be blocked or might not even be sent, so that the error messages will never be received.) The sender gets the identity of the router from the source of the error message. Traceroute will send packets until  $n$  reaches some set upper bound or until a packet actually gets through to the destination. It actually does this three times for each  $n$ . In this way, it identifies routers that are one step, two steps, three steps, ... away from the source computer. A packet for which no response is received is indicated in the output as a `*`.

Traceroute is installed on the computers. If was not installed in your virtual server last week, but you can install it with the command `sudo apt-get install traceroute`

The path taken through a network, can be measured using `traceroute`. The syntax for the command in Linux is:

```
traceroute <hostname>
```

The syntax in Windows is:

```
tracert <hostname>
```

You can specify either a hostname (e.g., `cse.iitb.ac.in`) or an IP address (e.g., `128.105.2.6`).

### 1.2.1 EXPERIMENTS WITH TRACEROUTE

From **your machine** traceroute to the following hosts:

1. `ee.iitb.ac.in`
2. `mscs.mu.edu`
3. `www.cs.grinnell.edu`
4. `csail.mit.edu`
5. `cs.stanford.edu`
6. `cs.manchester.ac.uk`

Store the output of each traceroute command in a separate file named `traceroute_HOSTNAME.log`, replacing `HOSTNAME` with the hostname for end-host you pinged

(e.g., traceroute\_ee.iitb.ac.in.log).

```
C:\Users\LENOVO>tracert www.cs.manchester.ac.uk
```

```
Tracing route to cs2.eps.its.man.ac.uk [64:ff9b::8258:6531]  
over a maximum of 30 hops:
```

1	2 ms	2 ms	1 ms	2402:3a80:1864:23ce:0:3b:ea6e:4001
2	*	*	*	Request timed out.
3	30 ms	*	602 ms	64:ff9b::a9fe:2901
4	32 ms	18 ms	43 ms	64:ff9b::76b9:6912
5	203 ms	47 ms	38 ms	64:ff9b::b613:6a71
6	647 ms	526 ms	288 ms	xe-8-3-2.mlu.cw.net [64:ff9b::c359:65b9]
7	*	205 ms	329 ms	mno-b2-link.telvia.net [64:ff9b::3e73:af0a]
8	*	*	*	Request timed out.
9	*	*	*	Request timed out.
10	*	410 ms	289 ms	ldn-b2-link.telvia.net [64:ff9b::3e73:7abd]
11	209 ms	156 ms	159 ms	jisc-ic-345131-ldn-b4.c.telvia.net [64:ff9b::3e73:af83]
12	349 ms	168 ms	160 ms	ae24.londhx-sbr1.ja.net [64:ff9b::9261:23c5]
13	339 ms	175 ms	431 ms	ae29.londpg-sbr2.ja.net [64:ff9b::9261:2102]
14	589 ms	360 ms	176 ms	ae31.erdiss-sbr2.ja.net [64:ff9b::9261:2116]
15	220 ms	180 ms	428 ms	ae29.manckh-sbr2.ja.net [64:ff9b::9261:212a]
16	179 ms	155 ms	298 ms	ae23.mancrh-rbr1.ja.net [64:ff9b::9261:262a]
17	*	*	*	Request timed out.
18	329 ms	174 ms	269 ms	64:ff9b::8258:f9c2
19	*	*	*	Request timed out.
20	*	*	*	Request timed out.
21	329 ms	190 ms	162 ms	eps.its.man.ac.uk [64:ff9b::8258:6531]

Trace complete.

```
C:\Users\LENOVO>tracert www.mscs.mu.edu
```

```
Tracing route to turing.mscs.mu.edu [64:ff9b::8630:422]  
over a maximum of 30 hops:
```

1	2 ms	2 ms	1 ms	2402:3a80:1864:23ce:0:3b:ea6e:4001
2	*	*	*	Request timed out.
3	183 ms	30 ms	47 ms	64:ff9b::a9fe:2901
4	305 ms	29 ms	36 ms	64:ff9b::76b9:6912
5	532 ms	302 ms	304 ms	ae31-100-xcr1.mlu.cw.net [64:ff9b::d526:fe21]
6	*	*	*	Request timed out.
7	*	*	*	Request timed out.
8	*	*	*	Request timed out.
9	246 ms	303 ms	308 ms	ae3-xcr2.ash.cw.net [64:ff9b::c302:1929]
10	515 ms	303 ms	305 ms	lag-16.ear1.WashingtonDC12.Level3.net [64:ff9b::444:274d]
11	*	313 ms	260 ms	ae-2-3603.ear3.Chicago2.Level3.net [64:ff9b::445:9fba]
12	784 ms	306 ms	305 ms	MARQUETTE-U.ear3.Chicago2.Level3.net [64:ff9b::410:2646]
13	275 ms	406 ms	258 ms	64:ff9b::8630:a1a
14	*	*	*	Request timed out.
15	*	*	*	Request timed out.
16	*	*	*	Request timed out.
17	*	*	*	Request timed out.
18	*	*	*	Request timed out.
19	*	*	*	Request timed out.
20	*	*	*	Request timed out.
21	*	*	*	Request timed out.
22	*	*	*	Request timed out.
23	*	*	*	Request timed out.
24	*	*	*	Request timed out.
25	*	*	*	Request timed out.
26	*	*	*	Request timed out.
27	*	*	*	Request timed out.
28	*	*	*	Request timed out.
29	*	*	*	Request timed out.
30	*	*	*	Request timed out.

Trace complete.

```
C:\Users\LENOVO>tracert www.cs.grinnell.edu
```

```
Tracing route to www.cs.grinnell.edu [64:ff9b::84a1:849f]  
over a maximum of 30 hops:
```

Hop	Source	Destination	Source IP	Destination IP
1	2 ms	2 ms	2 ms	2402:3a80:1864:23ce:0:3b:ea6e:4001
2	*	*	*	Request timed out.
3	44 ms	39 ms	41 ms	64:ff9b::a9fe:2a01
4	44 ms	30 ms	35 ms	64:ff9b::76b9:6b06
5	403 ms	308 ms	297 ms	ae11-100-xcr1.mar.cw.net [64:ff9b::d5b9:db35]
6	193 ms	179 ms	545 ms	64:ff9b::3e73:99be
7	*	*	*	Request timed out.
8	*	*	*	Request timed out.
9	*	*	*	Request timed out.
10	*	*	*	Request timed out.
11	492 ms	362 ms	305 ms	omha-b1-link.telia.net [64:ff9b::3e73:8fb7]
12	623 ms	406 ms	271 ms	aureon-ic-337963-omha-b1.c.telia.net [64:ff9b::3e73:2ee7]
13	*	*	*	Request timed out.
14	*	*	*	Request timed out.
15	*	*	*	Request timed out.
16	*	*	*	Request timed out.
17	312 ms	303 ms	304 ms	64:ff9b::43e0:403e
18	466 ms	262 ms	344 ms	grinnellcollege1.desm.netins.net [64:ff9b::a78e:412b]
19	*	*	*	Request timed out.
20	*	*	*	Request timed out.
21	*	*	*	Request timed out.
22	*	*	*	Request timed out.
23	*	*	*	Request timed out.
24	*	*	*	Request timed out.
25	*	*	*	Request timed out.
26	*	*	*	Request timed out.
27	*	*	*	Request timed out.
28	*	*	*	Request timed out.
29	*	*	*	Request timed out.
30	*	*	*	Request timed out.

```
Trace complete.
```



```
C:\Users\LENOVO>tracert www.ee.iitb.ac.in
```

```
Tracing route to www.ee.iitb.ac.in [64:ff9b::6715:7d84]  
over a maximum of 30 hops:
```

1	2 ms	1 ms	1 ms	2402:3a80:1864:23ce:0:3b:ea6e:4001
2	*	*	*	Request timed out.
3	32 ms	37 ms	37 ms	64:ff9b::a9fe:2a01
4	41 ms	37 ms	44 ms	64:ff9b::76b9:6b06
5	35 ms	38 ms	40 ms	64:ff9b::b613:6a6f
6	43 ms	38 ms	31 ms	14.142.18.97.static-Mumbai.vsnl.net.in [64:ff9b::e8e:1261]
7	*	*	*	Request timed out.
8	*	*	*	Request timed out.
9	528 ms	54 ms	32 ms	115.113.165.62.static-mumbai.vsnl.net.in [64:ff9b::7371:a53e]
10	*	*	*	Request timed out.
11	*	*	*	Request timed out.
12	*	*	*	Request timed out.
13	*	*	*	Request timed out.
14	*	*	*	Request timed out.
15	*	*	*	Request timed out.
16	*	*	*	Request timed out.
17	*	*	*	Request timed out.
18	*	*	*	Request timed out.
19	*	*	*	Request timed out.
20	*	*	*	Request timed out.
21	*	*	*	Request timed out.
22	*	*	*	Request timed out.
23	*	*	*	Request timed out.
24	*	*	*	Request timed out.
25	*	*	*	Request timed out.
26	*	*	*	Request timed out.
27	*	*	*	Request timed out.
28	*	*	*	Request timed out.
29	*	*	*	Request timed out.
30	*	*	*	Request timed out.

```
Trace complete.
```

```
C:\Windows\system32\cmd.exe
```

```
Microsoft Windows [Version 10.0.18363.476]  
(c) 2019 Microsoft Corporation. All rights reserved.
```

```
C:\Users\LENOVO>tracert www.csail.mit.edu
```

```
Tracing route to fe3.edge.pantheon.io [2620:12a:8000::3]  
over a maximum of 30 hops:
```

1	4 ms	4 ms	5 ms	2402:3a80:1864:23ce:0:3b:ea6e:4001
2	50 ms	35 ms	39 ms	2402:3a80:1864:23ce:0:3b:ea6e:4040
3	33 ms	36 ms	39 ms	fd00:abcd:abcd:128::1
4	27 ms	39 ms	37 ms	fd00:169:254:42::1
5	42 ms	18 ms	47 ms	2400:5200:1400:88::2
6	*	*	*	Request timed out.
7	59 ms	57 ms	57 ms	2400:5200:c00:4c::1
8	71 ms	70 ms	55 ms	2620:12a:8000::3

```
Trace complete.
```

```

C:\Windows\system32\cmd.exe
Microsoft Windows [Version 10.0.18363.476]
(c) 2019 Microsoft Corporation. All rights reserved.

C:\Users\LENOVO>tracert www.cs.stanford.edu

Tracing route to cs.stanford.edu [64:ff9b::ab40:4040]
over a maximum of 30 hops:

  1     2 ms     1 ms     1 ms    2402:3a80:1864:23ce:0:3b:ea6e:4001
  2     *         *         *      Request timed out.
  3    37 ms    33 ms    37 ms    64:ff9b::a9fe:2a01
  4    39 ms    43 ms    33 ms    64:ff9b::76b9:6b06
  5   247 ms   342 ms   259 ms   ae11-100-xcr1.mar.cw.net [64:ff9b::d5b9:db35]
  6   318 ms   171 ms   544 ms   ae10-xcr1.ptl.cw.net [64:ff9b::c302:1ed5]
  7   158 ms   391 ms   263 ms   10gigabitethernet-2-2.par2.he.net [64:ff9b::c32a:9068]
  8   277 ms   248 ms   378 ms   100ge10-2.core1.ash1.he.net [64:ff9b::b869:d5ad]
  9   870 ms   688 ms   535 ms   100ge7-2.core1.pao1.he.net [64:ff9b::b869:de29]
 10   318 ms   421 ms   303 ms   stanford-university.100gigabitethernet5-1.core1.pao1.he.net [64:ff9b::b869:b1ee]
 11   512 ms   472 ms   280 ms   csee-west-rtr-v13.SUNet [64:ff9b::ab42:ff8c]
 12   534 ms   612 ms   304 ms   CS.stanford.edu [64:ff9b::ab40:4040]

Trace complete.

```

**Exercise 2:** (Very short.) Use traceroute to trace the route from your computer to math.hws.edu and to www.hws.edu. Explain the difference in the results.

```

C:\Users\LENOVO>tracert math.hws.edu

Tracing route to math.hws.edu [64:ff9b::4059:90ed]
over a maximum of 30 hops:

  1     2 ms     3 ms     1 ms    2402:3a80:1864:23ce:0:3b:ea6e:4001
  2     *         *         *      Request timed out.
  3    42 ms    38 ms    36 ms    64:ff9b::a9fe:2a01
  4   109 ms    35 ms    39 ms    64:ff9b::76b9:6b06
  5   622 ms   304 ms   304 ms   ae11-100-xcr1.mar.cw.net [64:ff9b::d5b9:db35]
  6     *         *         *      Request timed out.
  7   565 ms   304 ms   304 ms   ae24-xcr2.ash.cw.net [64:ff9b::c302:19f5]
  8     *       508 ms   514 ms   lag-16.ear1.WashingtonDC12.Level3.net [64:ff9b::444:274d]
  9     *         *         *      Request timed out.
 10   237 ms   305 ms   305 ms   64:ff9b::444:483d
 11   506 ms   263 ms   246 ms   roc1-ar5-xe-11-0-0-0.us.twtelecom.net [64:ff9b::23f8:1a2]
 12   458 ms   301 ms   243 ms   66-195-65-170.static.ctl.one [64:ff9b::42c3:41aa]
 13   296 ms   457 ms   300 ms   64:ff9b::4059:9064
 14     *         *         *      Request timed out.
 15     *         *         *      Request timed out.
 16     *         *         *      Request timed out.
 17     *         *         *      Request timed out.
 18     *         *         *      Request timed out.
 19     *         *         *      Request timed out.
 20     *         *         *      Request timed out.
 21     *         *         *      Request timed out.
 22     *         *         *      Request timed out.
 23     *         *         *      Request timed out.
 24     *         *         *      Request timed out.
 25     *         *         *      Request timed out.
 26     *         *         *      Request timed out.
 27     *         *         *      Request timed out.
 28     *         *         *      Request timed out.
 29     *         *         *      Request timed out.
 30     *         *         *      Request timed out.

Trace complete.

```

```

C:\Users\LENOVO>tracert www.hws.edu

Tracing route to www.hws.edu [64:ff9b::4059:919f]
over a maximum of 30 hops:

  1      2 ms      2 ms      1 ms      2402:3a80:1864:23ce:0:3b:ea6e:4001
  2      *          *          *          Request timed out.
  3      47 ms     31 ms     32 ms     64:ff9b::a9fe:2901
  4      316 ms    45 ms     30 ms     64:ff9b::76b9:6912
  5      433 ms    304 ms    302 ms    ae31-100-xcr1.mlu.cw.net [64:ff9b::d526:fe21]
  6      *          *          *          Request timed out.
  7      *          *          *          Request timed out.
  8      *          *          *          Request timed out.
  9      746 ms    315 ms    304 ms    ae3-xcr2.ash.cw.net [64:ff9b::c302:1929]
 10     513 ms    304 ms    229 ms    lag-16.ear1.WashingtonDC12.Level3.net [64:ff9b::444:274d]
 11      *          *          *          Request timed out.
 12     417 ms    262 ms    347 ms    64:ff9b::444:483d
 13     522 ms    305 ms    301 ms    roc1-ar5-xe-11-0-0-0.us.twtelecom.net [64:ff9b::23f8:1a2]
 14     508 ms    304 ms    308 ms    66-195-65-170.static.ctl.one [64:ff9b::42c3:41aa]
 15     324 ms    490 ms    303 ms    64:ff9b::4059:9064
 16      *          *          *          Request timed out.
 17      *          *          *          Request timed out.
 18      *          *          *          Request timed out.
 19      *          *          *          Request timed out.
 20      *          *          *          Request timed out.
 21      *          *          *          Request timed out.
 22      *          *          *          Request timed out.
 23      *          *          *          Request timed out.
 24      *          *          *          Request timed out.
 25      *          *          *          Request timed out.
 26      *          *          *          Request timed out.
 27      *          *          *          Request timed out.
 28      *          *          *          Request timed out.
 29      *          *          *          Request timed out.
 30      *          *          *          Request timed out.

Trace complete.

```

- There is difference between ip address of both the website at hop 5 `www.math.hws.edu` goes to `ae11-100-xcr1.mar-cw.net` whereas `www.hws.edu` goes to `ae31-100-xcr1.mlu.cw.net`

**Exercise 3:** Two packets sent from the same source to the same destination do not necessarily follow the same path through the net. Experiment with some sources that are fairly far away. Can you find cases where packets sent to the same destination follow different paths? How likely does it seem to be? What about when the packets are sent at very different times? Save some of the outputs from traceroute. (You can copy them from the Terminal window by highlighting and right-clicking, then paste into a text editor.) Come back sometime next week, try the same destinations again, and compare the results with the results from today. Report your observations.



```

C:\Users\LENOVO>tracert www.ee.iitb.ac.in

Tracing route to www.ee.iitb.ac.in [64:ff9b::6715:7d84]
over a maximum of 30 hops:

  1      2 ms      1 ms      1 ms  2402:3a80:1864:23ce:0:3b:ea6e:4001
  2      *          *          *      Request timed out.
  3     32 ms     37 ms     37 ms  64:ff9b::a9fe:2a01
  4     41 ms     37 ms     44 ms  64:ff9b::76b9:6b06
  5     35 ms     38 ms     40 ms  64:ff9b::b613:6a6f
  6     43 ms     38 ms     31 ms  14.142.18.97.static-Mumbai.vsnl.net.in [64:ff9b::e8e:1261]
  7      *          *          *      Request timed out.
  8      *          *          *      Request timed out.
  9    528 ms     54 ms     32 ms  115.113.165.62.static-mumbai.vsnl.net.in [64:ff9b::7371:a53e]
 10      *          *          *      Request timed out.
 11      *          *          *      Request timed out.
 12      *          *          *      Request timed out.
 13      *          *          *      Request timed out.
 14      *          *          *      Request timed out.
 15      *          *          *      Request timed out.
 16      *          *          *      Request timed out.
 17      *          *          *      Request timed out.
 18      *          *          *      Request timed out.
 19      *          *          *      Request timed out.
 20      *          *          *      Request timed out.
 21      *          *          *      Request timed out.
 22      *          *          *      Request timed out.
 23      *          *          *      Request timed out.
 24      *          *          *      Request timed out.
 25      *          *          *      Request timed out.
 26      *          *          *      Request timed out.
 27      *          *          *      Request timed out.
 28      *          *          *      Request timed out.
 29      *          *          *      Request timed out.
 30      *          *          *      Request timed out.

Trace complete.

```

```

C:\Users\LENOVO>tracert www.ee.iitb.ac.in

Tracing route to www.ee.iitb.ac.in [103.21.125.132]
over a maximum of 30 hops:

  1      3 ms      2 ms      1 ms  192.168.43.1
  2      *          *          *      Request timed out.
  3     37 ms     36 ms     47 ms  10.40.20.61
  4     23 ms     31 ms     36 ms  10.50.182.253
  5     45 ms     34 ms     33 ms  125.18.121.157
  6     32 ms     71 ms     17 ms  182.79.177.104
  7     35 ms     26 ms     27 ms  115.110.234.141.static-Mumbai.vsnl.net.in [115.110.234.141]
  8     32 ms     35 ms     33 ms  172.23.78.233
  9     29 ms     26 ms     28 ms  172.23.78.238
 10     25 ms     35 ms     37 ms  115.113.165.62.static-mumbai.vsnl.net.in [115.113.165.62]
 11     29 ms     23 ms     37 ms  10.152.7.37
 12     37 ms     48 ms     28 ms  10.119.249.49
 13     49 ms     44 ms     40 ms  115.110.234.170.static-Mumbai.vsnl.net.in [115.110.234.170]
 14      *          *          *      Request timed out.
 15      *          *          *      Request timed out.
 16      *          *          *      Request timed out.
 17      *          *          *      Request timed out.
 18      *          *          *      Request timed out.
 19      *          *          *      Request timed out.
 20      *          *          *      Request timed out.
 21      *          *          *      Request timed out.
 22      *          *          *      Request timed out.
 23      *          *          *      Request timed out.
 24      *          *          *      Request timed out.
 25      *          *          *      Request timed out.
 26      *          *          *      Request timed out.
 27      *          *          *      Request timed out.
 28      *          *          *      Request timed out.
 29      *          *          *      Request timed out.
 30      *          *          *      Request timed out.

Trace complete.

```

- On performing this experiment we can observe that two packets sent from the same source to the same destination do not follow the same path.
- On hop 9 in case 1 it takes path 115.113.165.62.static-mumbai.vsnl.net.in whereas in case 2 it is 172.23.78.238
- Same results are obtained on different hops as well.

## QUESTIONS ABOUT PATHS

Now look at the results you gathered and answer the following questions about the paths taken by your packets. Store your answers in a file named `traceroute.txt`.

1. Is any part of the path common for all hosts you traceroute?
  - Yes, the first 4 hops of the path is common for all hosts that were traceroute.
2. Is there a relationship between the number of nodes that show up in the traceroute and the location of the host? If so, what is this relationship?
  - After tracing routes of different hosts each has a maximum of 30 hops.
  - [www.cs.stanford.edu](http://www.cs.stanford.edu) takes 12 hops while [www.ee.iitb.ac.in](http://www.ee.iitb.ac.in) takes 30 hops while [www.cs.manchester.ac.uk](http://www.cs.manchester.ac.uk) takes 18 hops.
  - We can conclude that the number of intermediate devices through which data must pass between source and destination decreases with distance.
3. Is there a relationship between the number of nodes that show up in the traceroute and latency of the host (from your ping results above)? Does the same relationship hold for all hosts?
  - If the traceroute requests to get timeout even after three tries, then it keeps sending the data packets until the host responds to certain hops. If the host responds in first request then traceroute stops.

**WhoIs** — The *whois* command can give detailed information about domain names and IP addresses. If it is not installed on the computers then install it with command `sudo apt-get install whois`. *Whois* can tell you what organization owns or is responsible for the name or address and where to contact them. It often includes a list of domain name servers for the organization.

When using *whois* to look up a domain name, use the simple two-part network name, not an individual computer name (for example, *whois spit.ac.in*).

**Exercise 4:** (Short.) Use *whois* to investigate a well-known web site such as `google.com` or `amazon.com`, and write a couple of sentences about what you find out.

C:\Windows\system32\cmd.exe

```
D:\>whois www.google.com

Whois v1.21 - Domain information lookup
Copyright (C) 2005-2019 Mark Russinovich
Sysinternals - www.sysinternals.com

Connecting to COM.whois-servers.net...

WHOIS Server: whois.markmonitor.com
  Registrar URL: http://www.markmonitor.com
  Updated Date: 2019-09-09T15:39:04Z
  Creation Date: 1997-09-15T04:00:00Z
  Registry Expiry Date: 2028-09-14T04:00:00Z
  Registrar: MarkMonitor Inc.
  Registrar IANA ID: 292
  Registrar Abuse Contact Email: abusecomplaints@markmonitor.com
  Registrar Abuse Contact Phone: +1.2083895740
  Domain Status: clientDeleteProhibited https://icann.org/epp#clientDeleteProhibited
  Domain Status: clientTransferProhibited https://icann.org/epp#clientTransferProhibited
  Domain Status: clientUpdateProhibited https://icann.org/epp#clientUpdateProhibited
  Domain Status: serverDeleteProhibited https://icann.org/epp#serverDeleteProhibited
  Domain Status: serverTransferProhibited https://icann.org/epp#serverTransferProhibited
  Domain Status: serverUpdateProhibited https://icann.org/epp#serverUpdateProhibited
  Name Server: NS1.GOOGLE.COM
  Name Server: NS2.GOOGLE.COM
  Name Server: NS3.GOOGLE.COM
  Name Server: NS4.GOOGLE.COM
  DNSSEC: unsigned
  URL of the ICANN Whois Inaccuracy Complaint Form: https://www.icann.org/wicf/
>>> Last update of whois database: 2020-09-01T06:38:59Z <<<

For more information on Whois status codes, please visit https://icann.org/epp

NOTICE: The expiration date displayed in this record is the date the
registrar's sponsorship of the domain name registration in the registry is
currently set to expire. This date does not necessarily reflect the expiration
date of the domain name registrant's agreement with the sponsoring
registrar. Users may consult the sponsoring registrar's Whois database to
view the registrar's reported date of expiration for this registration.

TERMS OF USE: You are not authorized to access or query our Whois
database through the use of electronic processes that are high-volume and
automated except as reasonably necessary to register domain names or
modify existing registrations; the Data in VeriSign Global Registry
Services' ("VeriSign") Whois database is provided by VeriSign for
information purposes only, and to assist persons in obtaining information
about or related to a domain name registration record. VeriSign does not
guarantee its accuracy. By submitting a Whois query, you agree to abide
by the following terms of use: You agree that you may use this Data only
for lawful purposes and that under no circumstances will you use this Data
to: (1) allow, enable, or otherwise support the transmission of mass
unsolicited, commercial advertising or solicitations via e-mail, telephone,
or facsimile; or (2) enable high volume, automated, electronic processes
```

- Domain Name- GOOGLE.COM
- Registrar URL-http://www.markmonitor.com
- Updated Date-2019-09-09T15:39:04Z
- Creation Date-1997-09-15T04:00:00Z
- Contact Us-At +1.8007459229,In Europe, at +44.02032062220



Conclusion: Understood the networking command such as ping, traceroute, whoIs and implemented it.

References:

1. [https://en.wikipedia.org/wiki/Hop\\_\(networking\)](https://en.wikipedia.org/wiki/Hop_(networking))
2. [http://docs.netapp.com/ontap-9/index.jsp?topic=%2Fcom.netapp.doc.dot-cm-cmpr-940%2Fnetwork\\_\\_traceroute.html](http://docs.netapp.com/ontap-9/index.jsp?topic=%2Fcom.netapp.doc.dot-cm-cmpr-940%2Fnetwork__traceroute.html)
3. <https://www.clouddirect.net/knowledge-base/KB0011455/using-traceroute-ping-mtr-and-pathping>