

HOMEWORK 9

6500-324: DATA MANAGEMENT FOR INFORMATION SYSTEMS (Fall 2022)

©2022 by ecourse.org

Part 1. Multiple Choice or True/False

1. (1 point) (check all that apply) Find all managers who has no supervisees
 A) select ename from emp where (job, empno) not in (select job, mgr from emp);
 B) select ename from emp where job = 'MANAGER' and empno not in (select mgr from emp where mgr is not null);
 C) (select ename from emp where job = 'MANAGER') minus (select ename from emp where empno in (select mgr from emp));
 D) (select ename from emp where job = 'MANAGER')) intersect (select ename from emp where empno in (select mgr from emp));
2. (1 point) Find the maximum salary in Dallas
 A) select max(sal) from emp, dept where dept.deptno = emp.deptno;
 B) select max(sal) from emp where deptno in (select deptno from dept where loc='DALLAS');
 C) select sal from emp, dept where loc='DALLAS';
 D) select max(sal) from emp where loc = 'DALLAS';
3. (1 point) (check all that apply) Find all the employees located in Dallas
 A) select ename from dept where loc = 'DALLAS';
 B) select ename from dept, emp where dept.deptno = emp.deptno and loc = 'DALLAS';
 C) select ename from dept, emp where loc = 'DALLAS';
 D) select ename from emp where loc = 'DALLAS';
 E) select ename from emp where deptno in (select deptno from dept where loc = 'DALLAS');
4. (1 point) (select all that apply) Find the employees who make more than everybody in Dallas
 A) select ename from emp where sal > (select max(sal) from dept where loc='DALLAS');
 B) select ename from emp where sal > (select max(sal) from dept, emp where dept.deptno = emp.deptno and loc='DALLAS');
 C) select ename from emp where sal > all (select sal from dept where loc='DALLAS');
 D) select ename from emp where sal > all (select sal from emp where loc='DALLAS');
 E) select ename from emp where sal > all (select sal from emp where deptno in (select deptno from dept where loc='DALLAS'));
5. (1 point) (check all that apply) Find all salesman who makes more than that all managers make
 A) select salesman from emp where sal > all (select max(sal) from emp where job = 'MANAGER');
 B) select ename from emp where sal > all (select sal from emp where mgr = empno);
 C) select ename from emp where job = 'SALESMAN' and sal > (select max(sal) from emp where job = 'MANAGER');
 D) select ename from emp where job = 'SALESMAN' and sal > all (select sal from emp where job = 'MANAGER');
 E) none of the above
6. (1 point) Find the department that has no employees

- A) (select deptno from dept) intersect (select deptno from emp);
B) select deptno from emp where deptno <= all (select deptno from dept);
C) select deptno from emp group by deptno having count(*) <= all (select count(*) from emp group by deptno);
D) None of the above
7. (1 point) A subquery in an SQL SELECT statement:
A) can only be used with two tables.
B) can always be duplicated by a join.
C) has a distinct form that cannot be duplicated by a join.
D) cannot have its results sorted using ORDER BY.
8. (1 point) Find department that has at least two employees and also in those departments, one or more employees' have names containing letter J.
A) (select deptno from emp where ename like '%J%') intersect (select deptno from emp group by deptno having count(*) >= 2);
B) select deptno from emp where ename like '%J%' group by deptno having count(*) >=2;
C) select deptno from dept where deptno in (select deptno from emp where ename like '%J%');
D) select deptno from dept where deptno in (select deptno from emp where ename like '%J%' group by deptno having count(*) >= 2);
9. (1 point) Based on the following table, which is the correct SQL statement to find the employees who work in the same department as SMITH?
A) select ename from emp where job = (select ename from emp where ename = 'SMITH');
B) select ename from emp where deptno = (select deptno from emp where ename = 'SMITH');
C) select ename from emp where dname = (select dname from emp where ename = 'SMITH');
D) select ename from emp where deptno = (select * from emp where ename = 'SMITH');
10. (1 point) Based on the following table, which is the correct SQL statement to find the employees who was hired in the same year as TURNER?
A) select ename from emp where hiredate = (select hiredate from emp where ename = 'TURNER');
B) select ename from emp where hiredate in (select * from emp where ename = 'TURNER');
C) select ename from emp where to_char(hiredate, 'YYYY') in (select to_char(hiredate, 'YYYY') from emp where ename = 'TURNER');
D) select ename from emp where * = (select * from emp where ename = 'TURNER');