

# **Banarsidas Chandiwalla Institute Of Information Technology**



## **Operating system LAB File**

**Submitted to :-**

Alok Mishra

**Submitted by :-**

Prachi Sharma  
04911104422  
MCA 1<sup>st</sup> Semester

# Index

Practical No	Practical Name
1	Que 1 Write the linux command to display the calendar with various options.
2	Que 2 Write a linux command to display date with various options.
3	Que 3 Write a linux command to display the list of users who are currently using linux server.
4	Que 4 Write a linux command to display your system details.
5	Que 5 Write a linux command to create text file
6	Que 6 Write linux command to list all the directories and files on the server.
7	Que 7 Write the linux command to display the content of a file.
8	Que 8 Write the linux command to print the content on standard output device.
9	Que 9 Write the linux command to perform calculations.
10	Que 10 Write the linux command to show the current working directory.
11	Ques 11 Write the Linux command to get help with various options.
12	Que 12 Write the linux command to display what all users are currently doing.
13	Que 13 Write the linux command to create a directory.
14	Que 14 Write the linux command to change the directory.
15	Que 15 Write the linux command to remove a directory.
16	Que 16 Write the linux command to delete a file.
17	Que 17 Write the linux Command to copy a file to some other location.
18	Que 18 Write the linux command to move a file to some different location.
19	Que 19 Write the linux command to count the number of words, lines and sentences in the file
20	Que 20 Write the linux command to give the alias name.

21	Que 21 Write the linux command to view the exiting aliases.
22	Que 22 Write the linux command to unalias the exiting alias name.
23	Que 23 Write the linux command to display the hostname of the system.
24	Ques 24 Write the linux command to get information about the operating System.
25	Que 25 Write the linux command to view first 5 lines of a file.
26	Que 26 Write the linux command to view last 20 lines of a file.
27	Que 27 Write the linux command to view last 2 lines of a file.
28	Que 28 Write the linux command to check the default permission of a file
29	Que 29 Write the linux command to show the use of Basic Regular Expressions using grep Command.
30	Que 30 Write the Linux command to display detailed information about processes.
31	Que 31. PROGRAM FOR SYSTEM CALLS OF UNIX OPERATING SYSTEMS (OPENDIR, REaddir, CLOSEDIR)
32	PROGRAM FOR SYSTEM CALLS OF UNIX OPERATING SYSTEM (fork, getpid, exit)
33	Write an appropriate „C“ program which implements the concept of dynamic memory allocation (use of malloc(), calloc(), realloc(), and free() system call.
34	Write an appropriate „C“ program which implements the concept of fork() system call.
35	. Write an appropriate „C“ program which implements the concept of exit() system call

## Que 1 Write the linux command to display the calendar with various options.

Command: Calendar

Syntax: cal

Description: This command displays the calendar on the screen.

Options:

Cal -3

Description: This command displays three months –previous,current and next

Cal -j

Description: This command displays the month with first day as Sunday

Cal -m

Description: This command displays the month with first day as Monday

cal year

Description: This command displays calendar of whole year

```
onworks@onworks-Standard-PC-l440FX-PIIX-1996:~/Desktop$ cal
  Februar 2023
So Mo Di Mi Do Fr Sa
   1  2  3  4
  5  6  7  8  9 10 11
12 13 14 15 16 17 18
19 20 21 22 23 24 25
26 27 28
```

```
onworks@onworks-Standard-PC-l440FX-PIIX-1996:~/Desktop$ cal -3
                2023
  Januar      Februar      März
So Mo Di Mi Do Fr Sa So Mo Di Mi Do Fr Sa So Mo Di Mi Do Fr Sa
 1  2  3  4  5  6  7   1  2  3  4   1  2  3  4
 8  9 10 11 12 13 14   5  6  7  8  9 10 11   5  6  7  8  9 10 11
15 16 17 18 19 20 21  12 13 14 15 16 17 18  12 13 14 15 16 17 18
22 23 24 25 26 27 28  19 20 21 22 23 24 25  19 20 21 22 23 24 25
29 30 31           26 27 28           26 27 28 29 30 31

onworks@onworks-Standard-PC-l440FX-PIIX-1996:~/Desktop$
```

```
onworks@onworks-Standard-PC-l440FX-PIIX-1996:~/Desktop$ cal -n feb
  Februar 2023
So Mo Di Mi Do Fr Sa
   1  2  3  4
  5  6  7  8  9 10 11
12 13 14 15 16 17 18
19 20 21 22 23 24 25
26 27 28

onworks@onworks-Standard-PC-l440FX-PIIX-1996:~/Desktop$
```

":c: l" c n\ 'il -a ri "ml

“.!k “ .r’.  
'.,r' r'c" l\ ""l i:c l r'•\ '.,ol°ol"\*P\lri-r'.a

## Que 2 Write a linux command to display date with various options.

### Syntax: date

Description : This command displays the current date on the screen.

Options:

Date --date="next mon"

Description :This command displays the date on next Monday.

Date --date="1 day ago"

Description: This command displays the previous date of 1 day ago.

Date --date"10 day ago"

Description: This command displays the previous date of 10 days ago.

Date +%y

Description: This command displays the last 2 digits of current year.

Date +%Y

Description: This command displays the current year.

```
$ date
Thu May  6 01:22:28 IST 2021
$ date --date="next mon"
Mon May 10 00:00:00 IST 2021
$ date --date="1 day ago"
Wed May  5 01:23:30 IST 2021
$ date --date="1 day after"
date: invalid date '1 day after'
$ date --date="10 days ago"
Mon Apr 26 01:25:24 IST 2021
```

```
$ date +%y
21
$ date +%Y
2021
$ █
```

**Que 3 Write a linux command to display the list of users who are currently using linux server.**

Command: Who

Syntax: who

Description: This command displays the number of users currently working on the server.

Options

who -a

who -d

who -H

who -b



Bash console 20117430

```
Mon May 10 00:00:00 UTC 2021
08:17 ~ $ who
08:18 ~ $ who -a
08:18 ~ $ who -d
08:18 ~ $ who -h
who: invalid option -- 'h'
Try 'who --help' for more information.
08:18 ~ $ who -H
NAME      LINE      TIME      COMMENT
08:18 ~ $ who -b
08:18 ~ $
```

#### Que 4 Write a linux command to display your system details.

Command: lscpu

Syntax: lscpu

Description: This command displays details of operating system.

```
$ lscpu
Architecture:      armv7l
Byte Order:        Little Endian
CPU(s):            8
On-line CPU(s) list: 0-7
Thread(s) per core: 1
Core(s) per socket: 4
Socket(s):         2
Vendor ID:         ARM
Model:             4
Model name:        Cortex-A53
Stepping:          r0p4
CPU max MHz:       2016.0000
CPU min MHz:       652.8000
BogoMIPS:          38.40
Flags:             half thumb fastmult vfp edsp neon vfpv3 tls
                   vfpv4 idiva idivt vfpd32 lpae evtstrm aes
                   pmull sha1 sha2 crc32

$ █
```

ESC      CTRL      ALT      —      ↓      ↑



## Que 5 Write a linux command to create text file

Command: touch ,cat

Syntax: touch t2.txt

cat > t3.txt

Description : This command will create text file in linux

```
14:41 ~ $ touch t5.txt
14:41 ~ $ touch t6.txt
14:41 ~ $ touch t7.txt
14:41 ~ $ cat > t8.txt
hello
^Z
[3]+  Stopped                  cat > t8.txt
14:41 ~ $ cat t9.txt
cat: t9.txt: No such file or directory
14:41 ~ $ cat >t9.txt
go went gone
^Z
[4]+  Stopped                  cat > t9.txt
14:42 ~ $ ls -l
total 36
-rwxr-xr-x 1 ffffok registered_users 232 Feb 1 12:51 README.txt
-rw-rw-r-- 1 ffffok registered_users 44 Feb 1 12:56 abc.txt
drwxrwxr-x 2 ffffok registered_users 4096 Feb 1 13:04 happy
drwxrwxr-x 5 ffffok registered_users 4096 Feb 1 13:31 mca
drwxrwxr-x 2 ffffok registered_users 4096 Feb 1 12:54 mca1
-rw-rw-r-- 1 ffffok registered_users 0 Feb 1 12:53 t1
-rw-rw-r-- 1 ffffok registered_users 0 Feb 1 12:54 t2
-rw-rw-r-- 1 ffffok registered_users 54 Feb 1 14:31 t2.txt
-rw-rw-r-- 1 ffffok registered_users 22 Feb 1 13:08 t3.txt
-rw-rw-r-- 1 ffffok registered_users 0 Feb 1 14:41 t5.txt
-rw-rw-r-- 1 ffffok registered_users 0 Feb 1 14:41 t6.txt
-rw-rw-r-- 1 ffffok registered_users 0 Feb 1 14:41 t7.txt
-rw-rw-r-- 1 ffffok registered_users 7 Feb 1 14:42 t8.txt
-rw-rw-r-- 1 ffffok registered_users 13 Feb 1 14:42 t9.txt
14:42 ~ $
```

## Que 6 Write linux command to list all the directories and files on the server.

Command: List

Syntax: ls

Description: This command displays the list of all directories and files in a particular directory.

Options:

ls -i

ls -l

ls -a

ls -b

ls -d



Bash console 27180400

Share wi

```
12:54 ~ $ ls -l
total 12
-rwxr-xr-x 1 ffffok registered_users 232 Feb 1 12:51 README.txt
drwxrwxr-x 2 ffffok registered_users 4096 Feb 1 12:53 mca
drwxrwxr-x 2 ffffok registered_users 4096 Feb 1 12:54 mca1
-rw-rw-r-- 1 ffffok registered_users 0 Feb 1 12:53 t1
-rw-rw-r-- 1 ffffok registered_users 0 Feb 1 12:54 t2
12:54 ~ $ ls -i
172805625 README.txt 193397840 mca 175483116 mca1 172805626 t1 172805627 t2
12:54 ~ $ ls -a
. . . .bashrc .cache .gitconfig .local .profile .pythonstartup.py .vimrc .virtualenvs README.txt mca mca1 t1 t2
12:54 ~ $ ls -b
README.txt mca mca1 t1 t2
12:54 ~ $ ls -d
.
12:54 ~ $
```

### Que 7 Write the linux command to display the content of a file.

Command: Cat

Syntax: cat

Description: This command displays the list of all directories and files in a particular directory.

```
12:56 ~ $ ls -l
total 16
-rwxr-xr-x 1 ffffok registered_users 232 Feb  1 12:51 README.txt
-rw-rw-r-- 1 ffffok registered_users  44 Feb  1 12:56 abc.txt
drwxrwxr-x 2 ffffok registered_users 4096 Feb  1 12:53 mca
drwxrwxr-x 2 ffffok registered_users 4096 Feb  1 12:54 mca1
-rw-rw-r-- 1 ffffok registered_users   0 Feb  1 12:53 t1
-rw-rw-r-- 1 ffffok registered_users   0 Feb  1 12:54 t2
12:56 ~ $ cat abc.txt
hello world how are you
what are you doing
12:56 ~ $
```

**Que 8 Write the linux command to print the content on standard output device.**

Command: Echo

Syntax: echo

Description: This command prints the content on standard output device.



Bash console 27180400

```
12:57 ~ $ echo "hy what are you doing i am mca student"
hy what are you doing i am mca student
12:58 ~ $ █
```

## Que 9 Write the linux command to perform calculations.

Command: Basic Calculator

Syntax: bc

Description: This command performs the basic calculations.

Options:

bc-i

bc-h

bc-l

bc-v

bc-s



Bash console 20117430

```
08:29 ~/bca $ 
08:29 ~/bca $ bc
bc 1.06.95
Copyright 1991-1994, 1997, 1998, 2000, 2004, 2006 Free Software Foundation, Inc.
This is free software with ABSOLUTELY NO WARRANTY.
For details type `warranty'.
10+5
15
4*6
24
5^3
125
bc -i
0
bc -h
0
bc -l
0
bc -s
0
```

**Que 10 Write the linux command to show the current working directory.**

Command: Working Directory

Syntax: pwd

Description: This command displays the current working directory .

---



Bash console 27180400

```
13:00 ~/mca $ pwd
/home/ffffok/mca
13:00 ~/mca $
```

## Ques 11 Write the Linux command to get help with various options.

### Command :-

- `Ls --help` : List help page of `ls` command with their option.
- `Cat --help` : Lists help page of `cat` command with their option.
- `cp --help` : Lists help page of `cp` command with their option.

```
14:02 ~ $ ls --help
Usage: ls [OPTION]... [FILE]...
List information about the FILES (the current directory by default).
Sort entries alphabetically if none of -cftuvSUX nor --sort is specified.

Mandatory arguments to long options are mandatory for short options too.
-a, --all                do not ignore entries starting with .
-A, --almost-all        do not list implied . and ..
--author                with -l, print the author of each file
-b, --escape             print C-style escapes for nongraphic characters
--block-size=SIZE       scale sizes by SIZE before printing them; e.g.,
                        '--block-size=M' prints sizes in units of
                        1,048,576 bytes; see SIZE format below
-B, --ignore-backups     do not list implied entries ending with ~
-c                      with -lt: sort by, and show, ctime (time of last
                        modification of file status information);
                        with -l: show ctime and sort by name;
                        otherwise: sort by ctime, newest first
-C                      list entries by columns
--color[=WHEN]          colorize the output; WHEN can be 'always' (default
                        if omitted), 'auto', or 'never'; more info below
-d, --directory          list directories themselves, not their contents
-D, --dired              generate output designed for Emacs' dired mode
-f                      do not sort, enable -aU, disable -ls --color
-F, --classify           append indicator (one of */=>@|) to entries
--file-type             likewise, except do not append '*'
--format=WORD            across -x, commas -m, horizontal -x, long -l,
                        single-column -l, verbose -l, vertical -C
--full-time             like -l --time-style=full-iso
-g                      like -l, but do not list owner
--group-directories-first
                        group directories before files;
                        can be augmented with a --sort option, but any
                        use of --sort=none (-U) disables grouping
-G, --no-group           in a long listing, don't print group names
-h, --human-readable     with -l and/or -s, print human readable sizes
                        (e.g., 1K 234M 2G)
--si                    likewise, but use powers of 1000 not 1024
-H, --dereference-command-line
                        follow symbolic links listed on the command line
--dereference-command-line-symlink-to-dir
                        follow each command line symbolic link
                        that points to a directory
```

```

--hide=PATTERN      that points to a directory
                    do not list implied entries matching shell PATTERN
                    (overridden by -a or -A)
--indicator-style=WORD append indicator with style WORD to entry names:
                    none (default), slash (-p),
                    file-type (--file-type), classify (-F)
-i, --inode          print the index number of each file
-I, --ignore=PATTERN do not list implied entries matching shell PATTERN
-k, --kibibytes      default to 1024-byte blocks for disk usage
-l                  use a long listing format
-L, --dereference     when showing file information for a symbolic
                    link, show information for the file the link
                    references rather than for the link itself
-m                  fill width with a comma separated list of entries
                    like -l, but list numeric user and group IDs
-N, --literal         print raw entry names (don't treat e.g. control
                    characters specially)
-o                  like -l, but do not list group information
-p, --indicator-style=slash append / indicator to directories
-q, --hide-control-chars print ? instead of nongraphic characters
--show-control-chars show nongraphic characters as-is (the default,
                    unless program is 'ls' and output is a terminal)
-Q, --quote-name      enclose entry names in double quotes
--quoting-style=WORD use quoting style WORD for entry names:
                    literal, locale, shell, shell-always,
                    shell-escape, shell-escape-always, c, escape
-r, --reverse         reverse order while sorting
-R, --recursive       list subdirectories recursively
-s, --size            print the allocated size of each file, in blocks
-S                  sort by file size, largest first
--sort=WORD           sort by WORD instead of name: none (-U), size (-S),
                    time (-t), version (-v), extension (-X)
--time=WORD           with -l, show time as WORD instead of default
                    modification time: atime or access or use (-u);
                    ctime or status (-c); also use specified time
                    as sort key if --sort=time (newest first)
--time-style=STYLE    with -l, show times using style STYLE:
                    full-iso, long-iso, iso, locale, or +FORMAT;
                    FORMAT is interpreted like in 'date'; if FORMAT
                    is FORMAT1<newline>FORMAT2, then FORMAT1 applies
                    to non-recent files and FORMAT2 to recent files;
                    if STYLE is prefixed with 'posix-', STYLE

```

```

                    if STYLE is prefixed with 'posix-', STYLE
                    takes effect only outside the POSIX locale
-t                  sort by modification time, newest first
-T, --tabsize=COLS  assume tab stops at each COLS instead of 8
-u                  with -lt: sort by, and show, access time;
                    with -l: show access time and sort by name;
                    otherwise: sort by access time, newest first
-U                  do not sort; list entries in directory order
-v                  natural sort of (version) numbers within text
-W, --width=COLS    set output width to COLS. 0 means no limit
-x                  list entries by lines instead of by columns
-X                  sort alphabetically by entry extension
-Z, --context        print any security context of each file
-l                  list one file per line. Avoid '\n' with -q or -b
--help              display this help and exit
--version            output version information and exit

```

The SIZE argument is an integer and optional unit (example: 10K is 10\*1024). Units are K,M,G,T,P,E,Z,Y (powers of 1024) or KB,MB,... (powers of 1000).

Using color to distinguish file types is disabled both by default and with --color=never. With --color=auto, ls emits color codes only when standard output is connected to a terminal. The LS\_COLORS environment variable can change the settings. Use the dircolors command to set it.

Exit status:

```

0 if OK,
1 if minor problems (e.g., cannot access subdirectory),
2 if serious trouble (e.g., cannot access command-line argument).

```

GNU coreutils online help: <<http://www.gnu.org/software/coreutils/>>

Report ls translation bugs to <<http://translationproject.org/team/>>

Full documentation at: <<http://www.gnu.org/software/coreutils/ls/>>

or available locally via: info '(coreutils) ls invocation'

14:19 ~ \$



```

14:28 ~ $ cat --help
Usage: cat [OPTION]... [FILE]...
Concatenate FILE(s) to standard output.

With no FILE, or when FILE is -, read standard input.

-A, --show-all           equivalent to -vET
-b, --number-nonblank     number nonempty output lines, overrides -n
-e                       equivalent to -vE
-E, --show-ends          display $ at end of each line
-n, --number             number all output lines
-s, --squeeze-blank      suppress repeated empty output lines
-t                       equivalent to -vT
-T, --show-tabs          display TAB characters as ^I
-u                       (ignored)
-v, --show-nonprinting   use ^ and M- notation, except for LFD and TAB
--help                  display this help and exit
--version               output version information and exit

Examples:
cat f - g  Output f's contents, then standard input, then g's contents.
cat        Copy standard input to standard output.

GNU coreutils online help: <http://www.gnu.org/software/coreutils/>
Report cat translation bugs to <http://translationproject.org/team/>
Full documentation at: <http://www.gnu.org/software/coreutils/cat>
or available locally via: info '(coreutils) cat invocation'
14:28 ~ $

```

```

14:28 ~ $ cp --help
Usage: cp [OPTION]... [-T] SOURCE DEST
or: cp [OPTION]... SOURCE... DIRECTORY
or: cp [OPTION]... -t DIRECTORY SOURCE...
Copy SOURCE to DEST, or multiple SOURCE(s) to DIRECTORY.

Mandatory arguments to long options are mandatory for short options too.
-a, --archive             same as -dR --preserve=all
--attributes-only        don't copy the file data, just the attributes
--backup[=CONTROL]       make a backup of each existing destination file
                        like --backup but does not accept an argument
-b, --copy-contents       copy contents of special files when recursive
                        same as --no-dereference --preserve=links
-d, --no-dereference      if an existing destination file cannot be
                        opened, remove it and try again (this option
                        is ignored when the -n option is also used)
-f, --force               prompt before overwrite (overrides a previous -n
                        option)
-i, --interactive         prompt before overwrite (overrides a previous -n
                        option)
-H, --follow              follow command-line symbolic links in SOURCE
-l, --link                hard link files instead of copying
-L, --dereference         always follow symbolic links in SOURCE
-n, --no-clobber          do not overwrite an existing file (overrides
                        a previous -i option)
-P, --no-dereference      never follow symbolic links in SOURCE
-p, --preserve[=ATTR_LIST]
                        same as --preserve=mode,ownership,timestamps
                        preserve the specified attributes (default:
                        mode,ownership,timestamps), if possible
                        additional attributes: context, links, xattr,
                        all
--no-preserve=ATTR_LIST  don't preserve the specified attributes
--parents                use full source file name under DIRECTORY
-R, --recursive           copy directories recursively
--reflink[=WHEN]         control clone/cow copies. See below
--remove-destination     remove each existing destination file before
                        attempting to open it (contrast with --force)
--sparse=WHEN            control creation of sparse files. See below
--strip-trailing-slashes  remove any trailing slashes from each SOURCE
                        argument
-s, --symbolic-link       make symbolic links instead of copying
-S, --suffix=SUFFIX       override the usual backup suffix
-t, --target-directory=DIRECTORY
                        copy all SOURCE arguments into DIRECTORY
-T, --no-target-directory
                        treat DEST as a normal file
-u, --update              copy only when the SOURCE file is newer

```

```

--no-larger-dreziory rear oesl as a nortal f4 e
--update copy only nhen she souRs& fle 1s n e r
<nan zhe deszinaion file or when the
desiinaion The is missing
--verba se exp a4n vhar 4s be ng doce
--one - f43e - s y s t e x stay on chs file system
set s 4 L4 n u « sec ur 4 ry cone ext. o I des t 4 n at or
fee zo defauñ type
--c ont ext: [=CTX ke - z , or 1 I Cox 1 s spe c I I N e d then se t t he
S E L 4 n u x o c S ? o C K se c u r t y c o n e e x r t a C T R
--he p d sp) ay r h s he p and ex 4 r
--ver s 4 or on i pur vers on 4 n for tar 4 on and ex 4 c

```

ay de l aut, sparse s00 RC8 f4 ) es are deveci ed by a 'z r o de ben r 4 sr 4 c and the corresponding 0EsT file ?s made sparse as well. Thai 4s the behavlo se eci ed by --s parse-an to. spec 4l y --s par se-always ro creare a sparse 0ENT f11e \heneve F the solJRC E 11 e cone a ns a long enough sequence of zera bytes es.

then --refJ nk [=a +xay s\$ s spec f4ed, perfaL a ghtwe ghr copy, \whe ce the data b ock s are cop 4 e d or yw her to d 4 f4ed. I I t h 4 s 4 s n o t p o s s 4 b ? e c h e fa#4s, or if --reflink=auzo ?s spec#f4ed, fall back zo a standard copy.

The backup suffix is - un ess set wkth--suffl x o c S T M P L E 6 A C K U P S U F F T X. The vers 4 on cour ro) method may be se eci ed v 4 a t h e -- backu p opt 4 or o t h r o u g h the V E R S T o N C O N T R o L env y r o n r e n t v a r a b e . H e c e a c e t h e v a u e s :

none, off	n ever ciak e back u p s (e ver 4 l -- back u p s g 4 ven 3
numbered, z	irak e nu zb e r e d b a c k u p s
e ? siing, nil	n u + 6 e r e d l l i n u z b e c e d b a c k u p s e x s t . , s m p e o f h e r w l s e
s4mp4e, never	al z ay s oak e s 4 u p e b a c k u p s

As a s pec 4 a 4 c ase , cp oakes a back up o l S O U R 2 E when r be No rce and back up  
opt on s are g 4 ven and & URGE and DESr are the same name to r as ex st 4 n g.  
regular 04e

Re po rr c p t u a s a t o n b u g s t o <hrt p : / l i r a s s l a r 4 o p r o j e c i . o r g / i e a t / >  
Fu4 doc umenu at: on at: <hrt p : / \ . g n u . o r g / s o f t w a r e / c o r e u t s / c p >  
or ava4 ab e l o c a ? 4 y v 4 a : l n t o ' ( c o r e u i 4 s ) c p 4 n v o c a r o n  
1A : ? 0 -

## Que 12 Write the linux command to display what all users are currently doing.

Command: w

Syntax: w

Description: This command displays what all users are currently doing.

Options

w-s

W -h

w-u

W-f


```
08:35 ~ $ w
08:36:16 up 14:02, 0 users, load average: 0.86, 0.95, 0.83
USER      TTY      FROM          LOGIN@  IDLE   JCPU   PCPU WHAT
08:36 ~ $ w -s
08:36:22 up 14:02, 0 users, load average: 0.79, 0.94, 0.82
USER      TTY      FROM          IDLE   WHAT
08:36 ~ $ w -h
08:36 ~ $ w -u
08:36:32 up 14:02, 0 users, load average: 0.67, 0.90, 0.81
USER      TTY      FROM          LOGIN@  IDLE   JCPU   PCPU WHAT
08:36 ~ $ w -f
08:36:36 up 14:02, 0 users, load average: 0.61, 0.89, 0.81
USER      TTY      FROM          LOGIN@  IDLE   JCPU   PCPU WHAT
08:36 ~ $
```

**Que 13 Write the linux command to create a directory.**

Command: Make directory

Syntax: mkdir

Description: This command creates a directory.



```
08:42 ~ $ mkdir go
08:42 ~ $
08:42 ~ $
08:42 ~ $
```

**Que 14 Write the linux command to change the directory.**

Command: Change directory

Syntax: cd

Description: This command changes the directory.



Bash console 20117605

```
08:36 ~ $ mkdir happy
08:37 ~ $ cd happy
08:37 ~/happy $
08:38 ~/happy $
08:38 ~/happy $
08:38 ~/happy $
```

**Que 15 Write the linux command to remove a directory.**

Command: Remove directory

Syntax: rmdir

Description : This command removes a directory.

```
13:04 ~ $ ls -l
total 24
-rwxr-xr-x 1 ffffok registered_users 232 Feb 1 12:51 README.txt
-rw-rw-r-- 1 ffffok registered_users 44 Feb 1 12:56 abc.txt
drwxrwxr-x 2 ffffok registered_users 4096 Feb 1 13:04 go
drwxrwxr-x 2 ffffok registered_users 4096 Feb 1 13:04 happy
drwxrwxr-x 2 ffffok registered_users 4096 Feb 1 12:53 mca
drwxrwxr-x 2 ffffok registered_users 4096 Feb 1 12:54 mca1
-rw-rw-r-- 1 ffffok registered_users 0 Feb 1 12:53 t1
-rw-rw-r-- 1 ffffok registered_users 0 Feb 1 12:54 t2
13:04 ~ $ rmdir go
13:04 ~ $ ls -l
total 20
-rwxr-xr-x 1 ffffok registered_users 232 Feb 1 12:51 README.txt
-rw-rw-r-- 1 ffffok registered_users 44 Feb 1 12:56 abc.txt
drwxrwxr-x 2 ffffok registered_users 4096 Feb 1 13:04 happy
drwxrwxr-x 2 ffffok registered_users 4096 Feb 1 12:53 mca
drwxrwxr-x 2 ffffok registered_users 4096 Feb 1 12:54 mca1
-rw-rw-r-- 1 ffffok registered_users 0 Feb 1 12:53 t1
-rw-rw-r-- 1 ffffok registered_users 0 Feb 1 12:54 t2
13:04 ~ $
```

## Que 16 Write the linux command to delete a file.

Command: Remove file

Syntax: rm

Description : This command removes a file.

```
13:05 ~ $ ls -l
total 20
-rwxr-xr-x 1 ffffok registered_users 232 Feb 1 12:51 README.txt
-rw-rw-r-- 1 ffffok registered_users 44 Feb 1 12:56 abc.txt
drwxrwxr-x 2 ffffok registered_users 4096 Feb 1 13:04 happy
drwxrwxr-x 2 ffffok registered_users 4096 Feb 1 12:53 mca
drwxrwxr-x 2 ffffok registered_users 4096 Feb 1 12:54 mca1
-rw-rw-r-- 1 ffffok registered_users 0 Feb 1 12:53 t1
-rw-rw-r-- 1 ffffok registered_users 0 Feb 1 12:54 t2
-rw-rw-r-- 1 ffffok registered_users 0 Feb 1 13:05 t2.txt
-rw-rw-r-- 1 ffffok registered_users 0 Feb 1 13:05 t3.txt
13:05 ~ $ rm t3.txt
13:06 ~ $ ls -l
total 20
-rwxr-xr-x 1 ffffok registered_users 232 Feb 1 12:51 README.txt
-rw-rw-r-- 1 ffffok registered_users 44 Feb 1 12:56 abc.txt
drwxrwxr-x 2 ffffok registered_users 4096 Feb 1 13:04 happy
drwxrwxr-x 2 ffffok registered_users 4096 Feb 1 12:53 mca
drwxrwxr-x 2 ffffok registered_users 4096 Feb 1 12:54 mca1
-rw-rw-r-- 1 ffffok registered_users 0 Feb 1 12:53 t1
-rw-rw-r-- 1 ffffok registered_users 0 Feb 1 12:54 t2
-rw-rw-r-- 1 ffffok registered_users 0 Feb 1 13:05 t2.txt
13:06 ~ $
```



### Que 17 Write the linux Command to copy a file to some other location.

Command: copy

Syntax: cp source\_file destination\_file

Description : This command copies a file to other location.

 Bash console 2 / 180400

```
13:07 ~ $ ls -l
total 24
-rwxr-xr-x 1 ffffok registered_users 232 Feb  1 12:51 README.txt
-rw-rw-r-- 1 ffffok registered_users  44 Feb  1 12:56 abc.txt
drwxrwxr-x 2 ffffok registered_users 4096 Feb  1 13:04 happy
drwxrwxr-x 2 ffffok registered_users 4096 Feb  1 12:53 mca
drwxrwxr-x 2 ffffok registered_users 4096 Feb  1 12:54 mca1
-rw-rw-r-- 1 ffffok registered_users   0 Feb  1 12:53 t1
-rw-rw-r-- 1 ffffok registered_users   0 Feb  1 12:54 t2
-rw-rw-r-- 1 ffffok registered_users  22 Feb  1 13:08 t2.txt
13:08 ~ $ cp t2.txt t3.txt
13:08 ~ $ cat t3.txt
hello this is file t2
13:08 ~ $ ls -l
total 28
-rwxr-xr-x 1 ffffok registered_users 232 Feb  1 12:51 README.txt
-rw-rw-r-- 1 ffffok registered_users  44 Feb  1 12:56 abc.txt
drwxrwxr-x 2 ffffok registered_users 4096 Feb  1 13:04 happy
drwxrwxr-x 2 ffffok registered_users 4096 Feb  1 12:53 mca
drwxrwxr-x 2 ffffok registered_users 4096 Feb  1 12:54 mca1
-rw-rw-r-- 1 ffffok registered_users   0 Feb  1 12:53 t1
-rw-rw-r-- 1 ffffok registered_users   0 Feb  1 12:54 t2
-rw-rw-r-- 1 ffffok registered_users  22 Feb  1 13:08 t2.txt
-rw-rw-r-- 1 ffffok registered_users  22 Feb  1 13:08 t3.txt
13:08 ~ $
```



**Que 18 Write the linux command to move a file to some different location.**

Command: move

Syntax: mv source\_file destination\_file

Description : This command move a file to other location.



Bash console 20117605

```
08:50 ~/happy $  
08:50 ~/happy $ ls -l  
total 12  
-rw-rw-r-- 1 bcaE2 registered_users 18 May 9 08:47 a.txt  
-rw-rw-r-- 1 bcaE2 registered_users 18 May 9 08:48 c.txt  
-rw-rw-r-- 1 bcaE2 registered_users 6 May 9 08:50 e.txt  
08:50 ~/happy $ mv a.txt e.txt  
08:50 ~/happy $ cat e.txt  
hello how are you  
08:50 ~/happy $  
08:50 ~/happy $
```

### Que 19 :Write the linux command to count the number of words, lines and sentences in the file

Command: Word Count

Syntax: wc filename

Description : This command count the number of words, lines and sentences in the file

Options

Wc -c

Wc -m

Wc -l

Wc -L

Wc -w



Bash console 20117605

```
08:55 ~/happy $ ls -l
total 8
-rw-rw-r-- 1 bcaE2 registered_users 18 May  9 08:48 c.txt
-rw-rw-r-- 1 bcaE2 registered_users 18 May  9 08:47 e.txt
08:55 ~/happy $ wc e.txt
 1  4 18 e.txt
08:55 ~/happy $ wc -c e.txt
18 e.txt
08:55 ~/happy $ wc -m
^Z
[4]+  Stopped                  wc -m
09:01 ~/happy $
09:01 ~/happy $ wc -m e.txt
18 e.txt
09:01 ~/happy $ wc -l e.txt
1 e.txt
09:01 ~/happy $ wc -w e.txt
4 e.txt
09:01 ~/happy $
09:02 ~/happy $
```

**Que 20 Write the linux command to give the alias name.**

Command: alias

Syntax: alias alias\_name="command"

Description : This command gives alias to another commands



Bash console 27180400


```
13:16 ~/mca $ alias folder="mkdir"
13:16 ~/mca $ folder mca3
13:16 ~/mca $ folder mca4
13:16 ~/mca $ ls -l
total 12
drwxrwxr-x 2 ffffof registered_users 4096 Feb  1 13:15 mca2
drwxrwxr-x 2 ffffof registered_users 4096 Feb  1 13:16 mca3
drwxrwxr-x 2 ffffof registered_users 4096 Feb  1 13:16 mca4
13:16 ~/mca $
```

**Que 21 Write the linux command to view the exiting aliases.**

Command: alias

Syntax: alias

Description : This command displays the existing aliases.



The screenshot shows a terminal window titled "Bash console 20117605". The terminal output is as follows:

```
09:05 ~/happy $ alias
alias p='pwd'
09:09 ~/happy $
09:09 ~/happy $
09:09 ~/happy $
```

**Que 22 Write the linux command to unalias the exiting alias name.**

Command: unalias

Syntax: unalias command\_name

Description : This command removes the aliases.



Bash console 20117605


```
09:09 ~/happy $ unalias p
09:10 ~/happy $ alias
09:10 ~/happy $
09:10 ~/happy $
09:11 ~/happy $
```

**Que 23 Write the linux command to display the hostname of the system.**

Command: hostname

Syntax: hostname

Description : This command display the hostname of system.

 Bash console 20117605

```
09:11 ~/happy $  
09:11 ~/happy $ hostname  
green-liveconsole7  
09:11 ~/happy $  
09:11 ~/happy $
```

## Ques 24 Write the linux command to get information about the operating System.

**Command** :-uname is used to give you information about your operating system. Uname is the short name for unix name.

- Uname -s : To reveal the kernel name
- Uname -r : Gives you details about kernel release youre using
- Uname -v: Used to fetch the kernel version.
- Uname -n: Parameter -n will give you the node hostname.
- Uname -i: To show you hardware platform.
- Uname -o: What operating system you are running
- Uname -a: One parameter that can reveal all information

```
14:49 ~ $ uname -s
Linux
14:53 ~ $ uname -r
5.4.0-1029-aws
14:53 ~ $ uname -v
#30 SMP Tue Nov 10 18:03:06 UTC 2020
14:53 ~ $ uname -n
green-liveconsole7
14:54 ~ $ uname -i
x86_64
14:54 ~ $ uname -o
uname: invalid option -- '0'
Try 'uname --help' for more information.
14:54 ~ $ uname -o
GNU/Linux
14:54 ~ $ uname -a
Linux green-liveconsole7 5.4.0-1029-aws #30 SMP Tue Nov 10 18:03:06 UTC 2020 x86_64 x86_64 x86_64 GNU/Linux
14:54 ~ $
```

**Que 25 Write the linux command to view first 5 lines of a file.**

Command: head

Syntax: head -5 filename

Description : This command display first 5 lines of a file.



Bash console 20116365

```
05:32 ~ $ cat > abc.txt
hello
this
is a
text file
created in
Linux
so be ready
to see what
linux can
do
^Z
[1]+  Stopped                  cat > abc.txt
05:33 ~ $ head -5 abc.txt
hello
this
is a
text file
created in
05:36 ~ $
```



## Que 26 Write the linux command to view last 2 lines of a file.

Command: tail

Syntax: tail -2 filename

Description : This command displays last 20 lines of a file.



Bash console 27181609

```
14:44 ~ $ wc -c t6.txt
0 t6.txt
14:44 ~ $ wc -c t9.txt
13 t9.txt
14:44 ~ $ cat > t10.txt
1
2
3
4
5
6
7
8
9
10^Z
[5]+  Stopped                  cat > t10.txt
14:47 ~ $ tail -2 t1-.txt
tail: cannot open 't1-.txt' for reading: No such file or directory
14:47 ~ $ tail -2 t10.txt
8
9
14:47 ~ $ █
```

**Que 27 Write the linux command to view last 20 lines of a file.**

Command: tail

Syntax: tail -20 filename

Description : This command displays last 20 lines of a file.



The screenshot shows a terminal window titled "Bash console 20116407". The prompt is a root symbol. The user enters the command `cat > hello.txt`, which creates a file. Then, the user enters `tail -20 hello.txt`. The terminal output shows the command being executed and the file's content, which is the string "444". The prompt returns to the root symbol.

```
Bash console 20116407
root@kali:~# cat > hello.txt
root@kali:~# tail -20 hello.txt
444
root@kali:~#
```

**Que 28 Write the linux command to check the default permission of a file**

Command: ls -l

Syntax: ls -l

Description : This command checks the default permission of a file



Bash console 27180400

```
13:22 ~/mca $ ls -l
total 12
drwxrwxr-x 2 ffffo registered_users 4096 Feb  1 13:15 mca2
drwxrwxr-x 2 ffffo registered_users 4096 Feb  1 13:16 mca3
drwxrwxr-x 2 ffffo registered_users 4096 Feb  1 13:16 mca4
13:22 ~/mca $
```

## Que 29 Write the linux command to show the use of Basic Regular Expressions using grep Command.

Command: grep

Syntax: grep "[aA]"

Description : This command searches for specific pattern in a file.



Bash console 20116692

```
cat: a/txt: No such file or directory
06:28 ~/bca $ cat a.txt
jan
feb
mar
apr
06:28 ~/bca $ grep -E 'apr' a.txt
apr
06:29 ~/bca $
```

**Que 30 Write the Linux command to display detailed information about processes.**

Command: ps

**Syntax: ps [OPTIONS]**

**Description:** ps displays information about a selection of active processes. If you want a repetitive update of the selection and displayed information, use top(1) instead.

ps -f: Ps is used for process state. -f command is used to show full list

ps -e: ps is used for process state. -e command is used to show process for your own system.

```
Himanginis-MacBook-Pro:~ himanginikhanna$ ps -f
  UID   PID  PPID   C  STIME   TTY      TIME CMD
  501 10633 10632   0 12:04AM ttys000   0:00.37 -bash
Himanginis-MacBook-Pro:~ himanginikhanna$ ps -e
  PID  TTY      TIME   CMD
    1  ??        6:57.20 /sbin/launchd
   90  ??        0:16.55 /usr/sbin/syslogd
   91  ??        1:17.13 /usr/libexec/UserEventAgent (System)
   94  ??        0:05.24 /System/Library/PrivateFrameworks/Uninstall.framework/Resources/un
   95  ??        0:48.81 /usr/libexec/kextd
   96  ??        1:44.89 /System/Library/Frameworks/CoreServices.framework/Versions/A/Frame
   97  ??        0:13.57 /System/Library/PrivateFrameworks/MediaRemote.framework/Support/me
  100  ??        3:41.17 /usr/sbin/systemstats --daemon
  101  ??        1:19.58 /usr/libexec/configd
  103  ??        1:09.86 /System/Library/CoreServices/powerd.bundle/powerd
  107  ??        1:50.80 /usr/libexec/logd
  111  ??        0:11.13 /usr/libexec/watchdogd
  115  ??        3:28.07 /System/Library/Frameworks/CoreServices.framework/Frameworks/Metad
  117  ??        0:07.26 /usr/libexec/diskarbitrationd
  123  ??        1:11.96 /usr/libexec/opendirectoryd
  124  ??        0:15.30 /System/Library/PrivateFrameworks/ApplePushService.framework/apsd
  125  ??        1:08.28 /System/Library/CoreServices/launchservicesd
  126  ??        0:04.48 /usr/libexec/timed
  128  ??        0:00.60 /System/Library/PrivateFrameworks/MobileDevice.framework/Versions/
  129  ??        1:11.91 /usr/sbin/securityd -i
  130  ??        0:00.03 auditd -l
  132  ??        0:41.64 /usr/libexec/locationd
  135  ??        0:00.03 autofsd
  136  ??        0:00.93 /usr/libexec/displaypolicyd -k 1
  137  ??        0:43.85 /usr/libexec/dasd
  142  ??        0:00.16 /System/Library/CoreServices/login
  143  ??        0:01.86 /System/Library/PrivateFrameworks/GenerationalStorage.framework/Ve
  144  ??        0:00.02 /usr/sbin/KernelEventAgent
  146  ??        0:29.23 /usr/sbin/bluetoothd
  147  ??       19:09.00 /usr/libexec/hidd
  149  ??        0:57.44 /usr/libexec/corebrightnessd --launchd
  150  ??        0:12.36 /usr/libexec/AirPlayXPCHelper
  151  ??        0:30.61 /usr/sbin/notifyd
  152  ??        0:01.89 /usr/sbin/distnoted daemon
  153  ??        0:25.45 /usr/sbin/cfprefsd daemon
  154  ??        0:04.17 /System/Library/CoreServices/coreservicesd
```

### **31. PROGRAM FOR SYSTEM CALLS OF UNIX OPERATING SYSTEMS (OPENDIR, READDIR, CLOSEDIR)**

#### **ALGORITHM:**

STEP 1: Start the program.

STEP 2: Create struct dirent.

STEP 3: declare the variable buff and pointer dptr.

STEP 4: Get the directory name.

STEP 5: Open the directory.

STEP 6: Read the contents in directory and print it.

STEP 7: Close the directory.

#### **PROGRAM:**

```
#include<stdio.h>

#include<dirent.h>

struct dirent *dptr;

int main(int argc, char *argv[])

{

    char buff[100];

    DIR *dirp;

    printf("\n\n ENTER DIRECTORY NAME");

    scanf("%s", buff);

    if((dirp=opendir(buff))==NULL)

    { printf("The given directory does not exist");

    exit(1); }
```

```
while(dpitr=readdir(dirp))  
{  
    printf("%s\n",dpitr->d_name);  
}  
closedir(dirp);  
}
```

## **32. PROGRAM FOR SYSTEM CALLS OF UNIX OPERATING SYSTEM (fork, getpid, exit)**

### **ALGORITHM:**

STEP 1: Start the program.

STEP 2: Declare the variables pid,pid1,pid2.

STEP 3: Call fork() system call to create process.

STEP 4: If pid==-1, exit.

STEP 5: If pid!=-1 , get the process id using getpid().

STEP 6: Print the process id.

STEP 7: Stop the program

### **PROGRAM:**

```
#include<stdio.h>

#include <unistd.h>

int main()

{

    int pid,pid1,pid2;

    pid=fork();

    if(pid==-1)

    {

        printf("ERROR IN PROCESS CREATION \n");

        exit(1);

    }

    if(pid!=0)

    {
```



```
pid1=getpid();  
printf("\n the parent process ID is %d\n", pid1);  
}  
else  
{  
pid2=getpid();  
printf("\n the child process ID is %d\n", pid2);  
}  
return 0;  
}
```

**33. Write an appropriate „C“ program which implements the concept of dynamic memory allocation (use of malloc(), calloc(), realloc(), and free() system call.**

```
#include <stdio.h>

#include <stdlib.h>

int main()
{
    int* ptr;

    int n, i;

    n = 5;

    printf("Enter number of elements: %d\n", n);

    ptr = (int*)calloc(n, sizeof(int));

    if (ptr == NULL) {
        printf("Memory not allocated.\n");
        exit(0);
    }
    else {
        printf("Memory successfully allocated using calloc.\n");

        for (i = 0; i < n; ++i) {
            ptr[i] = i + 1;
        }

        printf("The elements of the array are: ");

        for (i = 0; i < n; ++i) {
            printf("%d, ", ptr[i]);
        }
    }
}
```

```

n = 10;

printf("\n\nEnter the new size of the array: %d\n", n);

ptr = realloc(ptr, n * sizeof(int));

printf("Memory successfully re-allocated using realloc.\n");

for (i = 5; i < n; ++i) {

    ptr[i] = i + 1;

}

printf("The elements of the array are: ");

for (i = 0; i < n; ++i) {

    printf("%d, ", ptr[i]);

}

free(ptr);

}

return 0;

}

```

```

Enter number of elements: 5
Memory successfully allocated using calloc.
The elements of the array are: 1, 2, 3, 4, 5,

Enter the new size of the array: 10
Memory successfully re-allocated using realloc.
The elements of the array are: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10,

```

**34. Write an appropriate „C“ program which implements the concept of fork() system call.**

```
#include <stdio.h>

#include <unistd.h>

int main()
{
    int id;

    printf("Hello, World!\n");

    id = fork();

    if (id > 0) {
        printf("This is parent section [Process id: %d].\n", getpid());
    }

    else if (id == 0) {
        printf("fork created [Process id: %d].\n", getpid());
        printf("fork parent process id: %d.\n", getppid());
    }

    else {
        printf("fork creation failed!!!\n");
    }

    return 0;
}
```

```
Hello, World!
This is parent section [Process id: 1252].
fork created [Process id: 1253].
fork parent process id: 1252.
```

**35. Write an appropriate „C“ program which implements the concept of exit() system call**

```
#include <stdlib.h>

int main ()
{
    // declaration of the variables
    int i, num;

    printf ( " Enter the last number: ");
    scanf ( " %d", &num);

    for ( i = 1; i<num; i++)
    {
        // use if statement to check the condition
        if ( i == 6 )

            /* use exit () statement with passing 0 argument to show termination of the program
            without any error message. */

            exit(0);

        else

            printf (" \n Number is %d", i);
    }

    return 0;
}
```

```
Enter the last number: 10
```

```
Number is 1
```

```
Number is 2
```

```
Number is 3
```

```
Number is 4
```

```
Number is 5
```