

```
mysql -u root -p
```

```
CREATE DATABASE cursor_demo;
```

```
USE cursor_demo;
```

```
CREATE TABLE employees (  
    emp_id INT PRIMARY KEY,  
    emp_name VARCHAR(50),  
    salary INT  
);
```

```
INSERT INTO employees VALUES  
  
(1, 'Rahul', 25000),  
  
(2, 'Aman', 30000),  
  
(3, 'Priya', 28000),  
  
(4, 'Neha', 35000);
```

```
SELECT * FROM employees;
```

```
DELIMITER //
```



```
CREATE PROCEDURE employee_cursor()
BEGIN
    DECLARE done INT DEFAULT 0;
    DECLARE e_name VARCHAR(50);
    DECLARE e_salary INT;

    DECLARE emp_cursor CURSOR FOR
        SELECT emp_name, salary FROM employees;

    DECLARE CONTINUE HANDLER FOR NOT FOUND
        SET done = 1;

    OPEN emp_cursor;

    read_loop: LOOP

        FETCH emp_cursor INTO e_name, e_salary;

        IF done = 1 THEN
            LEAVE read_loop;
        END IF;

        SELECT CONCAT('Employee Name: ', e_name,
            ' Salary: ', e_salary) AS Details;

    END LOOP;

    CLOSE emp_cursor;

END //
```

DELIMITER ;

CALL employee_cursor();

DELIMITER //

CREATE FUNCTION yearly_salary(monthly_salary INT)

RETURNS INT

DETERMINISTIC

BEGIN

 RETURN monthly_salary * 12;

END //

DELIMITER ;

SELECT emp_name,

 salary,

 yearly_salary(salary) AS yearly_income

FROM employees;