Bhubharati searchData Encryption Guide

Generate the encrypted **searchData** value used for a survey number.

Verified example
Survey number: **1147**
Encrypted: **GToOfYzvSJq3GxwzolIGXw==**
URL encoded: **GToOfYzvSJq3GxwzolIGXw%3D%3D**

Encryption Settings

Algorithm: AES-128-CBC
Padding: PKCS7
Output: Base64
Key: u/Gu5posvwDsXUnV5Zaq4g==
IV: 5D9r9ZVzEYYgha93/aUK2w==

Method 1: Chrome Console Using CryptoJS

Step 1: Open Chrome, press **F12**, and select **Console**.

Step 2: If Chrome displays a paste warning, manually type **allow pasting** and press Enter.

Step 3: Paste the loader below. Do not include any HTML link tags copied from chat.

Step 4: After CryptoJS loads, paste the encryption code and press Enter.

```
var s = document.createElement('script');
s.src = 'https://cdnjs.cloudflare.com/ajax/libs/crypto-js/3.1.9-1/crypto-js.min.js';
document.head.appendChild(s);

var rkEncryptionKey =
  CryptoJS.enc.Base64.parse('u/Gu5posvwDsXUnV5Zaq4g==');
var rkEncryptionIv =
  CryptoJS.enc.Base64.parse('5D9r9ZVzEYYgha93/aUK2w==');
var encrypted = CryptoJS.AES.encrypt(
  '1147', rkEncryptionKey,
  { mode: CryptoJS.mode.CBC,
    padding: CryptoJS.pad.Pkcs7,
    iv: rkEncryptionIv }
);
console.log(encrypted.ciphertext.toString(CryptoJS.enc.Base64));
```

Expected output: GToOfYzvSJq3GxwzolIGXw==

Method 2: Reusable Function

Load CryptoJS first, then paste this function once:

```
function encryptSurveyNo(value) {
  var key = CryptoJS.enc.Base64.parse(
    'u/Gu5posvwDsXUnV5Zaq4g==');
  var iv = CryptoJS.enc.Base64.parse(
    '5D9r9ZVzEYYgha93/aUK2w==');
  var encrypted = CryptoJS.AES.encrypt(
    String(value), key,
    { mode: CryptoJS.mode.CBC,
      padding: CryptoJS.pad.Pkcs7,
      iv: iv }
  );
  return encrypted.ciphertext.toString(CryptoJS.enc.Base64);
}

encryptSurveyNo('1147');
```

Expected output: GToOfYzvSJq3GxwzolIGXw==

Generate multiple survey numbers

```
for (let i = 1140; i <= 1150; i++) {
  console.log(i + ' -> ' + encryptSurveyNo(String(i)));
}
```

Method 3: Node.js Without CryptoJS

Step 1: Create a file named **encode.js** and paste:

```
const crypto = require('crypto');
const surveyNumber = process.argv[2] || '1147';
const key = Buffer.from('u/Gu5posvwDsXUnV5Zaq4g==', 'base64');
const iv = Buffer.from('5D9r9ZVzEYYgha93/aUK2w==', 'base64');
const cipher = crypto.createCipheriv('aes-128-cbc', key, iv);
let encrypted = cipher.update(surveyNumber, 'utf8', 'base64');
encrypted += cipher.final('base64');
console.log('Survey number : ' + surveyNumber);
console.log('searchData    : ' + encrypted);
console.log('URL encoded   : ' + encodeURIComponent(encrypted));
```

Step 2: Open Command Prompt in the same folder and run:

```
node encode.js 1147
```

Expected output
Survey number: 1147
searchData: GToOfYzvSJq3GxwzolIGXw==
URL encoded: GToOfYzvSJq3GxwzolIGXw%3D%3D

Method 4: Verify From the Network Request

Step 1: Open the Bhubharati Land Details Search page.

Step 2: Select District, Mandal, Village, Survey Number, and Khata Number.

Step 3: Enter the current CAPTCHA.

Step 4: Press **F12**, select **Network**, and click Fetch.

Step 5: Select the **getPublicDataInfo** request.

Step 6: Under **Headers**, inspect the Request URL and copy the **searchData** parameter.

Important Notes

1. Base64 output must be URL encoded inside a URL: **=** becomes **%3D**, **+** becomes **%2B**, and **/** becomes **%2F**.

2. searchData is only the encrypted survey number.

3. A working request can also require current villageId, district, mandal, khataNoIdselect, CAPTCHA, and session cookies.

4. CAPTCHA and session values can expire. Use fresh values from the active browser session.

5. Use this only for authorized access and normal site workflows. Do not bypass CAPTCHA, session validation, access controls, or rate limits.